10**USB**





CLASSE 10 USB

A technological heart

The most sophisticated version.

New software guarantees proficient performance. Numerous functions and a new graphic display allows for rapid access and efficient programming.

A true technological heart.

1 i-Steam (Rancilio Patent) This new totally automatic steam wand allows milk to be heated and frothed using a mix of steam and air, until a soft and remarkably compact cream is obtained. The innovative water system makes it the fastest and most powerful steam wand on the market (500 cc from 10°C to 65°C in 30 seconds). Two program selection buttons: "Cappuccino", to heat and froth the milk, or "Latte", to heat the milk only.


The smart electronic control system injects air according to the quantity of milk present in the pitcher, giving constant quality time after time. When the programmed temperature is reached, the iSteam stops automatically. The user can set the final temperature of the drink and the quantity of air to be emulsified for both options.

2 4-TEA (Rancilio Patent) The hot-water temperature control system for tea, has four different temperatures and programmable dosages. Hot and cold water are mixed electronically to obtain the right temperature for your menu, and stop automatically when the programmed dosage has been reached. TO about 95°C, suitable for Indian Black Tea, T1 about 85°C, suitable for Herbal/Fruit tisanes, T2 about 70°C, suitable for Chinese/Taiwanese Green Tea, T3 about 60°C, suitable for Japanese Green Tea.

3 Load and Show The new 240x64 pixel graphic display combined with new USB electronics allows the machine to be used interactively with our customers. The presence of an onboard USB connection makes it possible to load personalized logos and phrases onto the display, quickly and easily. With a simple USB disk drive our customers can also copy and transfer settings from one machine to another







www.rancilio.com

On demand

iSteam

GAS

Technical Features

independent heat exchangers
electric heating
incorporated volumetric pump
numn pressure gauge
Dullio Diessole sanse
boiler pressure gauge
automatic water level control
electronic hoiler temperature/pressure control
electronic doner remoerature/bressure control
multifunction onboard computer with display
low-voltage dispensing controls (24 V)
housing in aluminium and stainless steel
electric cun-warmer with 3 temperature settings
CHECKE CON WATER A CONTROL OF THE CO

Endowments, accessories

ENDOWMENTS: 1 filter holder for 2 cups per group, 1 filter holder for 1 cup, ${\it 2\,steam\,wands,\,2\,hot\,water\,dispensers,\,with\,one\,mixed,\,programmable\,for\,dosage\,time,}\\$ coffee tamper, measuring scoop and washing disks, foot extensions.

ACCESSORISES: DP automatic or manual water softener, MD dosing grinder.

Colors

satin-finished metallic grey

Technical Data

2 GROUPS

dimensions (wxdxth) weight boiler Hz 30.7 x 21.2 x 20.8 inch 200.6 Lb 2.9 usgal 50/60 boiler power voltage 6000 W 120 / 220-240 / 380-415 3N 3 GROUPS dimensions (wxdxth) weight boiler Hz 40.1 x 21.2 x 20.8 inch 244.7 Lb 4.2 usgal 50/60 boiler power voltage 6000 W 220-240 / 380-415 3N 4 GROUPS dimensions (wxdxth) weight boiler Hz 49.6 x 21.2 x 20.8 inch 295.4 Lb 5.8 usgal 50/60 boiler power voltage 6000 W 220-240 / 380-415 3N	2 011001 3					
Voltage				i		
3 GROUPS	boiler power	voltage				
dimensions (wxdxh) weight boiler Hz 40.1 x 21.2 x 20.8 inch 244.7 Lb 4.2 usgal 50/60 boiler power voltage 6000 W 220-240 / 380-415 3N 4 GROUPS dimensions (wxdxh) weight boiler Hz 49.6 x 21.2 x 20.8 inch 295.4 Lb 5.8 usgal 50/60 boiler power voltage		120 / 220-240 / 380-415 3N				
40.1 x 21.2 x 20.8 inch 244.7 Lb 4.2 usgal 50/60 boiler power 6000 W 220-240 / 380-415 3N 4 GROUPS dimensions (wxdxh) 49.6 x 21.2 x 20.8 inch 295.4 Lb 5.8 usgal 50/60 boiler power voltage	3 GRUUPS					
boiler power voltage 6000 W 220-240 / 380-415 3N 4 GROUPS dimensions (wxdxh) weight boiler Hz 49.6 x 21.2 x 20.8 inch 295.4 Lb 5.8 usgal 50/60 boiler power voltage		, ,		i		
6000 W 220-240 / 380-415 3N 4 GROUPS dimensions (wxdxh) weight boiler Hz 49.6 x 21.2 x 20.8 inch 295.4 Lb 5.8 usgal 50/60 boiler power voltage	40.1 x 21.2 x 20.8 inch	244.7 Lb	4.2 usgal	50/60		
dimensions (wxdxh) weight boiler Hz 49.6 x 21.2 x 20.8 inch 295.4 Lb 5.8 usgal 50/60 boiler power voltage	•	_	_			
49.6 x 21.2 x 20.8 inch 295.4 Lb 5.8 usgal 50/60 boiler power voltage	4 GROUPS					
49.6 x 21.2 x 20.8 inch 295.4 Lb 5.8 usgal 50/60 boiler power voltage	dimensions (wordsh)	woight	hoiler	Ц-		
boiler power voltage				· · · -		
· ·	49.6 X 21.2 X 20.8 INCH	295.4 LD	5.8 USgai	50/60		
· ·	boiler power	voltage				
220-240 / 300-413 31V	•	-	-			
		220 210 7 300 113 311				

Standard









⊞ | LOAD& SHOW

New graphic display



4-TEA

Temperature programming



EASY CLEAN

Automatic washing programme



\$\rightarrow\$ PLUG

& BREW

Rapid setting



ABM.07

Smart power management



Voltage stabilizer



Advanced diagnostics



| CUP | WARMER

Electric cup warmer













