

## Contents

### 1 Geometry

- 1.1 Convex Hull Algorithm . . . . .
- 1.2 Delaunay Triangulation . . . . .
- 1.3 Various Geometry Functions . . . . .

### 2 Graphs

- 2.1 Dijkstra's Algorithm . . . . .
- 2.2 Max Flow (Dinic's Algorithm) . . . . .
- 2.3 Max Flow (Edmonds-Karp Algorithm) . . . . .
- 2.4 Eulerian Path . . . . .
- 2.5 Hopcroft-Karp Algorithm . . . . .
- 2.6 Lowest Common Ancestor . . . . .
- 2.7 Strongly Connected Components . . . . .
- 2.8 Union-Find Set . . . . .

### 3 Tree

- 3.1 Cartesian Tree . . . . .
- 3.2 Segment Tree . . . . .

### 4 Math

- 4.1 Extended Euclid's Algorithm . . . . .
- 4.2 Fast Prime Number Sieve . . . . .
- 4.3 Fast Fourier Transform . . . . .
- 4.4 Gauss-Jordan Elimination . . . . .
- 4.5 GCD and LCM . . . . .
- 4.6 Modular Linear Equation Solver . . . . .

### 5 Strings

- 5.1 Aho-Corasick Algorithm . . . . .
- 5.2 Knuth-Morris-Pratt Algorithm . . . . .
- 5.3 Suffix Array . . . . .

### 6 Techniques

- 6.1 Various algorithm techniques . . . . .

## 1 Geometry

### 1.1 Convex Hull Algorithm

```
bool compare(PT a,PT b){ return a.y<b.y || (a.y==b.y && a.x<b.x); }
double cross(PT o,PT a, PT b)
{
    return (a.x-o.x)*(b.y-o.y)-(a.y-o.y)*(b.x-o.x);
}

vector<PT> ConvexHull(vector<PT> p) { int n=p.size(); int k=0;
vector<PT> h(2*n);
sort(p.begin(),p.end(),compare);
//build lower hull
for(int i=0;i<n;++i)
{
    while(k>=2 && cross(h[k-2],h[k-1],p[i])<=0) k--;
    h[k++]=p[i];
}
//build top hull
for(int i=n-2,t=k+1;i>=0;--i)
{
    while(k>=t && cross(h[k-2],h[k-1],p[i])<=0) k--;
    h[k++]=p[i];
}
h.resize(k);
return h;
}
```

### 1.2 Delaunay Triangulation

```
/*
Stanford notebook
-----
Delaunay Algorithm Does not handle degenerate cases
Running time: O(n^4)
INPUT: x[] = x-coordinates
       y[] = y-coordinates
OUTPUT: triples = a vector containing m triples
        (indices corresponding to triangle vertices)
-----
*/

typedef double T;

struct triple {
    int i, j, k;
    triple() {}
    triple(int i, int j, int k) : i(i), j(j), k(k) {}
};

vector<triple> delaunayTriangulation(vector<T>& x, vector<T>& y)
{
    int n = x.size();
    vector<T> z(n);
    vector<triple> ret;

    for (int i = 0; i < n; i++)
        z[i] = x[i] * x[i] + y[i] * y[i];
    for (int i = 0; i < n-2; i++)
    {
        for (int j = i+1; j < n; j++)
        {
            for (int k = i+1; k < n; k++)
            {
                if (j == k) continue;
                double xn = (y[j]-y[i])*(z[k]-z[i]) - (y[k]-y[i])*(z[j]-z[i]);
                double yn = (x[k]-x[i])*(z[j]-z[i]) - (x[j]-x[i])*(z[k]-z[i]);
                double zn = (x[j]-x[i])*(y[k]-y[i]) - (x[k]-x[i])*(y[j]-y[i]);
                bool flag = zn < 0;
                for (int m = 0; flag && m < n; m++)
                    flag = flag && ((x[m]-x[i])*xn + (y[m]-y[i])*yn + (z[m]-z[i])*zn <= 0);
                if (flag) ret.push_back(triple(i, j, k));
            }
        }
    }
    return ret;
}

int main() {
    T xs[]={0, 0, 1, 0.9};
    T ys[]={0, 1, 0, 0.9};
    vector<T> x(&xs[0], &xs[4]), y(&ys[0], &ys[4]);
    vector<triple> tri = delaunayTriangulation(x, y);
    //expected: 0 1 3
    //           0 3 2
    int i;
    for(i = 0; i < tri.size(); i++)
        printf("%d %d %d\n", tri[i].i, tri[i].j, tri[i].k);
    return 0;
}
```

### 1.3 Various Geometry Functions

```
// Stanford Notebook
double INF = 1e100;
double EPS = 1e-12;

struct PT {
    double x, y;
    PT() {}
    PT(double x, double y) : x(x), y(y) {}
    PT(const PT &p) : x(p.x), y(p.y) {}
    PT operator + (const PT &p) const { return PT(x+p.x, y+p.y); }
    PT operator - (const PT &p) const { return PT(x-p.x, y-p.y); }
    PT operator * (double c) const { return PT(x*c, y*c); }
    PT operator / (double c) const { return PT(x/c, y/c); }
};

double dot(PT p, PT q) { return p.x*q.x+p.y*q.y; }
double dist2(PT p, PT q) { return dot(p-q,p-q); }
double cross(PT p, PT q) { return p.x*q.y-p.y*q.x; }
```

```

// rotate a point CCW or CW around the origin
PT RotateCCW90(PT p) { return PT(-p.y,p.x); }
PT RotateCW90(PT p) { return PT(p.y,-p.x); }
PT RotateCCW(PT p, double t) { return PT(p.x*cos(t)-p.y*sin(t), p.x*sin(t)+p.y*cos(t)); }

// project point c onto line through a and b // assuming a != b
PT ProjectPointLine(PT a, PT b, PT c) { return a + (b-a)*dot(c-a, b-a)/dot(b-a, b-a); }
// project point c onto line segment through a and b
PT ProjectPointSegment(PT a, PT b, PT c)
{
    double r = dot(b-a,b-a);
    if (fabs(r) < EPS) return a;
    r = dot(c-a, b-a)/r;
    if (r < 0) return a;
    if (r > 1) return b;
    return a + (b-a)*r;
}

// compute distance from c to segment between a and b
double DistancePointSegment(PT a, PT b, PT c)
{
    return sqrt(dist2(c, ProjectPointSegment(a, b, c)));
}

// compute distance between point (x,y,z) and plane ax+by+cz=d
double DistancePointPlane(double x, double y, double z, double a, double b, double c, double d)
{
    return fabs(a*x+b*y+c*z-d)/sqrt(a*a+b*b+c*c);
}

// determine if lines from a to b and c to d are parallel or collinear
bool LinesParallel(PT a, PT b, PT c, PT d) { return fabs(cross(b-a, c-d)) < EPS; }

bool LinesCollinear(PT a, PT b, PT c, PT d)
{
    return LinesParallel(a, b, c, d)
    && fabs(cross(a-b, a-c)) < EPS
    && fabs(cross(c-d, c-a)) < EPS;
}

// determine if line segment from a to b intersects with
// line segment from c to d
bool SegmentsIntersect(PT a, PT b, PT c, PT d)
{
    if (LinesCollinear(a, b, c, d))
    {
        if (dist2(a, c) < EPS || dist2(a, d) < EPS ||
            dist2(b, c) < EPS || dist2(b, d) < EPS) return true;
        if (dot(c-a, c-b) > 0 && dot(d-a, d-b) > 0 && dot(c-b, d-b) > 0)
            return false;
        return true;
    }
    if (cross(d-a, b-a) * cross(c-a, b-a) > 0)
        return false;
    if (cross(a-c, d-c) * cross(b-c, d-c) > 0)
        return false;
    return true;
}

// compute intersection of line passing through a and b
// with line passing through c and d, assuming that unique
// intersection exists; for segment intersection, check if
// segments intersect first
PT ComputeLineIntersection(PT a, PT b, PT c, PT d)
{
    b=b-a; d=d-c; c=c-a;
    assert(dot(b, b) > EPS && dot(d, d) > EPS);
    return a + b*cross(c, d)/cross(b, d);
}

// compute center of circle given three points
PT ComputeCircleCenter(PT a, PT b, PT c)
{
    b=(a+b)/2;
    c=(a+c)/2;
    return ComputeLineIntersection(b, b+RotateCW90(a-b), c, c+RotateCW90(a-c));
}

// determine if point is in a possibly non-convex polygon (by William
// Randolph Franklin); returns 1 for strictly interior points, 0 for
// strictly exterior points, and 0 or 1 for the remaining points.
// Note that it is possible to convert this into an "exact" test using
// integer arithmetic by taking care of the division appropriately
// (making sure to deal with signs properly) and then by writing exact
// tests for checking point on polygon boundary
bool PointInPolygon(const vector<PT> &p, PT q)
{
    bool c = 0;
    for (int i = 0; i < p.size(); i++)

```

```

{
    int j = (i+1)%p.size();
    if ((p[i].y <= q.y && q.y < p[j].y ||
        p[j].y <= q.y && q.y < p[i].y) &&
        q.x < p[i].x + (p[j].x - p[i].x) * (q.y - p[i].y) / (p[j].y - p[i].y))
        c = !c;
    return c;
}

// determine if point is on the boundary of a polygon
bool PointOnPolygon(const vector<PT> &p, PT q)
{
    for (int i = 0; i < p.size(); i++)
        if (dist2(ProjectPointSegment(p[i], p[(i+1)%p.size()], q), q) < EPS)
            return true;
    return false;
}

// compute intersection of line through points a and b with
// circle centered at c with radius r > 0
vector<PT> CircleLineIntersection(PT a, PT b, PT c, double r)
{
    vector<PT> ret;
    b = b-a; a = a-c;
    double A = dot(b, b);
    double B = dot(a, b);
    double C = dot(a, a) - r*r;
    double D = B*B - A*C;
    if (D < -EPS) return ret;
    ret.push_back(c+a+b*(-B+sqrt(D+EPS))/A);
    if (D > EPS)
        ret.push_back(c+a+b*(-B-sqrt(D))/A);
    return ret;
}

// compute intersection of circle centered at a with radius r
// with circle centered at b with radius R
vector<PT> CircleCircleIntersection(PT a, PT b, double r, double R)
{
    vector<PT> ret;
    double d = sqrt(dist2(a, b));
    if (d > r+R || d<min(r, R) < max(r, R)) return ret;
    double x = (d+d-R+r)/(2*d);
    double y = sqrt(r*r-x*x);
    PT v = (b-a)/d;
    ret.push_back(a+v*x + RotateCCW90(v)*y);
    if (y > 0) ret.push_back(a+v*x - RotateCCW90(v)*y);
    return ret;
}

// This code computes the area or centroid of a (possibly nonconvex)
// polygon, assuming that the coordinates are listed in a clockwise or
// counterclockwise fashion. Note that the centroid is often known as
// the "center of gravity" or "center of mass".
double ComputeSignedArea(const vector<PT> &p)
{
    double area = 0;
    for(int i = 0; i < p.size(); i++)
    {
        int j = (i+1) % p.size();
        area += p[i].x*p[j].y - p[j].x*p[i].y;
    }
    return area / 2.0;
}

double ComputeArea(const vector<PT> &p) { return fabs(ComputeSignedArea(p)); }

PT ComputeCentroid(const vector<PT> &p)
{
    PT c(0,0);
    double scale = 6.0 * ComputeSignedArea(p);
    for (int i = 0; i < p.size(); i++)
    {
        int j = (i+1) % p.size();
        c = c + (p[i]+p[j])*(p[i].x*p[j].y - p[j].x*p[i].y);
    }
    return c / scale;
}

// tests whether or not a given polygon (in CW or CCW order) is simple
bool IsSimple(const vector<PT> &p)
{
    for (int i = 0; i < p.size(); i++)
    {
        for (int k = i+1; k < p.size(); k++)
        {
            int j = (i+1) % p.size();
            int l = (k+1) % p.size();
            if (i == 1 || j == k) continue;

```

```

        if (SegmentsIntersect(p[i], p[j], p[k], p[l]))
            return false;
    }
    return true;
}

```

## 2 Graphs

### 2.1 Dijkstra's Algorithm

```

//Dijkstra Algorithm
int t,n,m,s,e;
vector<ii> edges[N]; //pair<NodeEnd,dist>
int distances[N]; // =INF=0x3f3f3f3f
int parent[N]; // ==-1

int Dijkstra()
{
    vector<ii> :: iterator it;
    priority_queue< ii, vector<ii>, greater<ii> > pq;
    distances[s]=0;
    pq.push(ii(distances[s],s));
    while(!pq.empty())
    {
        ii p = pq.top();
        pq.pop();
        int d=p.first;
        int a=p.second;
        for(it=edges[a].begin(); it!=edges[a].end(); ++it)
        {
            if(distances[it->first]>distances[a]+it->second)
            {
                distances[it->first]=distances[a]+it->second;
                parent[it->first]=a;
                pq.push(ii(distances[it->first],it->first));
            }
        }
    }
    return distances[e];
}

```

### 2.2 Max Flow (Dinic's Algorithm)

```

// Stanford Notebook
typedef long long LL;

struct Edge
{
    int from, to, cap, flow, index;
    Edge(int from, int to, int cap, int flow, int index) :
        from(from), to(to), cap(cap), flow(flow), index(index) {}
    LL rcap() { return cap - flow; }
};

struct Dinic
{
    int N;
    vector<vector<Edge> > G;
    vector<vector<Edge> > Lf;
    vector<int> layer;
    vector<int> Q;
    Dinic(int N) : N(N), G(N), Q(N) {}
    void AddEdge(int from, int to, int cap)
    {
        if (from == to) return;
        G[from].push_back(Edge(from, to, cap, 0, G[to].size()));
        G[to].push_back(Edge(to, from, 0, 0, G[from].size() - 1));
    }

    LL BlockingFlow(int s, int t)
    {
        layer.clear();
        layer.resize(N, -1);
        layer[s] = 0;
        Lf.clear(); Lf.resize(N);

        int head = 0, tail = 0;
        Q[tail++] = s;
        while (head < tail)

```

```

    {
        int x = Q[head++];
        for (int i = 0; i < G[x].size(); i++)
        {
            Edge &e = G[x][i]; if (e.rcap() <= 0) continue;
            if (layer[e.to] == -1)
            {
                layer[e.to] = layer[e.from] + 1;
                Q[tail++] = e.to;
            }
            if (layer[e.to] > layer[e.from])
            {
                Lf[e.from].push_back(&e);
            }
        }
    }

    if (layer[t] == -1) return 0;
    LL totflow = 0;
    vector<Edge> > P;
    while (!Lf[s].empty())
    {
        int curr = P.empty() ? s : P.back()->to;
        if (curr == t)
        {
            // Augment
            LL amt = P.front()->rcap();
            for (int i = 0; i < P.size(); ++i)
            {
                amt = min(amt, P[i]->rcap());
            }
            totflow += amt;
            for (int i = P.size() - 1; i >= 0; --i)
            {
                P[i]->flow += amt;
                G[P[i]->to][P[i]->index].flow -= amt;
                if (P[i]->rcap() <= 0)
                {
                    Lf[P[i]->from].pop_back();
                    P.resize(i);
                }
            }
        }
        else if (Lf[curr].empty())
        {
            // Retreat
            P.pop_back();
            for (int i = 0; i < N; ++i)
            {
                for (int j = 0; j < Lf[i].size(); ++j)
                {
                    if (Lf[i][j]->to == curr)
                        Lf[i].erase(Lf[i].begin() + j);
                }
            }
        }
        else
        {
            // Advance
            P.push_back(Lf[curr].back());
        }
    }
    return totflow;
}

LL GetMaxFlow(int s, int t)
{
    LL totflow = 0;
    while (LL flow = BlockingFlow(s, t))
        totflow += flow;
    return totflow;
}
};

```

### 2.3 Max Flow (Edmonds-Karp Algorithm)

```

/*
Stanford Notebook
MinCostMaxFlow (adjacency matrix, Edmonds and Karp 1972)
This implementation keeps track of forward and reverse edges separately
(so you can set cap[i][j] != cap[j][i]). For a regular max flow, set all edge costs to 0.
Running time,  $O(|V|^2)$  cost per augmentation
max flow:  $O(|V|^3)$  augmentations
min cost max flow:  $O(|V|^4 * MAX\_EDGE\_COST)$  augmentations
INPUT: - graph, constructed using AddEdge()
        - sink
OUTPUT: - (maximum flow value, minimum cost value)
        - To obtain the actual flow, look at positive values only.
*/
typedef vector<int> VI;

```

```

typedef vector<VI> VVI;
typedef long long L;
typedef vector<L> VL;
typedef vector<VL> VVL;
typedef pair<int, int> PII;
typedef vector<PII> VPII;

const L INF = numeric_limits<L>::max() / 4;

struct MinCostMaxFlow {
    int N;
    VVL cap, flow, cost;
    VI found;
    VL dist, pi, width;
    VPII dad;

    MinCostMaxFlow(int N) :
        N(N), cap(N, VL(N)), flow(N, VL(N)), cost(N, VL(N)),
        found(N), dist(N), pi(N), width(N), dad(N) {}

    void AddEdge(int from, int to, L cap, L cost)
    {
        this->cap[from][to] = cap;
        this->cost[from][to] = cost;
    }

    void Relax(int s, int k, L cap, L cost, int dir)
    {
        L val = dist[s] + pi[s] - pi[k] + cost;
        if (cap && val < dist[k])
        {
            dist[k] = val;
            dad[k] = make_pair(s, dir);
            width[k] = min(cap, width[s]);
        }
    }

    L Dijkstra(int s, int t)
    {
        fill(found.begin(), found.end(), false);
        fill(dist.begin(), dist.end(), INF);
        fill(width.begin(), width.end(), 0);
        dist[s] = 0;
        width[s] = INF;

        while (s != -1)
        {
            int best = -1;
            found[s] = true;
            for (int k = 0; k < N; k++)
            {
                if (found[k]) continue;
                Relax(s, k, cap[s][k] - flow[s][k], cost[s][k], 1);
                Relax(s, k, flow[k][s], -cost[k][s], -1);
                if (best == -1 || dist[k] < dist[best]) best = k;
            }
            s = best;
        }

        for (int k = 0; k < N; k++)
            pi[k] = min(pi[k] + dist[k], INF);
        return width[t];
    }

    pair<L, L> GetMaxFlow(int s, int t)
    {
        L totflow = 0, totcost = 0;
        while (L amt = Dijkstra(s, t))
        {
            totflow += amt;
            for (int x = t; x != s; x = dad[x].first)
            {
                if (dad[x].second == 1)
                {
                    flow[dad[x].first][x] += amt;
                    totcost += amt * cost[dad[x].first][x];
                }
                else
                {
                    flow[x][dad[x].first] -= amt;
                    totcost -= amt * cost[x][dad[x].first];
                }
            }
        }
        return make_pair(totflow, totcost);
    }
};

```

## 2.4 Eulerian Path

```

struct Edge;
typedef list<Edge>::iterator iter;
struct Edge
{
    int next_vertex;
    iter reverse_edge;
    Edge(int next_vertex) :next_vertex(next_vertex) {}
};

const int max_vertices = ;
int num_vertices;
list<Edge> adj[max_vertices]; // adjacency list
vector<int> path;

void find_path(int v)
{
    while(adj[v].size() > 0)
    {
        int vn = adj[v].front().next_vertex;
        adj[vn].erase(adj[v].front().reverse_edge);
        adj[v].pop_front();
        find_path(vn);
    }
    path.push_back(v);
}

void add_edge(int a, int b)
{
    adj[a].push_front(Edge(b));
    iter ita = adj[a].begin();
    adj[b].push_front(Edge(a));
    iter itb = adj[b].begin();
    ita->reverse_edge = itb;
    itb->reverse_edge = ita;
}

```

## 2.5 Hopcroft-Karp Algorithm

```

#include <vector>
vector<int> g[N];
int r[N], l[N], n, m, e, a, b;
// generate g;

bool dfs(int v)
{
    if(vis[v]) return false;
    vis[v] = true;
    for(int u=0; u<g[v].size(); ++u)
    {
        if(!r[g[v][u]])
        {
            l[v]=g[v][u];
            r[g[v][u]]=v;
            return true;
        }
    }
    for(int u=0; u<g[v].size(); ++u)
    {
        if(dfs(r[g[v][u]]))
        {
            l[v]=g[v][u];
            r[g[v][u]]=v;
            return true;
        }
    }
    return false;
}

void hopcroft_karp()
{
    bool change = true;
    while(change)
    {
        change = false;
        fill(vis, vis+n+1, false);
        for(int i=1; i<=n; ++i)
            if(!l[i])
                change |= dfs(i);
    }
}

```

## 2.6 Lowest Common Ancestor

```

const int max_nodes, log_max_nodes;

int num_nodes, log_num_nodes, root;
vector<int> children[max_nodes];
// children[i] contains the children of node i
int A[max_nodes][log_max_nodes+1]; // A[i][j] is the 2^j-th ancestor of node i, or -1 if that ancestor does not exist
int L[max_nodes]; // L[i] is the distance between node i and the root
// floor of the binary logarithm of n
int lb(unsigned int n)
{
    if(n==0) return -1;
    int p = 0;
    if (n >= 1<<16) { n >= 16; p += 16; }
    if (n >= 1<<8) { n >= 8; p += 8; }
    if (n >= 1<<4) { n >= 4; p += 4; }
    if (n >= 1<<2) { n >= 2; p += 2; }
    if (n >= 1<<1) { p += 1; }
    return p;
}

void DFS(int i, int l)
{
    L[i] = l;
    for(int j = 0; j < children[i].size(); j++)
        DFS(children[i][j], l+1);
}

int LCA(int p, int q) {
    // ensure node p is at least as deep as node q
    if(L[p] < L[q]) swap(p, q);

    // "binary search" for the ancestor of node p situated on the same level as q
    for(int i = log_num_nodes; i >= 0; i--)
        if(L[p] - (1<<i) >= L[q])
            p = A[p][i];
    if(p == q) return p;

    // "binary search" for the LCA
    for(int i = log_num_nodes; i >= 0; i--)
    {
        if(A[p][i] != -1 && A[p][i] != A[q][i])
        {
            p = A[p][i];
            q = A[q][i];
        }
    }
    return A[p][0];
}

int main(int argc, char* argv[])
{
    // read num_nodes, the total number of nodes
    log_num_nodes = lb(num_nodes);
    for(int i = 0; i < num_nodes; i++)
    {
        int p;
        // read p, the parent of node i or -1 if node i is the root
        A[i][0] = p;
        if(p != -1) children[p].push_back(i);
        else root = i;
    }
    // precompute A using dynamic programming
    for(int j = 1; j <= log_num_nodes; j++)
        for(int i = 0; i < num_nodes; i++)
            if(A[i][j-1] != -1) A[i][j] = A[A[i][j-1]][j-1];
            else A[i][j] = -1;
    // precompute L
    DFS(root, 0);
    return 0;
}

```

## 2.7 Strongly Connected Components

```

#include <memory.h>

struct edge
{
    int e, nxt;
};

int V, E;
edge e[MAXE], er[MAXE];

```

```

int sp[MAXV], spr[MAXV];
int group_cnt, group_num[MAXV];
bool v[MAXV];
int stk[MAXV];

void fill_forward(int x)
{
    int i;
    v[x] = true;
    for(i = sp[x]; i != e[i].nxt)
        if(!v[e[i].e]) fill_forward(e[i].e);
    stk[++stk[0]] = x;
}

void fill_backward(int x)
{
    int i;
    v[x] = false;
    group_num[x] = group_cnt;
    for(i = spr[x]; i != er[i].nxt)
        if(v[er[i].e]) fill_backward(er[i].e);
}

void add_edge(int v1, int v2) //add edge v1->v2
{
    e[++E].e = v2;
    e[E].nxt = sp[v1];
    sp[v1] = E;
    er[E].e = v1;
    er[E].nxt = spr[v2];
    spr[v2] = E;
}

void SCC()
{
    int i;
    stk[0] = 0;
    memset(v, false, sizeof(v));
    for(i = 1; i <= V; i++)
        if(!v[i]) fill_forward(i);

    group_cnt = 0;
    for(i = stk[0]; i >= 1; i--)
        if(v[stk[i]]) { group_cnt++; fill_backward(stk[i]); }
}

```

## 2.8 Union-Find Set

```

struct Edge // MST
{
    int a, b, d;
    bool operator < (const Edge &E) const {
        return this->d < E.d;
    }
};

int ranks[M]; int c[N];

int Find(int x)
{
    int y = x;
    while(y != c[y])
        y = c[y];
    while(x != c[x])
    {
        int aux = c[x];
        c[x] = y;
        x = aux;
    }
    return y;
}

void Union(int x, int y)
{
    if(ranks[x] > ranks[y])
        c[x] = y;
    else
        c[y] = x;
    if(ranks[x] == ranks[y])
        ranks[y]++;
}

```

## 3 Tree

### 3.1 Cartesian Tree

```

struct Tr
{
    Tr *l,*r;
    int key,pr,cnt,val,rev;
    long long sum;
    Tr(int new_key,int new_pr,int new_val)
    {
        rev=0;
        key=new_key;
        cnt=1;
        l=r=NULL;
        pr=new_pr;
        val=new_val;
        sum=new_val;
    }
};

#define T Tr*
T R=NULL;

int cnt(T t)
{
    if(!t) return 0;
    return t->cnt;
}

void upd_cnt(T &t)
{
    if(t) t->cnt=cnt(t->l)+cnt(t->r)+1;
}

long long sum(T t)
{
    if(!t) return 0;
    return t->sum;
}

void upd_sum(T &t)
{
    if(t) t->sum=sum(t->l)+sum(t->r)+t->val;
}

void push(T &t)
{
    if(t && t->rev)
    {
        t->rev=0;
        swap(t->l,t->r);
        upd_sum(t);
        if(t->l) t->l->rev^=1;
        if(t->r) t->r->rev^=1;
    }
}

void split(T t,T &l,T &r,int key,int add)
{
    if(!t) return void(l=r=NULL);
    push(t);
    upd_cnt(t);
    int current_key=add+cnt(t->l)+1;
    if(key<=current_key)
        split(t->l,l,t->l,key,add),r=t;
    else
        split(t->r,t->r,r,key,current_key),l=t;
    upd_cnt(t);
    upd_sum(t);
}

void merge(T &t,T l,T r)
{
    push(l);
    push(r);
    if(!l || !r)
        t=l?l:r;
    else if(l->pr>r->pr)
        merge(l->r,l->r,r), t=l;
    else
        merge(r->l,l,r->l), t=r;
    upd_cnt(t);
    upd_sum(t);
}

```

```

}

void insert(T &t,T it,int add)
{
    push(t);
    if(!t)
    {
        t=it;
        upd_cnt(t);
        return;
    }
    upd_sum(t);
    if(it->pr > t->pr)
        split(t,it->l,it->r,it->key,add),t=it;
    else if(it->key>add+cnt(t->l)+1)
        insert(t->r,it,add+cnt(t->l)+1);
    else
        insert(t->l,it,add);
    upd_sum(t);
    upd_cnt(t);
}

void print(T t)
{
    if(!t) return;
    print(t->l);
    cout<<t->val<<" ";
    print(t->r);
}

void reverse(int left,int right)
{
    Tr *t1,*t2,*t3;
    t1=t2=t3=NULL;
    split(R,t1,t2,left,0);
    split(t2,t2,t3,right-left+2,0);
    t2->rev^=1;
    merge(R,t1,t2);
    merge(R,R,t3);
}

void get_sum(int left,int right)
{
    Tr *t1,*t2,*t3;
    t1=t2=t3=NULL;
    split(R,t1,t2,left,0);
    split(t2,t2,t3,right-left+2,0);
    cout<<t2->sum<<"\n";
    merge(R,t1,t2);
    merge(R,R,t3);
}

int n,m, q,a,b;
void example()
{
    ios_base::sync_with_stdio(0);
    cin.tie(0);
    freopen("reverse.in","r",stdin);
    freopen("reverse.out","w",stdout);
    srand(time(0));
    cin>>n>>m;
    for(int i=1;i<=n;++i)
    {
        cin>>a;
        T it=new Tr(i,rand()+1,a);
        insert(R,it,0);
    }
    for(int i=0;i<m;++i)
    {
        cin>>q>>a>>b;
        if(q) reverse(a,b);
        else get_sum(a,b);
    }
    return 0;
}

```

### 3.2 Segment Tree

```

//Segment Tree
#include <iostream>
#define N (1<<18)

using namespace std;
//int find(vector <int>& C, int x){return (C[x]==x) ? x : C[x]=find(C, C[x]);} C++
//int find(int x){return (C[x]==x)?x:C[x]=find(C[x]);}

```

```

typedef pair<int,int> ii;
ii arb[N]={0,0};
int n,m,a,b,v;
char type;

void update(int node,int l,int r,int a,int b,int val,int p)
{
    if(a<=l && r<=b)
    {
        arb[node].first=val;
        arb[node].second=p;
    }
    else
    {
        int mid=(l+r)/2;
        if(a<=mid)
            update(node*2,l,mid,a,b,val,p);
        if(b>mid)
            update(2*node+1,mid+1,r,a,b,val,p);
    }
}

pair<int,int> search(int node,int l,int r,int a)
{
    if(a==l && a==r)
    {
        return arb[node];
    }
    else
    {
        int mid=(l+r)/2;
        ii cur;
        if(a<=mid)
            cur=search(2*node,l,mid,a);
        else
            cur=search(2*node+1,mid+1,r,a);
        if(cur.second<arb[node].second)
            return arb[node];
        else
            return cur;
    }
}

```

## 4 Math

### 4.1 Extended Euclid's Algorithm

```

#include "GcdLcm.h"

// returns d = gcd(a,b); find x, y such that d = ax + by
int extended_euclid(int a, int b, int &x, int &y){
    int current_x = y = 0;
    int current_y = x = 1;
    while(b)
    {
        int q = a/b;
        int t = b;
        b = a%b;
        a = t;
        t = current_x; current_x = x-q*current_x; x = t;
        t = current_y; current_y = y-q*current_y; y = t;
    }
    return a;
}

```

### 4.2 Fast Prime Number Sieve

```

// compute prime numbers to N really fast (Sieve)
#define N 10000100
vector<int> primes;
char p[N/8];

void GeneratePrimes()
{
    primes.push_back(2);
    int i,j;
    for(i=1; ((i+1)<<1)+(i<<1)<N; ++i)
    {
        if((p[i>>3] & (1<<(i&7)))==0)

```

```

        primes.push_back((i<<1)+1);
        for(j=((i+1)<<1)+(i<<1),k=(i<<1)+1; (j<<1)+1<N; j+=k)
        {
            p[j>>3] |= (1<<(j&7));
        }
    }
}

for(; (i<<1)+1<N; ++i)
{
    if((p[i>>3] & (1<<(i&7)))==0)
    {
        primes.push_back((i<<1)+1);
    }
}
}

```

### 4.3 Fast Fourier Transform

```

struct cpx
{
    cpx() {}
    cpx(double aa): a(aa) {}
    cpx(double aa, double bb): a(aa), b(bb) {}
    double a;
    double b;
    double modsq(void) const{ return a*a+b*b; }
    cpx bar(void) const {return cpx(a,-b);}
};

cpx b[N+100],c[N+100],B[N+100],C[N+100];
int a[N+100], int x[N+100];
double coss[N+100], sins[N+100];
int n,m,p;

cpx operator +(cpx a,cpx b) { return cpx(a.a+b.a,a.b+b.b); }
cpx operator *(cpx a,cpx b) { return cpx(a.a*b.a-a.b*b.b,a.a*b.b+a.b*b.a); }
cpx operator /(cpx a,cpx b) { cpx r = a*b.bar(); return cpx(r.a/b.modsq(),r.b/b.modsq()); }
cpx EXP(int i,int dir) { return cpx(coss[i],sins[i]*dir); }

const double two_pi = 4 * acos(0);

void FFT(cpx *in,cpx *out,int step,int size,int dir)
{
    if(size<1) return;
    if(size==1)
    {
        out[0]=in[0];
        return;
    }
    FFT(in,out,step*2,size/2,dir);
    FFT(in+step,out+size/2,step*2,size/2,dir);
    for(int i=0;i<size/2; ++i)
    {
        cpx even=out[i];
        cpx odd=out[i+size/2];
        out[i] = even+EXP(i*step,dir)*odd;
        out[i+size/2]=even+EXP((i+size/2)*step,dir)*odd;
    }
}

void exemple
{
    for(int i=0;i<N; ++i)
    {
        coss[i]=cos(two_pi*i/N);
        sins[i]=sin(two_pi*i/N);
    }
    while(scanf("%d",&n)==1)
    {
        fill(x,x+N+100,0);
        fill(a,a+N+100,0);
        for(int i=0;i<n; ++i)
        {
            scanf("%d",&p);
            x[p]=1;
        }
        for(int i=0;i<N+100; ++i)
        {
            b[i]=cpx(x[i],0);
        }
        scanf("%d",&m);
        for(int i=0;i<m; ++i)
        {
            scanf("%d",&a[i]);
        }
    }
}

```

```

        FFT(b,B,1,N,1);
        for(int i=0;i<N;++i)
            C[i]=B[i]*B[i];
        FFT(C,c,1,N,-1);
        for(int i=0;i<N;++i)
            c[i]=c[i]/N;
        int cnt=0;
        for(int i=0;i<16;++i)
            cout<<c[i].a<<" ";
        for(int i=0;i<m;++i)
            if(c[a[i]].a>0.5 || x[a[i]])
                cnt++;
        printf("%d\n",cnt);
    }
}

```

## 4.4 Gauss-Jordan Elimination

```

/*
Stanford notebook
-----
GaussJordan Algorithm (elimination with full pivoting)
Uses:
(1) solving systems of linear equations (AX=B)
(2) inverting matrices (AX=I)
(3) computing determinants of square matrices
Running time: O(n^3)
INPUT:  a[][] = an nxn matrix
        b[][] = an nxm matrix
OUTPUT: X      = an nxm matrix (stored in b[][])
        A^{-1} = an nxn matrix (stored in a[][])
        returns determinant of a[][]
-----
*/

const double EPS = 1e-10;
typedef vector<int> VI;
typedef double T;
typedef vector<T> VT;
typedef vector<VT> VVT;

T GaussJordan(VVT &a, VVT &b)
{
    const int n = a.size();
    const int m = b[0].size();
    VI irow(n), icol(n), ipiv(n);
    T det = 1;

    for (int i = 0; i < n; i++)
    {
        int pj = -1, pk = -1;
        for (int j = 0; j < n; j++)
            if (!ipiv[j])
                for (int k = 0; k < n; k++)
                    if (!ipiv[k])
                        if (pj == -1 || fabs(a[j][k]) > fabs(a[pj][pk])) { pj = j; pk = k; }

        if (fabs(a[pj][pk]) < EPS)
        {
            cerr << "Matrix is singular." << endl;
            exit(0);
        }

        ipiv[pj]++;
        swap(a[pj], a[pk]);
        swap(b[pj], b[pk]);
        if (pj != pk) det *= -1;
        irow[i] = pj;
        icol[i] = pk;

        T c = 1.0 / a[pk][pk];
        det *= a[pk][pk];
        a[pk][pk] = 1.0;

        for (int p = 0; p < n; p++)
            a[pk][p] *= c;
        for (int p = 0; p < m; p++)
            b[pk][p] *= c;
        for (int p = 0; p < n; p++)
        {
            if (p != pk)
            {
                c = a[p][pk];
                a[p][pk] = 0;
                for (int q = 0; q < n; q++)
                    a[p][q] -= a[pk][q] * c;
                for (int q = 0; q < m; q++)
                    b[p][q] -= b[pk][q] * c;
            }
        }
    }
}

```

```

    }
    for (int p = n-1; p >= 0; p--)
    {
        if (irow[p] != icol[p])
        {
            for (int k = 0; k < n; k++)
                swap(a[k][irow[p]], a[k][icol[p]]);
        }
        return det;
    }
}

int main()
{
    const int n = 4;
    const int m = 2;
    double A[n][n] = { {1,2,3,4},{1,0,1,0},{5,3,2,4},{6,1,4,6} };
    double B[n][m] = { {1,2},{4,3},{5,6},{8,7} };
    VVT a(n), b(n);
    for (int i = 0; i < n; i++)
    {
        a[i] = VT(A[i], A[i] + n);
        b[i] = VT(B[i], B[i] + m);
    }
    double det = GaussJordan(a, b);
    // expected: 60
    cout << "Determinant: " << det << endl;
    // expected: -0.233333 0.166667 0.133333 0.0666667
    //           0.166667 0.166667 0.333333 -0.333333
    //           0.233333 0.833333 -0.133333 -0.0666667
    //           0.05 -0.75 -0.1 0.2
    cout << "Inverse: " << endl;
    for (int i = 0; i < n; i++)
    {
        for (int j = 0; j < n; j++)
            cout << a[i][j] << ' ';
        cout << endl;
    }
    // expected: 1.63333 1.3
    //           -0.166667 0.5
    //           2.36667 1.7
    //           -1.85 -1.35
    cout << "Solution: " << endl;
    for (int i = 0; i < n; i++)
    {
        for (int j = 0; j < m; j++)
            cout << b[i][j] << ' ';
        cout << endl;
    }
}

```

## 4.5 GCD and LCM

```

// return a*b
int mod(int a, int b)
{
    return ((a%b)+b)%b;
}

// computes gcd(a,b)
int gcd(int a, int b)
{
    int tmp;
    while(b)
    {
        a %= b;
        tmp = a;
        a = b;
        b = tmp;
    }
    return a;
}

// computes lcm(a,b)
int lcm(int a, int b)
{
    return a/gcd(a,b)*b;
}

```

## 4.6 Modular Linear Equation Solver



```
// Stanford Notebook
#include <vector>
#include "ExtendedEuclid.h"

// find all solutions to ax = b (mod n)
vector<int> modular_linear_equation_solver(int a, int b, int n)
{
    int x, y;
    vector<int> sol;
    int d = extended_euclid(a, n, x, y);
    if(!(b%d)) {
        x = mod(x*(b/d), n);
        for(int i=0; i < d; ++i)
            sol.push_back(mod(x + i*(n/d), n));
    }
    return sol;
}

// computes b such tath ab = 1(mod n), returns -1 on failure
int mod_inverse(int a, int n)
{
    int x, y;
    int d = extended_euclid(a, n, x, y);
    if(d>1) return -1;
    return mod(x, n);
}

// computes x and y such that ax + by = c; on failure, x = y = -1
void linear_diophantine(int a, int b, int c, int &x, int &y)
{
    int d = gcd(a, b);
    if(c%d) x = y = -1;
    else {
        x = c/d + mod_inverse(a/d, b/d);
        y = (c-a*x)/b;
    }
}

```

## 5 Strings

### 5.1 Aho-Corasick Algorithm

```
/*
Implementation - Benoit Chabod
=====
Aho Corasick algorithm
=====
*/

struct node
{
    int f;
    map<char, int> g;
    vector<short> out;
    node(int fail = -1): f(fail) {}
};

vector<node> nodes;

void add_str(const string &s, int num)
{
    int cur = 0;
    int n = s.size();
    for(int i = 0; i < n; ++i)
    {
        auto it = nodes[cur].g.find(s[i]);
        if(it == nodes[cur].g.end())
        {
            nodes[cur].g[s[i]] = nodes.size();
            cur = nodes.size();
            nodes.push_back(node());
        }
        else {
            cur = it->second;
        }
    }
    nodes[cur].out.push_back(num);
}

void init_fail()
{
    int cur = 0;

```

```
queue<int> q;
q.push(cur);

while( !q.empty() )
{
    cur = q.front();
    map<char, int>::iterator it;
    for(it = nodes[cur].g.begin(); it != nodes[cur].g.end(); it++)
    {
        int child = it->second;
        int pfail = nodes[cur].f;
        char ch = it->first;
        map<char, int>::iterator f;
        while( pfail != -1 && ((f = nodes[pfail].g.find(ch)) == nodes[pfail].g.end()) )
        {
            pfail = nodes[pfail].f;
        }
        nodes[child].f = (pfail == -1)? 0 : f->second;
        pfail = nodes[child].f;
        nodes[child].out.insert(nodes[child].out.end(), nodes[pfail].out.begin(), nodes[pfail].out.end());
        q.push(child);
    }
    q.pop();
}

// Usage
void usage()
{
    nodes.push_back(node());
    for [each word] add_str(word, i)
        init_fail();
    for [each letter]
    {
        map<char, int>::iterator f;
        while( cur != -1 && ((f = nodes[cur].g.find(letter)) == nodes[cur].g.end()) )
        {
            cur = nodes[cur].f;
            if( cur == -1 )
            {
                cur = 0;
                continue;
            }
        }
        cur = f->second;
        for(auto v : nodes[cur].out)
        {
            // Word v was found
        }
    }
}

```

### 5.2 Knuth-Morris-Pratt Algorithm

```
/*
-----
KMP/Pi function
Note : cin>>(s+1) (the operations in the pi-function start at 1)
-----
*/

void preKmp()
{
    int k;
    k=kmpNext[1]=0;
    for(int i=2; i<=n; ++i)
    {
        while(k && p[k+1]!=p[i]) k=kmpNext[k];
        if(p[k+1]==p[i])
            k++;
        kmpNext[i]=k;
    }
}

void KMP()
{
    preKmp();
    int k=0;

    for(int i=1; i<=m; ++i)
    {
        while(k && p[k+1]!=s[i])
            k=kmpNext[k];
        if(p[k+1]==s[i])
            k++;
        if(k==n)
        {
            // here we have a match
            k=kmpNext[k];
        }
    }
}

```

## 5.3 Suffix Array

```
//Suffix Array

struct SuffixArray
{
    const int L;
    string s;
    vector<vector<int>> > P;
    vector<pair<pair<int,int>,int>> > M;
    SuffixArray(const string &s) : L(s.length()), s(s), P(1, vector<int>(L, 0)), M(L)
    {
        for (int i = 0; i < L; i++)
            P[0][i] = int(s[i]);
        for (int skip = 1, level = 1; skip < L; skip *= 2, level++)
        {
            P.push_back(vector<int>(L, 0));
            for (int i = 0; i < L; i++)
                M[i] = make_pair(make_pair(P[level-1][i], i + skip < L ? P[level-1][i]
                    + skip : -1000), i);
            sort(M.begin(), M.end());
            for (int i = 0; i < L; i++)
                P[level][M[i].second] = (i > 0 && M[i].first == M[i-1].first) ? P[
                    level][M[i-1].second] : i;
        }
    }

    vector<int> GetSuffixArray()
    {
        return P.back();
    }

    // returns the length of the longest common prefix of s[i...L-1] and s[j...L-1]
    int LongestCommonPrefix(int i, int j)
    {
        int len = 0;
        if (i == j) return L - i;
        for (int k = P.size() - 1; k >= 0 && i < L && j < L; k--)
        {
            if (P[k][i] == P[k][j])
            {
                i += 1 << k;
                j += 1 << k;
                len += 1 << k;
            }
        }
        return len;
    }
};

int main()
{
    // bobocel is the 0'th suffix
    // obocel is the 5'th suffix
    // bocel is the 1'st suffix
    // ocel is the 6'th suffix
    // cel is the 2'nd suffix
    // el is the 3'rd suffix
    // l is the 4'th suffix
    SuffixArray suffix("bobocel");
    vector<int> v = suffix.GetSuffixArray();
    // Expected output: 0 5 1 6 2 3 4
    //
    // 2
    for (int i = 0; i < v.size(); i++)
        cout << v[i] << " ";
    cout << endl;
    cout << suffix.LongestCommonPrefix(0, 2) << endl;
}
```

## 6 Techniques

### 6.1 Various algorithm techniques

Recursion  
Divide and conquer

Finding interesting points in  $N \log N$

Greedy algorithm

- Scheduling
- Max contiguous subvector sum
- Invariants
- Huffman encoding

Graph theory

- Dynamic graphs (extra book-keeping)
- Breadth first search
- Depth first search
- \* Normal trees / DFS trees
- Dijkstra's algorithm
- MST: Prim's algorithm
- Bellman-Ford
- Konig's theorem and vertex cover
- Min-cost max flow
- Lovasz toggle
- Matrix tree theorem
- Maximal matching, general graphs
- Hopcroft-Karp
- Hall's marriage theorem
- Graphical sequences
- Floyd-Warshall
- Eulercykler
- Flow networks
- \* Augmenting paths
- \* Edmonds-Karp
- Bipartite matching
- Min. path cover
- Topological sorting
- Strongly connected components
- 2-SAT
- Cutvertices, cutedges och biconnected components
- Edge coloring
- \* Trees
- Vertex coloring
- \* Bipartite graphs ( $\Rightarrow$  trees)
- \*  $3^n$  (special case of set cover)
- Diameter and centroid
- K'th shortest path
- Shortest cycle

Dynamic programming

- Knapsack
- Coin change
- Longest common subsequence
- Longest increasing subsequence
- Number of paths in a dag
- Shortest path in a dag
- Dynprog over intervals
- Dynprog over subsets
- Dynprog over probabilities
- Dynprog over trees
- $3^n$  set cover
- Divide and conquer
- Knuth optimization
- Convex hull optimizations
- RMQ (sparse table a.k.a  $2^k$ -jumps)
- Bitonic cycle
- Log partitioning (loop over most restricted)

Combinatorics

- Computation of binomial coefficients
- Pigeon-hole principle
- Inclusion/exclusion
- Catalan number
- Pick's theorem

Number theory

- Integer parts
- Divisibility
- Euklidean algorithm
- Modular arithmetic
- \* Modular multiplication
- \* Modular inverses
- \* Modular exponentiation by squaring
- Chinese remainder theorem
- Fermat's small theorem
- Euler's theorem
- Phi function
- Frobenius number
- Quadratic reciprocity
- Pollard-Rho
- Miller-Rabin
- Hensel lifting
- Vieta root jumping

Game theory

- Combinatorial games
- Game trees
- Mini-max
- Nim
- Games on graphs
- Games on graphs with loops
- Grundy numbers
- Bipartite games without repetition

- General games without repetition
- Alpha-beta pruning
- Probability theory
- Optimization
  - Binary search
  - Ternary search
  - Unimodality and convex functions
  - Binary search on derivative
- Numerical methods
  - Numeric integration
  - Newton's method
  - Root-finding with binary/ternary search
  - Golden section search
- Matrices
  - Gaussian elimination
  - Exponentiation by squaring
- Sorting
  - Radix sort
- Geometry
  - Coordinates and vectors
    - \* Cross product
    - \* Scalar product
  - Convex hull
  - Polygon cut
  - Closest pair
  - Coordinate-compression
  - Quadrees
  - KD-trees
  - All segment-segment intersection
- Sweeping
  - Discretization (convert to events and sweep)
  - Angle sweeping
  - Line sweeping

- Discrete second derivatives
- Strings
  - Longest common substring
  - Palindrome subsequences
  - Knuth-Morris-Pratt
  - Tries
  - Rolling polynomial hashes
  - Suffix array
  - Suffix tree
  - Aho-Corasick
  - Manacher's algorithm
  - Letter position lists
- Combinatorial search
  - Meet in the middle
  - Brute-force with pruning
  - Best-first (A\*)
  - Bidirectional search
  - Iterative deepening DFS / A\*
- Data structures
  - LCA (2\*k-jumps in trees in general)
  - Pull/push-technique on trees
  - Heavy-light decomposition
  - Centroid decomposition
  - Lazy propagation
  - Self-balancing trees
  - Convex hull trick ([wcipeg.com/wiki/Convex\\_hull\\_trick](http://wcipeg.com/wiki/Convex_hull_trick))
  - Monotone queues / monotone stacks / sliding queues
  - Sliding queue using 2 stacks
  - Persistent segment tree

---

$f(n) = O(g(n))$	iff $\exists$ positive $c, n_0$ such that $0 \leq f(n) \leq cg(n) \forall n \geq n_0$ .	$\sum_{i=1}^n i = \frac{n(n+1)}{2}, \quad \sum_{i=1}^n i^2 = \frac{n(n+1)(2n+1)}{6}, \quad \sum_{i=1}^n i^3 = \frac{n^2(n+1)^2}{4}.$
$f(n) = \Omega(g(n))$	iff $\exists$ positive $c, n_0$ such that $f(n) \geq cg(n) \geq 0 \forall n \geq n_0$ .	In general:
$f(n) = \Theta(g(n))$	iff $f(n) = O(g(n))$ and $f(n) = \Omega(g(n))$ .	$\sum_{i=1}^n i^m = \frac{1}{m+1} \left[ (n+1)^{m+1} - 1 - \sum_{i=1}^n ((i+1)^{m+1} - i^{m+1} - (m+1)i^m) \right]$
$f(n) = o(g(n))$	iff $\lim_{n \rightarrow \infty} f(n)/g(n) = 0$ .	$\sum_{i=1}^{n-1} i^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k n^{m+1-k}.$
$\lim_{n \rightarrow \infty} a_n = a$	iff $\forall \epsilon > 0, \exists n_0$ such that $ a_n - a  < \epsilon, \forall n \geq n_0$ .	Geometric series:
$\sup S$	least $b \in \mathbb{R}$ such that $b \geq s, \forall s \in S$ .	$\sum_{i=0}^n c^i = \frac{c^{n+1} - 1}{c - 1}, \quad c \neq 1, \quad \sum_{i=0}^{\infty} c^i = \frac{1}{1 - c}, \quad \sum_{i=1}^{\infty} c^i = \frac{c}{1 - c}, \quad  c  < 1,$
$\inf S$	greatest $b \in \mathbb{R}$ such that $b \leq s, \forall s \in S$ .	$\sum_{i=0}^n i c^i = \frac{nc^{n+2} - (n+1)c^{n+1} + c}{(c-1)^2}, \quad c \neq 1, \quad \sum_{i=0}^{\infty} i c^i = \frac{c}{(1-c)^2}, \quad  c  < 1.$
$\liminf_{n \rightarrow \infty} a_n$	$\lim_{n \rightarrow \infty} \inf \{a_i \mid i \geq n, i \in \mathbb{N}\}.$	Harmonic series:
$\limsup_{n \rightarrow \infty} a_n$	$\lim_{n \rightarrow \infty} \sup \{a_i \mid i \geq n, i \in \mathbb{N}\}.$	$H_n = \sum_{i=1}^n \frac{1}{i}, \quad \sum_{i=1}^n i H_i = \frac{n(n+1)}{2} H_n - \frac{n(n-1)}{4}.$
$\binom{n}{k}$	Combinations: Size $k$ subsets of a size $n$ set.	$\sum_{i=1}^n H_i = (n+1)H_n - n, \quad \sum_{i=1}^n \binom{i}{m} H_i = \binom{n+1}{m+1} \left( H_{n+1} - \frac{1}{m+1} \right).$
$[n]$	Stirling numbers (1st kind): Arrangements of an $n$ element set into $k$ cycles.	1. $\binom{n}{k} = \frac{n!}{(n-k)!k!}, \quad 2. \sum_{k=0}^n \binom{n}{k} = 2^n, \quad 3. \binom{n}{k} = \binom{n}{n-k},$
$\left\{ \begin{smallmatrix} n \\ k \end{smallmatrix} \right\}$	Stirling numbers (2nd kind): Partitions of an $n$ element set into $k$ non-empty sets.	4. $\binom{n}{k} = \frac{n}{k} \binom{n-1}{k-1}, \quad 5. \binom{n}{k} = \binom{n-1}{k} + \binom{n-1}{k-1},$
$\langle \begin{smallmatrix} n \\ k \end{smallmatrix} \rangle$	1st order Eulerian numbers: Permutations $\pi_1 \pi_2 \dots \pi_n$ on $\{1, 2, \dots, n\}$ with $k$ ascents.	6. $\binom{n}{m} \binom{m}{k} = \binom{n}{k} \binom{n-k}{m-k}, \quad 7. \sum_{k=0}^n \binom{r+k}{k} = \binom{r+n+1}{n},$
$\langle \langle \begin{smallmatrix} n \\ k \end{smallmatrix} \rangle \rangle$	2nd order Eulerian numbers.	8. $\sum_{k=0}^n \binom{k}{m} = \binom{n+1}{m+1}, \quad 9. \sum_{k=0}^n \binom{r}{k} \binom{s}{n-k} = \binom{r+s}{n},$
$C_n$	Catalan Numbers: Binary trees with $n+1$ vertices.	10. $\binom{n}{k} = (-1)^k \binom{k-n-1}{k}, \quad 11. \left\{ \begin{smallmatrix} n \\ 1 \end{smallmatrix} \right\} = \left\{ \begin{smallmatrix} n \\ n \end{smallmatrix} \right\} = 1,$
14. $\begin{bmatrix} n \\ 1 \end{bmatrix} = (n-1)!,$	15. $\begin{bmatrix} n \\ 2 \end{bmatrix} = (n-1)!H_{n-1},$	16. $\begin{bmatrix} n \\ n \end{bmatrix} = 1, \quad 17. \begin{bmatrix} n \\ k \end{bmatrix} \geq \left\{ \begin{smallmatrix} n \\ k \end{smallmatrix} \right\},$
18. $\begin{bmatrix} n \\ k \end{bmatrix} = (n-1) \begin{bmatrix} n-1 \\ k \end{bmatrix} + \begin{bmatrix} n-1 \\ k-1 \end{bmatrix},$	19. $\left\{ \begin{smallmatrix} n \\ n-1 \end{smallmatrix} \right\} = \begin{bmatrix} n \\ n-1 \end{bmatrix} = \binom{n}{2},$	20. $\sum_{k=0}^n \begin{bmatrix} n \\ k \end{bmatrix} = n!, \quad 21. C_n = \frac{1}{n+1} \binom{2n}{n},$
22. $\langle \begin{smallmatrix} n \\ 0 \end{smallmatrix} \rangle = \langle \begin{smallmatrix} n \\ n-1 \end{smallmatrix} \rangle = 1,$	23. $\langle \begin{smallmatrix} n \\ k \end{smallmatrix} \rangle = \langle \begin{smallmatrix} n \\ n-1-k \end{smallmatrix} \rangle,$	24. $\langle \begin{smallmatrix} n \\ k \end{smallmatrix} \rangle = (k+1) \langle \begin{smallmatrix} n-1 \\ k \end{smallmatrix} \rangle + (n-k) \langle \begin{smallmatrix} n-1 \\ k-1 \end{smallmatrix} \rangle,$
25. $\langle \begin{smallmatrix} 0 \\ k \end{smallmatrix} \rangle = \begin{cases} 1 & \text{if } k=0, \\ 0 & \text{otherwise} \end{cases}$	26. $\langle \begin{smallmatrix} n \\ 1 \end{smallmatrix} \rangle = 2^n - n - 1,$	27. $\langle \begin{smallmatrix} n \\ 2 \end{smallmatrix} \rangle = 3^n - (n+1)2^n + \binom{n+1}{2},$
28. $x^n = \sum_{k=0}^n \langle \begin{smallmatrix} n \\ k \end{smallmatrix} \rangle \binom{x+k}{n},$	29. $\langle \begin{smallmatrix} n \\ m \end{smallmatrix} \rangle = \sum_{k=0}^m \binom{n+1}{k} (m+1-k)^n (-1)^k,$	30. $m! \left\{ \begin{smallmatrix} n \\ m \end{smallmatrix} \right\} = \sum_{k=0}^n \langle \begin{smallmatrix} n \\ k \end{smallmatrix} \rangle \binom{k}{n-m},$
31. $\langle \begin{smallmatrix} n \\ m \end{smallmatrix} \rangle = \sum_{k=0}^n \left\{ \begin{smallmatrix} n \\ k \end{smallmatrix} \right\} \binom{n-k}{m} (-1)^{n-k-m} k!,$	32. $\langle \langle \begin{smallmatrix} n \\ 0 \end{smallmatrix} \rangle \rangle = 1,$	33. $\langle \langle \begin{smallmatrix} n \\ n \end{smallmatrix} \rangle \rangle = 0 \quad \text{for } n \neq 0,$
34. $\langle \langle \begin{smallmatrix} n \\ k \end{smallmatrix} \rangle \rangle = (k+1) \langle \langle \begin{smallmatrix} n-1 \\ k \end{smallmatrix} \rangle \rangle + (2n-1-k) \langle \langle \begin{smallmatrix} n-1 \\ k-1 \end{smallmatrix} \rangle \rangle,$	35. $\sum_{k=0}^n \langle \langle \begin{smallmatrix} n \\ k \end{smallmatrix} \rangle \rangle = \frac{(2n)n}{2^n},$	
36. $\left\{ \begin{smallmatrix} x \\ x-n \end{smallmatrix} \right\} = \sum_{k=0}^n \langle \langle \begin{smallmatrix} n \\ k \end{smallmatrix} \rangle \rangle \binom{x+n-1-k}{2n},$	37. $\left\{ \begin{smallmatrix} n+1 \\ m+1 \end{smallmatrix} \right\} = \sum_k \binom{n}{k} \left\{ \begin{smallmatrix} k \\ m \end{smallmatrix} \right\} = \sum_{k=0}^n \left\{ \begin{smallmatrix} k \\ m \end{smallmatrix} \right\} (m+1)^{n-k},$	

38. $\begin{bmatrix} n+1 \\ m+1 \end{bmatrix} = \sum_k \begin{bmatrix} n \\ k \end{bmatrix} \begin{bmatrix} k \\ m \end{bmatrix} = \sum_{k=0}^n \begin{bmatrix} k \\ m \end{bmatrix} n^{n-k} = n! \sum_{k=0}^n \frac{1}{k!} \begin{bmatrix} k \\ m \end{bmatrix},$	39. $\begin{bmatrix} x \\ x-n \end{bmatrix} = \sum_{k=0}^n \left\langle \begin{bmatrix} n \\ k \end{bmatrix} \right\rangle \begin{bmatrix} x+k \\ 2n \end{bmatrix},$	Every tree with $n$ vertices has $n-1$ edges. Kraft inequality: If the depths of the leaves of a binary tree are $d_1, \dots, d_n$ : $\sum_{i=1}^n 2^{-d_i} \leq 1,$ and equality holds only if every internal node has 2 sons.
40. $\left\{ \begin{matrix} n \\ m \end{matrix} \right\} = \sum_k \binom{n}{k} \left\{ \begin{matrix} k+1 \\ m+1 \end{matrix} \right\} (-1)^{n-k},$	41. $\begin{bmatrix} n \\ m \end{bmatrix} = \sum_k \begin{bmatrix} n+1 \\ k+1 \end{bmatrix} \begin{bmatrix} k \\ m \end{bmatrix} (-1)^{m-k},$	
42. $\left\{ \begin{matrix} m+n+1 \\ m \end{matrix} \right\} = \sum_{k=0}^m k \left\{ \begin{matrix} n+k \\ k \end{matrix} \right\},$	43. $\begin{bmatrix} m+n+1 \\ m \end{bmatrix} = \sum_{k=0}^m k(n+k) \begin{bmatrix} n+k \\ k \end{bmatrix},$	
44. $\binom{n}{m} = \sum_k \left\{ \begin{matrix} n+1 \\ k+1 \end{matrix} \right\} \begin{bmatrix} k \\ m \end{bmatrix} (-1)^{m-k},$	45. $(n-m)! \binom{n}{m} = \sum_k \begin{bmatrix} n+1 \\ k+1 \end{bmatrix} \left\{ \begin{matrix} k \\ m \end{matrix} \right\} (-1)^{m-k}, \text{ for } n \geq m,$	
46. $\left\{ \begin{matrix} n \\ n-m \end{matrix} \right\} = \sum_k \binom{m-n}{m+k} \binom{m+n}{n+k} \begin{bmatrix} m+k \\ k \end{bmatrix},$	47. $\begin{bmatrix} n \\ n-m \end{bmatrix} = \sum_k \binom{m-n}{m+k} \binom{m+n}{n+k} \left\{ \begin{matrix} m+k \\ k \end{matrix} \right\},$	
48. $\left\{ \begin{matrix} n \\ \ell+m \end{matrix} \right\} \binom{\ell+m}{\ell} = \sum_k \left\{ \begin{matrix} k \\ \ell \end{matrix} \right\} \left\{ \begin{matrix} n-k \\ m \end{matrix} \right\} \binom{n}{k},$	49. $\begin{bmatrix} n \\ \ell+m \end{bmatrix} \binom{\ell+m}{\ell} = \sum_k \begin{bmatrix} k \\ \ell \end{bmatrix} \begin{bmatrix} n-k \\ m \end{bmatrix} \binom{n}{k}.$	

## Recurrences

Master method:

$$T(n) = aT(n/b) + f(n), \quad a \geq 1, b > 1$$

If  $\exists \epsilon > 0$  such that  $f(n) = O(n^{\log_b a - \epsilon})$  then

$$T(n) = \Theta(n^{\log_b a}).$$

If  $f(n) = \Theta(n^{\log_b a})$  then

$$T(n) = \Theta(n^{\log_b a} \log_2 n).$$

If  $\exists \epsilon > 0$  such that  $f(n) = \Omega(n^{\log_b a + \epsilon})$ , and  $\exists c < 1$  such that  $af(n/b) \leq cf(n)$  for large  $n$ , then

$$T(n) = \Theta(f(n)).$$

Substitution (example): Consider the following recurrence

$$T_{i+1} = 2^{2^i} \cdot T_i^2, \quad T_1 = 2.$$

Note that  $T_i$  is always a power of two.

Let  $t_i = \log_2 T_i$ . Then we have

$$t_{i+1} = 2^i + 2t_i, \quad t_1 = 1.$$

Let  $u_i = t_i/2^i$ . Dividing both sides of the previous equation by  $2^{i+1}$  we get

$$\frac{t_{i+1}}{2^{i+1}} = \frac{2^i}{2^{i+1}} + \frac{t_i}{2^i}.$$

Substituting we find

$$u_{i+1} = \frac{1}{2} + u_i, \quad u_1 = \frac{1}{2},$$

which is simply  $u_i = i/2$ . So we find that  $T_i$  has the closed form  $T_i = 2^{i2^{i-1}}$ .

Summing factors (example): Consider the following recurrence

$$T(n) = 3T(n/2) + n, \quad T(1) = 1.$$

Rewrite so that all terms involving  $T$  are on the left side

$$T(n) - 3T(n/2) = n.$$

Now expand the recurrence, and choose a factor which makes the left side “telescope”

$$1(T(n) - 3T(n/2)) = n$$

$$3(T(n/2) - 3T(n/4)) = n/2$$

$$\vdots \quad \vdots \quad \vdots$$

$$3^{\log_2 n - 1} (T(2) - 3T(1)) = 2$$

Let  $m = \log_2 n$ . Summing the left side we get  $T(n) - 3^m T(1) = T(n) - 3^m = T(n) - n^k$  where  $k = \log_2 3 \approx 1.58496$ . Summing the right side we get

$$\sum_{i=0}^{m-1} \frac{n}{2^i} 3^i = n \sum_{i=0}^{m-1} \left(\frac{3}{2}\right)^i.$$

Let  $c = \frac{3}{2}$ . Then we have

$$n \sum_{i=0}^{m-1} c^i = n \left( \frac{c^m - 1}{c - 1} \right)$$

$$= 2n(c^{\log_2 n} - 1)$$

$$= 2n(c^{(k-1)\log_2 n} - 1)$$

$$= 2n^k - 2n,$$

and so  $T(n) = 3n^k - 2n$ . Full history recurrences can often be changed to limited history ones (example): Consider

$$T_i = 1 + \sum_{j=0}^{i-1} T_j, \quad T_0 = 1.$$

Note that

$$T_{i+1} = 1 + \sum_{j=0}^i T_j.$$

Subtracting we find

$$\begin{aligned} T_{i+1} - T_i &= 1 + \sum_{j=0}^i T_j - 1 - \sum_{j=0}^{i-1} T_j \\ &= T_i. \end{aligned}$$

And so  $T_{i+1} = 2T_i = 2^{i+1}$ .

Generating functions:

1. Multiply both sides of the equation by  $x^i$ .
2. Sum both sides over all  $i$  for which the equation is valid.
3. Choose a generating function  $G(x)$ . Usually  $G(x) = \sum_{i=0}^{\infty} x^i g_i$ .
3. Rewrite the equation in terms of the generating function  $G(x)$ .
4. Solve for  $G(x)$ .
5. The coefficient of  $x^i$  in  $G(x)$  is  $g_i$ .

Example:

$$g_{i+1} = 2g_i + 1, \quad g_0 = 0.$$

Multiply and sum:

$$\sum_{i \geq 0} g_{i+1} x^i = \sum_{i \geq 0} 2g_i x^i + \sum_{i \geq 0} x^i.$$

We choose  $G(x) = \sum_{i \geq 0} x^i g_i$ . Rewrite in terms of  $G(x)$ :

$$\frac{G(x) - g_0}{x} = 2G(x) + \sum_{i \geq 0} x^i.$$

Simplify:

$$\frac{G(x)}{x} = 2G(x) + \frac{1}{1-x}.$$

Solve for  $G(x)$ :



$$G(x) = \frac{x}{(1-x)(1-2x)}.$$

Expand this using partial fractions:

$$\begin{aligned} G(x) &= x \left( \frac{2}{1-2x} - \frac{1}{1-x} \right) \\ &= x \left( 2 \sum_{i \geq 0} 2^i x^i - \sum_{i \geq 0} x^i \right) \\ &= \sum_{i \geq 0} (2^{i+1} - 1) x^{i+1}. \end{aligned}$$

So  $g_i = 2^i - 1$ .

$n \sim 0.11100,$			$\psi = 2 \sim 1.01000,$		
$\psi = 2 \sim 1.01000,$			$\psi = 2 \sim 1.01000,$		
$i$	$2^i$	$p_i$	General	Probability	
1	2	2	Bernoulli Numbers ( $B_i = 0$ , odd $i \neq 1$ ):	Continuous distributions: If	
2	4	3	$B_0 = 1, B_1 = -\frac{1}{2}, B_2 = \frac{1}{6}, B_4 = -\frac{1}{30},$	$\Pr[a < X < b] = \int_a^b p(x) dx,$	
3	8	5	$B_6 = \frac{1}{42}, B_8 = -\frac{1}{30}, B_{10} = \frac{5}{66}.$	then $p$ is the probability density function of	
4	16	7	Change of base, quadratic formula:	$X$ . If	
5	32	11	$\log_b x = \frac{\log_a x}{\log_a b}, \quad \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}.$	$\Pr[X < a] = P(a),$	
6	64	13	Euler's number $e$ :	then $P$ is the distribution function of $X$ . If	
7	128	17	$e = 1 + \frac{1}{2} + \frac{1}{6} + \frac{1}{24} + \frac{1}{120} + \dots$	$P$ and $p$ both exist then	
8	256	19	$\lim_{n \rightarrow \infty} \left(1 + \frac{x}{n}\right)^n = e^x.$	$P(a) = \int_{-\infty}^a p(x) dx.$	
9	512	23	$\left(1 + \frac{1}{n}\right)^n < e < \left(1 + \frac{1}{n}\right)^{n+1}.$	Expectation: If $X$ is discrete	
10	1,024	29	$\left(1 + \frac{1}{n}\right)^n = e - \frac{e}{2n} + \frac{11e}{24n^2} - O\left(\frac{1}{n^3}\right).$	$E[g(X)] = \sum_x g(x) \Pr[X = x].$	
11	2,048	31	Harmonic numbers:	If $X$ continuous then	
12	4,096	37	$1, \frac{3}{2}, \frac{11}{6}, \frac{25}{12}, \frac{137}{60}, \frac{49}{20}, \frac{363}{140}, \frac{761}{280}, \frac{7129}{2520}, \dots$	$E[g(X)] = \int_{-\infty}^{\infty} g(x)p(x) dx = \int_{-\infty}^{\infty} g(x) dP(x).$	
13	8,192	41	$\ln n < H_n < \ln n + 1,$	Variance, standard deviation:	
14	16,384	43	$H_n = \ln n + \gamma + O\left(\frac{1}{n}\right).$	$\text{VAR}[X] = E[X^2] - E[X]^2,$	
15	32,768	47	Factorial, Stirling's approximation:	$\sigma = \sqrt{\text{VAR}[X]}.$	
16	65,536	53	$1, 2, 6, 24, 120, 720, 5040, 40320, 362880, \dots$	For events $A$ and $B$ :	
17	131,072	59	$n! = \sqrt{2\pi n} \left(\frac{n}{e}\right)^n \left(1 + \Theta\left(\frac{1}{n}\right)\right).$	$\Pr[A \vee B] = \Pr[A] + \Pr[B] - \Pr[A \wedge B]$	
18	262,144	61	Ackermann's function and inverse:	$\Pr[A \wedge B] = \Pr[A] \cdot \Pr[B],$	
19	524,288	67	$a(i, j) = \begin{cases} 2^j & i = 1 \\ a(i-1, 2) & j = 1 \\ a(i-1, a(i, j-1)) & i, j \geq 2 \end{cases}$	iff $A$ and $B$ are independent.	
20	1,048,576	71	$\alpha(i) = \min\{j \mid a(j, j) \geq i\}.$	$\Pr[A B] = \frac{\Pr[A \wedge B]}{\Pr[B]}$	
21	2,097,152	73	Binomial distribution:	For random variables $X$ and $Y$ :	
22	4,194,304	79	$\Pr[X = k] = \binom{n}{k} p^k q^{n-k}, \quad q = 1 - p,$	$E[X \cdot Y] = E[X] \cdot E[Y],$	
23	8,388,608	83	$E[X] = \sum_{k=1}^n k \binom{n}{k} p^k q^{n-k} = np.$	if $X$ and $Y$ are independent.	
24	16,777,216	89	Poisson distribution:	$E[X + Y] = E[X] + E[Y],$	
25	33,554,432	97	$\Pr[X = k] = \frac{e^{-\lambda} \lambda^k}{k!}, \quad E[X] = \lambda.$	$E[cX] = cE[X].$	
26	67,108,864	101	Normal (Gaussian) distribution:	Bayes' theorem:	
27	134,217,728	103	$p(x) = \frac{1}{\sqrt{2\pi}\sigma} e^{-(x-\mu)^2/2\sigma^2}, \quad E[X] = \mu.$	$\Pr[A_i B] = \frac{\Pr[B A_i] \Pr[A_i]}{\sum_{j=1}^n \Pr[A_j] \Pr[B A_j]}.$	
28	268,435,456	107	The "coupon collector": We are given a	Inclusion-exclusion:	
29	536,870,912	109	random coupon each day, and there are $n$	$\Pr\left[\bigvee_{i=1}^n X_i\right] = \sum_{i=1}^n \Pr[X_i] +$	
30	1,073,741,824	113	different types of coupons. The distribu-	$\sum_{k=2}^n (-1)^{k+1} \sum_{i_1 < \dots < i_k} \Pr\left[\bigwedge_{j=1}^k X_{i_j}\right].$	
31	2,147,483,648	127	tion of coupons is uniform. The expected	Moment inequalities:	
32	4,294,967,296	131	number of days to pass before we to col-	$\Pr[ X  \geq \lambda E[X]] \leq \frac{1}{\lambda},$	
Pascal's Triangle			lect all $n$ types is	$\Pr[ X - E[X]  \geq \lambda \cdot \sigma] \leq \frac{1}{\lambda^2}.$	
1			$nH_n.$	Geometric distribution:	
1 1				$\Pr[X = k] = pq^{k-1}, \quad q = 1 - p,$	
1 2 1				$E[X] = \sum_{k=1}^{\infty} kpq^{k-1} = \frac{1}{p}.$	
1 3 3 1					
1 4 6 4 1					
1 5 10 10 5 1					
1 6 15 20 15 6 1					
1 7 21 35 35 21 7 1					
1 8 28 56 70 56 28 8 1					
1 9 36 84 126 126 84 36 9 1					
1 10 45 120 210 252 210 120 45 10 1					

<div></div> <p>Pythagorean theorem: <math>C^2 = A^2 + B^2.</math></p> <p>Definitions:</p> $\sin a = A/C, \quad \cos a = B/C,$ $\csc a = C/A, \quad \sec a = C/B,$ $\tan a = \frac{\sin a}{\cos a} = \frac{A}{B}, \quad \cot a = \frac{\cos a}{\sin a} = \frac{B}{A}.$ <p>Area, radius of inscribed circle:</p> $\frac{1}{2}AB, \quad \frac{AB}{A+B+C}.$ <p>Identities:</p> $\sin x = \frac{1}{\csc x}, \quad \cos x = \frac{1}{\sec x},$ $\tan x = \frac{1}{\cot x}, \quad \sin^2 x + \cos^2 x = 1,$ $1 + \tan^2 x = \sec^2 x, \quad 1 + \cot^2 x = \csc^2 x,$ $\sin x = \cos\left(\frac{\pi}{2} - x\right), \quad \sin x = \sin(\pi - x),$ $\cos x = -\cos(\pi - x), \quad \tan x = \cot\left(\frac{\pi}{2} - x\right),$ $\cot x = -\cot(\pi - x), \quad \csc x = \cot \frac{x}{2} - \cot x,$ $\sin(x \pm y) = \sin x \cos y \pm \cos x \sin y,$ $\cos(x \pm y) = \cos x \cos y \mp \sin x \sin y,$ $\tan(x \pm y) = \frac{\tan x \pm \tan y}{1 \mp \tan x \tan y},$ $\cot(x \pm y) = \frac{\cot x \cot y \mp 1}{\cot x \pm \cot y},$ $\sin 2x = 2 \sin x \cos x, \quad \sin 2x = \frac{2 \tan x}{1 + \tan^2 x},$ $\cos 2x = \cos^2 x - \sin^2 x, \quad \cos 2x = 2 \cos^2 x - 1,$ $\cos 2x = 1 - 2 \sin^2 x, \quad \cos 2x = \frac{1 - \tan^2 x}{1 + \tan^2 x},$ $\tan 2x = \frac{2 \tan x}{1 - \tan^2 x}, \quad \cot 2x = \frac{\cot^2 x - 1}{2 \cot x},$ $\sin(x + y) \sin(x - y) = \sin^2 x - \sin^2 y,$ $\cos(x + y) \cos(x - y) = \cos^2 x - \sin^2 y.$ <p>Euler's equation:</p> $e^{ix} = \cos x + i \sin x, \quad e^{i\pi} = -1.$	<p>Multiplication:</p> $C = A \cdot B, \quad c_{i,j} = \sum_{k=1}^n a_{i,k} b_{k,j}.$ <p>Determinants: <math>\det A \neq 0</math> iff <math>A</math> is non-singular.</p> $\det A \cdot B = \det A \cdot \det B,$ $\det A = \sum_{\pi} \prod_{i=1}^n \text{sign}(\pi) a_{i,\pi(i)}.$ <p><math>2 \times 2</math> and <math>3 \times 3</math> determinant:</p> $\begin{vmatrix} a & b \\ c & d \end{vmatrix} = ad - bc,$ $\begin{vmatrix} a & b & c \\ d & e & f \\ g & h & i \end{vmatrix} = g \begin{vmatrix} b & c \\ e & f \end{vmatrix} - h \begin{vmatrix} a & c \\ d & f \end{vmatrix} + i \begin{vmatrix} a & b \\ d & e \end{vmatrix}$ $= aei + bfg + cdh - ceg - fha - ibd.$ <p>Permanents:</p> $\text{perm } A = \sum_{\pi} \prod_{i=1}^n a_{i,\pi(i)}.$ <p>Hyperbolic Functions</p> <p>Definitions:</p> $\sinh x = \frac{e^x - e^{-x}}{2}, \quad \cosh x = \frac{e^x + e^{-x}}{2},$ $\tanh x = \frac{e^x - e^{-x}}{e^x + e^{-x}}, \quad \text{csch } x = \frac{1}{\sinh x},$ $\text{sech } x = \frac{1}{\cosh x}, \quad \coth x = \frac{1}{\tanh x}.$ <p>Identities:</p> $\cosh^2 x - \sinh^2 x = 1, \quad \tanh^2 x + \text{sech}^2 x = 1,$ $\coth^2 x - \text{csch}^2 x = 1, \quad \sinh(-x) = -\sinh x,$ $\cosh(-x) = \cosh x, \quad \tanh(-x) = -\tanh x,$ $\sinh(x + y) = \sinh x \cosh y + \cosh x \sinh y,$ $\cosh(x + y) = \cosh x \cosh y + \sinh x \sinh y,$ $\sinh 2x = 2 \sinh x \cosh x,$ $\cosh 2x = \cosh^2 x + \sinh^2 x,$ $\cosh x + \sinh x = e^x, \quad \cosh x - \sinh x = e^{-x},$ $(\cosh x + \sinh x)^n = \cosh nx + \sinh nx, \quad n \in \mathbb{Z},$ $2 \sinh^2 \frac{x}{2} = \cosh x - 1, \quad 2 \cosh^2 \frac{x}{2} = \cosh x + 1.$ <table><tr><th><math>\theta</math></th><th><math>\sin \theta</math></th><th><math>\cos \theta</math></th><th><math>\tan \theta</math></th></tr><tr><td>0</td><td>0</td><td>1</td><td>0</td></tr><tr><td><math>\frac{\pi}{6}</math></td><td><math>\frac{1}{2}</math></td><td><math>\frac{\sqrt{3}}{2}</math></td><td><math>\frac{\sqrt{3}}{3}</math></td></tr><tr><td><math>\frac{\pi}{4}</math></td><td><math>\frac{\sqrt{2}}{2}</math></td><td><math>\frac{\sqrt{2}}{2}</math></td><td>1</td></tr><tr><td><math>\frac{\pi}{3}</math></td><td><math>\frac{\sqrt{3}}{2}</math></td><td><math>\frac{1}{2}</math></td><td><math>\sqrt{3}</math></td></tr><tr><td><math>\frac{\pi}{2}</math></td><td>1</td><td>0</td><td><math>\infty</math></td></tr></table> <p>... in mathematics you don't understand things, you just get used to them. - J. von Neumann</p>	$\theta$	$\sin \theta$	$\cos \theta$	$\tan \theta$	0	0	1	0	$\frac{\pi}{6}$	$\frac{1}{2}$	$\frac{\sqrt{3}}{2}$	$\frac{\sqrt{3}}{3}$	$\frac{\pi}{4}$	$\frac{\sqrt{2}}{2}$	$\frac{\sqrt{2}}{2}$	1	$\frac{\pi}{3}$	$\frac{\sqrt{3}}{2}$	$\frac{1}{2}$	$\sqrt{3}$	$\frac{\pi}{2}$	1	0	$\infty$	<div></div> <p>Law of cosines: <math>c^2 = a^2 + b^2 - 2ab \cos C.</math></p> <p>Area:</p> $A = \frac{1}{2}hc,$ $= \frac{1}{2}ab \sin C,$ $= \frac{c^2 \sin A \sin B}{2 \sin C}.$ <p>Heron's formula:</p> $A = \sqrt{s \cdot s_a \cdot s_b \cdot s_c},$ $s = \frac{1}{2}(a + b + c),$ $s_a = s - a,$ $s_b = s - b,$ $s_c = s - c.$ <p>More identities:</p> $\sin \frac{x}{2} = \sqrt{\frac{1 - \cos x}{2}},$ $\cos \frac{x}{2} = \sqrt{\frac{1 + \cos x}{2}},$ $\tan \frac{x}{2} = \sqrt{\frac{1 - \cos x}{1 + \cos x}},$ $= \frac{1 - \cos x}{\sin x},$ $= \frac{\sin x}{1 + \cos x},$ $\cot \frac{x}{2} = \sqrt{\frac{1 + \cos x}{1 - \cos x}},$ $= \frac{1 + \cos x}{\sin x},$ $= \frac{\sin x}{1 - \cos x},$ $\sin x = \frac{e^{ix} - e^{-ix}}{2i},$ $\cos x = \frac{e^{ix} + e^{-ix}}{2},$ $\tan x = -i \frac{e^{ix} - e^{-ix}}{e^{ix} + e^{-ix}},$ $= -i \frac{e^{2ix} - 1}{e^{2ix} + 1},$ $\sin x = \frac{\sinh ix}{i},$ $\cos x = \cosh ix,$ $\tan x = \frac{\tanh ix}{i}.$
$\theta$	$\sin \theta$	$\cos \theta$	$\tan \theta$																							
0	0	1	0																							
$\frac{\pi}{6}$	$\frac{1}{2}$	$\frac{\sqrt{3}}{2}$	$\frac{\sqrt{3}}{3}$																							
$\frac{\pi}{4}$	$\frac{\sqrt{2}}{2}$	$\frac{\sqrt{2}}{2}$	1																							
$\frac{\pi}{3}$	$\frac{\sqrt{3}}{2}$	$\frac{1}{2}$	$\sqrt{3}$																							
$\frac{\pi}{2}$	1	0	$\infty$																							

v2.02 ©1994 by Steve Seiden  
sseiden@acm.org  
<http://www.csc.lsu.edu/~seiden>

The Chinese remainder theorem: There exists a number  $C$  such that:

$$C \equiv r_1 \pmod{m_1}$$

$$\vdots \quad \vdots \quad \vdots$$

$$C \equiv r_n \pmod{m_n}$$

if  $m_i$  and  $m_j$  are relatively prime for  $i \neq j$ .

Euler's function:  $\phi(x)$  is the number of positive integers less than  $x$  relatively prime to  $x$ . If  $\prod_{i=1}^n p_i^{e_i}$  is the prime factorization of  $x$  then

$$\phi(x) = \prod_{i=1}^n p_i^{e_i-1} (p_i - 1).$$

Euler's theorem: If  $a$  and  $b$  are relatively prime then

$$1 \equiv a^{\phi(b)} \pmod{b}.$$

Fermat's theorem:

$$1 \equiv a^{p-1} \pmod{p}.$$

The Euclidean algorithm: if  $a > b$  are integers then

$$\gcd(a, b) = \gcd(a \bmod b, b).$$

If  $\prod_{i=1}^n p_i^{e_i}$  is the prime factorization of  $x$  then

$$S(x) = \sum_{d|x} d = \prod_{i=1}^n \frac{p_i^{e_i+1} - 1}{p_i - 1}.$$

Perfect Numbers:  $x$  is an even perfect number iff  $x = 2^{n-1}(2^n - 1)$  and  $2^n - 1$  is prime.

Wilson's theorem:  $n$  is a prime iff

$$(n - 1)! \equiv -1 \pmod{n}.$$

Möbius inversion:

$$\mu(i) = \begin{cases} 1 & \text{if } i = 1. \\ 0 & \text{if } i \text{ is not square-free.} \\ (-1)^r & \text{if } i \text{ is the product of } r \text{ distinct primes.} \end{cases}$$

If

$$G(a) = \sum_{d|a} F(d),$$

then

$$F(a) = \sum_{d|a} \mu(d) G\left(\frac{a}{d}\right).$$

Prime numbers:

$$p_n = n \ln n + n \ln \ln n - n + n \frac{\ln \ln n}{\ln n}$$

$$+ O\left(\frac{n}{\ln n}\right),$$

$$\pi(n) = \frac{n}{\ln n} + \frac{n}{(\ln n)^2} + \frac{2!n}{(\ln n)^3}$$

$$+ O\left(\frac{n}{(\ln n)^4}\right).$$

Definitions:

*Loop* An edge connecting a vertex to itself.

*Directed Simple* Each edge has a direction. Graph with no loops or multi-edges.

*Walk* A sequence  $v_0 e_1 v_1 \dots e_\ell v_\ell$ .

*Trail* A walk with distinct edges.

*Path* A trail with distinct vertices.

*Connected* A graph where there exists a path between any two vertices.

*Component* A maximal connected subgraph.

*Tree* A connected acyclic graph.

*Free tree* A tree with no root.

*DAG* Directed acyclic graph.

*Eulerian* Graph with a trail visiting each edge exactly once.

*Hamiltonian* Graph with a cycle visiting each vertex exactly once.

*Cut* A set of edges whose removal increases the number of components.

*Cut-set* A minimal cut.

*Cut edge* A size 1 cut.

*k-Connected* A graph connected with the removal of any  $k - 1$  vertices.

*k-Tough*  $\forall S \subseteq V, S \neq \emptyset$  we have  $k \cdot c(G - S) \leq |S|$ .

*k-Regular* A graph where all vertices have degree  $k$ .

*k-Factor* A  $k$ -regular spanning subgraph.

*Matching* A set of edges, no two of which are adjacent.

*Clique* A set of vertices, all of which are adjacent.

*Ind. set* A set of vertices, none of which are adjacent.

*Vertex cover* A set of vertices which cover all edges.

*Planar graph* A graph which can be embedded in the plane.

*Plane graph* An embedding of a planar graph.

$$\sum_{v \in V} \deg(v) = 2m.$$

If  $G$  is planar then  $n - m + f = 2$ , so

$$f \leq 2n - 4, \quad m \leq 3n - 6.$$

Any planar graph has a vertex with degree  $\leq 5$ .

Notation:

$E(G)$  Edge set

$V(G)$  Vertex set

$c(G)$  Number of components

$G[S]$  Induced subgraph

$\deg(v)$  Degree of  $v$

$\Delta(G)$  Maximum degree

$\delta(G)$  Minimum degree

$\chi(G)$  Chromatic number

$\chi_E(G)$  Edge chromatic number

$G^c$  Complement graph

$K_n$  Complete graph

$K_{n_1, n_2}$  Complete bipartite graph

$r(k, \ell)$  Ramsey number

Geometry

Projective coordinates: triples  $(x, y, z)$ , not all  $x, y$  and  $z$  zero.

$$(x, y, z) = (cx, cy, cz) \quad \forall c \neq 0.$$

Cartesian Projective

$$(x, y) \quad (x, y, 1)$$

$$y = mx + b \quad (m, -1, b)$$

$$x = c \quad (1, 0, -c)$$

Distance formula,  $L_p$  and  $L_\infty$  metric:

$$\sqrt{(x_1 - x_0)^2 + (y_1 - y_0)^2},$$


$$[|x_1 - x_0|^p + |y_1 - y_0|^p]^{1/p},$$

$$\lim_{p \rightarrow \infty} [|x_1 - x_0|^p + |y_1 - y_0|^p]^{1/p}.$$

Area of triangle  $(x_0, y_0), (x_1, y_1)$  and  $(x_2, y_2)$ :

$$\frac{1}{2} \text{abs} \begin{vmatrix} x_1 - x_0 & y_1 - y_0 \\ x_2 - x_0 & y_2 - y_0 \end{vmatrix}.$$

Angle formed by three points:



$$\cos \theta = \frac{(x_1, y_1) \cdot (x_2, y_2)}{l_1 l_2}.$$

Line through two points  $(x_0, y_0)$  and  $(x_1, y_1)$ :

$$\begin{vmatrix} x & y & 1 \\ x_0 & y_0 & 1 \\ x_1 & y_1 & 1 \end{vmatrix} = 0.$$

Area of circle, volume of sphere:

$$A = \pi r^2, \quad V = \frac{4}{3} \pi r^3.$$

If I have seen farther than others, it is because I have stood on the shoulders of giants.

– Issac Newton



Wallis' identity:

$$\pi = 2 \cdot \frac{2 \cdot 2 \cdot 4 \cdot 4 \cdot 6 \cdot 6 \cdots}{1 \cdot 3 \cdot 3 \cdot 5 \cdot 5 \cdot 7 \cdots}$$

Brouncker's continued fraction expansion:

$$\frac{\pi}{4} = 1 + \frac{1^2}{2 + \frac{3^2}{2 + \frac{5^2}{2 + \frac{7^2}{2 + \cdots}}}}$$

Gregory's series:

$$\frac{\pi}{4} = 1 - \frac{1}{3} + \frac{1}{5} - \frac{1}{7} + \frac{1}{9} - \cdots$$

Newton's series:

$$\frac{\pi}{6} = \frac{1}{2} + \frac{1}{2 \cdot 3 \cdot 2^3} + \frac{1 \cdot 3}{2 \cdot 4 \cdot 5 \cdot 2^5} + \cdots$$

Sharp's series:

$$\frac{\pi}{6} = \frac{1}{\sqrt{3}} \left( 1 - \frac{1}{3^1 \cdot 3} + \frac{1}{3^2 \cdot 5} - \frac{1}{3^3 \cdot 7} + \cdots \right)$$

Euler's series:

$$\frac{\pi^2}{6} = \frac{1}{1^2} + \frac{1}{2^2} + \frac{1}{3^2} + \frac{1}{4^2} + \frac{1}{5^2} + \cdots$$

$$\frac{\pi^2}{8} = \frac{1}{1^2} + \frac{1}{3^2} + \frac{1}{5^2} + \frac{1}{7^2} + \frac{1}{9^2} + \cdots$$

$$\frac{\pi^2}{12} = \frac{1}{1^2} - \frac{1}{2^2} + \frac{1}{3^2} - \frac{1}{4^2} + \frac{1}{5^2} - \cdots$$

### Partial Fractions

Let  $N(x)$  and  $D(x)$  be polynomial functions of  $x$ . We can break down  $N(x)/D(x)$  using partial fraction expansion. First, if the degree of  $N$  is greater than or equal to the degree of  $D$ , divide  $N$  by  $D$ , obtaining

$$\frac{N(x)}{D(x)} = Q(x) + \frac{N'(x)}{D(x)},$$

where the degree of  $N'$  is less than that of  $D$ . Second, factor  $D(x)$ . Use the following rules: For a non-repeated factor:

$$\frac{N(x)}{(x-a)D(x)} = \frac{A}{x-a} + \frac{N'(x)}{D(x)},$$

where

$$A = \left[ \frac{N(x)}{D(x)} \right]_{x=a}.$$

For a repeated factor:

$$\frac{N(x)}{(x-a)^m D(x)} = \sum_{k=0}^{m-1} \frac{A_k}{(x-a)^{m-k}} + \frac{N'(x)}{D(x)},$$

where

$$A_k = \frac{1}{k!} \left[ \frac{d^k}{dx^k} \left( \frac{N(x)}{D(x)} \right) \right]_{x=a}.$$

The reasonable man adapts himself to the world; the unreasonable persists in trying to adapt the world to himself. Therefore all progress depends on the unreasonable.  
– George Bernard Shaw

Derivatives:

$$1. \frac{d(cu)}{dx} = c \frac{du}{dx}, \quad 2. \frac{d(u+v)}{dx} = \frac{du}{dx} + \frac{dv}{dx}, \quad 3. \frac{d(uv)}{dx} = u \frac{dv}{dx} + v \frac{du}{dx},$$

$$4. \frac{d(u^n)}{dx} = nu^{n-1} \frac{du}{dx}, \quad 5. \frac{d(u/v)}{dx} = \frac{v \left( \frac{du}{dx} \right) - u \left( \frac{dv}{dx} \right)}{v^2}, \quad 6. \frac{d(e^{cu})}{dx} = ce^{cu} \frac{du}{dx},$$

$$7. \frac{d(c^u)}{dx} = (\ln c) c^u \frac{du}{dx}, \quad 8. \frac{d(\ln u)}{dx} = \frac{1}{u} \frac{du}{dx},$$

$$9. \frac{d(\sin u)}{dx} = \cos u \frac{du}{dx}, \quad 10. \frac{d(\cos u)}{dx} = -\sin u \frac{du}{dx},$$

$$11. \frac{d(\tan u)}{dx} = \sec^2 u \frac{du}{dx}, \quad 12. \frac{d(\cot u)}{dx} = -\csc^2 u \frac{du}{dx},$$

$$13. \frac{d(\sec u)}{dx} = \tan u \sec u \frac{du}{dx}, \quad 14. \frac{d(\csc u)}{dx} = -\cot u \csc u \frac{du}{dx},$$

$$15. \frac{d(\arcsin u)}{dx} = \frac{1}{\sqrt{1-u^2}} \frac{du}{dx}, \quad 16. \frac{d(\arccos u)}{dx} = \frac{-1}{\sqrt{1-u^2}} \frac{du}{dx},$$

$$17. \frac{d(\arctan u)}{dx} = \frac{1}{1+u^2} \frac{du}{dx}, \quad 18. \frac{d(\operatorname{arccot} u)}{dx} = \frac{-1}{1+u^2} \frac{du}{dx},$$

$$19. \frac{d(\operatorname{arcsec} u)}{dx} = \frac{1}{u\sqrt{1-u^2}} \frac{du}{dx}, \quad 20. \frac{d(\operatorname{arccsc} u)}{dx} = \frac{-1}{u\sqrt{1-u^2}} \frac{du}{dx},$$

$$21. \frac{d(\sinh u)}{dx} = \cosh u \frac{du}{dx}, \quad 22. \frac{d(\cosh u)}{dx} = \sinh u \frac{du}{dx},$$

$$23. \frac{d(\tanh u)}{dx} = \operatorname{sech}^2 u \frac{du}{dx}, \quad 24. \frac{d(\coth u)}{dx} = -\operatorname{csch}^2 u \frac{du}{dx},$$

$$25. \frac{d(\operatorname{sech} u)}{dx} = -\operatorname{sech} u \tanh u \frac{du}{dx}, \quad 26. \frac{d(\operatorname{csch} u)}{dx} = -\operatorname{csch} u \coth u \frac{du}{dx},$$

$$27. \frac{d(\operatorname{arcsinh} u)}{dx} = \frac{1}{\sqrt{1+u^2}} \frac{du}{dx}, \quad 28. \frac{d(\operatorname{arccosh} u)}{dx} = \frac{1}{\sqrt{u^2-1}} \frac{du}{dx},$$

$$29. \frac{d(\operatorname{arctanh} u)}{dx} = \frac{1}{1-u^2} \frac{du}{dx}, \quad 30. \frac{d(\operatorname{arcoth} u)}{dx} = \frac{1}{u^2-1} \frac{du}{dx},$$

$$31. \frac{d(\operatorname{arcsech} u)}{dx} = \frac{-1}{u\sqrt{1-u^2}} \frac{du}{dx}, \quad 32. \frac{d(\operatorname{arccsch} u)}{dx} = \frac{-1}{|u|\sqrt{1+u^2}} \frac{du}{dx}.$$

Integrals:

$$1. \int cu \, dx = c \int u \, dx, \quad 2. \int (u+v) \, dx = \int u \, dx + \int v \, dx,$$

$$3. \int x^n \, dx = \frac{1}{n+1} x^{n+1}, \quad n \neq -1, \quad 4. \int \frac{1}{x} \, dx = \ln x, \quad 5. \int e^x \, dx = e^x,$$

$$6. \int \frac{dx}{1+x^2} = \arctan x, \quad 7. \int u \frac{dv}{dx} \, dx = uv - \int v \frac{du}{dx} \, dx,$$

$$8. \int \sin x \, dx = -\cos x, \quad 9. \int \cos x \, dx = \sin x,$$

$$10. \int \tan x \, dx = -\ln |\cos x|, \quad 11. \int \cot x \, dx = \ln |\cos x|,$$

$$12. \int \sec x \, dx = \ln |\sec x + \tan x|, \quad 13. \int \csc x \, dx = \ln |\csc x + \cot x|,$$

$$14. \int \arcsin \frac{x}{a} \, dx = \arcsin \frac{x}{a} + \sqrt{a^2 - x^2}, \quad a > 0,$$

15.  $\int \arccos \frac{x}{a} dx = \arccos \frac{x}{a} - \sqrt{a^2 - x^2}, \quad a > 0,$
16.  $\int \arctan \frac{x}{a} dx = x \arctan \frac{x}{a} - \frac{a}{2} \ln(a^2 + x^2), \quad a > 0,$
17.  $\int \sin^2(ax) dx = \frac{1}{2a}(ax - \sin(ax) \cos(ax)),$
18.  $\int \cos^2(ax) dx = \frac{1}{2a}(ax + \sin(ax) \cos(ax)),$
19.  $\int \sec^2 x dx = \tan x,$
20.  $\int \csc^2 x dx = -\cot x,$
21.  $\int \sin^n x dx = -\frac{\sin^{n-1} x \cos x}{n} + \frac{n-1}{n} \int \sin^{n-2} x dx,$
22.  $\int \cos^n x dx = \frac{\cos^{n-1} x \sin x}{n} + \frac{n-1}{n} \int \cos^{n-2} x dx,$
23.  $\int \tan^n x dx = \frac{\tan^{n-1} x}{n-1} - \int \tan^{n-2} x dx, \quad n \neq 1,$
24.  $\int \cot^n x dx = -\frac{\cot^{n-1} x}{n-1} - \int \cot^{n-2} x dx, \quad n \neq 1,$
25.  $\int \sec^n x dx = \frac{\tan x \sec^{n-1} x}{n-1} + \frac{n-2}{n-1} \int \sec^{n-2} x dx, \quad n \neq 1,$
26.  $\int \csc^n x dx = -\frac{\cot x \csc^{n-1} x}{n-1} + \frac{n-2}{n-1} \int \csc^{n-2} x dx, \quad n \neq 1,$
27.  $\int \sinh x dx = \cosh x,$
28.  $\int \cosh x dx = \sinh x,$
29.  $\int \tanh x dx = \ln |\cosh x|,$
30.  $\int \coth x dx = \ln |\sinh x|,$
31.  $\int \operatorname{sech} x dx = \arctan \sinh x,$
32.  $\int \operatorname{csch} x dx = \ln \left| \tanh \frac{x}{2} \right|,$
33.  $\int \sinh^2 x dx = \frac{1}{4} \sinh(2x) - \frac{1}{2} x,$
34.  $\int \cosh^2 x dx = \frac{1}{4} \sinh(2x) + \frac{1}{2} x,$
35.  $\int \operatorname{sech}^2 x dx = \tanh x,$
36.  $\int \operatorname{arcsinh} \frac{x}{a} dx = x \operatorname{arcsinh} \frac{x}{a} - \sqrt{x^2 + a^2}, \quad a > 0,$
37.  $\int \operatorname{arctanh} \frac{x}{a} dx = x \operatorname{arctanh} \frac{x}{a} + \frac{a}{2} \ln |a^2 - x^2|,$
38.  $\int \operatorname{arccosh} \frac{x}{a} dx = \begin{cases} x \operatorname{arccosh} \frac{x}{a} - \sqrt{x^2 + a^2}, & \text{if } \operatorname{arccosh} \frac{x}{a} > 0 \text{ and } a > 0, \\ x \operatorname{arccosh} \frac{x}{a} + \sqrt{x^2 + a^2}, & \text{if } \operatorname{arccosh} \frac{x}{a} < 0 \text{ and } a > 0, \end{cases}$
39.  $\int \frac{dx}{\sqrt{a^2 + x^2}} = \ln \left( x + \sqrt{a^2 + x^2} \right), \quad a > 0,$
40.  $\int \frac{dx}{a^2 + x^2} = \frac{1}{a} \arctan \frac{x}{a}, \quad a > 0,$
41.  $\int \sqrt{a^2 - x^2} dx = \frac{x}{2} \sqrt{a^2 - x^2} + \frac{a^2}{2} \arcsin \frac{x}{a}, \quad a > 0,$
42.  $\int (a^2 - x^2)^{3/2} dx = \frac{x}{8} (5a^2 - 2x^2) \sqrt{a^2 - x^2} + \frac{3a^4}{8} \arcsin \frac{x}{a}, \quad a > 0,$
43.  $\int \frac{dx}{\sqrt{a^2 - x^2}} = \arcsin \frac{x}{a}, \quad a > 0,$
44.  $\int \frac{dx}{a^2 - x^2} = \frac{1}{2a} \ln \left| \frac{a+x}{a-x} \right|,$
45.  $\int \frac{dx}{(a^2 - x^2)^{3/2}} = \frac{x}{a^2 \sqrt{a^2 - x^2}},$
46.  $\int \sqrt{a^2 \pm x^2} dx = \frac{x}{2} \sqrt{a^2 \pm x^2} \pm \frac{a^2}{2} \ln \left| x + \sqrt{a^2 \pm x^2} \right|,$
47.  $\int \frac{dx}{\sqrt{x^2 - a^2}} = \ln \left| x + \sqrt{x^2 - a^2} \right|, \quad a > 0,$
48.  $\int \frac{dx}{ax^2 + bx} = \frac{1}{a} \ln \left| \frac{x}{a + bx} \right|,$
49.  $\int x \sqrt{a + bx} dx = \frac{2(3bx - 2a)(a + bx)^{3/2}}{15b^2},$
50.  $\int \frac{\sqrt{a + bx}}{x} dx = 2\sqrt{a + bx} + a \int \frac{1}{x\sqrt{a + bx}} dx,$
51.  $\int \frac{x}{\sqrt{a + bx}} dx = \frac{1}{\sqrt{2}} \ln \left| \frac{\sqrt{a + bx} - \sqrt{a}}{\sqrt{a + bx} + \sqrt{a}} \right|, \quad a > 0,$
52.  $\int \frac{\sqrt{a^2 - x^2}}{x} dx = \sqrt{a^2 - x^2} - a \ln \left| \frac{a + \sqrt{a^2 - x^2}}{x} \right|,$
53.  $\int x \sqrt{a^2 - x^2} dx = -\frac{1}{3} (a^2 - x^2)^{3/2},$
54.  $\int x^2 \sqrt{a^2 - x^2} dx = \frac{x}{8} (2x^2 - a^2) \sqrt{a^2 - x^2} + \frac{a^4}{8} \arcsin \frac{x}{a}, \quad a > 0,$
55.  $\int \frac{dx}{\sqrt{a^2 - x^2}} = -\frac{1}{a} \ln \left| \frac{a + \sqrt{a^2 - x^2}}{x} \right|,$
56.  $\int \frac{x dx}{\sqrt{a^2 - x^2}} = -\sqrt{a^2 - x^2},$
57.  $\int \frac{x^2 dx}{\sqrt{a^2 - x^2}} = -\frac{x}{2} \sqrt{a^2 - x^2} + \frac{a^2}{2} \arcsin \frac{x}{a}, \quad a > 0,$
58.  $\int \frac{\sqrt{a^2 + x^2}}{x} dx = \sqrt{a^2 + x^2} - a \ln \left| \frac{a + \sqrt{a^2 + x^2}}{x} \right|,$
59.  $\int \frac{\sqrt{x^2 - a^2}}{x} dx = \sqrt{x^2 - a^2} - a \arccos \frac{a}{|x|}, \quad a > 0,$
60.  $\int x \sqrt{x^2 \pm a^2} dx = \frac{1}{3} (x^2 \pm a^2)^{3/2},$
61.  $\int \frac{dx}{x \sqrt{x^2 + a^2}} = \frac{1}{a} \ln \left| \frac{x}{a + \sqrt{a^2 + x^2}} \right|,$

$$\begin{aligned}
62. \int \frac{dx}{x\sqrt{x^2-a^2}} &= \frac{1}{a} \arccos \frac{a}{|x|}, \quad a > 0, & 63. \int \frac{dx}{x^2\sqrt{x^2 \pm a^2}} &= \mp \frac{\sqrt{x^2 \pm a^2}}{a^2 x}, \\
64. \int \frac{x dx}{\sqrt{x^2 \pm a^2}} &= \sqrt{x^2 \pm a^2}, & 65. \int \frac{\sqrt{x^2 \pm a^2}}{x^4} dx &= \mp \frac{(x^2 + a^2)^{3/2}}{3a^2 x^3}, \\
66. \int \frac{dx}{ax^2 + bx + c} &= \begin{cases} \frac{1}{\sqrt{b^2 - 4ac}} \ln \left| \frac{2ax + b - \sqrt{b^2 - 4ac}}{2ax + b + \sqrt{b^2 - 4ac}} \right|, & \text{if } b^2 > 4ac, \\ \frac{2}{\sqrt{4ac - b^2}} \arctan \frac{2ax + b}{\sqrt{4ac - b^2}}, & \text{if } b^2 < 4ac, \end{cases} \\
67. \int \frac{dx}{\sqrt{ax^2 + bx + c}} &= \begin{cases} \frac{1}{\sqrt{a}} \ln \left| 2ax + b + 2\sqrt{a}\sqrt{ax^2 + bx + c} \right|, & \text{if } a > 0, \\ \frac{1}{\sqrt{-a}} \arcsin \frac{-2ax - b}{\sqrt{b^2 - 4ac}}, & \text{if } a < 0, \end{cases} \\
68. \int \sqrt{ax^2 + bx + c} dx &= \frac{2ax + b}{4a} \sqrt{ax^2 + bx + c} + \frac{4ac - b^2}{8a} \int \frac{dx}{\sqrt{ax^2 + bx + c}}, \\
69. \int \frac{x dx}{\sqrt{ax^2 + bx + c}} &= \frac{\sqrt{ax^2 + bx + c}}{a} - \frac{b}{2a} \int \frac{dx}{\sqrt{ax^2 + bx + c}}, \\
70. \int \frac{dx}{x\sqrt{ax^2 + bx + c}} &= \begin{cases} \frac{-1}{\sqrt{c}} \ln \left| \frac{2\sqrt{c}\sqrt{ax^2 + bx + c} + bx + 2c}{x} \right|, & \text{if } c > 0, \\ \frac{1}{\sqrt{-c}} \arcsin \frac{bx + 2c}{|x|\sqrt{b^2 - 4ac}}, & \text{if } c < 0, \end{cases} \\
71. \int x^3 \sqrt{x^2 + a^2} dx &= \left(\frac{1}{3}x^2 - \frac{2}{15}a^2\right)(x^2 + a^2)^{3/2}, \\
72. \int x^n \sin(ax) dx &= -\frac{1}{a}x^n \cos(ax) + \frac{n}{a} \int x^{n-1} \cos(ax) dx, \\
73. \int x^n \cos(ax) dx &= \frac{1}{a}x^n \sin(ax) - \frac{n}{a} \int x^{n-1} \sin(ax) dx, \\
74. \int x^n e^{ax} dx &= \frac{x^n e^{ax}}{a} - \frac{n}{a} \int x^{n-1} e^{ax} dx, \\
75. \int x^n \ln(ax) dx &= x^{n+1} \left( \frac{\ln(ax)}{n+1} - \frac{1}{(n+1)^2} \right), \\
76. \int x^n (\ln ax)^m dx &= \frac{x^{n+1}}{n+1} (\ln ax)^m - \frac{m}{n+1} \int x^n (\ln ax)^{m-1} dx.
\end{aligned}$$

$$\begin{aligned}
x^1 &= x^1 & x^{\bar{1}} &= x^{\bar{1}} \\
x^2 &= x^2 + x^1 & x^{\bar{2}} &= x^{\bar{2}} - x^{\bar{1}} \\
x^3 &= x^3 + 3x^2 + x^1 & x^{\bar{3}} &= x^{\bar{3}} - 3x^{\bar{2}} + x^{\bar{1}} \\
x^4 &= x^4 + 6x^3 + 7x^2 + x^1 & x^{\bar{4}} &= x^{\bar{4}} - 6x^{\bar{3}} + 7x^{\bar{2}} - x^{\bar{1}} \\
x^5 &= x^5 + 15x^4 + 25x^3 + 10x^2 + x^1 & x^{\bar{5}} &= x^{\bar{5}} - 15x^{\bar{4}} + 25x^{\bar{3}} - 10x^{\bar{2}} + x^{\bar{1}} \\
x^{\bar{1}} &= x^1 & x^1 &= x^1 \\
x^{\bar{2}} &= x^2 + x^1 & x^2 &= x^2 - x^1 \\
x^{\bar{3}} &= x^3 + 3x^2 + 2x^1 & x^3 &= x^3 - 3x^2 + 2x^1 \\
x^{\bar{4}} &= x^4 + 6x^3 + 11x^2 + 6x^1 & x^4 &= x^4 - 6x^3 + 11x^2 - 6x^1 \\
x^{\bar{5}} &= x^5 + 10x^4 + 35x^3 + 50x^2 + 24x^1 & x^{\bar{5}} &= x^5 - 10x^4 + 35x^3 - 50x^2 + 24x^1
\end{aligned}$$

Difference, shift operators:

$$\Delta f(x) = f(x+1) - f(x),$$

$$\mathbb{E} f(x) = f(x+1).$$

Fundamental Theorem:

$$f(x) = \Delta F(x) \Leftrightarrow \sum f(x) \delta x = F(x) + C.$$

$$\sum_a^b f(x) \delta x = \sum_{i=a}^{b-1} f(i).$$

Differences:

$$\Delta(cu) = c\Delta u, \quad \Delta(u+v) = \Delta u + \Delta v,$$

$$\Delta(uv) = u\Delta v + \mathbb{E} v \Delta u,$$

$$\Delta(x^n) = nx^{n-1},$$

$$\Delta(H_x) = x^{-1}, \quad \Delta(2^x) = 2^x,$$

$$\Delta(c^x) = (c-1)c^x, \quad \Delta\binom{x}{m} = \binom{x}{m-1}.$$

Sums:

$$\sum cu \delta x = c \sum u \delta x,$$

$$\sum (u+v) \delta x = \sum u \delta x + \sum v \delta x,$$

$$\sum u \Delta v \delta x = uv - \sum \mathbb{E} v \Delta u \delta x,$$

$$\sum x^n \delta x = \frac{x^{n+1}}{n+1}, \quad \sum x^{-1} \delta x = H_x,$$

$$\sum c^x \delta x = \frac{c^x}{c-1}, \quad \sum \binom{x}{m} \delta x = \binom{x}{m+1}.$$

Falling Factorial Powers:

$$x^{\underline{n}} = x(x-1) \cdots (x-n+1), \quad n > 0,$$

$$x^{\underline{0}} = 1,$$

$$x^{\underline{n}} = \frac{1}{(x+1) \cdots (x+|n|)}, \quad n < 0,$$

$$x^{\underline{n+m}} = x^{\underline{m}}(x-m)^{\underline{n}}.$$

Rising Factorial Powers:

$$x^{\overline{n}} = x(x+1) \cdots (x+n-1), \quad n > 0,$$

$$x^{\overline{0}} = 1,$$

$$x^{\overline{n}} = \frac{1}{(x-1) \cdots (x-|n|)}, \quad n < 0,$$

$$x^{\overline{n+m}} = x^{\overline{m}}(x+m)^{\overline{n}}.$$

Conversion:

$$x^{\underline{n}} = (-1)^n (-x)^{\overline{n}} = (x-n+1)^{\overline{n}}$$

$$= 1/(x+1)^{-n},$$

$$x^{\overline{n}} = (-1)^n (-x)^{\underline{n}} = (x+n-1)^{\underline{n}}$$

$$= 1/(x-1)^{-n},$$

$$x^n = \sum_{k=1}^n \left\{ \begin{matrix} n \\ k \end{matrix} \right\} x^{\underline{k}} = \sum_{k=1}^n \left\{ \begin{matrix} n \\ k \end{matrix} \right\} (-1)^{n-k} x^{\overline{k}},$$

$$x^{\underline{n}} = \sum_{k=1}^n \left[ \begin{matrix} n \\ k \end{matrix} \right] (-1)^{n-k} x^k,$$

$$x^{\overline{n}} = \sum_{k=1}^n \left[ \begin{matrix} n \\ k \end{matrix} \right] x^k.$$

Taylor's series:

$$f(x) = f(a) + (x-a)f'(a) + \frac{(x-a)^2}{2}f''(a) + \dots = \sum_{i=0}^{\infty} \frac{(x-a)^i}{i!} f^{(i)}(a).$$

Expansions:

$$\begin{aligned} \frac{1}{1-x} &= 1 + x + x^2 + x^3 + x^4 + \dots = \sum_{i=0}^{\infty} x^i, \\ \frac{1}{1-cx} &= 1 + cx + c^2x^2 + c^3x^3 + \dots = \sum_{i=0}^{\infty} c^i x^i, \\ \frac{1}{1-x^n} &= 1 + x^n + x^{2n} + x^{3n} + \dots = \sum_{i=0}^{\infty} x^{ni}, \\ \frac{x}{(1-x)^2} &= x + 2x^2 + 3x^3 + 4x^4 + \dots = \sum_{i=0}^{\infty} ix^i, \\ x^k \frac{d^n}{dx^n} \left( \frac{1}{1-x} \right) &= x + 2^n x^2 + 3^n x^3 + 4^n x^4 + \dots = \sum_{i=0}^{\infty} i^n x^i, \\ e^x &= 1 + x + \frac{1}{2}x^2 + \frac{1}{6}x^3 + \dots = \sum_{i=0}^{\infty} \frac{x^i}{i!}, \\ \ln(1+x) &= x - \frac{1}{2}x^2 + \frac{1}{3}x^3 - \frac{1}{4}x^4 + \dots = \sum_{i=1}^{\infty} (-1)^{i+1} \frac{x^i}{i}, \\ \ln \frac{1}{1-x} &= x + \frac{1}{2}x^2 + \frac{1}{3}x^3 + \frac{1}{4}x^4 + \dots = \sum_{i=1}^{\infty} \frac{x^i}{i}, \\ \sin x &= x - \frac{1}{3!}x^3 + \frac{1}{5!}x^5 - \frac{1}{7!}x^7 + \dots = \sum_{i=0}^{\infty} (-1)^i \frac{x^{2i+1}}{(2i+1)!}, \\ \cos x &= 1 - \frac{1}{2!}x^2 + \frac{1}{4!}x^4 - \frac{1}{6!}x^6 + \dots = \sum_{i=0}^{\infty} (-1)^i \frac{x^{2i}}{(2i)!}, \\ \tan^{-1} x &= x - \frac{1}{3}x^3 + \frac{1}{5}x^5 - \frac{1}{7}x^7 + \dots = \sum_{i=0}^{\infty} (-1)^i \frac{x^{2i+1}}{(2i+1)}, \\ (1+x)^n &= 1 + nx + \frac{n(n-1)}{2}x^2 + \dots = \sum_{i=0}^{\infty} \binom{n}{i} x^i, \\ \frac{1}{(1-x)^{n+1}} &= 1 + (n+1)x + \binom{n+2}{2}x^2 + \dots = \sum_{i=0}^{\infty} \binom{i+n}{i} x^i, \\ \frac{x}{e^x - 1} &= 1 - \frac{1}{2}x + \frac{1}{12}x^2 - \frac{1}{720}x^4 + \dots = \sum_{i=0}^{\infty} \frac{B_i x^i}{i!}, \\ \frac{1}{2x}(1 - \sqrt{1-4x}) &= 1 + x + 2x^2 + 5x^3 + \dots = \sum_{i=0}^{\infty} \frac{1}{i+1} \binom{2i}{i} x^i, \\ \frac{1}{\sqrt{1-4x}} &= 1 + x + 2x^2 + 6x^3 + \dots = \sum_{i=0}^{\infty} \binom{2i}{i} x^i, \\ \frac{1}{\sqrt{1-4x}} \left( \frac{1 - \sqrt{1-4x}}{2x} \right)^n &= 1 + (2+n)x + \binom{4+n}{2}x^2 + \dots = \sum_{i=0}^{\infty} \binom{2i+n}{i} x^i, \\ \frac{1}{1-x} \ln \frac{1}{1-x} &= x + \frac{3}{2}x^2 + \frac{11}{6}x^3 + \frac{25}{12}x^4 + \dots = \sum_{i=1}^{\infty} H_i x^i, \\ \frac{1}{2} \left( \ln \frac{1}{1-x} \right)^2 &= \frac{1}{2}x^2 + \frac{3}{4}x^3 + \frac{11}{24}x^4 + \dots = \sum_{i=2}^{\infty} \frac{H_{i-1} x^i}{i}, \\ \frac{x}{1-x-x^2} &= x + x^2 + 2x^3 + 3x^4 + \dots = \sum_{i=0}^{\infty} F_i x^i, \\ \frac{F_n x}{1 - (F_{n-1} + F_{n+1})x - (-1)^n x^2} &= F_n x + F_{2n} x^2 + F_{3n} x^3 + \dots = \sum_{i=0}^{\infty} F_{ni} x^i. \end{aligned}$$

Ordinary power series:

$$A(x) = \sum_{i=0}^{\infty} a_i x^i.$$

Exponential power series:

$$A(x) = \sum_{i=0}^{\infty} a_i \frac{x^i}{i!}.$$

Dirichlet power series:

$$A(x) = \sum_{i=1}^{\infty} \frac{a_i}{i^x}.$$

Binomial theorem:

$$(x+y)^n = \sum_{k=0}^n \binom{n}{k} x^{n-k} y^k.$$

Difference of like powers:

$$x^n - y^n = (x-y) \sum_{k=0}^{n-1} x^{n-1-k} y^k.$$

For ordinary power series:

$$\alpha A(x) + \beta B(x) = \sum_{i=0}^{\infty} (\alpha a_i + \beta b_i) x^i,$$

$$x^k A(x) = \sum_{i=k}^{\infty} a_{i-k} x^i,$$

$$\frac{A(x) - \sum_{i=0}^{k-1} a_i x^i}{x^k} = \sum_{i=0}^{\infty} a_{i+k} x^i,$$

$$A(cx) = \sum_{i=0}^{\infty} c^i a_i x^i,$$

$$A'(x) = \sum_{i=0}^{\infty} (i+1) a_{i+1} x^i,$$

$$xA'(x) = \sum_{i=1}^{\infty} i a_i x^i,$$

$$\int A(x) dx = \sum_{i=1}^{\infty} \frac{a_{i-1}}{i} x^i,$$

$$\frac{A(x) + A(-x)}{2} = \sum_{i=0}^{\infty} a_{2i} x^{2i},$$

$$\frac{A(x) - A(-x)}{2} = \sum_{i=0}^{\infty} a_{2i+1} x^{2i+1}.$$


Summation: If  $b_i = \sum_{j=0}^i a_j$  then

$$B(x) = \frac{1}{1-x} A(x).$$

Convolution:

$$A(x)B(x) = \sum_{i=0}^{\infty} \left( \sum_{j=0}^i a_j b_{i-j} \right) x^i.$$

God made the natural numbers;  
all the rest is the work of man.  
– Leopold Kronecker

Expansions:				
$\frac{1}{(1-x)^{n+1}} \ln \frac{1}{1-x}$	$= \sum_{i=0}^{\infty} (H_{n+i} - H_n) \binom{n+i}{i} x^i,$		$\left(\frac{1}{x}\right)^{-n}$	$= \sum_{i=0}^{\infty} \left\{ \begin{matrix} i \\ n \end{matrix} \right\} x^i,$
$x^{\overline{n}}$	$= \sum_{i=0}^{\infty} \left[ \begin{matrix} n \\ i \end{matrix} \right] x^i,$		$(e^x - 1)^n$	$= \sum_{i=0}^{\infty} \left\{ \begin{matrix} i \\ n \end{matrix} \right\} \frac{n! x^i}{i!},$
$\left(\ln \frac{1}{1-x}\right)^n$	$= \sum_{i=0}^{\infty} \left[ \begin{matrix} i \\ n \end{matrix} \right] \frac{n! x^i}{i!},$		$x \cot x$	$= \sum_{i=0}^{\infty} \frac{(-4)^i B_{2i} x^{2i}}{(2i)!},$
$\tan x$	$= \sum_{i=1}^{\infty} (-1)^{i-1} \frac{2^{2i} (2^{2i} - 1) B_{2i} x^{2i-1}}{(2i)!},$	$\zeta(x)$	$= \sum_{i=1}^{\infty} \frac{1}{i^x},$	
$\frac{1}{\zeta(x)}$	$= \sum_{i=1}^{\infty} \frac{\mu(i)}{i^x},$	$\frac{\zeta(x-1)}{\zeta(x)}$	$= \sum_{i=1}^{\infty} \frac{\phi(i)}{i^x},$	
$\zeta(x)$	$= \prod_p \frac{1}{1 - p^{-x}},$			
$\zeta^2(x)$	$= \sum_{i=1}^{\infty} \frac{d(i)}{x^i} \quad \text{where } d(n) = \sum_{d n} 1,$			
$\zeta(x)\zeta(x-1)$	$= \sum_{i=1}^{\infty} \frac{S(i)}{x^i} \quad \text{where } S(n) = \sum_{d n} d,$			
$\zeta(2n)$	$= \frac{2^{2n-1}  B_{2n} }{(2n)!} \pi^{2n}, \quad n \in \mathbb{N},$			
$\frac{x}{\sin x}$	$= \sum_{i=0}^{\infty} (-1)^{i-1} \frac{(4^i - 2) B_{2i} x^{2i}}{(2i)!},$			
$\left(\frac{1 - \sqrt{1 - 4x}}{2x}\right)^n$	$= \sum_{i=0}^{\infty} \frac{n(2i + n - 1)!}{i!(n + i)!} x^i,$			
$e^x \sin x$	$= \sum_{i=1}^{\infty} \frac{2^{i/2} \sin \frac{i\pi}{4}}{i!} x^i,$			
$\sqrt{\frac{1 - \sqrt{1 - x}}{x}}$	$= \sum_{i=0}^{\infty} \frac{(4i)!}{16^i \sqrt{2} (2i)!(2i + 1)!} x^i,$			
$\left(\frac{\arcsin x}{x}\right)^2$	$= \sum_{i=0}^{\infty} \frac{4^i i!^2}{(i + 1)(2i + 1)!} x^{2i}.$			
Cramer's Rule		Stieltjes Integration		
If we have equations:		If $G$ is continuous in the interval $[a, b]$ and $F$ is nondecreasing then		
$a_{1,1}x_1 + a_{1,2}x_2 + \cdots + a_{1,n}x_n = b_1$		$\int_a^b G(x) dF(x)$		
$a_{2,1}x_1 + a_{2,2}x_2 + \cdots + a_{2,n}x_n = b_2$		exists. If $a \leq b \leq c$ then		
$\vdots$		$\int_a^c G(x) dF(x) = \int_a^b G(x) dF(x) + \int_b^c G(x) dF(x).$		
$\vdots$		If the integrals involved exist		
$a_{n,1}x_1 + a_{n,2}x_2 + \cdots + a_{n,n}x_n = b_n$		$\int_a^b (G(x) + H(x)) dF(x) = \int_a^b G(x) dF(x) + \int_a^b H(x) dF(x),$		
Let $A = (a_{i,j})$ and $B$ be the column matrix $(b_i)$ . Then there is a unique solution iff $\det A \neq 0$ . Let $A_i$ be $A$ with column $i$ replaced by $B$ . Then		$\int_a^b G(x) d(F(x) + H(x)) = \int_a^b G(x) dF(x) + \int_a^b G(x) dH(x),$		
$x_i = \frac{\det A_i}{\det A}.$		$\int_a^b c \cdot G(x) dF(x) = \int_a^b G(x) d(c \cdot F(x)) = c \int_a^b G(x) dF(x),$		
		$\int_a^b G(x) dF(x) = G(b)F(b) - G(a)F(a) - \int_a^b F(x) dG(x).$		
		If the integrals involved exist, and $F$ possesses a derivative $F'$ at every point in $[a, b]$ then		
		$\int_a^b G(x) dF(x) = \int_a^b G(x) F'(x) dx.$		
		Fibonacci Numbers		
		00 47 18 76 29 93 85 34 61 52		1, 1, 2, 3, 5, 8, 13, 21, 34, 55, 89, ...
		86 11 57 28 70 39 94 45 02 63		Definitions:
		95 80 22 67 38 71 49 56 13 04		$F_i = F_{i-1} + F_{i-2}, \quad F_0 = F_1 = 1,$
		59 96 81 33 07 48 72 60 24 15		$F_{-i} = (-1)^{i-1} F_i,$
		73 69 90 82 44 17 58 01 35 26		$F_i = \frac{1}{\sqrt{5}} \left( \phi^i - \hat{\phi}^i \right),$
		68 74 09 91 83 55 27 12 46 30		Cassini's identity: for $i > 0$ :
		37 08 75 19 92 84 66 23 50 41		$F_{i+1}F_{i-1} - F_i^2 = (-1)^i.$
		14 25 36 40 51 62 03 77 88 99		Additive rule:
		21 32 43 54 65 06 10 89 97 78		$F_{n+k} = F_k F_{n+1} + F_{k-1} F_n,$
		42 53 64 05 16 20 31 98 79 87		$F_{2n} = F_n F_{n+1} + F_{n-1} F_n.$
		The Fibonacci number system:		Calculation by matrices:
		Every integer $n$ has a unique representation		$\begin{pmatrix} F_{n-2} & F_{n-1} \\ F_{n-1} & F_n \end{pmatrix} = \begin{pmatrix} 0 & 1 \\ 1 & 1 \end{pmatrix}^n.$
		$n = F_{k_1} + F_{k_2} + \cdots + F_{k_m},$		
		where $k_i \geq k_{i+1} + 2$ for all $i,$		
		$1 \leq i < m$ and $k_m \geq 2.$		
Improvement makes strait roads, but the crooked roads without Improvement, are roads of Genius. – William Blake (The Marriage of Heaven and Hell)				





