verilogA/va_signals_from_file_9b.va

```
// VerilogA for wk_carrerobardon, va_signals_from_file, veriloga

`include "constants.vams"
`include "disciplines.vams"

`define DATA_WIDTH 9

module va_signals_from_file_9b(data[`DATA_WIDTH-1:0]);

output [`DATA_WIDTH-1:0] data;
electrical [`DATA_WIDTH-1:0] data;

parameter string file_path = "input_signal.txt";

parameter real vlogic_high = 1.2;
parameter real vlogic_low = 0;
parameter real vtrans = 0.6;
parameter real tdel = 1e-12;
parameter real tfall = 50e-12;
parameter real trise = 50e-12;

integer file_descriptor;
real next_launch = 0.0;
genvar k;
integer j;
integer i = 0;
integer current_read [`DATA_WIDTH-1:0];

analog begin

@(initial_step) begin
    file_descriptor = $fopen(file_path, "r" );
end

@(timer(next_launch)) begin
    i = 0;
    for(k = 0; k < `DATA_WIDTH; k = k + 1) begin
         $fscanf(file_descriptor,"%d",current_read[`DATA_WIDTH-1-i]);
        i = i + 1;
    end
    $fscanf(file_descriptor,"%e",next_launch);
    next_launch = next_launch + $abstime;
end

generate i (0, `DATA_WIDTH-1, 1 ) V(data[i]) <+
transition(current_read[i]*vlogic_high, tdel, trise, tfall);

end

endmodule
```