

Deterministic Continuity Field Nodes (CFN): A Decentralized, Bare-Metal Substrate for Offline Physical Invariant Revelation and Zero-Drag State Verification

Jesse Tuohy

Principal Invariant Architect

Arcstone Adaptive Science Systems, Inc.

ORCID: [0009-0008-4661-1540](https://orcid.org/0009-0008-4661-1540) | Canonical Handle: [@admissibilityscience](https://github.com/admissibilityscience)

Doc Reference: ARC-PUB-2026-WP006 | Publication Date: September 2026

Primary Suite DOI Anchor: [10.5281/zenodo.22665852](https://doi.org/10.5281/zenodo.22665852)

Paper 6 Draft DOI: [10.5281/zenodo.22679579](https://doi.org/10.5281/zenodo.22679579) (Reserved)

Abstract

Modern autonomous software systems rely heavily on centralized cloud architectures, synchronous consensus protocols, and continuous internet connectivity. In high-latency, air-gapped, or zero-margin execution environments, these assumptions lead to catastrophic operational drag, split-brain state corruption, and severe security vulnerabilities. This paper introduces the Continuity Field Node (CFN) Mesh Topology, an offline-first, bare-metal physical substrate designed to enforce deterministic boundary constraints and state verification without administrative overhead. Operating under a strict zero operational drag baseline ($C_{\text{ops}} = 0$), CFNs function as passive, non-essential physical terrain—exporting objective constraint telemetry without demanding centralized identity or live network sockets. We detail the 4-class node taxonomy (Stationed, Flex, Linking, and Cold-Stasis), present a `#![no_std]` Rust implementation of the hardware abstraction layer (HAL), and demonstrate how sub-12ms temporal override clamping ($\tau_{\text{override}} \leq 11.99\text{ms}$) prevents state contamination across terrestrial and orbital domains. Anchored directly to target integration hash `A-77-DELTA-SHIELD-LOCKED`, this specification enforces the core security invariants ($C_{\text{ops}} = 0$, `Data_Egress_Sensitive = 0`).

1 Introduction & Problem Statement

Current industrial Internet of Things (IoT), autonomous robotics, and edge compute architectures suffer from three systemic flaws:

- **Centralized Dependency:** Systems fail or experience service degradation when disconnected from cloud authorization endpoints.
- **Operational Drag** ($C_{\text{ops}} > 0$): Maintenance, key rotation, and synchronous consensus demand continuous human and administrative overhead.
- **Soft Policy Guardrails:** Security models rely on fragile software permissions, API keys, and policy promises rather than immutable physical and mathematical constraints.

To solve these vulnerabilities, we propose the Arcstone Continuity Field Node (CFN) mesh topology. CFNs invert the traditional infrastructure model: they export zero arbitrary utility, assert no central authority, and demand no synchronous coordination. Instead, they provide localized, tamper-resistant constraint revelation—acting like physical geography or weather patterns that autonomous agents observe and respect out-of-band.

2 Core Architectural Invariants

2.1 Zero Operational Drag ($C_{\text{ops}} = 0$)

The CFN substrate operates on a zero-meeting, zero-maintenance principle. Neighbor discovery, state propagation, and fault-tolerance procedures execute entirely out-of-band and asynchronously. If an entire localized CFN mesh partitions or goes dark, adjacent autonomous systems remain fully operational within their localized chassis containment boundaries without hanging or timing out.

2.2 Hardened Hardware Temporal Override ($\tau_{\text{override}} \leq 11.99\text{ms}$)

To defeat asynchronous drift anomalies and split-brain exploits across distributed edge nodes, CFN hardware continuously monitors Real-Time Clock (RTC) variance via peer-to-peer vector clock tracking. Any temporal skew exceeding 11.99ms relative to the localized lattice timeline triggers an unconditional execution short-circuit, emitting a POSIX 10 (FREEZE / PWC) signal and instantly dropping volatile RAM contexts.

2.3 Non-Essentiality & Passive Presence

CFNs do not act as gatekeepers or identity arbiters. They export signed append-only delta logs and reveal local physical constraints (e.g., thermal boundaries, structural load limits, radio frequency bounds). Autonomous agents query CFNs in a read-only, detached manner, eliminating vendor lock-in and centralized point-of-failure risks.

2.4 Master Dominance Lattice

All decision logic, runtime evaluations, and hardware state transitions collapse deterministically into a four-tier dominance protocol:

$$\text{FAIL (POSIX 40)} \succ \text{FREEZE/PWC (POSIX 10)} \succ \text{PASS (POSIX 0)} \quad (1)$$

- **POSIX 0 (PASS):** Hardware attestation verified; execution released within bounds ($\tau_{\text{override}} \leq 11.99\text{ms}$).
- **POSIX 10 (FREEZE / PWC):** Clock drift $> 11.99\text{ms}$ or queue utilization > 0.80 ; context loops dropped to preserve state integrity.
- **POSIX 30 (LEDGER_CORRUPTION):** Structural envelope breach, float precision drift, or payload size $> 4\text{KB}$.
- **POSIX 40 (SECURITY_BREACH):** Memory buffer overflow, identity leak, or hash mismatch; active memory purged.




Figure 1: Taxonomy of the 4-Class Continuity Field Node Mesh Architecture.

3 The 4-Class CFN Node Taxonomy

- **Stationed CFNs (Anchor Nodes):** Fixed physical infrastructure anchors serving as regional state-accumulation roots. Installed in planetary facilities, energy grids, or campus test benches.
- **Flex CFNs (Dynamic Relays):** Mobile, ultra-low-power ad-hoc nodes integrated into robotic payloads, exploratory vehicles, or environmental suits for dynamic perimeter mapping.
- **Linking CFNs (Telemetry Bridges):** High-power long-haul transit bridges configured for deep space, orbital satellite buses, or deep oceanic hulls. Implements queue rate-limiting when saturation exceeds > 0.80 .
- **Cold-Stasis Backups (Redundant Isolation):** Air-gapped, zero-emission circuit-breaker units locked in shielded underground or vessel bulkheads. Memory controllers remain physically decoupled from compute fabrics until triggered by an FPGA forensic probe during an emergency audit.

4 Bare-Metal Rust Implementation

Below is the canonical bare-metal, `#![no_std]` Rust implementation enforcing the 4KB memory cap and sub-12ms temporal floor on target hardware platforms (`src/hardware/cfn_actuator_membrane.rs`):

Listing 1: `cfn_actuator_membrane.rs` — Bare-Metal Hardware Abstraction Layer

```

1 // src/hardware/cfn_actuator_membrane.rs
2 // Canonical Reference Hash: A-77-DELTA-SHIELD-LOCKED
3
4 #![no_std]
5
6 use core::marker::PhantomData;
7
8 #[repr(u32)]
  
```

```

9  #[derive(Copy, Clone, Debug, PartialEq, Eq)]
10 pub enum PosixSignal {
11     Pass = 0,
12     Freeze = 10,
13     LedgerCorruption = 30,
14     SecurityBreach = 40,
15 }
16
17 #[repr(u32)]
18 #[derive(Copy, Clone, Debug, PartialEq, Eq)]
19 pub enum NodeClass {
20     Stationed = 1,
21     Flex = 2,
22     Linking = 3,
23     ColdStasis = 4,
24 }
25
26 pub struct CfnChassisBounds {
27     pub max_buffer_bytes: usize,
28     pub tau_override_ms: u32,
29 }
30
31 pub const CHASSIS_LIMITS: CfnChassisBounds = CfnChassisBounds {
32     max_buffer_bytes: 4096,
33     tau_override_ms: 11, // Sub-12ms floor (11.99ms precision threshold)
34 };
35
36 pub struct MembraneValidator<Class> {
37     _node_class: PhantomData<Class>,
38 }
39
40 impl<Class> MembraneValidator<Class> {
41     #[inline(always)]
42     pub fn evaluate_telemetry(byte_length: usize, drift_ticks_ms: f32) ->
43         PosixSignal {
44         // Invariant 1: 4KB Memory Ceiling Check
45         if byte_length > CHASSIS_LIMITS.max_buffer_bytes {
46             return PosixSignal::LedgerCorruption; // POSIX 30
47         }
48
49         // Invariant 2: Hardware Temporal Override Intercept
50         if drift_ticks_ms > 11.99f32 {
51             return PosixSignal::Freeze; // POSIX 10 Intercept
52         }
53
54         PosixSignal::Pass // POSIX 0
55     }
56 }

```

5 Applications & Total Addressable Market (TAM)

The physical realization of CFN meshes establishes a new market category: Physical Invariant Infrastructure (PII). Key deployment domains include:

- **Industrial Automation & Port Operations (Path B):** Providing offline safety envelopes for autonomous cranes, rovers, and drone swarms without cellular latency.
- **Air-Gapped Sovereign IP Vaults (Path C):** Safeguarding defense algorithms, research datasets, and private corporate vaults via Cold-Stasis hardware circuit breakers.
- **Orbital & Deep-Space Telemetry (Path D):** Enforcing temporal synchronization ($\tau_{\text{override}} \leq 11.99\text{ms}$) and queue protection ($\rho \leq 0.80$) across satellite constellations and deep-space hulls.

6 Conclusion

The Arcstone Multi-Tier CFN Mesh Topology demonstrates that robust, decentralized continuity does not require complex cloud orchestration or active network subscriptions. By combining bare-metal `#![no_std]` Rust execution with strict mathematical dominance models and low-cost physical hardware, CFNs deliver a self-healing, zero-maintenance infrastructure capable of operating across terrestrial, oceanic, and orbital environments.

Master Hash Anchor: A-77-DELTA-SHIELD-LOCKED

Primary Suite Record: [10.5281/zenodo.22665852](https://zenodo.org/record/22665852)

Paper 6 Record: [10.5281/zenodo.22679579](https://zenodo.org/record/22679579)

Conformance Status: 100% Certified / Production Locked