Date

Expt. No. 5 Page No.

Aim: To perform initial switch configuration.

Steps:
→ Open packet tracer and place a switch. ~~from~~
→ Double click and go to 'CLI' tab

Configure hostname:
1) Type enable in CLI to enable EXEC mode.
2) Type 'conf t' to change global configuration.
3) Then type 'hostname [name]' to change the name of switch to 'name'.
~~4) Type 'exit' to exit from configuration mode.~~

Configure message of the day (motd)
4) Type banner motd $
5) Then type the message of the day.
6) After you are done type '$' at the end of message

Setting up password
7) 'line console 0' To enable console line configuration.
8) password 123 Set the password to 123
9) then type login and hit enter to enable login for line console.
10) Type exit to leave line console
11) Type enable secret 123 To set up password for exec mode to '123'.
12) Type exit to leave exec mode.

Teacher's Signature :

Changing hostname

Switch> enable
Switch # conf t
Switch (config)# hostname sw0
sw0 (config) #

Configuring message of the day

sw0 (config)# banner motd $
Enter TEXT message. End with character $.
!! Only authorized Personnel Allowed !! $

Setting up password

sw0 (config) # line console 0
sw0 (config-line) # password 123
sw0 (config-line) # login
sw0 (config-line) # exit
sw0 (config) # enable secret 123
sw0 (config) # exit
sw0 #

After configuration

!! Only Authorized personnel !!
User Access Verification
% Password :
sw0 >