Small batch. Big sound.

A practical guide to the smoker controls.



The signal path

Input trim feeds the pitch layer. The combined signal passes through EQ, saturation, compression and reverb. Sauce Mix blends it with a latency-aligned dry signal; Output and the optional safety limiter follow. Global Bypass returns delayed dry input.

Start with a recipe

Sweet & Clean: gentle top-end lift and light compression.
Low & Slow: warmth, compression and a little room.
Memphis Crunch: stronger drive with bass weight.
Hot Honey Vocals: air, compression, subtle detune and space.
Midnight Smoke: darker tone, octave layering and longer ambience.

> Recipes are starting points. Their parameter values are saved in your DAW session; the selector does not maintain or recall a custom preset name.

The smoker sections

Section	What the controls do
Prep Station	Input trim: -24 to +24 dB. Use it to control the level entering the effects.
The Rub	Low shelf at 140 Hz, mid bell at 1.2 kHz, high shelf at 6.5 kHz. Each band provides -12 to +12 dB.
The Firebox	Heat increases nonlinear saturation. Higher settings add stronger harmonic colour. The engine uses first-order antiderivative antialiasing; it is not an amp-model capture.
The Pitmaster	Amount raises the compression ratio from 1:1 toward 8:1. Threshold sets where reduction begins. Detection is stereo linked with a soft knee.
Double Stack	Semitones shifts one layer by -12 to +12. Blend mixes the shifted layer with unshifted input. Signalsmith supplies the pitch engine.
The Smokehouse	Size controls reverb feedback; Mix blends the stereo reverberant signal. This is algorithmic reverb, not a convolution room library.

Master controls

Sauce Mix is the global dry/wet balance. Output ranges from -24 to +12 dB. Each module has an ON switch. Double-click a knob to reset it; hover or drag to see precise values.

Advanced controls and workflow

Advanced

Open Advanced for compression attack (1-100 ms), release (20-1000 ms), makeup gain (0-18 dB), reverb damping, the safety-limiter switch and all host parameters. Controls can be automated by the DAW.

Output safety

The default limiter is a stereo-linked sample-peak attenuator with instantaneous attack and a 100 ms release. Its ceiling is 0.98 linear, about -0.18 dBFS. It is not an intersample true-peak limiter. Global Bypass skips this attenuation, so an already-overloaded input is not repaired by bypassing.

Latency

The pitch engine remains active even at zero layer blend to keep timing stable. The current preset reports 5760 samples at 48 kHz (120 ms). Other sample rates report their own latency. This beta is better suited to mixing than low-latency live monitoring; enable host delay compensation.

Meter and animation

The thermometer and footer show output level; the footer also shows compression reduction and latency. Ember overlays follow Heat, and extra chimney wisps follow Reverb Mix. Animation can be switched off and that preference is stored in the DAW session. Food and background smoke are static artwork.

What is not included

No standalone app, Pro Tools/AAX, AI choir generation, sample import, dynamic EQ, convolution IR browser, draggable module routing or external preset manager. Only Signalsmith is integrated from the proposed upstream list; other audio sections use original project code.

Source and licence

Source: https://github.com/trendyspenders-hub/IRSauce
Original source uses AGPL-3.0-or-later. JUCE 8 uses its AGPL route; Signalsmith dependencies retain MIT notices. See the repository licence and third-party notices.