



Red Hat Enterprise Linux 10-beta

Deploying and managing RHEL on Google Cloud Platform

Obtaining RHEL system images and creating RHEL instances on GCP

Red Hat Enterprise Linux 10-beta Deploying and managing RHEL on Google Cloud Platform

Obtaining RHEL system images and creating RHEL instances on GCP

Legal Notice

Copyright © 2025 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

To use Red Hat Enterprise Linux (RHEL) in a public cloud environment, you can create and deploy RHEL system images on various cloud platforms, including Google Cloud Platform (GCP). You can also create and configure a Red Hat High Availability (HA) cluster on GCP. The following chapters provide instructions for creating cloud RHEL instances and HA clusters on GCP. These processes include installing the required packages and agents, configuring fencing, and installing network resource agents.

Table of Contents

RHEL BETA RELEASE	4
CHAPTER 1. INTRODUCING RHEL ON PUBLIC CLOUD PLATFORMS	5
1.1. BENEFITS OF USING RHEL IN A PUBLIC CLOUD	5
1.2. PUBLIC CLOUD USE CASES FOR RHEL	6
1.3. FREQUENT CONCERNS WHEN MIGRATING TO A PUBLIC CLOUD	6
1.4. OBTAINING RHEL FOR PUBLIC CLOUD DEPLOYMENTS	7
1.5. METHODS FOR CREATING RHEL CLOUD INSTANCES	8
CHAPTER 2. UPLOADING IMAGES TO GCP WITH RHEL IMAGE BUILDER	9
2.1. PREPARING AND UPLOADING CUSTOM GCE IMAGES TO GCP	9
2.1.1. Configuring and uploading a gce image to GCP by using the CLI	9
2.1.2. How RHEL image builder sorts the authentication order of different GCP credentials	10
2.1.3. Specifying GCP credentials with the composer-cli command	11
2.1.4. Specifying credentials in the osbuild-composer worker configuration	11
CHAPTER 3. DEPLOYING A RHEL IMAGE ON GCP	12
3.1. IMAGE OPTIONS ON GCP	12
3.2. UNDERSTANDING BASE IMAGES	13
3.2.1. Using a custom base image	13
3.2.2. Virtual machine configuration settings	13
3.3. CREATING A BASE VM FROM AN ISO IMAGE	14
3.3.1. Creating a VM from the RHEL ISO image	14
3.3.2. Completing the RHEL installation	15
3.4. UPLOADING THE RHEL IMAGE TO GCP	15
3.4.1. Creating a new project on GCP	15
3.4.2. Installing the Google Cloud SDK	16
3.4.3. Creating SSH keys for Google Compute Engine	17
3.4.4. Creating a storage bucket in GCP Storage	17
3.4.5. Converting and uploading your image to your GCP Bucket	18
3.4.6. Creating an image from the object in the GCP bucket	18
3.4.7. Creating a Google Compute Engine instance from an image	19
3.4.8. Connecting to your instance	20
3.4.9. Attaching Red Hat subscriptions	20
CHAPTER 4. CONFIGURING A RED HAT HIGH AVAILABILITY CLUSTER ON GCP	22
4.1. BENEFITS OF USING HIGH-AVAILABILITY CLUSTERS ON PUBLIC CLOUD PLATFORMS	23
4.2. REQUIRED SYSTEM PACKAGES	23
4.3. IMAGE OPTIONS ON GCP	24
4.4. INSTALLING THE GOOGLE CLOUD SDK	25
4.5. CREATING A GCP IMAGE BUCKET	26
4.6. CREATING A CUSTOM VIRTUAL PRIVATE CLOUD NETWORK AND SUBNET	26
4.7. PREPARING AND IMPORTING A BASE GCP IMAGE	26
4.8. CREATING AND CONFIGURING A BASE GCP INSTANCE	27
4.9. CREATING A SNAPSHOT IMAGE	29
4.10. CREATING AN HA NODE TEMPLATE INSTANCE AND HA NODES	30
4.11. INSTALLING HA PACKAGES AND AGENTS	31
4.12. CONFIGURING HA SERVICES	31
4.13. CREATING A CLUSTER	32
4.14. CREATING A FENCING DEVICE	33
4.15. CONFIGURING THE GCP-VCP-MOVE-VIP RESOURCE AGENT	34
4.15.1. Primary subnet address range	34

RHEL BETA RELEASE

Red Hat provides Red Hat Enterprise Linux Beta access to all subscribed Red Hat accounts. The purpose of Beta access is to:

- Provide an opportunity to customers to test major features and capabilities prior to the general availability release and provide feedback or report issues.
- Provide Beta product documentation as a preview. Beta product documentation is under development and is subject to substantial change.

Note that Red Hat does not support the usage of RHEL Beta releases in production use cases. For more information, see the Red Hat Knowledgebase solution [What does Beta mean in Red Hat Enterprise Linux and can I upgrade a RHEL Beta installation to a General Availability \(GA\) release?](#).

CHAPTER 1. INTRODUCING RHEL ON PUBLIC CLOUD PLATFORMS

Public cloud platforms provide computing resources as a service. Instead of using on-premises hardware, you can run your IT workloads, including Red Hat Enterprise Linux (RHEL) systems, as public cloud instances.

1.1. BENEFITS OF USING RHEL IN A PUBLIC CLOUD

RHEL as a cloud instance located on a public cloud platform has the following benefits over RHEL on-premises physical systems or VMs:

- **Flexible and fine-grained allocation of resources**

A cloud instance of RHEL runs as a VM on a cloud platform, which means a cluster of remote servers maintained by the cloud service provider. Therefore, on the software level, allocating hardware resources to the instance is easily customizable, such as a specific type of CPU or storage.

In comparison to a local RHEL system, you are also not limited by the capabilities of physical host. Instead, you can choose from a variety of features, based on selections offered by the cloud provider.

- **Space and cost efficiency**

You do not need to own any on-premise servers to host cloud workloads. This avoids the space, power, and maintenance requirements associated with physical hardware.

Instead, on public cloud platforms, you pay the cloud provider directly for using a cloud instance. The cost is typically based on the hardware allocated to the instance and the time you spend using it. Therefore, you can optimize your costs based on your requirements.

- **Software-controlled configurations**

The entire configuration of a cloud instance is saved as data on the cloud platform, and is controlled by software. Therefore, you can easily create, remove, clone, or migrate the instance. A cloud instance is also operated remotely in a cloud provider console and is connected to remote storage by default.

In addition, you can back up the current state of a cloud instance as a snapshot at any time. Afterwards, you can load the snapshot to restore the instance to the saved state.

- **Separation from the host and software compatibility**

Similarly to a local VM, the RHEL guest operating system on a cloud instance runs on a virtualized kernel. This kernel is separate from the host operating system and from the *client* system that you use to connect to the instance.

Therefore, any operating system can be installed on the cloud instance. This means that on a RHEL public cloud instance, you can run RHEL-specific applications that cannot be used on your local operating system.

In addition, even if the operating system of the instance becomes unstable or is compromised, your client system is not affected in any way.

Additional resources

- [What is public cloud?](#)

- [What is a hyperscaler?](#)
- [Types of cloud computing](#)
- [Public cloud use cases for RHEL](#)
- [Obtaining RHEL for public cloud deployments](#)

1.2. PUBLIC CLOUD USE CASES FOR RHEL

Deploying on a public cloud provides many benefits, but might not be the most efficient solution in every scenario. If you are evaluating whether to migrate your RHEL deployments to the public cloud, consider whether your use case will benefit from the advantages of the public cloud.

Beneficial use cases

- Deploying public cloud instances is very effective for flexibly increasing and decreasing the active computing power of your deployments, also known as *scaling up* and *scaling down*. Therefore, using RHEL on public cloud is recommended in the following scenarios:
 - Clusters with high peak workloads and low general performance requirements. Scaling up and down based on your demands can be highly efficient in terms of resource costs.
 - Quickly setting up or expanding your clusters. This avoids high upfront costs of setting up local servers.
- Cloud instances are not affected by what happens in your local environment. Therefore, you can use them for backup and disaster recovery.

Potentially problematic use cases

- You are running an existing environment that cannot be adjusted. Customizing a cloud instance to fit the specific needs of an existing deployment may not be cost-effective in comparison with your current host platform.
- You are operating with a hard limit on your budget. Maintaining your deployment in a local data center typically provides less flexibility but more control over the maximum resource costs than the public cloud does.

Next steps

- [Obtaining RHEL for public cloud deployments](#)

Additional resources

- [Should I migrate my application to the cloud? Here's how to decide.](#)

1.3. FREQUENT CONCERNS WHEN MIGRATING TO A PUBLIC CLOUD

Moving your RHEL workloads from a local environment to a public cloud platform might raise concerns about the changes involved. The following are the most commonly asked questions.

Will my RHEL work differently as a cloud instance than as a local virtual machine?

In most respects, RHEL instances on a public cloud platform work the same as RHEL virtual machines on a local host, such as an on-premises server. Notable exceptions include:

- Instead of private orchestration interfaces, public cloud instances use provider-specific console interfaces for managing your cloud resources.
- Certain features, such as nested virtualization, may not work correctly. If a specific feature is critical for your deployment, check the feature's compatibility in advance with your chosen public cloud provider.

Will my data stay safe in a public cloud as opposed to a local server?

The data in your RHEL cloud instances is in your ownership, and your public cloud provider does not have any access to it.

In addition, major cloud providers support data encryption in transit, which improves the security of data when migrating your virtual machines to the public cloud.

The general security of RHEL public cloud instances is managed as follows:

- Your public cloud provider is responsible for the security of the cloud hypervisor
- Red Hat provides the security features of the RHEL guest operating systems in your instances
- You manage the specific security settings and practices in your cloud infrastructure

What effect does my geographic region have on the functionality of RHEL public cloud instances?

You can use RHEL instances on a public cloud platform regardless of your geographical location. Therefore, you can run your instances in the same region as your on-premises server.

However, hosting your instances in a physically distant region might cause high latency when operating them. In addition, depending on the public cloud provider, certain regions may provide additional features or be more cost-efficient. Before creating your RHEL instances, review the properties of the hosting regions available for your chosen cloud provider.

1.4. OBTAINING RHEL FOR PUBLIC CLOUD DEPLOYMENTS

To deploy a RHEL system in a public cloud environment, you need to:

1. Select the optimal cloud provider for your use case, based on your requirements and the current offer on the market.

The cloud providers currently certified for running RHEL instances are:

- [Amazon Web Services \(AWS\)](#)
- [Google Cloud Platform \(GCP\)](#)
- [Microsoft Azure](#)



NOTE

This document specifically talks about deploying RHEL on GCP.

2. Create a RHEL cloud instance on your chosen cloud platform. For details, see [Methods for creating RHEL cloud instances](#).
3. To keep your RHEL deployment up-to-date, use [Red Hat Update Infrastructure \(RHUI\)](#).

Additional resources

- [RHUI documentation](#)
- [Red Hat Open Hybrid Cloud](#)

1.5. METHODS FOR CREATING RHEL CLOUD INSTANCES

To deploy a RHEL instance on a public cloud platform, you can use one of the following methods:

Create a RHEL system image and import it to the cloud platform

- To create the system image, you can use the [RHEL image builder](#) or you can build the image manually.
- This method uses your existing RHEL subscription, and is also referred to as *bring your own subscription* (BYOS).
- You pre-pay a yearly subscription, and you can use your Red Hat customer discount.
- Your customer service is provided by Red Hat.
- For creating multiple images effectively, you can use the **cloud-init** tool.

Purchase a RHEL instance directly from the cloud provider marketplace

- You post-pay an hourly rate for using the service. Therefore, this method is also referred to as *pay as you go* (PAYG).
- Your customer service is provided by the cloud platform provider.



NOTE

For detailed instructions on using various methods to deploy RHEL instances on Google Cloud Platform, see the following chapters in this document.

Additional resources

- [What is a golden image?](#)
- [Configuring and managing cloud-init for RHEL](#)

CHAPTER 2. UPLOADING IMAGES TO GCP WITH RHEL IMAGE BUILDER

With RHEL image builder, you can build a **gce** image, provide credentials for your user or GCP service account, and then upload the **gce** image directly to the GCP environment.

2.1. PREPARING AND UPLOADING CUSTOM GCE IMAGES TO GCP

With RHEL image builder, you can build a **gce** image, provide credentials for your user or GCP service account, and then upload the **gce** image directly to the GCP environment.

2.1.1. Configuring and uploading a gce image to GCP by using the CLI

Set up a configuration file with credentials to upload your **gce** image to GCP by using the RHEL image builder CLI.



WARNING

You cannot manually import **gce** image to GCP, because the image will not boot. You must use either **gcloud** or RHEL image builder to upload it.

Prerequisites

- You have a valid Google account and credentials to upload your image to GCP. The credentials can be from a user account or a service account. The account associated with the credentials must have at least the following IAM roles assigned:
 - **roles/storage.admin** - to create and delete storage objects
 - **roles/compute.storageAdmin** - to import a VM image to Compute Engine.
- You have an existing GCP bucket.

Procedure

1. Use a text editor to create a **gcp-config.toml** configuration file with the following content:

```
provider = "gcp"
[settings]
bucket = "GCP_BUCKET"
region = "GCP_STORAGE_REGION"
object = "OBJECT_KEY"
credentials = "GCP_CREDENTIALS"
```

- **GCP_BUCKET** points to an existing bucket. It is used to store the intermediate storage object of the image which is being uploaded.
- **GCP_STORAGE_REGION** is both a regular Google storage region and a dual or multi region.

- **OBJECT_KEY** is the name of an intermediate storage object. It must not exist before the upload, and it is deleted when the upload process is done. If the object name does not end with **.tar.gz**, the extension is automatically added to the object name.
- **GCP_CREDENTIALS** is a **Base64**-encoded scheme of the credentials JSON file downloaded from GCP. The credentials determine which project the GCP uploads the image to.



NOTE

Specifying **GCP_CREDENTIALS** in the **gcp-config.toml** file is optional if you use a different mechanism to authenticate with GCP. For other authentication methods, see [Authenticating with GCP](#).

2. Retrieve the **GCP_CREDENTIALS** from the JSON file downloaded from GCP.

```
$ sudo base64 -w 0 cee-gcp-nasa-476a1fa485b7.json
```

3. Create a compose with an additional image name and cloud provider profile:

```
$ sudo composer-cli compose start BLUEPRINT-NAME gce IMAGE_KEY gcp-config.toml
```

The image build, upload, and cloud registration processes can take up to ten minutes to complete.

Verification

- Verify that the image status is FINISHED:

```
$ sudo composer-cli compose status
```

Additional resources

- [Identity and Access Management](#)
- [Create storage buckets](#)

2.1.2. How RHEL image builder sorts the authentication order of different GCP credentials

You can use several different types of credentials with RHEL image builder to authenticate with GCP. If RHEL image builder configuration is set to authenticate with GCP using multiple sets of credentials, it uses the credentials in the following order of preference:

1. Credentials specified with the **composer-cli** command in the configuration file.
2. Credentials configured in the **osbuild-composer** worker configuration.
3. **Application Default Credentials** from the **Google GCP SDK** library, which tries to automatically find a way to authenticate by using the following options:
 - a. If the **GOOGLE_APPLICATION_CREDENTIALS** environment variable is set, Application Default Credentials tries to load and use credentials from the file pointed to by the variable.

- b. Application Default Credentials tries to authenticate by using the service account attached to the resource that is running the code. For example, Google Compute Engine VM.



NOTE

You must use the GCP credentials to determine which GCP project to upload the image to. Therefore, unless you want to upload all of your images to the same GCP project, you always must specify the credentials in the **gcp-config.toml** configuration file with the **composer-cli** command.

2.1.3. Specifying GCP credentials with the **composer-cli** command

You can configure GCP authentication credentials to be used for GCP globally for all image builds. This way, if you want to import images to the same GCP project, you can use the same credentials for all image uploads to GCP.

Procedure

- In the **/etc/osbuild-worker/osbuild-worker.toml** worker configuration, set the following credential value:

```
[gcp]
credentials = "PATH_TO_GCP_ACCOUNT_CREDENTIALS"
```

2.1.4. Specifying credentials in the **osbuild-composer** worker configuration

You can configure GCP authentication credentials to be used for GCP globally for all image builds. This way, if you want to import images to the same GCP project, you can use the same credentials for all image uploads to GCP.

Procedure

- In the **/etc/osbuild-worker/osbuild-worker.toml** worker configuration, set the following credential value:

```
[gcp]
credentials = "PATH_TO_GCP_ACCOUNT_CREDENTIALS"
```

CHAPTER 3. DEPLOYING A RHEL IMAGE ON GCP

To set up a deployment of Red Hat Enterprise Linux on Google Cloud Platform (GCP), you can deploy RHEL as a Google Compute Engine (GCE) instance on GCP.



NOTE

For a list of Red Hat product certifications for GCP, see [Red Hat on Google Cloud Platform](#).



IMPORTANT

You can create a custom VM from an ISO image, but Red Hat recommends that you use the *Red Hat Image Builder* product to create customized images for use on specific cloud providers. See [Composing a Customized {ProductShortName} System Image](#) for more information.

Prerequisites

- You need a [Red Hat Customer Portal](#) account to complete the procedures in this chapter.
- Create an account with GCP to access the Google Cloud Platform Console. See [Google Cloud](#) for more information.

3.1. IMAGE OPTIONS ON GCP

You can use multiple types of images for deploying RHEL on Google Cloud Platform. Based on your requirements, consider which option is optimal for your use case.

Table 3.1. Image options

Image option	Subscriptions	Sample scenario	Considerations
Deploy a Red Hat Gold Image.	Use your existing Red Hat subscriptions.	Select a Red Hat Gold Image on Google Cloud Platform. For details on Gold Images and how to access them on Google Cloud Platform, see the Red Hat Cloud Access Reference Guide .	The subscription includes the Red Hat product cost; you pay Google for all other instance costs. Red Hat provides support directly for custom RHEL images.
Deploy a custom image that you move to GCP.	Use your existing Red Hat subscriptions.	Upload your custom image and attach your subscriptions.	The subscription includes the Red Hat product cost; you pay all other instance costs. Red Hat provides support directly for custom RHEL images.

Image option	Subscriptions	Sample scenario	Considerations
Deploy an existing GCP image that includes RHEL.	The GCP images include a Red Hat product.	Choose a RHEL image when you launch an instance on the GCP Compute Engine , or choose an image from the Google Cloud Platform Marketplace .	You pay GCP hourly on a pay-as-you-go model. Such images are called "on-demand" images. GCP offers support for on-demand images through a support agreement.

**NOTE**

You can create a custom image for GCP by using Red Hat Image Builder. See [Composing a Customized RHEL System Image](#) for more information.

**IMPORTANT**

You cannot convert an on-demand instance to a custom RHEL instance. To change from an on-demand image to a custom RHEL *bring-your-own-subscription* (BYOS) image:

1. Create a new custom RHEL instance and migrate data from your on-demand instance.
2. Cancel your on-demand instance after you migrate your data to avoid double billing.

Additional resources

- [Red Hat in the Public Cloud](#)
- [Compute Engine images](#)
- [Creating an instance from a custom image](#)

3.2. UNDERSTANDING BASE IMAGES

To create a base VM from an ISO image, you can use preconfigured base images and their configuration settings.

3.2.1. Using a custom base image

To manually configure a virtual machine (VM), first create a base (starter) VM image. Then, you can modify configuration settings and add the packages the VM requires to operate on the cloud. You can make additional configuration changes for your specific application after you upload the image.

To prepare a cloud image of RHEL, follow the instructions in the sections below. To prepare a Hyper-V cloud image of RHEL, see the [Prepare a Red Hat-based virtual machine from Hyper-V Manager](#).

3.2.2. Virtual machine configuration settings

Cloud VMs must have the following configuration settings.

Table 3.2. VM configuration settings

Setting	Recommendation
ssh	ssh must be enabled to provide remote access to your VMs.
dhcp	The primary virtual adapter should be configured for dhcp.

3.3. CREATING A BASE VM FROM AN ISO IMAGE

To create a RHEL base image from an ISO image, enable your host machine for virtualization and create a RHEL virtual machine (VM).

Prerequisites

- [Virtualization is enabled](#) on your host machine.
- You have downloaded the latest RHEL ISO image from the [Red Hat Customer Portal](#) and moved the image to `/var/lib/libvirt/images`.

3.3.1. Creating a VM from the RHEL ISO image

Procedure

1. Ensure that you have enabled your host machine for virtualization. See [Enabling virtualization in RHEL 9](#) for information and procedures.
2. Create and start a basic RHEL VM. For instructions, see [Creating virtual machines](#).
 - a. If you use the command line to create your VM, ensure that you set the default memory and CPUs to the capacity you want for the VM. Set your virtual network interface to **virtio**. For example, the following command creates a **kvmtest** VM by using the `/home/username/Downloads/rhel{ProductNumber}.iso` image:

```
# virt-install \
--name kvmtest --memory 2048 --vcpus 2 \
--cdrom /home/username/Downloads/rhel{ProductNumber}.iso,bus=virtio \
--os-variant=rhel{ProductNumber}.0
```

- b. If you use the web console to create your VM, follow the procedure in [Creating virtual machines by using the web console](#), with these caveats:
 - Do not check **Immediately Start VM**.
 - Change your **Memory** size to your preferred settings.
 - Before you start the installation, ensure that you have changed **Model** under **Virtual Network Interface Settings** to **virtio** and change your **vCPUs** to the capacity settings you want for the VM.

3.3.2. Completing the RHEL installation

To finish the installation of a RHEL system that you want to deploy on specific cloud service, customize the **Installation Summary** view, begin the installation, and enable root access once the VM launches.

Procedure

1. Choose the language you want to use during the installation process.
2. On the **Installation Summary** view:
 - a. Click **Software Selection** and check **Minimal Install**.
 - b. Click **Done**.
 - c. Click **Installation Destination** and check **Custom** under **Storage Configuration**.
 - i. Verify at least 500 MB for **/boot**. You can use the remaining space for root **/**.
 - ii. Standard partitions are recommended, but you can use Logical Volume Manager (LVM).
 - iii. You can use xfs, ext4, or ext3 for the file system.
 - iv. Click **Done** when you are finished with changes.
 1. Click **Begin Installation**.
 2. Set a **Root Password**. Create other users as applicable.
 3. Reboot the VM and log in as **root** once the installation completes.
 4. Register the VM and enable the RHEL repository:


```
# subscription-manager register --auto-attach
```
 5. Ensure that the **cloud-init** package is installed and enabled:


```
# {PackageManagerCommand} install cloud-init
# systemctl enable --now cloud-init.service
```
6. Power down the VM.

Additional resources

- [Introduction to cloud-init](#)

3.4. UPLOADING THE RHEL IMAGE TO GCP

To run your RHEL instance on Google Cloud Platform (GCP), you must upload your RHEL image to GCP.

3.4.1. Creating a new project on GCP

To upload your Red Hat Enterprise Linux image to Google Cloud Platform (GCP), you must first create a new project on GCP.

Prerequisites

- You have an account on [Google Cloud Platform](#).

Procedure

1. Launch the [GCP Console](#).
2. Click the drop-down menu to the right of **Google Cloud Platform**.
3. From the pop-up menu, click **NEW PROJECT**.
4. From the **New Project** window, enter a name for your new project.
5. Check **Organization**. Click the drop-down menu to change the organization, if necessary.
6. Confirm the **Location** of your parent organization or folder. Click **Browse** to search for and change this value, if necessary.
7. Click **CREATE** to create your new GCP project.

Additional resources

- [Creating and Managing Resources in Google Cloud](#)

3.4.2. Installing the Google Cloud SDK

Many of the procedures to manage HA clusters on Google Cloud Platform (GCP) require the tools in the Google Cloud SDK.

Procedure

1. Follow the GCP instructions for downloading and extracting the Google Cloud SDK archive. See the GCP document [Quickstart for Linux](#) for details.
2. Follow the same instructions for initializing the Google Cloud SDK.

Next steps

1. Once you initialize the Google Cloud SDK, you can use the **gcloud** CLI commands to perform tasks and manage your project and instances.
2. Create a project:

```
# gcloud projects create <example-gcp-project-id> --name <example-gcp-project>
```

The example creates a project with the project ID **<example-gcp-project-id>** and the project name **<example-gcp-project>**.

3. Display project information:

```
# gcloud compute <example-project-info> describe --project <example-project-name>
```

Additional resources

- [Quickstart for Linux](#)
- [gcloud project create](#)
- [gcloud command-line tool overview](#)

3.4.3. Creating SSH keys for Google Compute Engine

Generate and register SSH keys with GCE so that you can SSH directly into an instance by using its public IP address.

Procedure

1. Use the **ssh-keygen** command to generate an SSH key pair for use with GCE.

```
# ssh-keygen -t rsa -f ~/.ssh/google_compute_engine
```

2. From the [GCP Console Dashboard page](#), click the **Navigation** menu to the left of the Google **Cloud Console banner** and select **Compute Engine** and then select **Metadata**.
3. Click **SSH Keys** and then click **Edit**.
4. Enter the output generated from the `~/.ssh/google_compute_engine.pub` file and click **Save**. You can now connect to your instance by using standard SSH.

```
# ssh -i ~/.ssh/google_compute_engine <username>@<instance_external_ip>
```



NOTE

You can run the **gcloud compute config-ssh** command to populate your config file with aliases for your instances. The aliases allow simple SSH connections by instance name. For information about the **gcloud compute config-ssh** command, see [gcloud compute config-ssh](#).

Additional resources

- [gcloud compute config-ssh](#)
- [Connecting to instances](#)

3.4.4. Creating a storage bucket in GCP Storage

To import RHEL image to GCP, you must first create a GCP Storage Bucket.

Procedure

1. If you are not already logged in to GCP, log in:

```
# gcloud auth login
```

2. Create a storage bucket:

```
# gsutil mb gs://bucket_name
```

**NOTE**

Alternatively, you can use the Google Cloud Console to create a bucket. For details, see [Create a bucket](#).

Additional resources

- [Create a bucket](#)

3.4.5. Converting and uploading your image to your GCP Bucket

Before a local RHEL image can be deployed in GCP, you must first convert and upload the image to your GCP Bucket. The following steps describe converting an **qcow2** image to **raw** format and then uploading the image as a **tar** archive. However, using different formats is possible as well.

Procedure

1. Run the **qemu-img** command to convert your image. The converted image must have the name **disk.raw**.

```
# qemu-img convert -f qcow2 -O raw rhel-10.0-sample.qcow2 disk.raw
```

1. Tar the image.

```
# tar --format=oldgnu -Sczf disk.raw.tar.gz disk.raw
```

2. Upload the image to the bucket you created previously. Upload could take a few minutes.

```
# gsutil cp disk.raw.tar.gz gs://bucket_name
```

3. From the **Google Cloud Platform** home screen, click the collapsed menu icon and select **Storage** and then select **Browser**.
4. Click the name of your bucket.
The tarred image is listed under your bucket name.

**NOTE**

You can also upload your image by using the **GCP Console**. To do so, click the name of your bucket and then click **Upload files**.

Additional resources

- [Manually importing virtual disks](#)
- [Choosing an import method](#)


3.4.6. Creating an image from the object in the GCP bucket

Before you can create a GCE image from an object that you uploaded to your GCP bucket, you must convert the object into a GCE image.

Procedure

1. Run the following command to create an image for GCE. Specify the name of the image you are creating, the bucket name, and the name of the tarred image.

```
# **gcloud compute images create my-image-name --source-uri gs://my-bucket-name/disk.raw.tar.gz**
```



NOTE

Alternatively, you can use the Google Cloud Console to create an image. See [Creating, deleting, and deprecating custom images](#) for more information.

2. Optional: Find the image in the GCP Console.
 - a. Click the **Navigation** menu to the left of the **Google Cloud Console** banner.
 - b. Select **Compute Engine** and then **Images**.

Additional resources

- [Creating, deleting, and deprecating custom images](#)
- [gcloud compute images create](#)

3.4.7. Creating a Google Compute Engine instance from an image

To configure a GCE VM instance from an image, use the GCP Console.



NOTE

See [Creating and starting a VM instance](#) for more information about GCE VM instances and their configuration options.

Procedure

1. From the [GCP Console Dashboard page](#), click the **Navigation** menu to the left of the **Google Cloud Console banner** and select **Compute Engine** and then select **Images**.
2. Select your image.
3. Click **Create Instance**.
4. On the **Create an instance** page, enter a **Name** for your instance.
5. Choose a **Region** and **Zone**.
6. Choose a **Machine configuration** that meets or exceeds the requirements of your workload.
7. Ensure that **Boot disk** specifies the name of your image.
8. Optional: Under **Firewall**, select **Allow HTTP traffic** or **Allow HTTPS traffic**.
9. Click **Create**.

**NOTE**

These are the minimum configuration options necessary to create a basic instance. Review additional options based on your application requirements.

10. Find your image under **VM instances**.
11. From the GCP Console Dashboard, click the **Navigation** menu to the left of the Google **Cloud Console banner** and select **Compute Engine** and then select **VM instances**.

**NOTE**

Alternatively, you can use the **gcloud compute instances create** CLI command to create a GCE VM instance from an image. A simple example follows.

```
# gcloud compute instances create myinstance3 --zone=us-central1-a --image test-iso2-image
```

The example creates a VM instance named **myinstance3** in zone **us-central1-a** based upon the existing image **test-iso2-image**. See [gcloud compute instances create](#) for more information.

3.4.8. Connecting to your instance

Connect to your GCE instance by using its public IP address.

Procedure

1. Ensure that your instance is running. The following command lists information about your GCE instance, including whether the instance is running, and, if so, the public IP address of the running instance.

```
# gcloud compute instances list
```

2. Connect to your instance by using standard SSH. The example uses the **google_compute_engine** key created earlier.

```
# ssh -i ~/.ssh/google_compute_engine <user_name>@<instance_external_ip>
```

**NOTE**

GCP offers a number of ways to SSH into your instance. See [Connecting to instances](#) for more information. You can also connect to your instance using the root account and password you set previously.

Additional resources

- [gcloud compute instances list](#)
- [Connecting to instances](#)

3.4.9. Attaching Red Hat subscriptions

Using the **subscription-manager** command, you can register and attach your Red Hat subscription to a RHEL instance.

Prerequisites

- You have an active [Red Hat account](#).

Procedure

1. Register your system:

```
# subscription-manager register --auto-attach
```

2. Attach your subscriptions:

- You can use an activation key to attach subscriptions. See [Creating Red Hat Customer Portal Activation Keys](#) for more information.
- Alternatively, you can manually attach a subscription by using the ID of the subscription pool (Pool ID). See [Attaching a host-based subscription to hypervisors](#).

3. Optional: To collect various system metrics about the instance in the [Red Hat Hybrid Cloud Console](#), you can register the instance with [Red Hat Insights](#).

```
# insights-client register --display-name <display-name-value>
```

For information on further configuration of Red Hat Insights, see [Client Configuration Guide for Red Hat Insights](#).

Additional resources

- [Creating Red Hat Customer Portal Activation Keys](#)
- [Attaching a host-based subscription to hypervisors](#)
- [Client Configuration Guide for Red Hat Insights](#)

CHAPTER 4. CONFIGURING A RED HAT HIGH AVAILABILITY CLUSTER ON GCP

To create a cluster where RHEL nodes automatically redistribute their workloads if a node failure occurs, use the Red Hat High Availability Add-On. Such high availability (HA) clusters can also be hosted on public cloud platforms, including Google Cloud Platform (GCP). Creating RHEL HA clusters on GCP is similar to creating HA clusters in non-cloud environments, with certain specifics.

To configure a Red Hat HA cluster on Google Cloud Platform (GCP) using Google Compute Engine (GCE) virtual machine (VM) instances as cluster nodes, see the following sections.

These provide information on:

- Setting up your environment for GCP. Once you have set up your environment, you can create and configure VM instances.
- Creation of HA clusters, which transform individual nodes into a cluster of HA nodes on GCP. These include procedures for installing the High Availability packages and agents on each cluster node, configuring fencing, and installing network resource agents.

Prerequisites

- Red Hat Enterprise Linux 10 Server: **rhel-10-server-rpms/8Server/x86_64**
- Red Hat Enterprise Linux 10 Server (High Availability): **rhel-10-server-ha-rpms/8Server/x86_64**
- You must belong to an active GCP project and have required permissions to create resources in the project.
- Your project should have a [service account](#) that belongs to a VM instance and not an individual user. See [Using the Compute Engine Default Service Account](#) for information about using the default service account instead of creating a separate service account.

If you or your project administrator create a custom service account, the service account should be configured for the following roles.

- Cloud Trace Agent
- Compute Admin
- Compute Network Admin
- Cloud Datastore User
- Logging Admin
- Monitoring Editor
- Monitoring Metric Writer
- Service Account Administrator
- Storage Admin

4.1. BENEFITS OF USING HIGH-AVAILABILITY CLUSTERS ON PUBLIC CLOUD PLATFORMS

A high-availability (HA) cluster is a set of computers (called *nodes*) that are linked together to run a specific workload. The purpose of HA clusters is to provide redundancy in case of a hardware or software failure. If a node in the HA cluster fails, the Pacemaker cluster resource manager distributes the workload to other nodes and no noticeable downtime occurs in the services that are running on the cluster.

You can also run HA clusters on public cloud platforms. In this case, you would use virtual machine (VM) instances in the cloud as the individual cluster nodes. Using HA clusters on a public cloud platform has the following benefits:

- *Improved availability:* In case of a VM failure, the workload is quickly redistributed to other nodes, so running services are not disrupted.
- *Scalability:* Additional nodes can be started when demand is high and stopped when demand is low.
- *Cost-effectiveness:* With the pay-as-you-go pricing, you pay only for nodes that are running.
- *Simplified management:* Some public cloud platforms offer management interfaces to make configuring HA clusters easier.

To enable HA on your RHEL systems, Red Hat offers a High Availability Add-On. The High Availability Add-On provides all necessary components for creating HA clusters on RHEL systems. The components include high availability service management and cluster administration tools.

Additional resources

- [High Availability Add-On overview](#)

4.2. REQUIRED SYSTEM PACKAGES

To create and configure a base image of RHEL, your host system must have the following packages installed.

Table 4.1. System packages

Package	Repository	Description
libvirt	rhel-{ProductNumber}-for-x86_64-appstream-rpms	Open source API, daemon, and management tool for managing platform virtualization
virt-install	rhel-{ProductNumber}-for-x86_64-appstream-rpms	A command-line utility for building VMs
libguestfs	rhel-{ProductNumber}-for-x86_64-appstream-rpms	A library for accessing and modifying VM file systems

Package	Repository	Description
guestfs-tools	rhel-{ProductNumber}-for-x86_64-appstream-rpms	System administration tools for VMs; includes the virt-customize utility

4.3. IMAGE OPTIONS ON GCP

You can use multiple types of images for deploying RHEL on Google Cloud Platform. Based on your requirements, consider which option is optimal for your use case.

Table 4.2. Image options

Image option	Subscriptions	Sample scenario	Considerations
Deploy a Red Hat Gold Image.	Use your existing Red Hat subscriptions.	Select a Red Hat Gold Image on Google Cloud Platform. For details on Gold Images and how to access them on Google Cloud Platform, see the Red Hat Cloud Access Reference Guide .	The subscription includes the Red Hat product cost; you pay Google for all other instance costs. Red Hat provides support directly for custom RHEL images.
Deploy a custom image that you move to GCP.	Use your existing Red Hat subscriptions.	Upload your custom image and attach your subscriptions.	The subscription includes the Red Hat product cost; you pay all other instance costs. Red Hat provides support directly for custom RHEL images.
Deploy an existing GCP image that includes RHEL.	The GCP images include a Red Hat product.	Choose a RHEL image when you launch an instance on the GCP Compute Engine , or choose an image from the Google Cloud Platform Marketplace .	You pay GCP hourly on a pay-as-you-go model. Such images are called "on-demand" images. GCP offers support for on-demand images through a support agreement.



NOTE

You can create a custom image for GCP by using Red Hat Image Builder. See [Composing a Customized RHEL System Image](#) for more information.



IMPORTANT

You cannot convert an on-demand instance to a custom RHEL instance. To change from an on-demand image to a custom RHEL *bring-your-own-subscription* (BYOS) image:

1. Create a new custom RHEL instance and migrate data from your on-demand instance.
2. Cancel your on-demand instance after you migrate your data to avoid double billing.

Additional resources

- [Red Hat in the Public Cloud](#)
- [Compute Engine images](#)
- [Creating an instance from a custom image](#)

4.4. INSTALLING THE GOOGLE CLOUD SDK

Many of the procedures to manage HA clusters on Google Cloud Platform (GCP) require the tools in the Google Cloud SDK.

Procedure

1. Follow the GCP instructions for downloading and extracting the Google Cloud SDK archive. See the GCP document [Quickstart for Linux](#) for details.
2. Follow the same instructions for initializing the Google Cloud SDK.

Next steps

1. Once you initialize the Google Cloud SDK, you can use the **gcloud** CLI commands to perform tasks and manage your project and instances.
2. Create a project:

```
# gcloud projects create <example-gcp-project-id> --name <example-gcp-project>
```

The example creates a project with the project ID **<example-gcp-project-id>** and the project name **<example-gcp-project>**.

3. Display project information:

```
# gcloud compute <example-project-info> describe --project <example-project-name>
```

Additional resources

- [Quickstart for Linux](#)
- [gcloud project create](#)
- [gcloud command-line tool overview](#)

4.5. CREATING A GCP IMAGE BUCKET

The following document includes the minimum requirements for creating a [multi-regional](#) bucket in your default location.

Prerequisites

- GCP storage utility (gsutil)

Procedure

1. If you are not already logged in to Google Cloud Platform, log in with the following command:

```
$ gcloud auth login
```

2. Create a storage bucket:

```
$ gsutil mb gs://BucketName
```

Example:

```
$ gsutil mb gs://rhel-ha-bucket
```

Additional resources

- [Make buckets](#)

4.6. CREATING A CUSTOM VIRTUAL PRIVATE CLOUD NETWORK AND SUBNET

A custom virtual private cloud (VPC) network and subnet are required for a cluster to be configured with a High Availability (HA) function.

Procedure

1. Launch the GCP Console.
2. Select **VPC networks** under **Networking** in the left navigation pane.
3. Click **Create VPC Network**
4. Enter a name for the VPC network.
5. Under the **New subnet**, create a **Custom subnet** in the region where you want to create the cluster.
6. Click **Create**.

4.7. PREPARING AND IMPORTING A BASE GCP IMAGE

Before a local RHEL 10 image can be deployed in GCP, you must first convert and upload the image to your GCP Bucket.

Procedure

1. Convert the file. Images uploaded to GCP must be in **raw** format and named **disk.raw**.

```
$ qemu-img convert -f qcow2 ImageName.qcow2 -O raw disk.raw
```

2. Compress the **raw** file. Images uploaded to GCP must be compressed.

```
$ tar -Sczf ImageName.tar.gz disk.raw
```

3. Import the compressed image to the bucket created earlier.

```
$ gsutil cp ImageName.tar.gz gs://BucketName
```

4.8. CREATING AND CONFIGURING A BASE GCP INSTANCE

To create and configure a GCP instance that complies with GCP operating and security requirements, complete the following steps.

Procedure

1. Create an image from the compressed file in the bucket.

```
$ gcloud compute images create BaseImageName --source-uri  
gs://BucketName/BaseImageName.tar.gz
```

Example:

```
$ gcloud compute images create rhel-76-server --source-uri gs://user-rhelha/rhel-server-  
76.tar.gz  
Created [https://www.googleapis.com/compute/v1/projects/MyProject/global/images/rhel-  
server-76].  
NAME          PROJECT          FAMILY DEPRECATED STATUS  
rhel-76-server rhel-ha-testing-on-gcp          READY
```

2. Create a template instance from the image. The minimum size required for a base RHEL instance is n1-standard-2. See [gcloud compute instances create](#) for additional configuration options.

```
$ gcloud compute instances create BaseInstanceName --can-ip-forward --machine-type n1-  
standard-2 --image BaseImageName --service-account ServiceAccountEmail
```

Example:

```
$ gcloud compute instances create rhel-76-server-base-instance --can-ip-forward --machine-  
type n1-standard-2 --image rhel-76-server --service-account account@project-name-on-  
gcp.iam.gserviceaccount.com  
Created [https://www.googleapis.com/compute/v1/projects/rhel-ha-testing-on-gcp/zones/us-  
east1-b/instances/rhel-76-server-base-instance].  
NAME  ZONE  MACHINE_TYPE  PREEMPTIBLE  INTERNAL_IP  EXTERNAL_IP  
STATUS  
rhel-76-server-base-instance  us-east1-bn1-standard-2      10.10.10.3  192.227.54.211  
RUNNING
```

3. Connect to the instance with an SSH terminal session.

```
$ ssh root@PublicIPAddress
```

4. Update the RHEL software.

- Register with Red Hat Subscription Manager (RHSM).
- Enable a Subscription Pool ID (or use the **--auto-attach** command).
- Disable all repositories.

```
# subscription-manager repos --disable=*
```

- Enable the following repository.

```
# subscription-manager repos --enable=rhel-10-server-rpms
```

- Run the **dnf update** command.

```
# dnf update -y
```

5. Install the GCP Linux Guest Environment on the running instance (in-place installation).

See [Install the guest environment in-place](#) for instructions.

6. Select the **CentOS/RHEL** option.

7. Copy the command script and paste it at the command prompt to run the script immediately.

8. Make the following configuration changes to the instance. These changes are based on GCP recommendations for custom images. See [gcloudcompute images list](#) for more information.

- Edit the **/etc/chrony.conf** file and remove all NTP servers.
- Add the following NTP server.

```
metadata.google.internal iburst Google NTP server
```

- Remove any persistent network device rules.

```
# rm -f /etc/udev/rules.d/70-persistent-net.rules
# rm -f /etc/udev/rules.d/75-persistent-net-generator.rules
```

- Set the network service to start automatically.

```
# chkconfig network on
```

- Set the **sshd service** to start automatically.

```
# systemctl enable sshd
# systemctl is-enabled sshd
```

- Set the time zone to UTC.


```
# ln -sf /usr/share/zoneinfo/UTC /etc/localtime
```

- g. Optional: Edit the **/etc/ssh/ssh_config** file and add the following lines to the end of the file. This keeps your SSH session active during longer periods of inactivity.


```
# Server times out connections after several minutes of inactivity.
# Keep alive ssh connections by sending a packet every 7 minutes.
ServerAliveInterval 420
```

- h. Edit the **/etc/ssh/sshd_config** file and make the following changes, if necessary. The **ClientAliveInterval 420** setting is optional; this keeps your SSH session active during longer periods of inactivity.

```
PermitRootLogin no
PasswordAuthentication no
AllowTcpForwarding yes
X11Forwarding no
PermitTunnel no
# Compute times out connections after 10 minutes of inactivity.
# Keep ssh connections alive by sending a packet every 7 minutes.
ClientAliveInterval 420
```

9. Disable password access.

```
ssh_pwauth from 1 to 0.
ssh_pwauth: 0
```



IMPORTANT

Previously, you enabled password access to allow SSH session access to configure the instance. You must disable password access. All SSH session access must be passwordless.

10. Unregister the instance from the subscription manager.

```
# subscription-manager unregister
```

11. Clean the shell history. Keep the instance running for the next procedure.

```
# export HISTSIZE=0
```

4.9. CREATING A SNAPSHOT IMAGE

To preserve the configuration and disk data of a GCP HA instance, create a snapshot of it.

Procedure

1. On the running instance, synchronize data to disk.

```
# sync
```

2. On your host system, create the snapshot.

```
$ gcloud compute disks snapshot InstanceName --snapshot-names SnapshotName
```

3. On your host system, create the configured image from the snapshot.

```
$ gcloud compute images create ConfiguredImageFromSnapshot --source-snapshot SnapshotName
```

Additional resources

- [Creating Persistent Disk Snapshots](#)

4.10. CREATING AN HA NODE TEMPLATE INSTANCE AND HA NODES

After you have configured an image from the snapshot, you can create a node template. Then, you can use this template to create all HA nodes.

Procedure

1. Create an instance template.

```
$ gcloud compute instance-templates create InstanceTemplateName --can-ip-forward --  
machine-type n1-standard-2 --image ConfiguredImageFromSnapshot --service-account  
ServiceAccountEmailAddress
```

Example:

```
$ gcloud compute instance-templates create rhel-101-instance-template --can-ip-forward --  
machine-type n1-standard-2 --image rhel-{ProductNumber}1-gcp-image --service-account  
account@project-name-on-gcp.iam.gserviceaccount.com  
Created [https://www.googleapis.com/compute/v1/projects/project-name-on-  
gcp/global/instanceTemplates/rhel-101-instance-template].  
NAME MACHINE_TYPE PREEMPTIBLE CREATION_TIMESTAMP  
rhel-101-instance-template n1-standard-2 2018-07-25T11:09:30.506-07:00
```

2. Create multiple nodes in one zone.

```
# gcloud compute instances create NodeName01 NodeName02 --source-instance-template  
InstanceTemplateName --zone RegionZone --network=NetworkName --  
subnet=SubnetName
```

Example:

```
$ gcloud compute instances create rhel81-node-01 rhel81-node-02 rhel81-node-03 --source-  
instance-template rhel-101-instance-template --zone us-west1-b --network=projectVPC --  
subnet=range0  
Created [https://www.googleapis.com/compute/v1/projects/project-name-on-gcp/zones/us-  
west1-b/instances/rhel81-node-01].  
Created [https://www.googleapis.com/compute/v1/projects/project-name-on-gcp/zones/us-  
west1-b/instances/rhel81-node-02].  
Created [https://www.googleapis.com/compute/v1/projects/project-name-on-gcp/zones/us-  
west1-b/instances/rhel81-node-03].
```

NAME STATUS	ZONE	MACHINE_TYPE	PREEMPTIBLE	INTERNAL_IP	EXTERNAL_IP
rhel81-node-01	us-west1-b	n1-standard-2		10.10.10.4	192.230.25.81
rhel81-node-02	us-west1-b	n1-standard-2		10.10.10.5	192.230.81.253
rhel81-node-03	us-east1-b	n1-standard-2		10.10.10.6	192.230.102.15

4.11. INSTALLING HA PACKAGES AND AGENTS

On each of your nodes, you need to install the High Availability packages and agents to be able to configure a Red Hat High Availability cluster on Google Cloud Platform (GCP).

Procedure

1. In the Google Cloud Console, select **Compute Engine** and then select **VM instances**.
2. Select the instance, click the arrow next to **SSH**, and select the **View** gcloud command option.
3. Paste this command at a command prompt for passwordless access to the instance.
4. Enable sudo account access and register with Red Hat Subscription Manager.
5. Enable a Subscription Pool ID (or use the **--auto-attach** command).
6. Disable all repositories.

```
# subscription-manager repos --disable=*
```

7. Enable the following repositories.

```
# subscription-manager repos --enable=rhel-10-server-rpms
# subscription-manager repos --enable=rhel-10-for-x86_64-highavailability-rpms
```

8. Install **pcs pacemaker**, the fence agents, and the resource agents.

```
# dnf install -y pcs pacemaker fence-agents-gce resource-agents-gcp
```

9. Update all packages.

```
# dnf update -y
```

4.12. CONFIGURING HA SERVICES

On each of your nodes, configure the HA services.

Procedure

1. The user **hacluster** was created during the **pcs** and **pacemaker** installation in the previous step. Create a password for the user **hacluster** on all cluster nodes. Use the same password for all nodes.

```
# passwd hacluster
```

2. If the **firewalld** service is installed, add the HA service.

```
# firewall-cmd --permanent --add-service=high-availability
# firewall-cmd --reload
```

3. Start the **pcs** service and enable it to start on boot.

```
# systemctl start pcsd.service
# systemctl enable pcsd.service

Created symlink from /etc/systemd/system/multi-user.target.wants/pcsd.service to
/usr/lib/systemd/system/pcsd.service.
```

Verification

1. Ensure the **pcsd** service is running.

```
# systemctl status pcsd.service

pcsd.service - PCS GUI and remote configuration interface
Loaded: loaded (/usr/lib/systemd/system/pcsd.service; enabled; vendor preset: disabled)
Active: active (running) since Mon 2018-06-25 19:21:42 UTC; 15s ago
Docs: man:pcsd(8)
      man:pcs(8)
Main PID: 5901 (pcsd)
CGroup: /system.slice/pcsd.service
        └─5901 /usr/bin/ruby /usr/lib/pcsd/pcsd > /dev/null &
```

2. Edit the **/etc/hosts** file. Add RHEL host names and internal IP addresses for all nodes.

Additional resources

- [How should the /etc/hosts file be set up on RHEL cluster nodes?](#) (Red Hat Knowledgebase)

4.13. CREATING A CLUSTER

To convert multiple nodes into a cluster, use the following steps.

Procedure

1. On one of the nodes, authenticate the **pcs** user. Specify the name of each node in the cluster in the command.

```
# pcs host auth hostname1 hostname2 hostname3
Username: hacluster
Password:
hostname1: Authorized
hostname2: Authorized
hostname3: Authorized
```

2. Create the cluster.

```
# pcs cluster setup cluster-name hostname1 hostname2 hostname3
```

Verification

1. Run the following command to enable nodes to join the cluster automatically when started.

```
# pcs cluster enable --all
```

2. Start the cluster.

```
# pcs cluster start --all
```

4.14. CREATING A FENCING DEVICE

High Availability (HA) environments require a fencing device, which ensures that malfunctioning nodes are isolated and the cluster remains available if an outage occurs.

Note that for most default configurations, the GCP instance names and the RHEL host names are identical.

Procedure

1. Obtain GCP instance names. Note that the output of the following command also shows the internal ID for the instance.

```
# fence_gce --zone us-west1-b --project=rhel-ha-on-gcp -o list
```

Example:

```
[root@rhel81-node-01 ~]# fence_gce --zone us-west1-b --project=rhel-ha-testing-on-gcp -o list
```

```
4435801234567893181,InstanceName-3
4081901234567896811,InstanceName-1
7173601234567893341,InstanceName-2
```

2. Create a fence device.

```
# pcs stonith create FenceDeviceName fence_gce zone=Region-Zone
project=MyProject
```

Verification

- Verify that the fence devices started.

```
# pcs status
```

Example:

```
[root@rhel81-node-01 ~]# pcs status
Cluster name: gcp-cluster
```

```
Stack: corosync
Current DC: rhel81-node-02 (version 1.1.18-11.el7_5.3-2b07d5c5a9) - partition with quorum
Last updated: Fri Jul 27 12:53:25 2018
Last change: Fri Jul 27 12:51:43 2018 by root via cibadmin on rhel81-node-01
```

```
3 nodes configured
3 resources configured
```

```
Online: [ rhel81-node-01 rhel81-node-02 rhel81-node-03 ]
```

```
Full list of resources:
```

```
us-west1-b-fence (stonith:fence_gce): Started rhel81-node-01
```

```
Daemon Status:
corosync: active/enabled
pacemaker: active/enabled
pcsd: active/enabled
```

4.15. CONFIGURING THE GCP-VCP-MOVE-VIP RESOURCE AGENT

The **gcp-vpc-move-vip** resource agent attaches a secondary IP address (alias IP) to a running instance. This is a floating IP address that can be passed between different nodes in the cluster.

To show more information about this resource:

```
# pcs resource describe gcp-vpc-move-vip
```

You can configure the resource agent to use a primary subnet address range or a secondary subnet address range:

4.15.1. Primary subnet address range

Complete the following steps to configure the resource for the primary VPC subnet.

Procedure

1. Create the **aliasip** resource. Include an unused internal IP address. Include the CIDR block in the command.

```
# pcs resource create aliasip gcp-vpc-move-vip alias_ip=UnusedIPAddress/CIDRblock
```

Example:

```
[root@rhel81-node-01 ~]# pcs resource create aliasip gcp-vpc-move-vip
alias_ip=10.10.10.200/32
```

2. Create an **IPAddr2** resource for managing the IP on the node.

```
# pcs resource create vip IPAddr2 nic=interface ip=AliasIPAddress cidr_netmask=32
```

Example:

```
[root@rhel81-node-01 ~]# pcs resource create vip IPAddr2 nic=eth0 ip=10.10.10.200
cidr_netmask=32
```

3. Group the network resources under **vipgrp**.

```
# pcs resource group add vipgrp aliasip vip
```

Verification

1. Verify that the resources have started and are grouped under **vipgrp**.

```
# pcs status
```

2. Verify that the resource can move to a different node.

```
# pcs resource move vip Node
```

Example:

```
[root@rhel81-node-01 ~]# pcs resource move vip rhel81-node-03
```

3. Verify that the **vip** successfully started on a different node.

```
# pcs status
```

4.15.2. Secondary subnet address range

Complete the following steps to configure the resource for a secondary subnet address range.

Prerequisites

- [You have created a custom network and a subnet](#)

Procedure

1. Create a secondary subnet address range.

```
# gcloud compute networks subnets update SubnetName --region RegionName --add-
secondary-ranges SecondarySubnetName=SecondarySubnetRange
```

Example:

```
# gcloud compute networks subnets update range0 --region us-west1 --add-secondary-
ranges range1=10.10.20.0/24
```

2. Create the **aliasip** resource. Create an unused internal IP address in the secondary subnet address range. Include the CIDR block in the command.

```
# pcs resource create aliasip gcp-vpc-move-vip alias_ip=UnusedIPaddress/CIDRblock
```

Example:

```
[root@rhel81-node-01 ~]# pcs resource create aliasip gcp-vpc-move-vip  
alias_ip=10.10.20.200/32
```

3. Create an **IPaddr2** resource for managing the IP on the node.

```
# pcs resource create vip IPaddr2 nic=interface ip=AliasIPaddress cidr_netmask=32
```

Example:

```
[root@rhel81-node-01 ~]# pcs resource create vip IPaddr2 nic=eth0 ip=10.10.20.200  
cidr_netmask=32
```

4. Group the network resources under **vipgrp**.

```
# pcs resource group add vipgrp aliasip vip
```

Verification

1. Verify that the resources have started and are grouped under **vipgrp**.

```
# pcs status
```

2. Verify that the resource can move to a different node.

```
# pcs resource move vip Node
```

Example:

```
[root@rhel81-node-01 ~]# pcs resource move vip rhel81-node-03
```

3. Verify that the **vip** successfully started on a different node.

```
# pcs status
```

Additional resources

- [Support Policies for Red Hat High Availability clusters - Transport Protocols](#)
- [Exploring Red Hat High Availability's Components, Concepts, and Features - Overview of Transport Protocols](#)
- [Design Guidance for Red Hat High Availability Clusters - Selecting the Transport Protocol](#)