```
-- ============================
-- DROP TABLES (children → parents)
-- ============================
DROP TABLE IF EXISTS Uses_T;
DROP TABLE IF EXISTS WorksIn_T;
DROP TABLE IF EXISTS DoesBusinessIn_T;
DROP TABLE IF EXISTS EmployeeSkills_T;
DROP TABLE IF EXISTS Supplies_T;
DROP TABLE IF EXISTS ProducedIn_T;
DROP TABLE IF EXISTS OrderLine_T;
DROP TABLE IF EXISTS Product_T;
DROP TABLE IF EXISTS ProductLine_T;
DROP TABLE IF EXISTS Order_T;
DROP TABLE IF EXISTS Salesperson_T;
DROP TABLE IF EXISTS Vendor_T;
DROP TABLE IF EXISTS Skill_T;
DROP TABLE IF EXISTS RawMaterial_T;
DROP TABLE IF EXISTS Territory_T;
DROP TABLE IF EXISTS WorkCenter_T;
DROP TABLE IF EXISTS Employee_T;
DROP TABLE IF EXISTS Customer_T;

-- ============================
-- CREATE TABLES (parents → children)
-- ============================

CREATE TABLE Customer_T
```

```
(
  CustomerID         INT           NOT NULL,
  CustomerName       VARCHAR(25)   NOT NULL,
  CustomerAddress    VARCHAR(30),
  CustomerCity       VARCHAR(20),
  CustomerState      CHAR(2),
  CustomerPostalCode VARCHAR(10),
  CONSTRAINT Customer_PK PRIMARY KEY (CustomerID)
);

CREATE TABLE Territory_T
(
  TerritoryID   INT          NOT NULL,
  TerritoryName VARCHAR(50),
  CONSTRAINT Territory_PK PRIMARY KEY (TerritoryID)
);

CREATE TABLE DoesBusinessIn_T
(
  CustomerID  INT NOT NULL,
  TerritoryID INT NOT NULL,
  CONSTRAINT DoesBusinessIn_PK  PRIMARY KEY (CustomerID,
TerritoryID),
  CONSTRAINT DoesBusinessIn_FK1 FOREIGN KEY (CustomerID)
REFERENCES Customer_T(CustomerID),
  CONSTRAINT DoesBusinessIn_FK2 FOREIGN KEY (TerritoryID)
REFERENCES Territory_T(TerritoryID)
);
```

```
CREATE TABLE Employee_T
(
  EmployeeID         VARCHAR(10)  NOT NULL,
  EmployeeName       VARCHAR(25),
  EmployeeAddress    VARCHAR(30),
  EmployeeBirthDate  DATE,
  EmployeeCity       VARCHAR(20),
  EmployeeState      CHAR(2),
  EmployeeZipCode    VARCHAR(10),
  EmployeeDateHired  DATE,
  EmployeeSupervisor VARCHAR(10),
  CONSTRAINT Employee_PK PRIMARY KEY (EmployeeID)
);

CREATE TABLE Skill_T
(
  SkillID          VARCHAR(12)  NOT NULL,
  SkillDescription VARCHAR(30),
  CONSTRAINT Skill_PK PRIMARY KEY (SkillID)
);

CREATE TABLE EmployeeSkills_T
(
  EmployeeID VARCHAR(10) NOT NULL,
  SkillID    VARCHAR(12) NOT NULL,
  CONSTRAINT EmployeeSkills_PK  PRIMARY KEY (EmployeeID, SkillID),
```

```
  CONSTRAINT EmployeeSkills_FK1 FOREIGN KEY (EmployeeID)
REFERENCES Employee_T(EmployeeID),
  CONSTRAINT EmployeeSkills_FK2 FOREIGN KEY (SkillID)
REFERENCES Skill_T(SkillID)
);

CREATE TABLE Order_T
(
  OrderID    INT  NOT NULL,
  CustomerID INT,
  OrderDate  DATE,
  CONSTRAINT Order_PK  PRIMARY KEY (OrderID),
  CONSTRAINT Order_FK1 FOREIGN KEY (CustomerID) REFERENCES
Customer_T(CustomerID)
);

CREATE TABLE WorkCenter_T
(
  WorkCenterID       VARCHAR(12) NOT NULL,
  WorkCenterLocation VARCHAR(30),
  CONSTRAINT WorkCenter_PK PRIMARY KEY (WorkCenterID)
);

CREATE TABLE ProductLine_T
(
  ProductLineID   INT          NOT NULL,
  ProductLineName VARCHAR(50),
  CONSTRAINT ProductLine_PK PRIMARY KEY (ProductLineID)
```

```
);


CREATE TABLE Product_T
(
  ProductID            INT          NOT NULL,
  ProductLineID        INT,
  ProductDescription   VARCHAR(50),
  ProductFinish        VARCHAR(20),
  ProductStandardPrice NUMERIC(6,2),
  Saleprice            NUMERIC(6,2),
  CONSTRAINT Product_PK  PRIMARY KEY (ProductID),
  CONSTRAINT Product_FK1 FOREIGN KEY (ProductLineID) REFERENCES
ProductLine_T(ProductLineID)
);


CREATE TABLE ProducedIn_T
(
  ProductID    INT         NOT NULL,
  WorkCenterID VARCHAR(12) NOT NULL,
  CONSTRAINT ProducedIn_PK  PRIMARY KEY (ProductID, WorkCenterID),
  CONSTRAINT ProducedIn_FK1 FOREIGN KEY (ProductID)
REFERENCES Product_T(ProductID),
  CONSTRAINT ProducedIn_FK2 FOREIGN KEY (WorkCenterID)
REFERENCES WorkCenter_T(WorkCenterID)
);


CREATE TABLE OrderLine_T
(
```

```
  OrderID        INT NOT NULL,
  ProductID      INT NOT NULL,
  OrderedQuantity INT,
  CONSTRAINT OrderLine_PK  PRIMARY KEY (OrderID, ProductID),
  CONSTRAINT OrderLine_FK1 FOREIGN KEY (OrderID)   REFERENCES
Order_T(OrderID),
  CONSTRAINT OrderLine_FK2 FOREIGN KEY (ProductID) REFERENCES
Product_T(ProductID)
);

CREATE TABLE RawMaterial_T
(
  MaterialID          VARCHAR(12) NOT NULL,
  MaterialName        VARCHAR(30),
  MaterialStandardCost NUMERIC(6,2),
  UnitOfMeasure       VARCHAR(10),
  CONSTRAINT RawMaterial_PK PRIMARY KEY (MaterialID)
);

CREATE TABLE Salesperson_T
(
  SalespersonID   INT         NOT NULL,
  SalespersonName VARCHAR(25),
  SalespersonPhone VARCHAR(50),
  SalespersonFax   VARCHAR(50),
  TerritoryID      INT,
  CONSTRAINT Salesperson_PK  PRIMARY KEY (SalespersonID),
```

```
  CONSTRAINT Salesperson_FK1 FOREIGN KEY (TerritoryID)
REFERENCES Territory_T(TerritoryID)
);


CREATE TABLE Vendor_T
(
  VendorID      INT         NOT NULL,
  VendorName    VARCHAR(25),
  VendorAddress VARCHAR(30),
  VendorCity    VARCHAR(20),
  VendorState   CHAR(2),
  VendorZipcode VARCHAR(50),
  VendorFax     VARCHAR(10),
  VendorPhone   VARCHAR(10),
  VendorContact VARCHAR(50),
  VendorTaxID   VARCHAR(50),
  CONSTRAINT Vendor_PK PRIMARY KEY (VendorID)
);


CREATE TABLE Supplies_T
(
  VendorID          INT         NOT NULL,
  MaterialID        VARCHAR(12) NOT NULL,
  SuppliesUnitPrice NUMERIC(6,2),
  CONSTRAINT Supplies_PK  PRIMARY KEY (VendorID, MaterialID),
  CONSTRAINT Supplies_FK1 FOREIGN KEY (MaterialID) REFERENCES
RawMaterial_T(MaterialID),
```

```
  CONSTRAINT Supplies_FK2 FOREIGN KEY (VendorID)   REFERENCES Vendor_T(VendorID)
);


CREATE TABLE Uses_T
(
  ProductID        INT         NOT NULL,
  MaterialID       VARCHAR(12) NOT NULL,
  GoesIntoQuantity INT,
  CONSTRAINT Uses_PK  PRIMARY KEY (ProductID, MaterialID),
  CONSTRAINT Uses_FK1 FOREIGN KEY (ProductID)  REFERENCES Product_T(ProductID),
  CONSTRAINT Uses_FK2 FOREIGN KEY (MaterialID) REFERENCES RawMaterial_T(MaterialID)
);


CREATE TABLE WorksIn_T
(
  EmployeeID  VARCHAR(10) NOT NULL,
  WorkCenterID VARCHAR(12) NOT NULL,
  CONSTRAINT WorksIn_PK  PRIMARY KEY (EmployeeID, WorkCenterID),
  CONSTRAINT WorksIn_FK1 FOREIGN KEY (EmployeeID)  REFERENCES Employee_T(EmployeeID),
  CONSTRAINT WorksIn_FK2 FOREIGN KEY (WorkCenterID) REFERENCES WorkCenter_T(WorkCenterID)
);


-- ============================
```

```
-- INSERT DATA
-- ==========================

INSERT INTO Customer_T (CustomerID, CustomerName, CustomerAddress,
CustomerCity, CustomerState, CustomerPostalCode) VALUES
(1,  'Contemporary Casuals', '1355 S Hines Blvd',  'Gainesville', 'FL', '32601-
2871'),
(2,  'Value Furniture',      '15145 S.W. 17th St.', 'Plano',      'TX', '75094-
7743'),
(3,  'Home Furnishings',     '1900 Allard Ave.',   'Albany',     'NY', '12209-
1125'),
(4,  'Eastern Furniture',    '1925 Beltline Rd.',  'Carteret',   'NJ', '07008-
3188'),
(5,  'Impressions',          '5585 Westcott Ct.',  'Sacramento', 'CA', '94206-
4056'),
(6,  'Furniture Gallery',    '325 Flatiron Dr.',   'Boulder',    'CO', '80514-
4432'),
(7,  'Period Furniture',     '394 Rainbow Dr.',    'Seattle',    'WA', '97954-
5589'),
(8,  'California Classics',  '816 Peach Rd.',      'Santa Clara','CA', '96915-
7754'),
(9,  'M and H Casual Furniture', '3709 First Street',
'Clearwater','FL','34620-2314'),
(10, 'Seminole Interiors',   '2400 Rocky Point Dr.','Seminole',  'FL', '34646-
4423'),
(11, 'American Euro Lifestyles', '2424 Missouri Ave N.','Prospect
Park','NJ','07508-5621'),
(12, 'Battle Creek Furniture','345 Capitol Ave. SW','Battle
Creek','MI','49015-3401'),
(13, 'Heritage Furnishings', '66789 College Ave.', 'Carlisle',   'PA', '17013-
8834'),
```

(14, 'Kaneohe Homes', '112 Kiowai St.', 'Kaneohe', 'HI', '96744-2537'),

(15, 'Mountain Scenes', '4132 Main Street', 'Ogden', 'UT', '84403-4432');

INSERT INTO Territory_T (TerritoryID, TerritoryName) VALUES

(1, 'SouthEast'),

(2, 'SouthWest'),

(3, 'NorthEast'),

(4, 'NorthWest'),

(5, 'Central');

INSERT INTO DoesBusinessIn_T (CustomerID, TerritoryID) VALUES

(1,1),(1,2),(2,2),(3,3),(4,3),(5,2),(6,5);

INSERT INTO Employee_T (EmployeeID, EmployeeName, EmployeeAddress, EmployeeCity, EmployeeState, EmployeeZipCode, EmployeeDateHired, EmployeeBirthDate, EmployeeSupervisor) VALUES

('123-44-345', 'Jim Jason', '2134 Hilltop Rd', '', 'TN', '', '1999-06-12', '1958-12-12', '454-56-768'),

('454-56-768', 'Robert Lewis', '17834 Deerfield Ln','Nashville','TN','', '1999-01-01', '1974-05-05', '');

INSERT INTO Skill_T (SkillID, SkillDescription) VALUES

('BS12','12in Band Saw'),

('QC1','Quality Control'),

('RT1','Router'),

('SO1','Sander-Orbital'),

('SB1','Sander-Belt'),

('TS10','10in Table Saw'),

('TS12','12in Table Saw'),

('UC1','Upholstery Cutter'),

('US1','Upholstery Sewer'),

('UT1','Upholstery Tacker');

INSERT INTO EmployeeSkills_T (EmployeeID, SkillID) VALUES

('123-44-345','BS12'),

('123-44-345','RT1'),

('454-56-768','BS12');

-- Orders (ISO dates)

INSERT INTO Order_T (OrderID, CustomerID, OrderDate) VALUES

(1021,1,'2024-10-21'),

(1022,8,'2024-10-21'),

(1023,15,'2024-10-22'),

(1024,5,'2024-10-22'),

(1025,3,'2024-10-24'),

(1026,2,'2024-10-24'),

(1027,11,'2024-10-27'),

(1028,12,'2024-10-30'),

(1029,4,'2024-11-05'),

(1030,1,'2024-11-05'),

(1011,1,'2023-09-14'),

(1012,2,'2023-09-21'),

(1013,12,'2023-10-05'),

(1014,8,'2023-10-07'),

```
(1015,1,'2023-10-08'),
(1016,5,'2023-10-10'),
(1017,12,'2023-10-12'),
(1018,11,'2023-10-14'),
(1019,2,'2023-11-07'),
(1020,15,'2023-12-10'),
(1001,1,'2022-08-10'),
(1002,4,'2022-08-12'),
(1003,12,'2022-08-13'),
(1004,3,'2022-08-14'),
(1005,1,'2022-08-14'),
(1006,15,'2022-08-16'),
(1007,12,'2022-08-17'),
(1008,15,'2022-09-03'),
(1009,3,'2022-09-05'),
(1010,1,'2022-09-07');

INSERT INTO ProductLine_T (ProductLineID, ProductLineName) VALUES
(1,'Cherry Tree'),
(2,'Scandinavia'),
(3,'Country Look');

INSERT INTO Product_T (ProductID, ProductDescription, ProductFinish,
ProductStandardPrice, Saleprice, ProductLineID) VALUES
(1,'End Table','Cherry',        175, 148.75, 1),
(2,'Coffee Table','Natural Ash',  200, 127.50, 2),
(3,'Computer Desk','Natural Ash', 375, 318.75, 2),
```

(4,'Entertainment Center','Natural Maple',650, 585.00, 3),

(5,'Writers Desk','Cherry', 325, 276.25, 1),

(6,'8-Drawer Desk','White Ash', 750, 675.00, 2),

(7,'Dining Table','Natural Ash', 800, 720.00, 2),

(8,'Computer Desk','Walnut', 250, 212.50, 3);

INSERT INTO OrderLine_T (OrderID, ProductID, OrderedQuantity) VALUES

(1016,5,1),

(1001,1,2),

(1001,2,2),

(1001,4,1),

(1002,3,5),

(1003,3,3),

(1004,6,2),

(1004,8,2),

(1005,4,4),

(1006,4,1),

(1006,5,2),

(1006,7,2),

(1007,1,3),

(1007,2,2),

(1008,3,3),

(1008,8,3),

(1009,4,2),

(1009,7,3),

(1010,8,10),

(1021,8,2),

(1021,2,3),

(1021,5,1),

(1022,1,6),

(1023,2,2),

(1024,2,8),

(1024,5,6),

(1025,1,8),

(1026,8,9),

(1026,4,5),

(1026,2,5),

(1027,6,1),

(1027,1,2),

(1028,2,3),

(1028,7,3),

(1029,5,2),

(1029,2,3),

(1030,2,15),

(1011,4,2),

(1011,5,2),

(1011,2,1),

(1012,3,8),

(1013,4,3),

(1014,7,2),

(1014,4,3),

(1015,8,8),

(1016,2,2),

(1016,4,1),

(1016,6,5),

(1017,6,2),

(1017,3,5),

(1018,2,3),

(1018,5,3),

(1019,1,2),

(1019,7,3),

(1020,2,12);

INSERT INTO Salesperson_T (SalespersonID, SalespersonName, SalespersonPhone, SalespersonFax, TerritoryID) VALUES

(1,'Doug Henny','8134445555','',1),

(2,'Robert Lewis','8139264006','',2),

(3,'William Strong','5053821212','',3),

(4,'Julie Dawson','4355346677','',4),

(5,'Jacob Winslow','2238973498','',5);

INSERT INTO WorkCenter_T (WorkCenterID, WorkCenterLocation) VALUES

('SM1','Main Saw Mill'),

('WR1','Warehouse and Receiving');

INSERT INTO WorksIn_T (EmployeeID, WorkCenterID) VALUES

('123-44-345','SM1');

-- (The original script had no data for RawMaterial_T / Vendor_T / Supplies_T / Uses_T / ProducedIn_T beyond definitions.)

```
-- ============================
-- SAMPLE QUERIES
-- ============================

SELECT * FROM Uses_T;
SELECT * FROM WorksIn_T;
SELECT * FROM WorkCenter_T;
SELECT * FROM DoesBusinessIn_T;
SELECT * FROM EmployeeSkills_T;
SELECT * FROM Supplies_T;
SELECT * FROM ProducedIn_T;
SELECT * FROM OrderLine_T;
SELECT * FROM Product_T;
SELECT * FROM ProductLine_T;
SELECT * FROM Order_T;
SELECT * FROM Salesperson_T;
SELECT * FROM Vendor_T;
SELECT * FROM Skill_T;
SELECT * FROM RawMaterial_T;
SELECT * FROM Territory_T;
SELECT * FROM Employee_T;
SELECT * FROM Customer_T;

-- COMMIT; -- optional (PostgreSQL needs explicit transactions; MySQL autocommits by default)
```