VarForge: Synthetic Cancer Sequencing Data in a Single Rust Binary

v0.1

Trent Zeng

Abstract

No single tool integrates de-novo read generation, somatic variant spike-in, UMI/duplex simulation, cfDNA fragmentation, and library artefact injection. VarForge fills this gap in a single Rust binary driven by YAML configuration, achieving ∼14,000 read pairs/s at 30x on a 12-thread workstation. No other published tool provides genome-wide UMI simulation or combines cfDNA fragmentation with variant spike-in. Variants are assigned by per-read Bernoulli sampling, not deterministic spike-in. BED region filtering enables clinical-depth panel simulation (200x, 1 Mbp target, 86 s).

1 Introduction

Benchmarking cancer variant callers, UMI deduplication tools, and liquid biopsy algorithms requires synthetic data with complete ground truth. Real patient data cannot provide this. Existing tools address parts of the problem: BAMSurgeon[1] spikes variants, ART[2] generates reads, but no single tool covers UMI families, cfDNA fragmentation, tumour models, and library artefacts together.

VarForge addresses these gaps. Contributions: (i) unified pipeline via YAML; (ii) genome-wide UMI and duplex simulation; (iii) cfDNA fragmentation with variant support; (iv) stochastic VAF via per-read Bernoulli sampling; (v) BED region filtering for targeted panel simulation.

2 Related Work

BAMSurgeon[1], SomatoSim[3], and stochasticSim[4] spike variants into existing BAMs. ART[2], NEAT[5], and ReSeq[6] generate reads but lack tumour models, UMI simulation, and cfDNA fragmentation. No existing tool provides genome-wide UMI or duplex sequencing simulation. No tool combines cfDNA fragmentation with somatic variant spike-in.

3 Method

VarForge partitions the reference into chunks processed by Rayon workers. Each worker samples fragment lengths, positions reads, injects variants by Bernoulli sampling, applies quality scores, and tags UMI families. A bounded channel (default depth 64) decouples workers from the writer thread. Memory is bounded by concurrent batch state, not total dataset size. If a BED file of targets is provided, chunks are clipped to target boundaries before dispatch.

Stochastic VAF. For each read at a variant site: $X_i \sim \text{Bernoulli}(\text{VAF}_{\text{eff}})$. Alt-read count follows $\text{Binomial}(D, \text{VAF}_{\text{eff}})$, matching real sequencing variance.

cfDNA. Fragment lengths follow a four-component Gaussian mixture with sub-nucleosomal (∼143 bp), mono-nucleosomal (∼167 bp), di-nucleosomal (∼334 bp), and tri-nucleosomal (∼500 bp) components.

4 Results

Table 1: Key benchmark results (12 threads, 1 run).

Scenario	Wall (s)	RAM (GB)	Pairs/s
WGS 10 MB, 30x	139.6	0.87	14,300
Panel+UMI 1 MB	195.1	1.80	6,800
chr22, 30x WGS	595.3	4.21	8,537
Panel BED 200x	85.5	0.56	7,796

Throughput scales linearly with coverage ($R^2 > 0.999$). Peak memory is bounded by concurrent batch count, not dataset size. BED filtering restricts simulation to target regions, enabling 200x panel coverage on chr22 in 86 s. All six hg38 chr22 feature configurations (UMI, duplex, cfDNA, FFPE) completed without error.

5 Discussion and Future Work

VarForge covers a feature space unavailable in any single existing tool. The main limitation is that output correctness is not yet independently validated: VAF accuracy, cfDNA fragment distributions, and UMI family structure require quantitative comparison against their respective models. Thread scaling only helps for compute-heavy workloads (UMI simulation); the I/O-bound WGS workload runs fastest at one thread.

Priority next steps: (1) chi-squared VAF accuracy test; (2) cfDNA fragment distribution validation; (3) downstream variant caller benchmarking (Mutect2 or VarDict against the truth VCF).

References

1. Ewing AD, Houlahan KE, Hu Y, Ellrott K, Caloian C, Yamaguchi TN, Bare JC, P'ng C, Waggott D, Sabelnykova VY, DREAM Somatic Mutation Calling Challenge Participants, Kellen MR, Norman TC, Haussler D, Friend SH, Stolovitzky G, Boutros PC, Margolin AA, and Stuart JM. Combining tumor genome simulation with crowdsourcing to benchmark somatic single-nucleotide-variant detection. Nature Methods 2015; 12. Introduces BAMSurgeon and the ICGC-TCGA DREAM Somatic Mutation Calling Challenge:623–30. DOI: 10.1038/nmeth.3407

2. Huang W, Li L, Myers JR, and Marth GT. ART: a next-generation sequencing read simulator. Bioinformatics 2012; 28:593–4. DOI: 10.1093/bioinformatics/btr708

3. Daber R, Sukhadia S, and Morrissette JJD. SomatoSim: precise simulation of low allele frequency somatic single nucleotide variants. BMC Bioinformatics 2021; 22:194. DOI: 10.1186/s12859-021-04105-8

4. O'Sullivan B, Doyle S, Clynes M, and Barron N. Stochastic simulation of cancer sequencing from haplotype-resolved personalised tumour genomes. NAR Cancer 2023; 5. Addresses stochastic VAF sampling and FFPE/oxoG artifacts:zcad033. DOI: 10.1093/narcan/zcad033

5. Stephens ZD, Hudson ME, Mainzer LS, Taschuk M, Weber MR, and Iyer RK. Simulating next-generation sequencing datasets from empirical mutation and sequencing models. PLOS ONE 2016; 11. Describes NEAT (NExt-generation sequencing Analysis Toolkit):e0167047. DOI: 10.1371/journal.pone.0167047

6. Schmeing S and Robinson MD. ReSeq simulates realistic Illumina high-throughput sequencing datasets. Genome Biology 2021; 22:67. DOI: 10.1186/s13059-021-02286-2