

HOME TOP CONTESTS GYM PROBLEMSET GROUPS RATING EDU API CALENDAR HELP

PROBLEMS SUBMIT STATUS STANDINGS CUSTOM TEST

C. Alternating Subsequence

time limit per test: 1 second memory limit per test: 256 megabytes input: standard input output: standard output

Recall that the sequence b is a a subsequence of the sequence a if b can be derived from a by removing zero or more elements without changing the order of the remaining elements. For example, if a=[1,2,1,3,1,2,1], then possible subsequences are: [1,1,1,1], [3] and [1,2,1,3,1,2,1], but not [3,2,3] and [1,1,1,1,2].

You are given a sequence a consisting of n positive and negative elements (there is no zeros in the sequence).

Your task is to choose **maximum by size** (length) *alternating* subsequence of the given sequence (i.e. the sign of each next element is the opposite from the sign of the current element, like positive-negative-positive and so on or negative-positive-negative and so on). Among all such subsequences, you have to choose one which has the **maximum sum** of elements.

In other words, if the maximum length of *alternating* subsequence is k then your task is to find the **maximum sum** of elements of some *alternating* subsequence of length k.

You have to answer t independent test cases.

Input

The first line of the input contains one integer t ($1 \le t \le 10^4$) — the number of test cases. Then t test cases follow.

The first line of the test case contains one integer n ($1 \le n \le 2 \cdot 10^5$) — the number of elements in a. The second line of the test case contains n integers a_1, a_2, \ldots, a_n ($-10^9 \le a_i \le 10^9, a_i \ne 0$), where a_i is the i-th element of a.

It is guaranteed that the sum of n over all test cases does not exceed $2\cdot 10^5$ ($\sum n \le 2\cdot 10^5$).

Output

For each test case, print the answer — the maximum sum of the maximum by size (length) alternating subsequence of a.

Fyample

input	Сору
4	
5	
1 2 3 -1 -2	
4	
-1 -2 -1 -3	
10	
-2 8 3 8 -4 -15 5 -2 -3 1	
6	
1 -1000000000 1 -1000000000 1 -100000000	
output	Сору
2	
-1	
6	
-299999997	

Codeforces Round #636 (Div. 3)

Finished

→ Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

Start virtual contest

→ Problem tags



Contest materials

- Announcement
- Tutorial

Note

In the first test case of the example, one of the possible answers is $[1,2,\underline{3},\underline{-1},-2]$.

In the second test case of the example, one of the possible answers is $[-1,-2,\underline{-1},-3]$.

In the third test case of the example, one of the possible answers is $[\underline{-2},8,3,\underline{8},\underline{-4},-15,\underline{5},\underline{-2},-3,\underline{1}].$

In the fourth test case of the example, one of the possible answers is $[\underline{1},-100000000,\underline{1},-1000000000,\underline{1},-1000000000].$

Codeforces (c) Copyright 2010-2021 Mike Mirzayanov
The only programming contests Web 2.0 platform
Server time: Apr/05/2021 21:47:58^{UTC-5} (j1).
Desktop version, switch to mobile version.
Privacy Policy.

Supported by



