

B. Honest Coach

time limit per test: 2 seconds

memory limit per test: 256 megabytes

input: standard input

output: standard output

There are n athletes in front of you. Athletes are numbered from 1 to n from left to right. You know the strength of each athlete — the athlete number i has the strength s_i .

You want to split all athletes into two teams. Each team must have at least one athlete, and each athlete must be exactly in one team.

You want the strongest athlete from the first team to differ as little as possible from the weakest athlete from the second team. Formally, you want to split the athletes into two teams A and B so that the value $|\max(A) - \min(B)|$ is as small as possible, where $\max(A)$ is the maximum strength of an athlete from team A , and $\min(B)$ is the minimum strength of an athlete from team B .

For example, if $n = 5$ and the strength of the athletes is $s = [3, 1, 2, 6, 4]$, then one of the possible split into teams is:

- first team: $A = [1, 2, 4]$,
- second team: $B = [3, 6]$.

In this case, the value $|\max(A) - \min(B)|$ will be equal to $|4 - 3| = 1$. This example illustrates one of the ways of optimal split into two teams.

Print the minimum value $|\max(A) - \min(B)|$.

Input

The first line contains an integer t ($1 \leq t \leq 1000$) — the number of test cases in the input. Then t test cases follow.

Each test case consists of two lines.

The first line contains positive integer n ($2 \leq n \leq 50$) — number of athletes.

The second line contains n positive integers s_1, s_2, \dots, s_n ($1 \leq s_i \leq 1000$), where s_i — is the strength of the i -th athlete. Please note that s values may not be distinct.

Output

For each test case print one integer — the minimum value of $|\max(A) - \min(B)|$ with the optimal split of all athletes into two teams. Each of the athletes must be a member of exactly one of the two teams.

Example

input

Copy

Codeforces Round #644 (Div. 3)

Finished

→ Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.



Start virtual contest

→ Problem tags

[greedy](#) [sortings](#) [*800](#)

No tag edit access

→ Contest materials

- Announcement 
- Tutorial 

```
5
5
3 1 2 6 4
6
2 1 3 2 4 3
4
7 9 3 1
2
1 1000
3
100 150 200
```

output[Copy](#)

```
1
0
2
999
50
```

Note

The first test case was explained in the statement. In the second test case, one of the optimal splits is $A = [2, 1]$, $B = [3, 2, 4, 3]$, so the answer is $|2 - 2| = 0$.

[Codeforces](#) (c) Copyright 2010-2021 Mike Mirzayanov

The only programming contests Web 2.0 platform

Server time: Feb/08/2021 18:39:26^{UTC-5} (f2).

Desktop version, switch to [mobile version](#).

[Privacy Policy](#)

Supported by



ITMO UNIVERSITY