

## A. And Then There Were K

time limit per test: 1 second  
 memory limit per test: 256 megabytes  
 input: standard input  
 output: standard output

Given an integer  $n$ , find the maximum value of integer  $k$  such that the following condition holds:

$$n \& (n - 1) \& (n - 2) \& (n - 3) \& \dots \& (k) = 0$$

where  $\&$  denotes the [bitwise AND operation](#).

### Input

The first line contains a single integer  $t$  ( $1 \leq t \leq 3 \cdot 10^4$ ). Then  $t$  test cases follow.

The first line of each test case contains a single integer  $n$  ( $1 \leq n \leq 10^9$ ).

### Output

For each test case, output a single integer — the required integer  $k$ .

### Example

| input             | Copy |
|-------------------|------|
| 3<br>2<br>5<br>17 |      |
| output            | Copy |
| 1<br>3<br>15      |      |

### Note

In the first testcase, the maximum value for which the continuous  $\&$  operation gives 0 value, is 1.

In the second testcase, the maximum value for which the continuous  $\&$  operation gives 0 value, is 3. No value greater than 3, say for example 4, will give the  $\&$  sum 0.

- $5 \& 4 \neq 0$ ,
- $5 \& 4 \& 3 = 0$ .

Hence, 3 is the answer.

### Codeforces Round #721 (Div. 2)

Finished

### → Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

Start virtual contest

### → Problem tags

bitmasks \*800

No tag edit access

### → Contest materials

- Announcement (en) ✕
- Tutorial (en) ✕

