

A. Dense Array

time limit per test: 2 seconds

memory limit per test: 256 megabytes

input: standard input

output: standard output

Polycarp calls an array dense if the greater of any two adjacent elements is not more than twice bigger than the smaller. More formally, for any i ($1 \leq i \leq n - 1$), this condition must be satisfied:

$$\frac{\max(a[i], a[i + 1])}{\min(a[i], a[i + 1])} \leq 2$$

For example, the arrays $[1, 2, 3, 4, 3]$, $[1, 1, 1]$ and $[5, 10]$ are dense. And the arrays $[5, 11]$, $[1, 4, 2]$, $[6, 6, 1]$ are **not** dense.

You are given an array a of n integers. What is the minimum number of numbers you need to add to an array to make it dense? You can insert numbers anywhere in the array. If the array is already dense, no numbers need to be added.

For example, if $a = [4, 2, 10, 1]$, then the answer is 5, and the array itself after inserting elements into it may look like this: $a = [4, 2, \underline{3}, \underline{5}, 10, \underline{6}, \underline{4}, \underline{2}, 1]$ (there are other ways to build such a).

Input

The first line contains one integer t ($1 \leq t \leq 1000$). Then t test cases follow.

The first line of each test case contains one integer n ($2 \leq n \leq 50$) — the length of the array a .

The next line contains n integers a_1, a_2, \dots, a_n ($1 \leq a_i \leq 50$).

Output

For each test case, output one integer — the minimum number of numbers that must be added to the array to make it dense.

Example

input	Copy
<pre>6 4 4 2 10 1 2 1 3 2 6 1 3 1 4 2 5 1 2 3 4 3 12 4 31 25 50 30 20 34 46 42 16 15 16</pre>	
output	Copy
<pre>5 1 2 1 0</pre>	

Codeforces Round #702 (Div. 3)

Finished

→ Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

Start virtual contest

→ Problem tags

[greedy](#) [math](#) [*800](#)

No tag edit access

→ Contest materials

- Announcement ×
- Tutorial ×

**Note**

The first test case is explained in the statements.

In the second test case, you can insert one element, $a = [1, \underline{2}, 3]$.

In the third test case, you can insert two elements, $a = [6, \underline{4}, \underline{2}, 1]$.

In the fourth test case, you can insert one element, $a = [1, \underline{2}, 4, 2]$.

In the fifth test case, the array a is already dense.

[Codeforces](#) (c) Copyright 2010-2021 Mike Mirzayanov

The only programming contests Web 2.0 platform

Server time: Jul/30/2021 13:22:49^{UTC-5} (j3).

Desktop version, switch to [mobile version](#).

[Privacy Policy](#)

Supported by



ITMO UNIVERSITY