

4ME98 - Electric Air Compressor: 5 hp, 1 Stage, Vertical, 60 gal Tank, 14.2 cfm, Splash Lubricated



PN210021

Auto Drain Valve

PN210024

.5 HP, 60 gal., Vertical Splash Lubricated Tank Mounted Electric Air Compressor 14.2

.Item # **4ME98**

Mfr. Model #4ME98

| ITEM | ELECTRIC AIR COMPRESSOR |
|---------------------------------------|-------------------------|
| LUBRICATION TYPE | SPLASH LUBRICATED |
| AIR TANK STYLE | VERTICAL |
| Number of stages | 1 |
| OUTPUT POWER | 5 HP |
| FREE AIR FLOW RATE @ MAXIMUM PRESSURE | 14.2 CFM |
| MAXIMUM OPER. PRESSURE | 135 PSI |
| AIR TANK SIZE | 60 GAL |
| INPUT VOLTAGE | 208-240V AC, 480V AC |
| PHASE | THREE |
| FREQUENCY | 60Hz |
| COMPRESSOR PACKAGE TYPE | BASE MODEL |
| PUMP STYLE | SIMPLEX |
| PUMP TYPE | RECIPROCATING |
| PUMP LOCATION | TOP MOUNT |
| PUMP OIL CAPACITY | 40 FLOZ |
| MOTOR TYPE | OPEN DRIPPROOF |
| CURRENT RATING | 13.4 TO 13.2 A, 6.6 A |
| MAXIMUM SPEED | 950 RPM |

| DUTY CYCLE | INTERMITTENT |
|-----------------------------|--|
| THERMAL PROTECTION | YES |
| SOUND LEVEL | 85 dBA |
| INCLUDES | MANUAL DRAIN VALVE, OIL SIGHT GLASS, PRESSURE GAUGE, PRESSURE SAFETY VALVE |
| CYLINDER MATERIAL | CAST IRON |
| FINISH | POWDER COATED |
| ASME TANK | YES |
| CONTROL TYPE | PRESSURE SWITCH |
| ON PRESSURE SWITCH SETTING | 105 PSI |
| OFF PRESSURE SWITCH SETTING | 140 PSI |
| INLET SIZE | 3/4 IN |
| OUTLET SIZE | 3/4 IN |
| OUTLET TYPE | NPT |
| OUTLET GENDER | FEMALE |
| OVERALL LENGTH | 23 IN |
| OVERALL WIDTH | 31 IN |
| OVERALL HEIGHT | 71 IN |
| STANDARDS | ASME APPROVED, CSA, CALIFORNIA CODE 462(L)(2), UL LISTED, UL1450 |