



## **Gutter Depth Marker/ Target - Vinyl Decal Installation**

Your graphics will come in three layers, a backing paper layer on the bottom to keep the adhesive from being exposed, the vinyl layer (this is your graphic), and a masking layer on top. The masking layer makes the vinyl easier to handle and keeps everything pre-spaced for you to apply your graphic as one piece.

You will need:

- Clean rags
- Denatured alcohol
- Microfiber towel
- Vinyl applicator

It is best to do this process when the pool is not in use.

1. Lower Water Level
  - a. Water level should be lowered at least an inch below the bottom level of the decal.
  - b. Make sure to turn off any auto-fill devices to keep water from rising while applying decals.
2. Clean Gutter Thoroughly
  - a. Wipe away any moisture.
  - b. Clean the entire area where the decals will be applied using denatured alcohol and a clean rag.
  - c. Wipe dry with a clean microfiber cloth.
3. Apply Decal
  - a. Peel the backing from the decal making sure they stay attached to the protective paper on the front.
  - b. Take care to make sure the decal is level and spaced correctly.
  - c. Apply the decal sticking the top part first to the cleaned gutter surface and using your hand or applicator, slowly starting from the top, slide down the decal gently pressing it onto the gutter until the decal is fully applied.
  - d. Using the applicator, firmly press the decal from the center out to push any air bubbles to the edge.
  - e. Carefully peel the protective paper off making sure the decal sticks to the gutter (If decal starts to come off with the protective paper, stop, put the protective paper back as far as needed, and use applicator to press decal to gutter surface).
4. Cure
  - a. Wait at least 12 hours before introducing water to decals.
5. You can use a SEALITPEN to seal the edges of the graphic for longer durability. Follow directions on the pen.

If you have any question(s) contact customer service see below for our information.