PADDOCK
POOL EQUIPMENT COMPANY
100% EMPLOYEE OWNED

Filter(s) Operation & Maintenance Manual

© Paddock Pool Equipment Co. | 555 Paddock Parkway, Rock Hill, SC 29730
Phone (803)324-1111 | www.paddockpoolequipment.com | 800-849-2729 | E: info@paddock-usa.com
Rev. 08/2026

PADDOCK
POOL EQUIPMENT COMPANY
100% EMPLOYEE OWNED

SAFETY &/or HAZARD INFORMATION

This bulletin includes important safety information that should be read by owners, managers, service personnel, and anyone in charge of the pool or pool area. Also, we suggest a copy be posted for quick reference.

1. Only personnel trained and familiar with the proper use of pool chemicals should handle acid, liquid chlorine or chlorine compounds. Chemicals should never be used when swimmers are in the pool. Acid and liquid chlorine should always be stored, carried, or handled in plastic containers.

2. If grating is a part of the perimeter system, it should be kept firmly always clamped down and in good repair. When a section of grating becomes loose or damaged, that area must be immediately covered and a replacement of grating ordered. Under no circumstances should swimmers be allowed to use any portion of the perimeter that contains loose or damaged grating. Perimeter grating is not intended for foot traffic. Swimmers should be advised not to walk, stand, or jump on perimeter grates.

3. Ladders and grab rails are intended for the use of one swimmer at a time; they are not designed for handstands or other gymnastic stunts, and they should not be used for this purpose. Ladder treads should be inspected regularly. If a tread becomes loose or damaged, the ladder should be taken out of service until repairs are made.

4. Lifeguard Chairs are intended for the individual use of trained "on duty" lifeguards, one (1) guard per chair. Lifeguard chairs are not to be used by swimmers, spectators, or by more than one (1) person at a time. There should be no diving from portable lifeguard chairs. Umbrellas should be closed or removed from portable lifeguard chairs during windy conditions. All frame connections are to be checked for tightness. The seat is bolted to the frame assembly. It is important to advise all users to periodically check to determine that the studs are firmly fastened to the seat and the nuts are tight. If they become loose or detached, it could result in serious injury. On outdoor installations or usage, it is suggested that the seat be removed and stored inside during the winter.

5. Starting Platforms should only be used by trained competitive swimmers or under the direct supervision of an instructor. Swimmers should execute shallow racing dives only. Impact with the pool bottom can cause severe injury. Starting platforms have warning labels and inform the purchaser of the need to remove the platforms during non-usage. If your starting platforms do not have warning labels, please contact the manufacturer immediately.

6. Bulkheads are designed and built for strength and safety. Any grating should be kept fully secured to avoid injury. **NO swimming under bulkhead. Never use bulkhead as a support or staging for equipment**. The bulkhead includes a compressor; please refer to owner's manual provided with the unit.

For questions concerning the usage of our equipment, please contact Paddock Pool Equipment Co., customer service.

PADDOCK
POOL EQUIPMENT COMPANY
100% EMPLOYEE OWNED

Notes and Tips - From the Engineering Department

General notes:

1. Filter aid(s) such as alum are generally not required. Consult manufacture before use.

2. Clean and repack the recirculation pump and/or check the seal and overhaul the motor at least once a year.

3. Establish definite periods for using the vacuum cleaner and skimmer in removing leaves and other foreign matter from the pool.

    3.1. Do not allow nails, pins or other metal articles to remain in the pool for any length of time, as a rust stain will mar the finish.

    3.2. If the pool is empty for any reason, do not allow any walking on the floor, as stains and marks will result.

4. Brush walls and the floor of the pool frequently.

5. Filter(s) requires the pump strainer(s) to be cleaned regularly to eliminate the pump operating without water.

    5.1. Leaves become waterlogged, sink to the bottom of the pool, are sucked into the strainer and clog it. This causes the pump to run dry, overheating the motor and damaging the seal.

If you have a sand filter:

1. Only use grade no. 20, or 16/20 filter sand.

2. Periodically check the filter media and remove any accumulation of pine needles, grass cuttings or the like. This type of material may enter the tank through the over drain distributor and become trapped therein.

3. If an amount of fine sand or similar material has accumulated in the bottom of a new pool prior to start-up, it is recommended that the pool be vacuumed to waste.

4. Pressure sand filter(s) are equipped with an automatic air relief valve to expel all air from the tank interior. Air relief valve should be inspected periodically to ensure proper operations.

If you have a regenerative filter:

1. Only use a premium grade of Perlite or DE for filtration media.
2. Do not use flocculant agents as this can damage the filter elements.

Specific notes for your filter can be found in the filter instruction.

PADDOCK
POOL EQUIPMENT COMPANY
100% EMPLOYEE OWNED

Winterizing

Pressure Sand Filter

Follow the suggested procedures below:

1. Backwash the filter thoroughly.
2. Close the main drain and return valves. Open backwash valve (gravity drain line assumed). Open all valves, which are a part of the filter face piping.
3. Drain all water from the filter tank and piping by opening the tank drain valve (except 6800 series; follow specific instructions).
4. Remove the manway cover (indoor installations only), gauges, and flowmeter and store in a dry place.
5. Check the sand bed in filter, clean if necessary.
6. Check filter tank for damages (if necessary).
7. Remove strainer lid and basket. (Loosen lid and remove basket(s) on outdoor installations).
8. For the longest service life, recirculating pump and motor should be in a dry area during shutdown, remove and store as required.

PADDOCK
POOL EQUIPMENT COMPANY
100% EMPLOYEE OWNED

General Filter - Trouble Shooting

Questions to think about when trouble shooting:

A. Motor Will Not Run

1. Open switch or wiring
2. Blown fuse or open thermal reset.
3. Burned-out motor or start switch.
4. Locked shaft
5. Impeller jammed with rock.

B. Motor Runs Too Slow or Hot

1. Low or improper voltage
2. Binding shaft or rubbing impeller
3. Inadequate ventilation
4. Pump strainer full

C. Low Pump Action

1. Valves are partially closed on suction or discharge.
2. Plugged suction or discharge line.
3. Undersized piping on suction or discharge line.
4. Pump rotation wrong.
5. Impeller clearance is too great.
6. Impeller partially clogged.
7. A plugged skimmer basket or hair and lint in pump strainer.
8. Dirty filter
9. Air leak in suction line or gate valve

D. High Pump or Filter Pressure Reading

1. Dirty filter.
2. Valve on discharge side partially closed.
3. Return lines are too small.
4. Heater bypass valve restricted.

E. Noisy Pump and Motor

1. Clogged hair and lint in the pump strainer.
2. Bad bearings in motor.
3. Partially closed valve or clogged suction line.

PADDOCK
POOL EQUIPMENT COMPANY
100% EMPLOYEE OWNED

General Trouble-Shooting – continued:

F. Short Filter Cycles

1. Excessive dirt load
2. Heavy bathing loads
3. Inadequate backwash flow or duration
4. Algae is present in water.
5. Bathers use an excessive amount of suntan lotion.
6. Algaecide or alum is added to pool water.
7. Wrong filter media or grade of media too fine.
8. Check filter media for hard spots.

G. Water Leakage from Pump Shaft

1. Replace seals on pumps with mechanical seals.
2. Shafts with glands - tighten gland nut or repack gland.

H. Excessive Amount of Air Returning to Pool

1. Leak or restriction in suction line.
2. Low pool level.
3. Air relief clogged.
4. Check all valves and tighten.
5. Check strainer on pump; lid & gasket and tighten securely.

I. Dirt Or Large Amount of Sand Returned to Pool

1. The backwash or cleaning cycle was not performed properly.
2. Improper placement of media.
3. Check filter media.
4. Reset filter media (underdrain to be covered at least 2” with 1/16” or 1/8” rock).
5. Broken underdrain or over drain.

PADDOCK
POOL EQUIPMENT COMPANY
100% EMPLOYEE OWNED

EQUIPMENT LIST

The following items have been provided by Paddock Pool Equipment Company, Inc.