



CHEMICAL & PUMP ROOM EVACUATOR (CPRE UNIT)

CPRE Unit Maintenance & Care SS Equipment

CPRE – CHEMICAL & PUMP ROOM

Features and Benefits with Options – Refer to Drawing(s)

Congratulations on your recent purchase and installation of a Paddock Evacuator® Source-Capture System. The Chemical and Pump Room Evacuator (CPRE) is designed to reduce airborne chloramines and other DBPs from chemical storage rooms and pump rooms alike. By reducing these harmful contaminants through source-capture exhaust, the rate of rust and corrosion to equipment should be reduced. Additionally, this should provide a much safer working environment for anyone working in the room on a regular basis.

CPRE - Chemical & Pump Room

Paddock Chemical and pump room Evacuator (CPRE) is a one size fits all solutions to poorly ventilated chemical and pump rooms. The compact design allows for simple installation, requiring only a 15 AMP 120 Volt GFCI- protected outlet and exhaust vent opening.

Chemical and pump rooms are typically hot, humid, and corrosive environments as the result of poor airflow and the presence of chemicals, motors, and pool equipment. Paddock's CPRE is your solution by creating a cross-ventilation airflow while source-capturing and exhausting corrosive chemical fumes.

Safety & Hazard

WARNING: TO REDUCE THE RISK OF FIRE OR ELECTRIC SHOCK, OR INJURY TO PERSONS, OBSERVE THE FOLLOWING:

- a) Use this unit only in the manner intended by the manufacturer. If you have any questions, contact the manufacturer (PPEC).
- b) Before servicing or cleaning the unit, switch the power off at the service panel and lock the service disconnecting means to prevent power from being switched on accidentally. When the service disconnecting means cannot be locked; securely fasten a prominent warning device such as a tag to the service panel.

Installation work and electrical wiring must be done by qualified person(s) in accordance with all applicable codes & standards including fire rated construction.

Care and Maintenance

Chemical and Pump Room Evacuator

Before cleaning refer to Warning section b listed in Installation section.

- Disconnect the power before starting.
- Rinse the air intake grilles with fresh water (**not pool water**) weekly to maintain maximum airflow.
- Refer to the section on **Powder Coated Metal Care & Maintenance**.
- The CPRE unit should run 24/7 when the pool is in use and chemicals being added.
- If the pool closes for an off-season, whereas the pool will not be treated with chemicals and all pumps will be turned off, the CPRE unit may be turned off although this would not be recommended by Paddock.

For Maximum Effectiveness

- The Evacuator is designed and should operate 24 hours a day 365 days per year.

Refer to the **Care and Maintenance section**.

Recipe for Success

Tips for maintaining an optimum chemical and pump room environment:

- Maintaining clean chemical and pump rooms is not an easy task but will yield satisfactory results for the long-term life of the equipment and facility.
- Clean the equipment and rinse floor with fresh water on a regular basis (weekly at a minimum). This will minimize any organics that may react with chemicals in the room and lead to off gassing.
- Maintain proper caps on all chemical containers and feed systems. Lines from liquid acid/chlorine should be fed through an appropriate cap and not simply inserted into the mouth of the container. This will prevent chemical evaporation and increased corrosion/air quality issues in space.
- Chemical buckets or bottles should have a sealed, secure lid at all times. This will prevent chemical evaporation and increased corrosion/air quality issues in space.
- Thoroughly clean the backwash area after backwashing any filters. Using a hose with a strong spray nozzle should be sufficient in most cases. Filter backwash can contain large amounts of corrosive by- products and should be washed away as soon as possible.

- The fresh air source should be clean of dirt and debris. Whether this is air from a supply vent, or a louver from the outside, any accumulation of particulates can hamper the ability of the Evacuator to properly remove contaminants from the area.
- The ideal turnover rate for chemical and pump rooms is ten (10) air changes per hour (ACH).
- If the recommended air changes per hour cannot be accomplished, an additional CPRE unit may be needed.
- If the recommended air changes per hour can be accomplished with a lower exhaust volume than the CPRE Unit provides at 100% operation, a volume damper can be installed in the duct, or a speed control device can be utilized to vary the speed of the motor as needed.

For questions concerning the usage of our equipment, please contact Paddock Pool Equipment Co., customer service.

Maintenance Stainless Steel Products

Care & Maintenance Guide - Refer to Drawings -if applicable

General procedures for Stainless steel equipment will need to be cleaned on a regular basis for aesthetic considerations and to preserve corrosion resistance against evaporated chloramines or spotting. Stainless steel is protected from corrosion by a thin layer of chromium oxide. Oxygen from the atmosphere combines with chromium in stainless steel to form this passive chromium oxide film that helps protect against corrosion.

Any contamination of surface by dirt, chlorides, greases, or other material will hinder this passivation process, and traps corrosive agents thus reducing corrosion protection. Chlorine and bromine used for sanitation are highly caustic chemicals to stainless steel, while heat and humidity enhance corrosiveness of these chemicals especially in natatoriums.

Thus, some form of routine maintenance is necessary to preserve appearance and integrity of surface. Stainless steel is easily cleaned by many different methods. They thrive with frequent cleaning, and unlike some other materials it is impossible to “wear out” stainless steel by excessive cleaning.

Safety & Hazard Precautions:

Scratching can occur on a bright finish by cleaners that contain hard abrasives or even by “grit” in wash water. The best preventive measure is to avoid using abrasive cleaners unless necessary. When abrasives are needed first experiment on an inconspicuous area. A “soft abrasive”, such as Zud liquid or Bon Ami should be tried first to see initial test results. While cleaning with the products mentioned be sure to observe the direction of grain in material. Following grain while cleaning material will limit scratching. Many cleaners contain corrosive ingredients which require thorough cleaning and rinsing with clean water is recommended for all cleaning procedures.

NEVER use steel wool, sandpaper, hydrochloric acid, muriatic acid, mineral acids, or harsh abrasive cleaners on stainless steel equipment. Steel wool will add corrosion due to dissimilar metal materials encountering equipment. Discoloration should be removed at first sign with a cleaner or polisher recommended for stainless steel equipment.

Note: Avoid adding chlorine, near stainless steel equipment. Dilute chlorine in a 5-gallon bucket and pour as far from stainless equipment as possible. Also, avoid cleaning masonry, and pool decks with strong acid solutions that encounter stainless steel products. Do not pour straight muriatic acid directly into pool for PH control. This method increases corrosion to stainless steel around the application area.

Your goal should be a robust maintenance and cleaning program to keep stainless steels protective chromium oxide layer intact which helps prevent corrosion.

Longevity of your stainless-steel equipment, follow these steps:

When and after installing the equipment, create routine maintenance:

1. Establish proper grounding of all equipment being installed at aquatic facilities.
 - a. Make it a point that **dissimilar metals are not in direct contact with one another.**
 - b. **Taking this precaution** will minimize the risk of forming an electrolytic cell between equipment, pool water and atmosphere at facility.
2. Once all equipment has been installed, **create weekly/monthly/yearly inspection:**
 - a. Apply a **coat of paste wax (automotive or marine wax) and buff equipment with soft cloth** to assist in extended corrosion protection.
 - b. Redo this process by **waxing after using cleaners or at six-month intervals** on stainless equipment. The wax will form a protective barrier between stainless steel and environmental elements left behind by evaporating pool water on equipment.
3. As stated previously, **rinse all equipment frequently with fresh water and dry with soft, clean cloth.**
 - a. This should wash away any accumulated halogen salts such as chlorine or bromine.
 - b. **DO NOT use pool water, salt water, high PH or iron in water to clean your stainless-steel products.**
4. Pool equipment should be inspected regularly.
 - a. Look for any tarnish, discoloration, stubborn stains, grease build up, blemishes or water spotting of stainless equipment.
 - b. If apparent, then take appropriate steps to remove corrosive elements with a non-chlorinated stainless-steel cleaner and clean water rinse.

Effective Cleaning Methods:

There are many choices available for cleaning stainless steel in the market that consumers may utilize. Depending upon cleaning needed and degree of contamination, some products may be better than others. **Although some products are listed as stainless steel cleaners, they may scratch the surface and may contain chloride bleach which will discolor, tarnish or dull finish if not removed completely.**

There are many industry associations that have listed available products that can be utilized in cleaning stainless steel products. The use of these proprietary names is intended only to indicate a type of product available and does not constitute endorsement. Omission of any proprietary product does not imply inadequacy.

Review each product being utilized in strict accordance with instructions on packaging. No one product is best for every form of cleaning, since there are many levels of corrosion.

The simplest, safest, and least costly method that will adequately do the job is always best.

- The longer a stain is on surface of stainless equipment, the higher chance of permanent discoloration or damage.
- Stainless steel surfaces thrive with frequent cleaning because there is no surface coating to wear off material.
- A soft cloth and clean warm water (no pool water) should always be first choice for mild stains and loose dirt and soil.
- A final rinse with clean water and wipe dry with soft cloth will complete the process and eliminate possibility of water stains. **DO NOT** use pool water, salt water, water with high PH or iron content to clean your stainless-steel products.
- Refer to step 2 under Longevity of stainless steel by applying a coat of wax.

Dealing with stubborn stains, discolored, or tarnished stainless steel product try and utilize recommended merchandise per various manufacturers.

Some recommended products:

CitriSurf product such as 77 plus or 2310, Sta-clean, Zud liquid, Samae, Bon Ami, Allchem concentrated cleaner, Twinkle, 3M stainless steel cleaner and polish, Sheila Shine, Perfect Sink, Liquid Nu Steel, Lumin cleaner, Gade FFF or Grade F Italian pumice, Highlite and many others.

Review the product application, Warnings, and other information before applying to surface of stainless-steel.

Surface restoration may be needed when stainless steel is scratched or pitted due to heavy corrosion. This can be accomplished by mechanically polishing as opposed to chemical cleaning above. A professional familiar with process should be contacted to handle.

For questions concerning the usage of our equipment, please contact Paddock Pool Equipment Co., customer service.

Powder Coated Metal Care & Maintenance

Refer to Drawing(s) – if applicable.

Powder coating is a type of coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, which is delivered via an evaporating solvent, powder coating is typically applied electrostatically and then cured under heat or with ultraviolet light. It's very durable and can last for many years if treated well.

Clean as follows:

1. **Clean with mild soap and fresh water (not pool water)**, after washed, rinse off completely.
2. **Dry the surface completely after cleaning**; when water is left on the surface it can cause staining. **Avoid using any type of abrasive cleaner, pads or brushes as this can damage the finish.**
3. If you need to remove a **tough stain**, try using a soft cloth dampened with white vinegar. Gently rub the stained area until the stain is removed. Be sure to rinse the area off with fresh water (not pool water) afterwards then dry it completely. If tough stain(s) are still there, use a soft cloth or non-abrasive sponge with a water-based gentle cleaner for cleaning powder-coating surfaces.
4. **Power Wash on Low Settings** is one of the best ways to clean your powder-coated items. However, power washers are **super powerful**, so be prudent and use the low setting to avoid damage. **Dry the surface completely after cleaning/rinsing**; when water is left on the surface it can cause staining.
5. **Protecting the surface of the powder-coated metal by Waxing the Exposed Areas:**
 1. Waxing the exposed areas of your powder-coated metal will help to protect it from the elements and keep it looking shiny and new. You can use commercial car wax or beeswax furniture polish by applying the wax with a soft cloth and rub it in using circular motions. Allow the wax to dry for at least 20 minutes before buffing it off with a clean, dry cloth.
 2. **DO NOT** put wax on **non-skid surfaces**, this will cause safety hazards on the surface.

SAFETY & HAZARDS - AVOID

Harsh Chemical Cleaners, Abrasives and Harsh Weather Conditions - these things can damage the finish on your product(s).

For questions concerning the usage of our equipment, please contact Paddock Pool Equipment Co., customer service.