



HDPE GRATING Maintenance Manual

Refer to Project Specific Drawing(s)

SAFETY &/or HAZARD INFORMATION

This bulletin includes important safety information that should be read by owners, managers, service personnel, and anyone in charge of the pool or pool area. Also, we suggest a copy be posted for quick reference.

1. Only personnel trained and familiar with the proper use of pool chemicals should handle acid, liquid chlorine or chlorine compounds. Chemicals should never be used when swimmers are in the pool. Acid and liquid chlorine should always be stored, carried, or handled in plastic containers.
2. If grating is a part of the perimeter system &/or deck drain, it should be kept firmly always clamped down and in good repair. When a section of grating become loose or damaged that particular area must be immediately covered and a replacement of grating ordered. Under no circumstances should swimmers be allowed to use any portion of the perimeter that contains loose or damaged grating. Perimeter grating is not intended for foot traffic. Swimmers should be advised not to walk, stand, or jump on perimeter grates.
3. Ladders and grab rails are intended for the use of one swimmer at a time; they are not designed for handstands or other gymnastic stunts and they should not be used for this purpose. Ladder treads should be inspected regularly. If a tread becomes loose or damaged, the ladder should be taken out of service until repairs are made.
4. Lifeguard Chairs are intended for the individual use of trained "on duty" lifeguards, one (1) guard per chair. Lifeguard chairs are not to be used by swimmers, spectators, or by more than one (1) person at a time. There should be no diving from portable lifeguard chairs. Umbrellas should be closed or removed from portable lifeguard chairs during windy conditions. All frame connections are to be checked for tightness. The seat is bolted to the frame assembly. It is important to advise all users to periodically check to determine that the studs are firmly fastened to the seat and the nuts are tight. If they become loose or detached, it could result in serious injury. On outdoor installations or usage, it is suggested that the seat be removed and stored inside during the winter.
5. Starting Platforms should only be used by trained competitive swimmers or under the direct supervision of an instructor. Swimmers should execute shallow racing dives only. Impact with the pool bottom can cause severe injury. Starting platforms have warning labels and inform the purchaser of the need to remove the platforms during non-usage. If your starting platforms do not have warning labels, please contact the manufacturer immediately.
6. Bulkheads are designed and built for strength and safety. Any grating should be kept fully secured to avoid injury. **NO swimming under bulkhead. Never use bulkhead as a support or staging for equipment.** The bulkhead includes a compressor; please refer to owner's manual provided with the unit.

For questions concerning the usage of our equipment, please contact Paddock Pool Equipment Co., customer service.

High Density Polyethylene (HDPE) GRATING

Refer to Drawing(s)

FEATURES:

- Machined slots are to allow fast flow of water through grating.
- Matte-textured slip-resistant finish provides non-skid surface.
- Low maintenance finish is easy to clean and eliminates need for repair.
- Will not crack, rot, delaminate, swell or absorb water.
- Environmentally stabilized for harsh sun and tough aquatic environments.
- Does not react with pool chemicals.
- Designed to fit a radius gutter or hard configuration.

Proper Care & Maintenance Guide refers to - [GRATING - High Density Polyethylene \(HDPE\)](#).

- Check grating for loose or damaged area(s), refer to the [Safety &/or Hazard Information sheet #2](#).
- Your HDPE Grating will require some maintenance referring to [Grating Adjustment & Characteristics](#)

GRATING

High Density Polyethylene (HDPE)

ADJUSTMENTS & CHARACTERISTICS with CARE & CLEANING MAINTENANCE

HDPE Grating Adjustments & Characteristics (if applicable)

HDPE grating is highly durable and will give years of good service in the pool environment. The grating is held in place by either a front capture strip and a rear HDPE camlock or by a HDPE camlock front and back. A 1/4" x 1 1/2" x 3/16" allen head screw is used to tighten the camlock.

- Grating can be gapped up to 3/8" (three-eighths of inch), however at normal operating temperatures, the gap for indoor pool is 1/8" (one-eighth of inch) and outdoor pool is 1/4" (one-fourth of inch). An outdoor pool grating will contract and expand with sizeable temperature swings. Larger gaps can be expected in cold temperatures. At initial startup grating may need to be adjusted when pool reaches operating temperature.
- Grating fasteners needs to be inspected at the start of the swim season and periodically throughout the year. Adjust as needed, by hand loosening cam-locks with a 3/16" allen wrench, re-adjust gaps as listed above and re-tighten.

Care and Maintenance

- Paddock's HDPE grating is marine-grade polymer sheeting which is resistant to most chemicals and requires little maintenance to keep it looking new.
- Keep harsh solvents, acids, wood stains and wood preservatives away from Paddock HDPE finish. They may cause permanent staining and damage.
- Staining from rust is very difficult to remove so keep uncoated non stainless metals away from HDPE material
- Shoes with marking soles can leave scuff marks that can be difficult to remove

Cleaning

- For daily cleaning of everyday dirt and stains, use a non-abrasive cleaner such as "Zud" or "Soft Scrub" and a nylon brush to scrub lightly. Excessively hard scrubbing can mar the finish.
- Hard to remove stains will usually go away if you soak the area with bleach. **When using this method, you must remove the grating from the stainless steel so it will not cause corrosion.** Do not use 100% granular or tablet chlorine as a bleach alternate.
- Pressure washing can mar the finish.
- Petroleum based stains can be difficult to remove, soak the area with WD-40®. Then use acetone or toluene with a white nylon scrub pad (color-based pads can transfer dye color to finish when combined with acetone)
- Do not use MEK, turpentine or naphtha solvent.
- Do not use polishes such as Armor-All ® to non-skid areas, this will reduce the slip coefficient and cause a fall/slip hazard.

For questions concerning the usage of our equipment, please contact Paddock Pool Equipment Co., customer service.