

High Density Polyethylene (HDPE) Products

Refer to Drawing(s) – if applicable

Care & Maintenance Guide

- Paddock's HDPE grating is marine-grade polymer sheeting which is resistant to most chemicals and requires little maintenance to keep it looking new.
- Keep harsh solvents, acids, wood stains and wood preservatives away from Paddock HDPE finish. They may cause permanent staining and damage.
- Staining from rust is very difficult to remove so keep uncoated non stainless metals away from HDPE material.
- Shoes with marking soles can leave scuff marks that can be difficult to remove.

Cleaning

- For daily cleaning of everyday dirt and stains, use a non-abrasive cleaner such as "Zud" or "Soft Scrub" and a nylon brush to scrub lightly. Excessively hard scrubbing can diminish the finish of the grating.
- Hard to remove stains will usually go away if you soak the area with bleach.
When using this method, you must remove the grating from the stainless steel so it will not cause corrosion. Do not use 100% granular or tablet chlorine as a bleach alternate.
- Pressure washing can diminish the finish on HDPE.
- Petroleum based stains can be difficult to remove, soak the area with WD-40®. Then use acetone or toluene with a white nylon scrub pad (color-based pads can transfer dye color to finish when combined with acetone)
- Do not use MEK, turpentine or naphtha solvent.

SAFETY & HAZARDS - AVOID

Do not use polishes such as Armor-All ® to non-skid areas, this will reduce the slip coefficient and cause a fall/slip hazard.

For questions concerning the usage of our equipment, please contact Paddock Pool Equipment Co., customer service.