



LADDERS & RAILS (GRAB &/OR HAND/RAMP)

Maintenance & Care Equipment

Ladders with Cross Brace

Features and Benefits with Options – Refer to Drawing(s)

Paddock's Ladders are fabricated from type 304L or 316L stainless steel tubing with an outside diameter of 1.90" and standard wall thickness of .083". (Outside diameter of 1.5" or wall thickness of .120" is also available.)

The ladder rails are spaced 19" apart with a cross brace 24-inch standard (center to center for added stability and furnished with slip-resistant stainless-steel treads. A wider cross brace 30-inch (center to center) is for wider gutter.

Rubber bumpers are on bottom of each rail to protect the interior from scratches or damage to the pool surface.

Exposed surfaces shall be polished to a Paddock buff finish (standard).

Powder Coating is available by request.

Paddock deck anchors and escutcheons are available.

Paddock's ladders sizes:

2-Tread, 3-Tread, 4-Tread, & 5-Tread types with slip-resistance treads.

Safety & Hazard

Ladders and grab rails are intended for the use of one swimmer at a time; they are not designed for handstands or other gymnastic stunts, and they should not be used for this purpose. Ladder treads should be inspected regularly. If a tread becomes loose or damaged, the ladder should be taken out of service until repairs are made.

For questions concerning the usage of our equipment, please contact Paddock Pool Equipment Co., customer service.

Grab Rails - Refer to Drawing(s)

Features and Benefits with Options

Paddock Pretzel Bend, California Style and Figure Four Grab rails come as a pair with optional bends, depending on your project.

Paddock's Grab rails are fabricated from type 304L or 316L stainless steel tubing with an outside diameter of 1.90" and standard wall thickness of .083". (Outside diameter of 1.5" or wall thickness of .120" is also available.)

All the rails are 33 inches above the deck to top of rail and 22 inches center to center between the rails. The legs are mounted to allow maximum walking space on the pool deck.

Exposed surfaces shall be polished to a Paddock buff finish (standard).

Powder Coating is available by request.

Paddock deck anchors and escutcheons are available.

Safety & Hazard

Ladders and grab rails are intended for the use of one swimmer at a time; they are not designed for handstands or other gymnastic stunts, and they should not be used for this purpose. Ladder treads should be inspected regularly. If a tread becomes loose or damaged, the ladder should be taken out of service until repairs are made.

Pretzel Bend rails have legs are mounted side by side, allowing maximum walking space on pool deck, with 8 inches from deck to center of bottom of the rail and 17 inches from edge of pool wall to center of anchor.

California Style rails have the same design as the Pretzel bend rails but extend an additional 9 inches (17 inches plus 9 inches) which is 26 inches from edge of pool wall to center of anchor. This is to accommodate pools with very wide gutters and/or unusually extreme deck-to-water dimensions. Legs are mounted side by side, allowing maximum walking space on the pool deck.

Figure Four rails have legs mounted in-line on the deck with 8 inches between post, the front and back anchors. There are 12 inches from the deck to center of bottom of the rail with 28 inches from the edge of pool wall to center of back anchor. This accommodates very wide gutters and/or unusually extreme deck to water dimensions.

For questions concerning the usage of our equipment, please contact Paddock Pool Equipment Co., customer service.

Handrails/Ramp Rails - Refer to Drawing(s)

Paddock Handrails come as a single with optional bends, depending on your project.

Paddock's rails are fabricated from type 304L or 316L stainless steel tubing with an outside diameter of 1.90" and standard wall thickness of .083". (Outside diameter of 1.5" or wall thickness of .120" is also available.)

All the rails are 34 inches above the pool floor and inclines at same angel as that of stair(s) or ramp(s).

The legs are mounted with anchor sockets located in the bottom pool and on pool deck, this allows them to be removed if necessary.

Exposed surfaces shall be polished to a Paddock buff finish (standard).

Powder Coating is available by request for handrails and escutcheons.

Paddock deck wedge anchors and escutcheons are available.

Paddock Handrails or ramp rails are custom made per request.

Safety & Hazard

Handrails are intended for the use of swimmers to enter the pool safely; they are not designed for handstands or other gymnastic stunts, and they should not be used for this purpose. Handrails should be inspected regularly to make they are secure. If a handrail(s) becomes loose or damaged, they should be taken out of service until repairs are made.

For questions concerning the usage of our equipment, please contact Paddock Pool Equipment Co., customer service.