

The ShorTeX package

Trevor Campbell, Jonathan Huggins, and Jeff Negrea

Updated March 24, 2024

Abstract

The purpose of the ShorTeX (meta)package is to make the process of typesetting typical mathematical documents in \LaTeX more efficient, and the resulting code easier to read. It achieves this by (1) providing an extensive, internally consistent, and easy to learn set of macro shorthands and custom commands, and (2) incorporating a set of packages that are dedicated to reducing manual coding effort.

Contents

1	Usage and package options	2
2	Environments	3
3	Delimiters	4
4	Greek characters and variants	5
5	Font styles and accents	6
5.1	Default font, accent combination macros	6
5.2	Advanced usage: flexible font, accent combination macro	6
6	Commenting	9
7	Referencing figures, equations, tables, etc.	10
8	Custom macros	11
8.1	Shrinking whitespace in math	11
8.2	Wide bar	11
8.3	Sets and set operations	12
8.4	Linear algebra	12
8.5	Calculus	13
8.6	General mathematics	13
8.7	Common words and names with accents	14
8.8	Probability and statistics	14
8.9	Vector spaces and operators	15

8.10 Paired delimiters	16
9 Example Document	17

1 Usage and package options

Put a copy of `shortex.sty` in the folder alongside your other document files, and include ShorTeX in the document by adding `\usepackage{shortex}` to the preamble. **Do not install ShorTeX system-wide**; this package has not yet reached a stable version 1.0, and we are updating things regularly without any guarantee of backwards compatibility. **You must compile your document 4 times when using ShorTeX** to ensure that equation numbers and references update properly.

ShorTeX will include and configure many common packages for you (e.g., `graphicx`, `subcaption`, `hyperref`, `algorithm`, `algpseudocode`, `amsmath`, among others), so you do not need to explicitly include and set these up yourself. If you are writing a document that must use a specific style file (e.g., for a conference or journal) that itself includes some of these packages, we recommend editing those style files to remove the package imports.

The ShorTeX package has a few options:

manualnumbering Do not include `autonum.sty`. This disables automatic equation numbering.

blacklinks Switch hyperlinks, citations, references, etc. to be typeset in black font. The default is dark blue.

draft Turn on draft mode for `graphicx`, `hyperref` (with placeholder figures etc).

nomathfontdefaults Disable default font style/accent combinations (see Section 5 for details).

commenters Specify names of commenters for comment commands (see Section 6 for details).

suppresscomments Suppress comments (see Section 6 for details).

2 Environments

L^AT_EX documents often include a lot of verbose code related to creating environments (`\begin{blah}... \end{blah}`). ShorTeX provides a set of shortened macros for common environments. Each shortened begin and end command starts with `\b...` and `\e...`, respectively. Note that all theorem-like environments (theorem, lemma, proposition, etc.) are numbered by default; unnumbered versions can be obtained by appending a `u`. For example, `\bthmu... \ethmu` creates an unnumbered theorem environment, while `\blemu... \elemu` creates an unnumbered lemma environment.

Environment	Syntax
abstract	<code>\babs... \eabs</code>
itemize	<code>\bitem... \eitem</code>
enumerate	<code>\benum... \eenum</code>
description	<code>\bdesc... \edesc</code>
algorithm	<code>\balg... \ealg</code>
algorithmic	<code>\balgc... \ealgc</code>
table	<code>\btabs... \etabs</code>
subtable	<code>\bsubtab... \esubtab</code>
tabular	<code>\btabr... \etabr</code>
figure	<code>\bfig... \efig</code>
figure*	<code>\bfigs... \efigs</code>
subfigure	<code>\bsubfig... \esubfig</code>
center	<code>\bcent... \ecent</code>
align	<code>\[... \]</code>
inline math	<code>\$... \$</code>
<i>Note: These are numbered theorem-like environments.</i>	
<i>For unnumbered, append a <code>u</code>: e.g., <code>\bthmu... \ethmu</code>.</i>	
theorem	<code>\bthm... \ethm</code>
lemma	<code>\blem... \elem</code>
proposition	<code>\bprop... \eprop</code>
corollary	<code>\bcor... \ecor</code>
conjecture	<code>\bconj... \econj</code>
definition	<code>\bdefn... \edefn</code>
assumption	<code>\bassump... \eassump</code>
example	<code>\bexa... \eexa</code>
remark	<code>\brmk... \ermk</code>
fact	<code>\bfact... \efact</code>
exercise	<code>\bexer... \eexer</code>
proof	<code>\bprf... \eprf</code>
proofof	<code>\bprfof{\cref{theorem_label}}... \eprf</code>
matrix	<code>\bmat... \emat</code>
bmatrix	<code>\bbmat... \ebmat</code>
pmatrix	<code>\bpmat... \epmat</code>

3 Delimiters

Mathematics in L^AT_EX often includes quite a few delimiters (parentheses, brackets, curly brackets, etc.). A very common usage of these involves the `\left...\right` commands for automatic sizing. One can also use `\bigl...\bigr`, `\Bigl...\Bigr`, `\biggl...\biggr`, `\Biggl...\Biggr` to control sizing manually. ShorTeX creates shorthands for these.

Description	Syntax
automatic	<code>\lt...\rt</code>
big	<code>\lb...\rb</code>
Big	<code>\lB...\rB</code>
bigg	<code>\lbg...\rbg</code>
Bigg	<code>\lBg...\rBg</code>

These can be applied to all the usual delimiter characters. The following tables demonstrate usage for automatically sized delimiters.

Description	Example	Text style	Display style
parentheses	<code>\lt(\frac{x}{y}\rt)</code>	$\left(\frac{x}{y}\right)$	$\left(\frac{x}{y}\right)$
curly brackets	<code>\lt\{\frac{x}{y}\rt\}</code>	$\left\{\frac{x}{y}\right\}$	$\left\{\frac{x}{y}\right\}$
square brackets	<code>\lt[\frac{x}{y}\rt]</code>	$\left[\frac{x}{y}\right]$	$\left[\frac{x}{y}\right]$
pipes	<code>\lt \frac{x}{y}\rt </code>	$\left \frac{x}{y}\right $	$\left \frac{x}{y}\right $
double pipes	<code>\lt \frac{x}{y}\rt </code>	$\left\ \frac{x}{y}\right\ $	$\left\ \frac{x}{y}\right\ $
angle brackets	<code>\lt<\frac{x}{y}\rt></code>	$\left\langle\frac{x}{y}\right\rangle$	$\left\langle\frac{x}{y}\right\rangle$

4 Greek characters and variants

ShorTeX defines shorthands for Greek characters and variants. The syntax is just the first two characters of the greek name (except for omicron, which is identical to the Roman o and O and so no special characters are required). Variants are obtained by preceding the usual command with `\v`...

Letter	Syntax	Symbol	Variant Syntax	Variant Symbol
alpha	<code>\al,A</code>	α, A		
beta	<code>\be,B</code>	β, B		
gamma	<code>\ga,\Ga</code>	γ, Γ		
delta	<code>\de,\De</code>	δ, Δ		
epsilon	<code>\ep,E</code>	ϵ, E	<code>\vep,E</code>	ε
zeta	<code>\ze,Z</code>	ζ, Z		
eta	<code>\et,H</code>	η, H		
theta	<code>\th,\Th</code>	θ, Θ	<code>\vth</code>	ϑ
iota	<code>\io,I</code>	ι, I		
kappa	<code>\ka,K</code>	κ, K	<code>\vka</code>	\varkappa
lambda	<code>\la,\La</code>	λ, Λ		
mu	<code>\mu,M</code>	μ, M		
nu	<code>\nu,N</code>	ν, N		
xi	<code>\xi,\Xi</code>	ξ, Ξ		
omicron	<code>o,O</code>	o, O		
pi	<code>\pi,\Pi</code>	π, Π	<code>\vpi</code>	ϖ
rho	<code>\rh,P</code>	ρ, P	<code>\vrh</code>	ϱ
sigma	<code>\si,\Si</code>	σ, Σ	<code>\vsi</code>	ς
tau	<code>\ta,T</code>	τ, T		
upsilon	<code>\up,\Up</code>	υ, Υ		
phi	<code>\ph,\Ph</code>	ϕ, Φ	<code>\vph</code>	φ
chi	<code>\ch,X</code>	χ, X		
psi	<code>\ps,\Psi</code>	ψ, Ψ		
omega	<code>\om,\Om</code>	ω, Ω		

5 Font styles and accents

Applying accents (e.g., hats \hat{a} , tildes \tilde{a} , bars \bar{a}) and changing fonts (e.g., double-stroke \mathbb{A} , caligraphic \mathcal{A} , and bold \mathbf{A}) is quite cumbersome in standard L^AT_EX. For example, the code to make a tilde caligraphic A, $\tilde{\mathcal{A}}$ is `\widetilde{\mathcal{A}}`. By itself that code is not too bad, but many such characters in a large mathematical expression results in unreadable code.

5.1 Default font, accent combinations

ShorTeX defines an efficient syntax for changing math fonts and applying accents to characters. The syntax takes the form `\s<modifiers>character`, where `<modifiers>` is a set of single characters that represent font/accident modifications to `character`. For example, the code for tilde caligraphic A is `\stcA` where `t` represents “tilde,” `c` represents “caligraphic,” and `A` is the character to typeset. The table below shows the modifier characters that are implemented by default with all upper/lowercase Greek and Roman characters.

Style	Modifier	Example	Typeset Example
caligraphic (<code>\mathcal</code>)	<code>c</code>	<code>\scA</code>	\mathcal{A}
bold (<code>\mathbf</code>)	<code>k</code>	<code>\skA</code>	\mathbf{A}
doublestroke (<code>\mathbb</code>)	<code>d</code>	<code>\sdA</code>	\mathbb{A}
Accent	Modifier	Example	Typeset Example
hat (<code>\widehat</code>)	<code>h</code>	<code>\shA</code>	\hat{A}
tilde (<code>\widetilde</code>)	<code>t</code>	<code>\stA</code>	\tilde{A}
bar (<code>\widebar</code>)	<code>b</code>	<code>\sbA</code>	\bar{A}
dot (<code>\dot</code>)	<code>o</code>	<code>\soA</code>	\dot{A}

In addition, ShorTeX allows the use of combinations of any one of the above fonts with any one of the above accents. For example, we can combine the caligraphic style `c` with all the accents via `\stcA`, `\socA`, `\sbcA`, `\shcA`:

$$\tilde{\mathcal{A}} \quad \dot{\mathcal{A}} \quad \bar{\mathcal{A}} \quad \hat{\mathcal{A}}.$$

To disable these default shortcuts, pass the `\nomathfontdefaults` option to ShorTeX.

5.2 Advanced usage: flexible font, accent combinations

For most users, the default font style/accident combinations that come with ShorTeX will suffice. However, the `\s...` commands are actually implemented under the hood using a more flexible `\s[modifiers]character` command that can take a wide variety of combinations of font/accident modifiers. For example, the code for tilde caligraphic A is `\s[tc]A` where `t` represents “tilde,” `c` represents “caligraphic,” and `A` is the character to typeset.

Style	Modifier	Example	Typeset	Example
caligraphic (<code>\mathcal</code>)	<code>c</code>	<code>\s[c]A</code>	\mathcal{A}	
bold (<code>\mathbf</code>)	<code>k</code>	<code>\s[k]A</code>	\mathbf{A}	
doublestroke (<code>\mathbb</code>)	<code>d</code>	<code>\s[d]A</code>	\mathbb{A}	
fraktur (<code>\mathfrak</code>)	<code>f</code>	<code>\s[f]A</code>	\mathfrak{A}	
Accent	Modifier	Example	Typeset	Example
hat (<code>\widehat</code>)	<code>h</code>	<code>\s[h]A</code>	\widehat{A}	
tilde (<code>\widetilde</code>)	<code>t</code>	<code>\s[t]A</code>	\widetilde{A}	
bar (<code>\widebar</code>)	<code>b</code>	<code>\s[b]A</code>	\widebar{A}	
dot (<code>\dot</code>)	<code>o</code>	<code>\s[o]A</code>	\dot{A}	

These style modifiers can be combined; the underlying code is flexible enough that it will happily produce a wide variety of combinations, including those that aren't very sensible.

Note: modifiers are applied in the reverse of the order in which they appear; the modifier furthest to the right is applied first. This matches the order that the corresponding commands would appear in TeX code.

Style/Accent	Modifier	Example	Typeset	Example
caligraphic tilde	<code>ct</code>	<code>\s[ct]A</code>	$\widetilde{\mathcal{A}}$	
bold hat	<code>kh</code>	<code>\s[kh]A</code>	$\widehat{\mathbf{A}}$	
tilde hat	<code>ht</code>	<code>\s[ht]A</code>	$\widehat{\widetilde{A}}$	
hat tilde	<code>th</code>	<code>\s[th]A</code>	$\widetilde{\widehat{A}}$	
fraktur dot	<code>of</code>	<code>\s[of]A</code>	$\dot{\mathfrak{A}}$	

The default `\s...` commands included in ShorTeX are compiled in advance from the more general `\s[...]` via the `\parsefontstylestrings` command; this lets us avoid having to type `[]` for common style/accent combinations. For example, if we use “bold hat” symbols frequently, we might want to use commands like `\skh...` instead of `\s[kh]...`. We can accomplish this using the `\parsefontstylestrings` command, with syntax

```
\parsefontstylestrings{<fstr1>}{<fstr2>...}{<alphabet>}
```

For example, to define “bold hat” and “caligraphic hat” styles for the characters A, B, C, and D, we would use the command

```
\parsefontstylestrings{{kh}{ch}}{ABCD}
```

and then in the L^AT_EX document, use the commands `\skhA` `\skhB` `\skhC` `\skhD` and `\schA` `\schB` `\schC` `\schD` to obtain the following symbols:

$$\widehat{\mathbf{A}}\widehat{\mathbf{B}}\widehat{\mathbf{C}}\widehat{\mathbf{D}}\widehat{\mathcal{A}}\widehat{\mathcal{B}}\widehat{\mathcal{C}}\widehat{\mathcal{D}}$$

As another example, for “bold hat” applied to α , β , and γ , we would use the syntax

`\parsefontstylestrings{{kh}}{{\al}{\be}{\ga}}`

and then in the \LaTeX document, use the commands `\skhal` `\skhbe` `\skhga` to obtain the following symbols:

$$\hat{\alpha}\hat{\beta}\hat{\gamma}$$

For convenience we also provide a few common alphabets of symbols for use in the `\parsefontstylestrings` command. Note that not every Greek character has a lowercase or uppercase version (in cases where it is identical to its Roman counterpart). Also note that we use ShorTeX Greek letter syntax; see Section 4.

Syntax	Characters
<code>\lowercaseRoman</code>	abcdefghijklmnopqrstuvwxyz
<code>\uppercaseRoman</code>	ABCDEFGHIJKLMNOPQRSTUVWXYZ
<code>\lowercaseGreek</code>	al,be,ga,de,ep,ze,et,th,io,ka,la,mu,nu,xi,pi,rh si,ta,up,ph,ch,ps,om,vep,vth,vka,vpi,vrh,vsi,vph
<code>\uppercaseGreek</code>	Ga,De,Th,La,Xi,Pi,Si,Up,Ph,Ps,Om

6 Commenting

ShorTeX defines four types of document markup that can be used: *comment*, *emphasized comment*, *margin comment*, and *highlight*. This is a lightweight alternative to some more common todo packages (e.g., `todonotes`). In order to create comments, you must pass the `commenters` option to the package, and specify an identifier for each commenter. For example, one could specify three commenters (named A, B, C) using the command

```
\usepackage[commenters={A,B,C}]{shortex}
```

For each commenter, there are four commands (one for each markup type). The table below contains examples for commenter “A”. Notice that each comment is tagged with a number (specific to each commenter) for easy referencing.

Comment Type	Syntax	Example	Typeset Example
comment	<code>\c...{comment}</code>	<code>\cA{hello!}</code>	(A1) hello!
emphasized comment	<code>\e...{comment}</code>	<code>\eA{hello!}</code>	(A2) hello!
margin comment	<code>\m...{comment}</code>	<code>text\mA{hello!}</code>	text (A3) (A3) hello!
highlight	<code>\h...{text}</code>	<code>\hA{hello!}</code>	hello!

Note that each commenter gets their own color. Currently ShorTeX supports nine different commenter colors, and will wrap around back to the first color if the number of commenters exceeds nine:

- (A4) example(A5) **emphasized example**more text (A6) (A6) margin example
- (B1) example(B2) **emphasized example**more text (B3) (B3) margin example
- (C1) example(C2) **emphasized example**more text (C3) (C3) margin example
- (D1) example(D2) **emphasized example**more text (D3) (D3) margin example
- (E1) example(E2) **emphasized example**more text (E3) (E3) margin example
- (F1) example(F2) **emphasized example**more text (F3) (F3) margin example
- (G1) example(G2) **emphasized example**more text (G3) (G3) margin example
- (H1) example(H2) **emphasized example**more text (H3) (H3) margin example
- (I1) example(I2) **emphasized example**more text (I3) (I3) margin example
- Back to first color: (J1) example(J2) **emphasized example**more text (J3) (J3) margin example

You can also disable all comments to see a clean version of the current document using the `suppresscomments` package option. This option will blank out all comments and render highlighted text normally.

7 Referencing figures, equations, tables, etc.

ShorTeX includes the `cleveref` package, which simplifies the process of typesetting references. Use the `\cref` command (or `\Cref` at the beginning of a sentence) to automatically typeset the names of the objects you reference (including properly handling multiple references). For example, if `\label{fig:first}` is applied to the first figure in the document,

In `\cref{fig:first}`, you can see...

would typeset as “In Fig. 1, you can see...” Similarly, if `\label{thm:first}` references a theorem and `\label{second_result}` references a lemma,

`\cref{thm:first,lem:second}` show that...

will typeset as “Theorem 1 and Lemma 2 show that...” This works for many different reference types (Figure, Algorithm, Equation, Table, etc), and can be extended if needed. See the `cleveref` documentation at <https://ctan.org/pkg/cleveref?lang=en> and the homepage at <https://www.dr-qubit.org/cleveref.html> for more information.

ShorTeX also includes the `autonum` package, which simplifies the process of equation numbering. Typically when you typeset equations, you have to choose between `...\$, $$...$$`, `\begin{align}...\end{align}`, `\begin{aligned}...\end{aligned}`, `\begin{equation}...\end{equation}`, not to mention starred versions of those environments and `\nonumber/\notag` commands, depending on whether/where you want equation numbers,

The `autonum` package automatically decides which equations to provide numbers based on *which equations you reference*. So when using ShorTeX, you only need two commands for math mode: single dollar signs `...\$` for inline math, and `align` environments (redefined in ShorTeX to be `\[...\]`) for display math.¹

For example, if you create the following display math,

```
\[
  a+b = c \label{eq:the_equation}
\]
```

then if you use the command `\cref{eq:the_equation}` somewhere in the document, that equation will automatically be assigned a number. If not, it won't get a number. See the `autonum` package documentation <https://ctan.org/pkg/autonum?lang=en> for more information.

¹There are differences between how `align` and other math display environments typeset equations. I have not ever encountered a case where it mattered much. If you are very picky about typesetting, note that ShorTeX does not *disable* any functionality, so you can use other environments anywhere you feel it is necessary.

8 Custom macros

8.1 Shrinking whitespace in math

The command `\squish{<frac>}` in math mode enables you to shrink whitespace in mathematics, where `<frac>` represents the fraction of whitespace reduction. Below, the first line is regularly spaced, the second line has `\squish{0.5}`, and the third has `\squish{0.0}`.

$$\begin{aligned} &\sqrt{\frac{1^2}{0.111222}(0.111222 \times 1.111163 + 0.066987^2 \times 0.111222) - 1} = \sqrt{0.111222} \\ &\sqrt{\frac{1^2}{0.111222}(0.111222 \times 1.111163 + 0.066987^2 \times 0.111222) - 1} = \sqrt{0.111222} \\ &\sqrt{\frac{1^2}{0.111222}(0.111222 \times 1.111163 + 0.066987^2 \times 0.111222) - 1} = \sqrt{0.111222} \end{aligned}$$

The code for `\squish` was taken from <https://tex.stackexchange.com/questions/467942/how-to-squeeze-a-long-equation>.

8.2 Wide bar

ShorTeX provides the `\widebar` command to typeset a wide bar accent on top of a character (similar to the usual `\widehat` and `\widetilde` commands). Compare to the usual `\bar` and `\overline` commands:

widebar: \bar{A} overline: \overline{A} bar: \bar{A}

The code for `\widebar` was taken from <https://tex.stackexchange.com/questions/16337/can-i-get-a-widebar-without-using-the-mathabx-package>. Note that the shortened style/accent code `b` in Section 5 encodes `\widebar`, not `\bar`.

8.3 Sets and set operations

Name	Syntax	Symbol
reals	<code>\reals</code>	\mathbb{R}
extended reals	<code>\extreals</code>	$\overline{\mathbb{R}}$
rational numbers	<code>\rats</code>	\mathbb{Q}
integers	<code>\ints</code>	\mathbb{Z}
natural numbers	<code>\nats</code>	\mathbb{N}
complex numbers	<code>\comps</code>	\mathbb{C}
measures	<code>\measures</code>	\mathcal{M}
probability measures	<code>\pmeasures</code>	\mathcal{M}_1
(big) intersection	<code>\intersect, \Intersect</code>	\cap, \bigcap
(big) union	<code>\union, \Union</code>	\cup, \bigcup
(big) disjoint union	<code>\djunion, \djUnion</code>	\sqcup, \bigsqcup
volume	<code>\vol</code>	vol
diameter	<code>\diam</code>	diam
boundary	<code>\boundary</code>	∂
closure	<code>\closure</code>	cl
span	<code>\spann</code>	span
cone	<code>\cone</code>	cone
convex hull	<code>\conv</code>	conv

8.4 Linear algebra

Name	Syntax	Symbol
trace	<code>\tr A</code>	$\text{tr } A$
rank	<code>\rank A</code>	$\text{rank } A$
transpose	<code>A\T</code>	A^\top
inverse transpose	<code>A\nT</code>	$A^{-\top}$
diagonal	<code>\diag A</code>	$\text{diag } A$
adjoint	<code>A\adj</code>	A^\dagger
spectrum	<code>\spec A</code>	σA
kronecker product	<code>A\kron B</code>	$A \otimes B$

8.5 Calculus

Name	Syntax	Symbol
differential symbol	<code>\d x</code>	dx
partial differential symbol	<code>\pd x</code>	∂x
gradient symbol	<code>\grad f</code>	∇f
derivative	<code>\der{x}{y}</code>	$\frac{dx}{dy}$
double derivative	<code>\dder{x}{y}</code>	$\frac{d^2 x}{dy^2}$
derivative w.r.t.	<code>\derwrt{y}</code>	$\frac{d}{dy}$
partial derivative	<code>\pder{x}{y}</code>	$\frac{\partial x}{\partial y}$
partial double derivative	<code>\pdder{x}{y}</code>	$\frac{\partial^2 x}{\partial y^2}$
i^{th} partial derivative	<code>\pderi{x}{y}{i}</code>	$\frac{\partial^i x}{\partial y^i}$
partial derivative w.r.t.	<code>\pderwrt{y}</code>	$\frac{\partial}{\partial y}$
Hessian	<code>\hes{a}{x}{y}</code>	$\frac{\partial^2 a}{\partial x \partial y}$

8.6 General mathematics

Name	Syntax	Symbol
argmax	<code>\argmax_{x\in \reals}</code>	$\arg \max_{x \in \mathbb{R}}$
argmin	<code>\argmin_{x\in \reals}</code>	$\arg \min_{x \in \mathbb{R}}$
esssup	<code>\esssup_{x\in \reals}</code>	$\text{ess sup}_{x \in \mathbb{R}}$
essinf	<code>\essinf_{x\in \reals}</code>	$\text{ess inf}_{x \in \mathbb{R}}$
indicator	<code>\ind[x=3]</code>	$1[x = 3]$
sign	<code>\sgn x</code>	$\text{sgn } x$
scientific notation	<code>\scin{3}{5}</code>	3×10^5
given	<code>\given</code>	$ $
defined as	<code>\defas</code>	$:=$
defines	<code>\defines</code>	$=:$
half	<code>\half</code>	$1/2$
third	<code>\third</code>	$1/3$
quarter	<code>\quarter</code>	$1/4$

8.7 Common words and names with accents

Syntax	Symbol
<code>\cadlag</code>	càdlàg
<code>\Frechet</code>	Fréchet
<code>\Gronwall</code>	Grönwall
<code>\Holder</code>	Hölder
<code>\Ito</code>	Itô
<code>\Levy</code>	Lévy
<code>\Matern</code>	Matérn
<code>\Nystrom</code>	Nyström
<code>\Renyi</code>	Rényi
<code>\Schatten</code>	Schatten

8.8 Probability and statistics

Name	Syntax	Symbol
i.i.d.	<code>\iid</code>	i.i.d.
almost sure	<code>\as</code>	a.s.
almost everywhere	<code>\aev</code>	a.e.
convergence almost surely	<code>\convas</code>	$\xrightarrow{a.s.}$
convergence in probability	<code>\convp</code>	\xrightarrow{p}
convergence in distribution	<code>\convd</code>	\xrightarrow{d}
equality in distribution	<code>\eqd</code>	$\stackrel{d}{=}$
equality almost surely	<code>\eqas</code>	$\stackrel{a.s.}{=}$
probability	<code>\P</code>	\mathbb{P}
expectation	<code>\E</code>	\mathbb{E}
variance	<code>\var</code>	Var
covariance	<code>\cov</code>	Cov
correlation	<code>\cor</code>	Corr
support	<code>\supp</code>	supp
distributed as	<code>\dist</code>	\sim
distributed i.i.d.	<code>\distiid</code>	$\stackrel{iid}{\sim}$
distributed independently	<code>\distind</code>	$\stackrel{ind}{\sim}$
independent	<code>\indep</code>	\perp
Entropy	<code>\ent{q}</code>	$\mathcal{H}(q)$
KL divergence	<code>\kl{q}{p}, \kl[a]{q}{p}</code>	$D_{\text{KL}}(q p), D_{\text{KL}}^a(q p)$
Hellinger distance	<code>\hell{q}{p}, \hell[a]{q}{p}</code>	$D_{\text{H}}(q, p), D_{\text{H}}^a(q, p)$
Total variation distance	<code>\tvd{q}{p}, \tvd[a]{q}{p}</code>	$D_{\text{TV}}(q, p), D_{\text{TV}}^a(q, p)$

Name	Syntax	Symbol
Bernoulli	<code>\distBern</code>	Bern
beta	<code>\distBeta</code>	Beta
beta prime	<code>\distBetaPrime</code>	Beta'
binomial	<code>\distBinom</code>	Binom
categorical	<code>\distCat</code>	Categorical
Cauchy	<code>\distCauchy</code>	Cauchy
chi-squared	<code>\distChiSq</code>	χ^2
Dirichlet	<code>\distDir</code>	Dir
exponential	<code>\distExp</code>	Exp
gamma	<code>\distGam</code>	Gam
inverse gamma	<code>\distInvGam</code>	InvGam
geometric	<code>\distGeom</code>	Geom
Gumbel	<code>\distGum</code>	Gumbel
generalized extreme value	<code>\distGEV</code>	GEV
Laplace	<code>\distLap</code>	Lap
multinomial	<code>\distMulti</code>	Multi
normal	<code>\distNorm</code>	\mathcal{N}
Poisson	<code>\distPoiss</code>	Poiss
student-t	<code>\distT</code>	\mathcal{T}
uniform	<code>\distUnif</code>	Unif
von Mises-Fisher	<code>\distVMF</code>	vMF
Wishart	<code>\distWish</code>	\mathcal{W}
inverse Wishart	<code>\distInvWish</code>	\mathcal{IW}
Bernoulli process	<code>\distBeP</code>	BeP
beta process	<code>\distBP</code>	BP
beta prime process	<code>\distBPP</code>	BPP
Dirichlet process	<code>\distDP</code>	DP
Chinese restaurant process	<code>\distCRP</code>	CRP
completely random measure	<code>\distCRM</code>	CRM
normalized completely random measure	<code>\distNCRM</code>	NCRM
gamma process	<code>\distGamP</code>	Γ P
normalized gamma process	<code>\distNGamP</code>	N Γ P
Gaussian process	<code>\distGP</code>	GP
Pitman-Yor process	<code>\distPYP</code>	PY
Poisson process	<code>\distPP</code>	PP

8.9 Vector spaces and operators

Description	Syntax	Symbol
Norm	<code>\norm{\frac{x}{y}}</code>	$\ \frac{x}{y}\ $
Norm with subscript	<code>\normsub*{\frac{x}{y}}{2}</code>	$\left\ \frac{x}{y}\right\ _2$
Inner product	<code>\inner{\frac{x}{y}}{\frac{y}{z}}</code>	$\langle \frac{x}{y}, \frac{y}{z} \rangle$
Inner prod with subscript	<code>\innersub*{\frac{x}{y}}{z}{2}</code>	$\left\langle \frac{x}{y}, z \right\rangle_2$
L^p space	<code>\Lp{2}</code>	L^2
L^p space for specified measure	<code>\Lpm{2}{\mu}</code>	$L^2(\mu)$
	<code>\Lpm*{2}{\mu}</code>	$L^2(\mu)$
	<code>\Lpm[\Big]{2}{\mu}</code>	$L^2(\mu)$
L^p norm	<code>\Lpnorm{\Gamma}{2}</code>	$\ \Gamma\ _{L^2}$
	<code>\Lpnorm*{\Gamma}{2}</code>	$\ \Gamma\ _{L^2}$
	<code>\Lpnorm[\Big]{\Gamma}{2}</code>	$\left\ \Gamma\right\ _{L^2}$
L^p norm for specified measure	<code>\Lpmnorm{\Gamma}{2}{\mu}</code>	$\ \Gamma\ _{L^2(\mu)}$
	<code>\Lpmnorm*{\Gamma}{2}{\mu}</code>	$\ \Gamma\ _{L^2(\mu)}$
	<code>\Lpmnorm[\Big]{\Gamma}{2}{\mu}</code>	$\left\ \Gamma\right\ _{L^2(\mu)}$
L^p inner product	<code>\Lpinner{\Gamma}{\Gamma}{2}</code>	$\langle \Gamma, \Gamma \rangle_{L^2}$
	<code>\Lpinner*{\Gamma}{\Gamma}{2}</code>	$\langle \Gamma, \Gamma \rangle_{L^2}$
	<code>\Lpinner[\Big]{\Gamma}{\Gamma}{2}</code>	$\left\langle \Gamma, \Gamma \right\rangle_{L^2}$
L^p inner product for specified measure	<code>\Lpminner{\Gamma}{\Gamma}{2}{\mu}</code>	$\langle \Gamma, \Gamma \rangle_{L^2(\mu)}$
	<code>\Lpminner*{\Gamma}{\Gamma}{2}{\mu}</code>	$\langle \Gamma, \Gamma \rangle_{L^2(\mu)}$
	<code>\Lpminner[\big]{\Gamma}{\Gamma}{2}{\mu}</code>	$\langle \Gamma, \Gamma \rangle_{L^2(\mu)}$

8.10 Paired delimiters

Description	Example	Text style	Display style
Round brackets	<code>\rbra{\frac{x}{y}}</code>	$(\frac{x}{y})$	$(\frac{x}{y})$
Curly brackets	<code>\cbr{*}{\frac{x}{y}}</code>	$\{\frac{x}{y}\}$	$\{\frac{x}{y}\}$
Square brackets	<code>\sbra[\bigg]{\frac{x}{y}}</code>	$\left[\frac{x}{y}\right]$	$\left[\frac{x}{y}\right]$
Absolute value	<code>\abs{\frac{x}{y}}</code>	$ \frac{x}{y} $	$ \frac{x}{y} $
Set	<code>\set{\frac{x}{y}, \frac{y}{z}}</code>	$\{\frac{x}{y}, \frac{y}{z}\}$	$\{\frac{x}{y}, \frac{y}{z}\}$
Floor	<code>\floor{\frac{x}{y}}</code>	$\lfloor\frac{x}{y}\rfloor$	$\lfloor\frac{x}{y}\rfloor$
Ceiling	<code>\ceil{\frac{x}{y}}</code>	$\lceil\frac{x}{y}\rceil$	$\lceil\frac{x}{y}\rceil$
Cardinality	<code>\card{\s[h]A}</code>	$ \hat{A} $	$ \hat{A} $

9 Example Document

TODO: full shortex example