

## ▼ CHEM277B Homework 11

Trevor Oldham

Double-click (or enter) to edit

```
import numpy as np
import torch
```

### ▼ Process the MNIST data into np arrays

```
import pandas as pd

training_set, validation_set = pd.read_pickle('mnist.pkl')

#normalized the training data and reshape to shape (ndata, nfeatures)
normalized_train_set = tuple([z / 255 for z in training_set])
normalized_train_set_x = np.array(normalized_train_set[0])
normalized_train_set_x = normalized_train_set_x.reshape(60000, 1024)
print(normalized_train_set_x.shape)

train_set_y = np.array(training_set[1])
#print(normalized_train_set_y.shape)

#normalized the test data and reshape to shape (ndata, nfeatures)
normalized_test_set = tuple([z / 255 for z in validation_set])
normalized_test_set_x = np.array(normalized_test_set[0])
normalized_test_set_x = normalized_test_set_x.reshape(10000, 1024)
print(normalized_test_set_x.shape)

test_set_y = np.array(validation_set[1])

(60000, 1024)
(10000, 1024)
```

### ▼ Define Variational Autoencoder Model

```
from torch import nn
import torch.nn.functional as F

- .../ ...
```



```

def __init__(self, x_dim, h_dim1, h_dim2, z_dim):
    super(VAE, self).__init__()

    # encoder part
    self.fc1 = nn.Linear(x_dim, h_dim1)
    self.fc2 = nn.Linear(h_dim1, h_dim2)
    self.fc31 = nn.Linear(h_dim2, z_dim)
    self.fc32 = nn.Linear(h_dim2, z_dim)
    # decoder part
    self.fc4 = nn.Linear(z_dim, h_dim2)
    self.fc5 = nn.Linear(h_dim2, h_dim1)
    self.fc6 = nn.Linear(h_dim1, x_dim)

def encoder(self, x):
    h = F.relu(self.fc1(x))
    h = F.relu(self.fc2(h))
    return self.fc31(h), self.fc32(h) # mu, log_var

def bottleneck(self, mu, log_var):
    std = torch.exp(0.5*log_var)
    eps = torch.randn_like(std)
    return eps * std + mu # return z sampled

def decoder(self, z):
    h = F.relu(self.fc4(z))
    h = F.relu(self.fc5(h))
    return F.sigmoid(self.fc6(h))

def forward(self, x):
    mu, log_var = self.encoder(x)
    z = self.bottleneck(mu, log_var)
    return self.decoder(z), mu, log_var

```

```

vae = VAE(1024, 256, 128, 32)
print(vae)

```

```

VAE(
  (fc1): Linear(in_features=1024, out_features=256, bias=True)
  (fc2): Linear(in_features=256, out_features=128, bias=True)
  (fc31): Linear(in_features=128, out_features=32, bias=True)
  (fc32): Linear(in_features=128, out_features=32, bias=True)
  (fc4): Linear(in_features=32, out_features=128, bias=True)
  (fc5): Linear(in_features=128, out_features=256, bias=True)
  (fc6): Linear(in_features=256, out_features=1024, bias=True)
)

```

## Define Loss Function using Binary Cross Entropy Loss and KL Divergence

```
def loss_fn(recon_x, x, mu, logvar):
    BCE = F.binary_cross_entropy(recon_x, x, size_average=False)

    KLD = -0.5 * torch.mean(1 + logvar - mu.pow(2) - logvar.exp())

    return BCE + KLD
```

## Define timing **decorator** and helper functions

```
from functools import wraps
from time import time

def timing(f):
    @wraps(f)
    def wrap(*args, **kw):
        ts = time()
        result = f(*args, **kw)
        te = time()
        print('func:%r   took: %2.4f sec' % (f.__name__, te-ts))
        return result
    return wrap

def reconstruct(vae,data_gen):
    """given a VAE model, plot original data and reconstructed data from VAE"""
    inp = next(data_gen)[0]
    #print('Original Data:')
    #plot_digits(inp)
    with torch.no_grad():
        reconst,mu,log_var = vae(torch.tensor(inp,dtype=torch.float))

    #print('Reconstructed Data:')
    #plot_digits(reconst.detach().numpy())

def plot_digits(data):
    #plot 100 digit. data shape(100,32,32)
    fig, ax = plt.subplots(10, 10, figsize=(12, 12),
                           subplot_kw=dict(xticks=[], yticks=[]))
    fig.subplots_adjust(hspace=0.1, wspace=0.1)
    for i, axi in enumerate(ax.flat):
        im = axi.imshow(data[i].reshape(32, 32), cmap=plt.get_cmap('gray'))
        im.set_clim(0, 1)
```

## Define Trainer Class and Train/Validate function

```

import matplotlib.pyplot as plt
from torch.optim import SGD, Adam
import torch.nn.functional as F
import random
from tqdm import tqdm
import math
from sklearn.model_selection import train_test_split

def data_gen(X,y, batchsize):
    """
    Generator for data
    """
    for i in range(len(X)//batchsize):
        yield X[i*batchsize:(i+1)*batchsize],y[i*batchsize:(i+1)*batchsize]
        i+=1
    yield X[i*batchsize:],y[i*batchsize:]

class Trainer():
    def __init__(self, model, optimizer_type, learning_rate, epoch, batch_size, input_transform):
        """ The class for training the model
        model: nn.Module
            A pytorch model
        optimizer_type: 'adam' or 'sgd'
        learning_rate: float
        epoch: int
        batch_size: int
        input_transform: func
            transforming input. Can do reshape here
        """
        self.model = model
        if optimizer_type == "sgd":
            self.optimizer = SGD(model.parameters(), learning_rate, momentum=0.9)
        elif optimizer_type == "adam":
            self.optimizer = Adam(model.parameters(), learning_rate)
        elif optimizer_type == 'adam_l2':
            self.optimizer = Adam(model.parameters(), learning_rate, weight_decay=1)

        self.epoch = epoch
        self.batch_size = batch_size
        self.input_transform = input_transform

    @timing
    def train(self, inputs, outputs, val_inputs, val_outputs, draw_curve=False, early_stop=False):
        """ train self.model with specified arguments
        inputs: np.array, The shape of input_transform(input) should be (ndata,nfeat)
        outputs: np.array shape (ndata,)
        val_inputs: np.array, The shape of input_transform(val_input) should be (ndata,nfeat)
        val_outputs: np.array shape (ndata,)
        """

```

```

val_inputs: np.array, the shape of input_transform(val_input) should be (n_data, n_features)
val_outputs: np.array shape (n_data,)
early_stop: bool
l2: bool
silent: bool. Controls whether or not to print the train and val error during training
"""

inputs = self.input_transform(torch.tensor(inputs, dtype=torch.float))
outputs = torch.tensor(outputs, dtype=torch.int64)
val_inputs = self.input_transform(torch.tensor(val_inputs, dtype=torch.float))
val_outputs = torch.tensor(val_outputs, dtype=torch.int64)

losses = []
val_losses = []
weights = self.model.state_dict()
lowest_val_loss = np.inf

for n_epoch in tqdm(range(self.epoch), leave=False):
    self.model.train()
    #shuffle the data in each epoch
    idx = torch.randperm(inputs.size()[0])
    inputs=inputs[idx]
    outputs=outputs[idx]
    train_gen = data_gen(inputs,outputs,self.batch_size)

    epoch_loss = 0

    for batch_input,batch_output in train_gen:
        batch_importance = len(batch_output) / len(outputs)
        batch_predictions, mu, logvar = self.model(batch_input)
        loss = loss_fn(batch_predictions, batch_input, mu, logvar)
        if l2:
            l2_lambda = 1e-5
            l2_norm = sum(p.pow(2.0).sum() for p in self.model.parameters())
            loss = loss + l2_lambda * l2_norm
        self.optimizer.zero_grad()
        loss.backward()
        self.optimizer.step()
        epoch_loss += loss.detach().cpu().item() /self.batch_size * batch_importance

    val_loss = self.evaluate(val_inputs, val_outputs, print_loss=False)
    if n_epoch % 10 ==0 and not silent:
        print("Epoch %d/%d - Loss: %.3f " % (n_epoch + 1, self.epoch, epoch_loss))
        print("Val_loss: %.3f" % (val_loss))
    losses.append(epoch_loss)
    val_losses.append(val_loss)
    if early_stop:
        if val_loss < lowest_val_loss:
            lowest_val_loss = val_loss
            weights = self.model.state_dict()

if draw_curve:
    plt.figure()

```

```

        plt.plot(np.arange(self.epoch) + 1, losses, label='Training loss')
        plt.plot(np.arange(self.epoch) + 1, val_losses, label='Validation loss')
        plt.xlabel('Epochs')
        plt.ylabel('Loss')
        plt.legend()

    if early_stop:
        self.model.load_state_dict(weights)

    return {"losses": losses, "val_losses": val_losses}

def evaluate(self, inputs, outputs, print_loss=True):
    if torch.is_tensor(inputs):
        inputs = self.input_transform(inputs)
    else:
        inputs = self.input_transform(torch.tensor(inputs, dtype=torch.float))
        outputs = torch.tensor(outputs, dtype=torch.int64)
    self.model.eval()
    gen = data_gen(inputs, outputs, self.batch_size)
    losses = 0

    for batch_input, batch_output in gen:
        batch_importance = len(batch_output) / len(outputs)
        with torch.no_grad():
            batch_predictions, mu, logvar = self.model(batch_input)
            loss = loss_fn(batch_predictions, batch_input, mu, logvar)

        losses += loss.detach().cpu().item() / self.batch_size * batch_importance

    if print_loss:
        print("Loss: %.3f" % losses)
    return losses

from sklearn.model_selection import train_test_split, KFold
from torchsummary import summary
def train_model(model, Xs, ys, test_Xs, test_ys, epochs, draw_curve=True, early_stop=False):
    train_Xs, val_Xs, train_ys, val_ys = train_test_split(Xs, ys, test_size=1/3, random_state=42)
    model=model
    summary(model, input_shape[1:])

    print(f"{model} parameters:", sum([len(item.flatten()) for item in model.parameters()]))

    trainer = Trainer(model, optimizer, lr, epochs, batchsize, lambda x: x.reshape(-1))
    log=trainer.train(train_Xs, train_ys, val_Xs, val_ys, early_stop=early_stop, l2=l2)

    if draw_curve:
        plt.figure()
        plt.plot(log["losses"], label="losses")
        plt.plot(log["val_losses"], label="validation_losses")

```

```

plt.legend()
plt.title(f'loss')

# Report result for this fold
if early_stop:
    report_idx= np.argmin(log["val_losses"])
else:
    report_idx=-1
test_loss=trainer.evaluate(test_Xs,test_ys,print_loss=False)
print("Test loss:",test_loss)
return model

```

## Test the VAE model on MNIST training and test data

```

#normalized_train_set_x= normalized_train_set_x.reshape(-1, 1, 32, 32)
#normalized_test_set_x = normalized_test_set_x.reshape(-1, 1, 32, 32)

output = train_model(vae, Xs = normalized_train_set_x, ys = train_set_y, test_Xs =

```

Layer (type)	Output Shape	Param #
Linear-1	[-1, 256]	262,400
Linear-2	[-1, 128]	32,896
Linear-3	[-1, 32]	4,128
Linear-4	[-1, 32]	4,128
Linear-5	[-1, 128]	4,224
Linear-6	[-1, 256]	33,024
Linear-7	[-1, 1024]	263,168

Total params: 603,968

Trainable params: 603,968

Non-trainable params: 0

Input size (MB): 0.00

Forward/backward pass size (MB): 0.01

Params size (MB): 2.30

Estimated Total Size (MB): 2.32

VAE(

(fc1): Linear(in\_features=1024, out\_features=256, bias=True)

(fc2): Linear(in\_features=256, out\_features=128, bias=True)

(fc31): Linear(in\_features=128, out\_features=32, bias=True)

(fc32): Linear(in\_features=128, out\_features=32, bias=True)

(fc4): Linear(in\_features=32, out\_features=128, bias=True)

(fc5): Linear(in\_features=128, out\_features=256, bias=True)


(fc6): Linear(in\_features=256, out\_features=1024, bias=True)

) parameters: 603968

```

10%|█          | 1/10 [00:11<01:40, 11.14s/it]Epoch 1/10 - Loss: 128.490
      Val_loss: 112.476
func:'train' took: 89.7847 sec
Test loss: 76.08635925445559

```



```

def reconstruct_plot(vae,data_gen):
    """given a VAE model, plot original data and reconstructed data from VAE"""
    inp = next(data_gen)[0]
    print('Original Data:')
    plot_digits(inp)
    with torch.no_grad():
        reconst,mu,log_var = vae(torch.tensor(inp, dtype=torch.float))

    print('Reconstructed Data:')
    plot_digits(reconst.detach().numpy())

```

## Examine reconstructed images from test set of MNIST images

```

image = data_gen(normalized_test_set_x[0:100][:], test_set_y[0:100][:], 100)
#print(normalized_test_set_x[0:10][:].shape)
reconstruct_plot(vae, image)


```


Original Data:

Reconstructed Data:









Overall the model does improve over training and reaches a minimum around the end of 10

epochs. The training and validation curves minimize the Binary Cross Entropy loss during training, and the model is used to demonstrate that the reconstructed images are very similar to the images used as input to the model.

[Colab paid products](#) - [Cancel contracts here](#)