


UNC LAB: Error Analysis and Propagation Exercise

Revised April 06, 2006

Your Name: _____



This exercise is designed to help you understand error analysis and error propagation. You need to determine the area of the shaded region in the figure above; that is, the area of a triangle minus the area of a circle. If the triangle has a height, h , and width, w , and the circle has diameter d , then the shaded area is given by the formula $A = hw/2 - \pi d^2/4$.

Every measurement has an associated uncertainty. The uncertainties can be labeled with the symbol, δ , which indicates a small change in the associated quantity. The uncertainties of h , w , and d are given by δ_h , δ_w , and δ_d respectively.

Use a metric ruler to measure h , w , and d , estimate the uncertainties δ_h , δ_w , and δ_d in your measurements of each quantity and enter these values below, in cm. For your convenience, copy these values onto the other side of this page.

$\frac{\quad}{h} \pm \frac{\quad}{\delta_h} \text{ cm}$	$\frac{\quad}{w} \pm \frac{\quad}{\delta_w} \text{ cm}$	$\frac{\quad}{d} \pm \frac{\quad}{\delta_d} \text{ cm}$
---	---	---

Now calculate $A = hw/2 - \pi d^2/4 = \underline{\hspace{2cm}} \text{ cm}^2$

To estimate the *uncertainty* in A , δ_A , we need to *propagate* each individual contribution to the uncertainty (δ_h , δ_w , and δ_d) through the equation for A to find out how much each contributes to the uncertainty in A (*these terms are labeled as δ_{Ah} , δ_{Aw} , and δ_{Ad}*) and then add these contributions in quadrature $\delta_A = (\delta_{Ah}^2 + \delta_{Aw}^2 + \delta_{Ad}^2)^{1/2}$.

The first step is to determine δ_{Ah} , δ_{Aw} , and δ_{Ad} . This may be done by one of two methods. In the computational method, you calculate the change in A caused by substituting for each term, such as h , the value plus its estimated uncertainty, such as $h + \delta_h$ (or $h - \delta_h$). The derivative method has you calculate terms such as δ_{Ah} using the idea that any small change in A due to a small change in h is given by the derivative of A with respect to h , treating all the other terms such as w and d as constants. This is properly called a *partial derivative* and uses the symbol ∂ as in $\frac{\partial A}{\partial h}$ rather than $\frac{dA}{dh}$. Once you know how A changes as a function of h , you can simply multiply this by the estimated uncertainty in h , δ_h , to find $\delta_{Ah} = |\partial A / \partial h| \delta_h$.

Now, for some practice in error propagation, fill in each of the blanks on the other side of this page.

COMPUTATIONAL METHOD

$$\delta_{Ah} = |(hw/2 - \pi d^2/4) - ((h + \delta_h)w/2 - \pi d^2/4)| = \{ \text{this simplifies to } \delta_h w/2 \} = \underline{\hspace{2cm}} \underline{\hspace{2cm}}$$

(units)

$$\delta_{Aw} = |(hw/2 - \pi d^2/4) - \underline{\hspace{4cm}}| = \underline{\hspace{2cm}} \underline{\hspace{2cm}}$$

$$\delta_{Ad} = |(hw/2 - \pi d^2/4) - \underline{\hspace{4cm}}| = \underline{\hspace{2cm}} \underline{\hspace{2cm}}$$

$$\delta_A = (\delta_{Ah}^2 + \delta_{Aw}^2 + \delta_{Ad}^2)^{1/2} = \underline{\hspace{2cm}} \underline{\hspace{2cm}}$$

You should quote your value for A in the form $A \pm \delta_A$ (units): $\underline{\hspace{2cm}} \pm \underline{\hspace{2cm}}$
(δ_A is normally given with one or at most two significant figures while the most significant figure in the value of A should be determined from δ_A , as in $A = 3.65 \pm 0.03 \text{ cm}^2$. See Appendix V, Section D.)

DERIVATIVE METHOD

(Optional for P115 students)

$$\delta_{Ah} = \left| \frac{\partial A}{\partial h} \right| \delta_h = \left| \frac{\partial}{\partial h} \left(\frac{hw}{2} - \frac{\pi d^2}{4} \right) \right| \delta_h = \frac{\delta_h w}{2} = \underline{\hspace{2cm}} \underline{\hspace{2cm}}$$

(units)

$$\delta_{Aw} = \left| \frac{\partial A}{\partial w} \right| \delta_w = \left| \frac{\partial}{\partial w} \left(\frac{hw}{2} - \frac{\pi d^2}{4} \right) \right| \delta_w = \underline{\hspace{2cm}} = \underline{\hspace{2cm}}$$

$$\delta_{Ad} = \left| \frac{\partial A}{\partial d} \right| \delta_d = \underline{\hspace{2cm}} = \underline{\hspace{2cm}} = \underline{\hspace{2cm}}$$

$$\delta_A = \sqrt{\delta_{Ah}^2 + \delta_{Aw}^2 + \delta_{Ad}^2} = \underline{\hspace{2cm}} \underline{\hspace{2cm}}$$

$$A = \underline{\hspace{2cm}} \pm \underline{\hspace{2cm}}$$

You should find that the computational and derivative methods give similar results.

GRADE: $\underline{\hspace{2cm}}$
(out of 10 points)

GRADED BY $\underline{\hspace{2cm}}$
(TA's initials)