Final Report

Trey Dufrene, Alan Wallingford, David Orcutt, Ryan Warner, Zack Johnson

ME 407

Preliminary Design of Robotic Systems

Embry-Riddle Aeronautical University

Contents

List of Figures

List of Tables

1 Introduction

2 Requirements

3 Conceptual Design

4 Specifications

5 Preliminary Design

5.1 CAD

5.2 Forward Kinematics

5.3 Velocity Kinematics

5.4 Inverse Kinematics

5.5 Equations of Motion

5.6 Open-Loop Simulation

5.7 Control System

5.8 Closed-Loop Simulation

5.9 ANSYS

5.10 Electrical Schematic

5.11 Software Flowchart

5.12 Project Status and Future

5.13 Parts List



Figure 1: Coordinate Systems

Given the lengths of each of the manipulator links,

$$
{}^{I}_{B}r_1 = \begin{bmatrix} 0 \\ 0 \\ \ell_b \end{bmatrix} \quad {}^{1}_{1}r_2 = \begin{bmatrix} 0 \\ 0 \\ \ell_1 \end{bmatrix} \quad {}^{2}_{2}r_3 = \begin{bmatrix} 0 \\ \ell_2 \\ 0 \end{bmatrix} \quad {}^{3}_{3}r_4 = \begin{bmatrix} 0 \\ \ell_3 \\ 0 \end{bmatrix} \quad {}^{4}_{4}r_5 = \begin{bmatrix} 0 \\ \ell_4 \\ 0 \end{bmatrix} \quad {}^{5}_{5}r_6 = \begin{bmatrix} 0 \\ \ell_5 \\ 0 \end{bmatrix}
$$

The position of each link relative to the inertial frame is given as:

$$
{}^{I}_{B}r_1 = \begin{bmatrix} 0 \\ 0 \\ \ell_b \end{bmatrix} \quad {}^{I}_{B}r_2 = \begin{bmatrix} 0 \\ 0 \\ \ell_b + \ell_1 \end{bmatrix} \quad {}^{I}_{B}r_3 = \begin{bmatrix} -\ell_2 c_{\theta_2} s_{\theta_1} \\ \ell_2 c_{\theta_{12}} \\ \ell_b + \ell_1 + \ell_2 s_{\theta_2} \end{bmatrix} \quad {}^{I}_{B}r_4 = \begin{bmatrix} -s_{\theta_1}(\ell_3 c_{\theta_{23}} + \ell_2 c_{\theta_2}) \\ c_{\theta_1}(\ell_3 c_{\theta_{23}} + \ell_2 c_{\theta_2}) \\ \ell_1 + \ell_b + \ell_3 s_{\theta_{23}} + \ell_2 s_{\theta_2} \end{bmatrix}
$$

$$
{}^{I}_{B}r_5 = \begin{bmatrix} -s_{\theta_1}(\ell_3 c_{\theta_{23}} + \ell_4 c_{\theta_{23}} + \ell_2 c_{\theta_2}) \\ c_{\theta_1}(\ell_3 c_{\theta_{23}} + \ell_4 c_{\theta_{23}} + \ell_2 c_{\theta_2}) \\ \ell_1 + \ell_b + \ell_3 s_{\theta_{23}} + \ell_4 s_{\theta_{23}} + \ell_2 s_{\theta_2} \end{bmatrix}
$$

$$
{}^{I}_{B}r_6 = \begin{bmatrix} \begin{array}{l} \ell_5 c_{\theta_1} s_{\theta_4} s_{\theta_5} - \ell_4 c_{\theta_{23}} s_{\theta_1} - \ell_2 c_{\theta_2} s_{\theta_1} - \ell_5 c_{\theta_{23}} c_{\theta_5} s_{\theta_1} - \ell_3 c_{\theta_{23}} s_{\theta_1} \\ \qquad + \ell_5 c_{\theta_2} c_{\theta_4} s_{\theta_1} s_{\theta_3} s_{\theta_5} + \ell_5 c_{\theta_3} c_{\theta_4} s_{\theta_1} s_{\theta_2} s_{\theta_5} \\ \ell_5(s_{\theta_5}(s_{\theta_1} s_{\theta_4} - c_{\theta_4}(c_{\theta_1} c_{\theta_2} s_{\theta_3} + c_{\theta_1} c_{\theta_3} s_{\theta_2})) - c_{\theta_5}(c_{\theta_1} s_{\theta_2} s_{\theta_3} - c_{\theta_1} c_{\theta_2} c_{\theta_3})) \\ \qquad - \ell_3(c_{\theta_1} s_{\theta_2} s_{\theta_3} - c_{\theta_1} c_{\theta_2} c_{\theta_3}) - \ell_4(c_{\theta_1} s_{\theta_2} s_{\theta_3} - c_{\theta_1} c_{\theta_2} c_{\theta_3}) + \ell_2 c_{\theta_1} c_{\theta_2} \\ \ell_1 + \ell_b + \ell_3 s_{\theta_{23}} + \ell_4 s_{\theta_{23}} + \ell_2 s_{\theta_2} + \dfrac{\ell_5 c_{\theta_{23}} s_{\theta_{45}}}{2} + \ell_5 s_{\theta_{23}} c_{\theta_5} - \dfrac{\ell_5 s_{\theta_4 - \theta_5} c_{\theta_{23}}}{2} \end{array} \end{bmatrix}
$$

The orientation of each link with respect to the inertial frame is given as:

$$rotz(\theta_1)\ rotx(\theta_2)\ rotx(\theta_3)\ roty(\theta_4)\ rotx(\theta_5)\ roty(\theta_6)$$

$$^{I}T_1 = \begin{bmatrix} c_{\theta_1} & -s_{\theta_1} & 0 \\ s_{\theta_1} & c_{\theta_1} & 0 \\ 0 & 0 & 1 \end{bmatrix} \quad ^{I}T_2 = \begin{bmatrix} c_{\theta_1} & -c_{\theta_2} s_{\theta_1} & s_{\theta_1} s_{\theta_2} \\ s_{\theta_1} & c_{\theta_1} c_{\theta_2} & -c_{\theta_1} s_{\theta_2} \\ 0 & s_{\theta_2} & c_{\theta_2} \end{bmatrix} \qquad ^{I}T_3 = \begin{bmatrix} c_{\theta_1} & -c_{\theta_{23}} s_{\theta_1} & s_{\theta_{23}} s_{\theta_1} \\ s_{\theta_1} & c_{\theta_{23}} c_{\theta_1} & -s_{\theta_{23}} c_{\theta_1} \\ 0 & s_{\theta_{23}} & c_{\theta_{23}} \end{bmatrix}$$

$$^{I}T_4 = \begin{bmatrix} c_{\theta_1} c_{\theta_4} - s_{\theta_{23}} s_{\theta_1} s_{\theta_4} & -c_{\theta_{23}} s_{\theta_1} & c_{\theta_1} s_{\theta_4} + s_{\theta_{23}} c_{\theta_4} s_{\theta_1} \\ c_{\theta_4} s_{\theta_1} + s_{\theta_{23}} c_{\theta_1} s_{\theta_4} & c_{\theta_{23}} c_{\theta_1} & s_{\theta_1} s_{\theta_4} - s_{\theta_{23}} c_{\theta_1} c_{\theta_4} \\ -c_{\theta_{23}} s_{\theta_4} & s_{\theta_{23}} & c_{\theta_{23}} c_{\theta_4} \end{bmatrix}$$

$$^{I}T_5 = \begin{bmatrix} c_{\theta_1} c_{\theta_4} - s_{\theta_{23}} s_{\theta_1} s_{\theta_4} & s_{\theta_5}(c_{\theta_1} s_{\theta_4} + s_{\theta_{23}} c_{\theta_4} s_{\theta_1}) - c_{\theta_{23}} c_{\theta_5} s_{\theta_1} & c_{\theta_5}(c_{\theta_1} s_{\theta_4} + s_{\theta_{23}} c_{\theta_4} s_{\theta_1}) + c_{\theta_{23}} s_{\theta_1} s_{\theta_5} \\ c_{\theta_4} s_{\theta_1} + s_{\theta_{23}} c_{\theta_1} s_{\theta_4} & s_{\theta_5}(s_{\theta_1} s_{\theta_4} - s_{\theta_{23}} c_{\theta_1} c_{\theta_4}) + c_{\theta_{23}} c_{\theta_1} c_{\theta_5} & c_{\theta_5}(s_{\theta_1} s_{\theta_4} - s_{\theta_{23}} c_{\theta_1} c_{\theta_4}) - c_{\theta_{23}} c_{\theta_1} s_{\theta_5} \\ -c_{\theta_{23}} s_{\theta_4} & s_{\theta_{23}} c_{\theta_5} + c_{\theta_{23}} c_{\theta_4} s_{\theta_5} & c_{\theta_{23}} c_{\theta_4} c_{\theta_5} - s_{\theta_{23}} s_{\theta_5} \end{bmatrix}$$

$$^{I}T_6 = \begin{bmatrix} ^{I}T_{6(1,1)} & ^{I}T_{6(1,2)} & ^{I}T_{6(1,3)} \\ ^{I}T_{6(2,1)} & ^{I}T_{6(2,2)} & ^{I}T_{6(2,3)} \\ ^{I}T_{6(3,1)} & ^{I}T_{6(3,2)} & ^{I}T_{6(3,3)} \end{bmatrix}$$

$$\begin{aligned}
^{I}T_{6(1,1)} &= c_{\theta_6}(c_{\theta_1} c_{\theta_4} - s_{\theta_{23}} s_{\theta_1} s_{\theta_4}) - s_{\theta_6}(c_{\theta_5}(c_{\theta_1} s_{\theta_4} + s_{\theta_{23}} c_{\theta_4} s_{\theta_1}) + c_{\theta_{23}} s_{\theta_1} s_{\theta_5}) \\
^{I}T_{6(1,2)} &= s_{\theta_5}(c_{\theta_1} s_{\theta_4} + s_{\theta_{23}} c_{\theta_4} s_{\theta_1}) - c_{\theta_{23}} c_{\theta_5} s_{\theta_1} \\
^{I}T_{6(1,3)} &= c_{\theta_6}(c_{\theta_5}(c_{\theta_1} s_{\theta_4} + s_{\theta_{23}} c_{\theta_4} s_{\theta_1}) + c_{\theta_{23}} s_{\theta_1} s_{\theta_5}) + s_{\theta_6}(c_{\theta_1} c_{\theta_4} - s_{\theta_{23}} s_{\theta_1} s_{\theta_4}) \\
^{I}T_{6(2,1)} &= c_{\theta_6}(c_{\theta_4} s_{\theta_1} + s_{\theta_{23}} c_{\theta_1} s_{\theta_4}) - s_{\theta_6}(c_{\theta_5}(s_{\theta_1} s_{\theta_4} - s_{\theta_{23}} c_{\theta_1} c_{\theta_4}) - c_{\theta_{23}} c_{\theta_1} s_{\theta_5}) \\
^{I}T_{6(2,2)} &= s_{\theta_5}(s_{\theta_1} s_{\theta_4} - s_{\theta_{23}} c_{\theta_1} c_{\theta_4}) + c_{\theta_{23}} c_{\theta_1} c_{\theta_5} \\
^{I}T_{6(2,3)} &= s_{\theta_6}(c_{\theta_4} s_{\theta_1} + s_{\theta_{23}} c_{\theta_1} s_{\theta_4}) + c_{\theta_6}(c_{\theta_5}(s_{\theta_1} s_{\theta_4} - s_{\theta_{23}} c_{\theta_1} c_{\theta_4}) - c_{\theta_{23}} c_{\theta_1} s_{\theta_5}) \\
^{I}T_{6(3,1)} &= s_{\theta_6}(s_{\theta_{23}} s_{\theta_5} - c_{\theta_{23}} c_{\theta_4} c_{\theta_5}) - c_{\theta_{23}} c_{\theta_6} s_{\theta_4} \\
^{I}T_{6(3,2)} &= s_{\theta_{23}} c_{\theta_5} + c_{\theta_{23}} c_{\theta_4} s_{\theta_5} \\
^{I}T_{6(3,3)} &= c_{\theta_6}(s_{\theta_{23}} s_{\theta_5} - c_{\theta_{23}} c_{\theta_4} c_{\theta_5}) - c_{\theta_{23}} s_{\theta_4} s_{\theta_6}
\end{aligned}$$

Given robot dynamics described by $H(\gamma)\ddot{\gamma} + n(\gamma, \dot{\gamma}) = \tau$, the torque, τ, provided by the servo motors is necessary to solve the closed loop dynamics of the system. Assuming the servo is driven by a D.C. motor with proportional derivative control,

$$\tau_a = Ki_a = J_a\ddot{\theta}_a + b_a\dot{\theta}_a + \tau_L \tag{1}$$

Where τ_a is the actuator torque, K is the back-EMF constant, i_a is the motor current, J_a is the armature inertia, θ_a, $\dot{\theta}_a, \ddot{\theta}_a$ is the motor position and it's first and second time derivatives, respectively, b_a is the viscous friction coefficient, and τ_L is the torque available for the actuator to do work. The basic equation for a motor is known to be:

$$V_a = i_aR_a + K\dot{\theta}_a \tag{2}$$

Where V_a is the voltage applied to the actuator and R_a is the armature resistance. Given a gearbox with in/out ratio N and efficiency η,



The motor equation (1) can be expressed in the output coordinates:

$$Ki_a = J_aN\ddot{\theta} + b_aN\dot{\theta} + \frac{\tau}{N\eta}$$

Substituing into equation (2) and solving for i_a:

$$i_a = \frac{J_aN}{K}\ddot{\theta} + b_aN\dot{\theta} + \frac{\tau}{N\eta}$$

$$V_a = \frac{R_aJ_aN}{K}\ddot{\theta} + \frac{R_ab_aN}{K}\dot{\theta} + \frac{R_a}{KN\eta}\tau + KN\dot{\theta} \tag{3}$$

Assuming P.D. control, $V_a = K_p(\theta - \theta_d) + K_d\dot{\theta}$, where θ_d is the desired orientation of the actuator, the following solution is found by setting the P.D. solution equal to (3). After collecting like terms:

$$\frac{R_aJ_aN}{K}\ddot{\theta} + \left(\frac{R_aJ_aN}{K} - K_d + KN\right)\dot{\theta} - K_p\theta = -K_p\theta_d - \frac{R_a}{KN\eta}\tau \tag{4}$$

The following parameters of the system can be obtained by applying a step input to the system with $\tau = 0$ and measuring the characteristics of it's response. Denoting ζ as the damping ratio and ω_n as the natural frequency of the system,

$$\%\text{ Overshoot} = \left(\frac{\theta_{max} - \theta_{ss}}{\theta_{ss}}\right) \times 100 \ , \quad \zeta = \frac{-\ln(\%\text{OS}/100)}{\sqrt{\pi^2 + \ln^2(\%\text{OS}/100)}} \ , \quad \omega_n = \frac{\pi}{T_p\sqrt{1-\zeta^2}}$$

Given θ_{max}, θ_{ss}, and T_p as measured parameters of the system's max output, steady state, and time to peak, respectively.

Refactoring equation (4) and equating with the general solution for a second order system given by $\ddot{\theta} + 2\zeta\omega_n\dot{\theta} + \omega_n^2\theta = \omega_n^2\theta_d$,

$$2\zeta\omega_n = \frac{b_a}{J_a} - \frac{KK_d}{R_aJ_aN} + \frac{K^2}{R_aJ_a} \ , \quad \omega_n^2 = \frac{-KK_p}{R_aJ_aN} \tag{5}$$

Performing a similar experiment as previously described, except with a known inertial load $\tau = J_m\ddot{\theta}$, the following parameters can be found:

$$\alpha_m \equiv 2\zeta\omega_n = \frac{R_ab_aN^2\eta - KK_dN\eta + K^2N^2\eta}{R_aJ_aN^2\eta + R_aJ_m} \ , \quad \beta_m \equiv \omega_n = -\frac{KK_pN\eta}{R_aJ_aN^2\eta + R_aJ_m} \tag{6}$$

$$\begin{bmatrix} 1 & -(\alpha_1J_1 + \beta_1J_1) \\ 1 & -(\alpha_2J_2 + \beta_2J_2) \\ \vdots & \vdots \end{bmatrix} \begin{bmatrix} \dfrac{R_ab_aN^2\eta - KK_dN\eta + K^2N^2\eta - KK_pN\eta}{R_aJ_aN^2\eta} \\ \\ \dfrac{1}{J_aN^2\eta} \end{bmatrix} = \begin{bmatrix} \alpha_1 + \beta_1 \\ \alpha_2 + \beta_2 \\ \vdots \end{bmatrix} \tag{7}$$

Finally, with multiple datasets (varying inertial loads, J_m) the coefficients of the second order system equation can be found using the least squares solution of (7).

Acknowledgements & Attributions

We would like to acknowledge the following people for their contibutions to creating this report?

— Dr. Isenberg

I Appendix

i Drawings

ii Salient Code