

Search Results

SEARCH:

Futaba S3010 Standard High-Torque BB Servo

Stock Number	FUTM0043
Manufacturer Number	S3010
Accessories Needed	Parts Listing



Notes from the Tech Department

This is the Futaba Standard Size Ball Bearing High Torque Servo.

This servo can produce high-current draw from your batteries.
If using NiMH or NiCd batteries, make sure they are capable of delivering approximately 2A for each servo.

FEATURES: Ideal for high-torque applications requiring a standard size servo
Universal connector fits Futaba, Hitec, JR, KO Propo, Airtronics Z, and Tower Hobbies. Does not fit old Airtronics A plug w/out adapter
Nylon gears
One bearing pre-mounted on output shaft.
One year warranty

INCLUDES: One Futaba standard size high torque servo with;
One 1.4" (35mm) diameter round servo wheel
One 1.5" (39mm) diameter 4 point servo wheel
One 1.25" (32mm) diameter 6 point servo wheel
Four 2mm x 11mm phillips screws
Four rubber grommets & Four metal eyelets

REQUIRES: Small phillips screwdriver to mount to surface

SPECS: Speed: 0.20 sec/60° @ 4.8V
0.16 sec/60° @ 6.0V
Torque: 72 oz-in (5.2 kg-cm) @ 4.8V and
90 oz-in (6.5 kg-cm) @ 6V
Dimensions: 1.6 x 0.8 x 1.5" (1-9/16 x 13/16 x 1-1/2")
(40 x 20 x 38mm)
Weight: 1.5oz (1-7/16oz) (41g)

jxs 5/14/03
ir/jxs
updt jxs 9/29/03
jxs 10/29/04

[< < Go Back](#)

[Manuals](#) | [Team Futaba](#) | [Futaba Store](#) | [Contact Us](#) | [Team Tips](#) | [Multimedia](#)
[Software Updates](#) | [Downloads](#) | [News](#) | [Promotions](#) | [Find a Dealer](#) | [Air Events](#) | [Surface Events](#)

© 1997-2017 Hobbico, Inc. All rights reserved. Terms of Use

NEWSLETTER
Sign up today!



HOBBICO