



# Protocol Audit Report

Version 1.0

*Treylon Wofford*

June 5, 2024

# Protocol Audit Report

Treylon Wofford

June 3, 2024

Prepared by: Treylon Wofford Lead Auditors: - Treylon Wofford

## Table of Contents

- Table of Contents
- Protocol Summary
- Disclaimer
- Risk Classification
- Audit Details
  - Scope
  - Roles
- Executive Summary
  - Issues found
- Findings
  - High
    - \* [H-1] String the `PasswordStore::getPassword` on-chain makes it visible to anyone and no longer private
    - \* [H-2] `PasswordStore::setPassword` has no access controls, meaning a non-owner could change the password
  - Informational
    - \* [I-1] The `PasswordStore::getPassword` natspec indicates a parameter that doesn't exist, causing the natspec to be incorrect

## Protocol Summary

A smart contract applicatoin for storing a password. Users should be able to store a password and then retrieve it later. Others should not be able to access the password.

## Disclaimer

Treylon Wofford makes all effort to find as many vulnerabilities in the code in the given time period, but holds no responsibilities for the findings provided in this document. A security audit by the team is not an endorsement of the underlying business or product. The audit was time-boxed and the review of the code was solely on the security aspects of the Solidity implementation of the contracts.

## Risk Classification

		Impact		
		High	Medium	Low
Likelihood	High	H	H/M	M
	Medium	H/M	M	M/L
	Low	M	M/L	L

We use the CodeHawks severity matrix to determine severity. See the documentation for more details.

## Audit Details

The findings decribed in this doucment correspond the following commit hash:

```
1 2e8f81e263b3a9d18fab4fb5c46805ffc10a9990
```

## Scope

```
1 ./src/
2 #--PasswordStore.sol
```

## Roles

Owner: The user who can set the password and read the password. Outsiders: No one else should be able to set or read the password. # Executive Summary ## Issues found

Sevterity	Number of Issues found
High	2
Medium	0
Low	0
Info	1
Total	3

## Findings

### High

#### [H-1] String the PasswordStore::getPassword on-chain makes it visable to anyone and no longer private

**Description:** All data stored on-chain is visible to anyone, and can be read directly from the blockchain. The `PasswordStore::s_password` variable is intended to be a private variable and only accessed through the `PasswordStore::getPassword` function, which is intended to only called by the owner of the contract.

We show one such method of reading any data off chain below.

**Impact:** Anyone can read the private password, severely breaking the functionality of the protocol.

**Proof of Concept:**(Proof of code) The below test case shows how anyone can read the password directly from the blockchain.

1. Create a locally running chain

```
1 make anvil
```

2. Deploy the contract to the chain

```
1 make deploy
```

### 3. Run the storage tool

we use 1 because that's the storage slot of s\_password in the contract.

```
1 cast storage <ADDRESS_HERE> 1 --rpc-url http://127.0.0.1:8545
```

You'll get an output that looks like this: 0x6d7950617373776f726400000000000000000000000000000000

You can then parse that hex to a string with:

[illegible]

And get an output of:

```
1 myPassword
```

**Recommended Mitigation:** Due to this, the overall architecture of the contract should be rethought. One could encrypt the password off-chain, and then store the encrypted password on-chain. This would require the user to remember another password on-chain to decrypt the password. However, you'd also likely want to remove the view function as you wouldn't want the user to accidentally send a transaction with the password that decrypts your password.

## [H-2] PasswordStore::setPassword has no access controls, meaning a non-owner could change the password

**Description:** The `PasswordStore::setPassword` function is set to be an `external` function, however, the natspec of the function and overall purpose of the smart contract is that `This function allows only the owner to set a new password.`

```
1     function setPassword(string memory newPassword) external {
2 @>         // @audit - There are no access controls
3             s_password = newPassword;
4             emit SetNetPassword();
5     }
```

**Impact:** Anyone can set/change the password of the contract, severely breaking the contract intended functionality.

**Proof of Concept:** Add the following to the `PasswordStore.t.sol` test file.

Code

```
1 function test_anyone_can_set_password(address randomAddress) public
```

```
2      vm.assume(randomAddress != owner);
3      vm.prank(randomAddress);
4      string memory expectedPassword = "myNewPassword";
5      passwordStore.setPassword(expectedPassword);
6
7      vm.prank(owner);
8      string memory actualPassword = passwordStore.getPassword();
9      assertEq(actualPassword, expectedPassword);
10 }
```

**Recommended Mitigation:** Add an access control conditional to the `setPassword` function.

```
1  if(msg.sender != s_owner){
2      revert PasswordStore__NotOwner();
3  }
```

## Informational

**[I-1] The PasswordStore::getPassword natspec indicates a parameter that doesn't exist, causing the natspec to be incorrect**

### Description:

```
1  //@notice This allows only the owner to retrieve the password.
2  @> //@param newPassword The new password to set.
3  function getPassword() external view returns (string memory) {
```

The `PasswordStore::getPassword` function signature is `getPassword()` which the natspec says it should be `getPassword(string)`.

**Impact:** The natspec is incorrect

**Recommended Mitigation:** Remove the incorrect natspec line.

```
1  -      * @param newPassword The new password to set.
```