

Use Case - Run Weekly Accounting Procedure

Context - Executes the main accounting batch procedure automatically at Friday midnight (or manually when requested by a ChocAn Manager) to process the week's record of services provided, calculate total fees, and generate all required financial files and reports.

Actors -

- ChocAn Manager (Secondary triggers manual on-demand execution)

Main Success Scenario -

1. The ChocAn Manager initiates the main accounting batch procedure from the manager's terminal.

1.1 Alternatively, the system automatically triggers the procedure at midnight on Friday.

2. The system opens and reads the week's file of recorded service transactions.

3. For each transaction, the system parses the stored fields:

3.1. Current date and time (MM-DD-YYYY HH:MM:SS)

3.2. Date service was provided (MM-DD-YYYY)

3.3. Provider number (9 digits)

3.4. Member number (9 digits)

3.5. Service code (6 digits)

3.6. Comments (optional, up to 100 characters)

4. The system aggregates and sorts all service data by member, provider, and overall totals

5. The system automatically executes the sub-use cases to output all required files:

5.1. Generate a member report for each active member who received services.

5.2. Generate a provider report for each provider who billed ChocAn.

5.3. Generate a Summary Report for the Accounts Payable manager.

5.4. Generate an EFT Record containing bank transfer amounts.

6. The system displays/logs a completion status message indicating that accounting processing for the week is complete.

Extensions

1a. The process crashes or fails to complete mid-run:

1a.1. The ChocAn Manager manually re-runs the procedure from the terminal keyboard/screen interface.

2a. The weekly service transactions file is empty or missing:

2a.1. The system generates an error log stating "No service data found for the specified period".

2a.2. The system exits without generating individual member/provider reports.

3a. Corrupted or invalid record formatting in the transaction file:

3a.1. The system logs the corrupted record details to an error log file.

3a.2. The system skips the invalid record and continues processing the remaining valid records.

Use Case - Generate Member Report

Context - Generates an individual report file for every member who received health care services during the past week, formatted according to ChocAn report guidelines and saved locally to simulate an email attachment.

Actors -

- ChocAn Manager (Secondary triggers when manually running accounting or on-demand reports)

Main Success Scenario -

1. The system reads the processed weekly service records to group transactions by Member Number.
2. For each member who consulted a provider during the week, the system creates a new text file named with the member's name followed by the report date
3. The system writes the member's header information to the file:
 - 3.1. Member Name (25 characters)
 - 3.2. Member Number (9 digits)
 - 3.3. Member Street Address (25 characters)
 - 3.4. Member City (14 characters)
 - 3.5. Member State (2 letters)
 - 3.6. Member ZIP Code (5 digits)
4. The system sorts all services received by the member in chronological order of service date (MM-DD-YYYY).
5. For each service provided to the member, the system writes:
 - 5.1. Date of service (MM-DD-YYYY)
 - 5.2. Provider name (25 characters)
 - 5.3. Service name (20 characters)
6. The system saves and closes the report file.

Extensions

- 1a. Member received no services during the current week:
 - 1a.1. The system skips generating a report file for this member.
- 3a. Member address data or a required field is missing from records:
 - 3a.1. The system inserts a placeholder ("N/A") for the missing field and logs a warning in the system log.
 - 3a.2. The system completes file generation.

Use Case - Generate Provider Report

Context - Generates a detailed summary report file for each health care provider who billed ChocAn during the week, detailing consultations and calculating total fee payouts.

Actors -

- ChocAn Manager (Secondary triggers when manually running accounting or on-demand reports)

Main Success Scenario -

1. The system reads the weekly service data and groups records by Provider Number.
2. For each provider who billed ChocAn during the week, the system opens a new text file named using the provider's name and report date.
3. The system writes the provider's header information:
 - 3.1. Provider Name (25 characters)
 - 3.2. Provider Number (9 digits)
 - 3.3. Provider Street Address (25 characters)
 - 3.4. Provider City (14 characters)

- 3.5. Provider State (2 letters)
- 3.6. Provider ZIP Code (5 digits)
- 4. The system lists each service provided in the order the computer received the data:
 - 4.1. Date of service (MM-DD-YYYY)
 - 4.2. Date and time data were received by the computer (MM-DD-YYYY HH:MM:SS)
 - 4.3. Member name (25 characters)
 - 4.4. Member number (9 digits)
 - 4.5. Service code (6 digits)
 - 4.6. Fee to be paid (up to \$999.99)
- 5. The system calculates and writes the summary section at the end of the report:
 - 5.1. Total number of consultations with members (3 digits)
 - 5.2. Total fee for the week (up to \$99,999.99)
- 6. The system saves and closes the report file.

Extensions

- 1a. Provider did not bill ChocAn during the week:
 - 1a.1. The system skips generating a report file for that provider.
- 5a. Provider's total calculated fee exceeds \$99,999.99:
 - 5a.1. The system caps/flags the overflow value in the report and flags the account for manager review in the error log.

Use Case - Generate EFT Record

Context - Creates an Electronic Funds Transfer (EFT) data file on disk containing provider payment details so banking systems can credit provider accounts.

Actors -

- ChocAn Manager (Secondary triggers when manually running accounting or on-demand reports)

Main Success Scenario -

- 1. The system identifies all providers who are due payment for services billed during the week.
- 2. The system creates or overwrites the standard EFT data file on disk.
- 3. For each payable provider, the system writes an EFT record line consisting of:
 - 3.1. Provider Name (25 characters)
 - 3.2. Provider Number (9 digits)
 - 3.3. Amount to be transferred (total fee calculated for the week)
- 4. The system saves the file to disk for external banking computers to access.

Extensions

- 1a. No providers billed ChocAn during the week:
 - 1a.1. The system creates an empty EFT file with a header stating "No transfers scheduled" and exits.
- 3a. A disk write error or permission issue occurs while creating the file:
 - 3a.1. The system displays an error on the screen/log stating "EFT file creation failed."
 - 3a.2. The system alerts the manager to re-run the procedure or check system storage.

Use Case - Generate Summary Report

Context - Produces an aggregate Accounts Payable summary report detailing all providers to be paid, consultation totals, and total financial outlay across the entire organization.

Actors -

- ChocAn Manager (Secondary triggers when manually running accounting or on-demand reports)

Main Success Scenario -

1. The system processes the complete set of weekly service transactions.
2. The system creates a new summary report file formatted for the Accounts Payable manager.
3. The system lists every provider to be paid that week, including:
 - 3.1. Provider Name
 - 3.2. Number of consultations provided by that provider
 - 3.3. Total fee owed to that provider for the week
4. The system calculates and appends the grand totals at the end of the report:
 - 4.1. Total number of providers who provided services
 - 4.2. Total number of consultations across all providers
 - 4.3. Overall fee total to be paid by ChocAn
5. The system outputs/saves the file for manager review.

Extensions

- 3a. No transactions occurred during the entire week:
 - 3a.1. The system generates a summary report with all totals set to zero (0 providers, 0 consultations, \$0.00 total fee).