

MY THESIS

TOVA RAY HOLMES



An Homage to The Elements of Typographic Style

August 2016 – version 1.0

Tova Ray Holmes: *My Thesis*, An Homage to The Elements of Typographic Style, © August 2016

ABSTRACT

PUBLICATIONS

Some ideas and figures have appeared previously in the following publications:

Put your publications from the thesis here. The packages `multibib` or `bibtopic` etc. can be used to handle multiple different bibliographies in your document.

ACKNOWLEDGEMENTS

Put your acknowledgements here.

CONTENTS

I	INTRODUCTION	1
1	INTRODUCTION	3
II	THEORY AND MOTIVATION	5
2	THEORY AND MOTIVATION	7
2.1	The Standard Model	7
2.1.1	How do you explain the standard model? . . .	7
2.1.2	Problems in the Standard Model	7
2.2	Supersymmetry	7
III	WHERE DATA COME FROM	9
3	THE LARGE HADRON COLLIDER	11
3.1	Operation of the Large Hadron Collider	11
4	THE ATLAS DETECTOR	13
4.1	Subdetectors of ATLAS	13
4.1.1	The Pixel Detector	13
5	APPLICATION OF NEURAL NETWORKS TO THE PIXEL CLUSTERING	15
5.1	Clustering in the Pixel Detector	15
5.1.1	Analog Clustering	15
5.1.2	A Neural Network	15
5.2	Impact of the Neural Network	15
IV	SEARCHING FOR SUSY	17
V	CONCLUSIONS	19
VI	APPENDIX	21
	BIBLIOGRAPHY	23

LIST OF FIGURES

LIST OF TABLES

LISTINGS

ACRONYMS

LHC Large Hadron Collider

IBL Inner B Layer

NN Neural Network

Part I

INTRODUCTION

You can put some informational part preamble text here. Illo principalmente su nos. Non message *occidental* anglo-romanian da. Debitas effortio simplicate sia se, auxiliar summarios da que, se avantiate publicationes via. Pan in terra summarios, capital interlingua se que. Al via multo esser specimen, campo responder que da. Le usate medical addresses pro, europa origine sanctificate nos se.

INTRODUCTION

The pages that follow detail the author's work on the ATLAS experiment from 2011 through 2016, focusing on an analysis of 13TeV proton-proton collisions at the Large Hadron Collider ([LHC](#)) looking for Supersymmetry with the ATLAS Detector.

CHAPTER 1 outlines the theory behind Supersymmetry and the motivation behind this particular analysis.

Part II

THEORY AND MOTIVATION

You can put some informational part preamble text here.

THEORY AND MOTIVATION

Some kind of preamble here I guess.

2.1 THE STANDARD MODEL

2.1.1 *How do you explain the standard model?*

I will put this off for now.

2.1.2 *Problems in the Standard Model*

2.2 SUPERSYMMETRY

Part III

WHERE DATA COME FROM

You can put some informational part preamble text here.

THE LARGE HADRON COLLIDER

The [LHC](#) is unique in the world, producing particle collisions at energies an order of magnitude higher than any accelerator before. It provides unique environments in its proton-proton collisions where massive, unstable particles can exist for an instant, then decay to the ordinary material of the universe.

3.1 OPERATION OF THE LARGE HADRON COLLIDER

THE ATLAS DETECTOR

The ATLAS detector circumscribes the LHC ring, enclosing the collision point with a series of particle detecting subsystems, aimed at making as many measurements of the particles leaving the interaction as possible. Its goal is to get a precise measurement of all the stable particles flying from proton-proton collisions at its center, allowing analyzers to fully reconstruct the kinematics of the underlying event.

4.1 SUBDETECTORS OF ATLAS

The ATLAS Detector consists of many layers of detectors, each of which contributes to the measurements of the position and energy of particles in different ways. This section will describe each of these detectors, in the order in which they are traversed by a particle coming from the collision point.

4.1.1 *The Pixel Detector*

The Pixel detector lies closest to the beam pipe of the [LHC](#), and has four layers comprising 92 million read-out channels. There are three standard layers, referred to as L1-L3, and an additional layer added for the 2015 datataking, called the Inner B Layer ([IBL](#)).

4.1.1.1 *The Original Pixel Detector*

4.1.1.2 *Addition of the IBL*

In 2015, the [IBL](#) was lowered into the ATLAS cavern and added to the Pixel Detector. As its name suggests, it was added to improve detection of B mesons, whose non-trivial lifetimes create secondary vertices in ATLAS events, which allow them to be distinguished from other particles with precise track measurement. The [IBL](#) is closer to the interaction point and has a smaller spacing between sensors, giving it a better chance to see these slightly displaced vertices.

APPLICATION OF NEURAL NETWORKS TO THE PIXEL CLUSTERING

I suppose I have to explain the NN.

5.1 CLUSTERING IN THE PIXEL DETECTOR

5.1.1 *Analog Clustering*

5.1.2 *A Neural Network*

To improve on this simple approach to clustering, a Neural Network (NN) was created [1] [2].

Robustness [3]

5.2 IMPACT OF THE NEURAL NETWORK

Part IV

SEARCHING FOR SUSY

You can put some informational part preamble text here.

Part V

CONCLUSIONS

You can put some informational part preamble text here.

Part VI

APPENDIX

BIBLIOGRAPHY

- [1] ATLAS Collaboration. “A neural network clustering algorithm for the ATLAS silicon pixel detector.” In: *JINST* 9 (2014), P09009. DOI: [10 . 1088 / 1748 - 0221 / 9 / 09 / P09009](https://doi.org/10.1088/1748-0221/9/09/P09009). arXiv: [1406 . 7690](https://arxiv.org/abs/1406.7690) [hep-ex].
- [2] ATLAS Collaboration. *Measurement of performance of the pixel neural network clustering algorithm of the ATLAS experiment at $\sqrt{s} = 13$ TeV*. ATL-PHYS-PUB-2015-044. 2015. URL: [http : / / cdsweb . cern . ch / record / 2054921](http://cdsweb.cern.ch/record/2054921).
- [3] ATLAS Collaboration. *Robustness of the Artificial Neural Network Clustering Algorithm of the ATLAS experiment*. ATL-PHYS-PUB-2015-052. 2015. URL: [http : / / cdsweb . cern . ch / record / 2116350](http://cdsweb.cern.ch/record/2116350).