Base R
Cheat Sheet

Getting Help

Accessing the help files

?mean
Get help of a particular function.

help.search('weighted mean')
Search the help files for a word or phrase.

help(package = 'dplyr')
Find help for a package.

More about an object

str(iris)
Get a summary of an object's structure.

class(iris)
Find the class an object belongs to.

Using Packages

install.packages('dplyr')
Download and install a package from CRAN.

library(dplyr)
Load the package into the session, making all its functions available to use.

dplyr::select
Use a particular function from a package.

data(iris)
Load a built-in dataset into the environment.

Working Directory

getwd()
Find the current working directory (where inputs are found and outputs are sent).

setwd('C://file/path')
Change the current working directory.

Use projects in RStudio to set the working directory to the folder you are working in.

Vectors

Creating Vectors

`c(2, 4, 6)`	`2 4 6`	Join elements into a vector
`2:6`	`2 3 4 5 6`	An integer sequence
`seq(2, 3, by=0.5)`	`2.0 2.5 3.0`	A complex sequence
`rep(1:2, times=3)`	`1 2 1 2 1 2`	Repeat a vector
`rep(1:2, each=3)`	`1 1 1 2 2 2`	Repeat elements of a vector

Vector Functions

sort(x)
Return x sorted.

rev(x)
Return x reversed.

table(x)
See counts of values.

unique(x)
See unique values.

Selecting Vector Elements

By Position

`x[4]`	The fourth element.
`x[-4]`	All but the fourth.
`x[2:4]`	Elements two to four.
`x[-(2:4)]`	All elements except two to four.
`x[c(1, 5)]`	Elements one and five.

By Value

`x[x == 10]`	Elements which are equal to 10.
`x[x < 0]`	All elements less than zero.
`x[x %in% c(1, 2, 5)]`	Elements in the set 1, 2, 5.

Named Vectors

`x['apple']`	Element with name 'apple'.

Programming

For Loop

```
for (variable in sequence){
   Do something
}
```

Example

```
for (i in 1:4){
   j <- i + 10
   print(j)
}
```

While Loop

```
while (condition){
   Do something
}
```

Example

```
while (i < 5){
   print(i)
   i <- i + 1
}
```

If Statements

```
if (condition){
   Do something
} else {
   Do something different
}
```

Example

```
if (i > 3){
   print('Yes')
} else {
   print('No')
}
```

Functions

```
function_name <- function(var){
   Do something
   return(new_variable)
}
```

Example

```
square <- function(x){
   squared <- x*x
   return(squared)
}
```

Reading and Writing Data

Also see the **readr** package.

Input	Ouput	Description
`df <- read.table('file.txt')`	`write.table(df, 'file.txt')`	Read and write a delimited text file.
`df <- read.csv('file.csv')`	`write.csv(df, 'file.csv')`	Read and write a comma separated value file. This is a special case of read.table/ write.table.
`load('file.RData')`	`save(df, file = 'file.Rdata')`	Read and write an R data file, a file type special for R.

Conditions

`a == b`	Are equal	`a > b`	Greater than	`a >= b`	Greater than or equal to	`is.na(a)`	Is missing
`a != b`	Not equal	`a < b`	Less than	`a <= b`	Less than or equal to	`is.null(a)`	Is null

RStudio® is a trademark of RStudio, Inc. • CC BY Mhairi McNeill • mhairihmcneill@gmail.com

Types

Converting between common data types in R. Can always go from a higher value in the table to a lower value.

`as.logical`	`TRUE, FALSE, TRUE`	Boolean values (TRUE or FALSE).
`as.numeric`	`1, 0, 1`	Integers or floating point numbers.
`as.character`	`'1', '0', '1'`	Character strings. Generally preferred to factors.
`as.factor`	`'1', '0', '1', levels: '1', '0'`	Character strings with preset levels. Needed for some statistical models.

Maths Functions

`log(x)`	Natural log.	`sum(x)`	Sum.
`exp(x)`	Exponential.	`mean(x)`	Mean.
`max(x)`	Largest element.	`median(x)`	Median.
`min(x)`	Smallest element.	`quantile(x)`	Percentage quantiles.
`round(x, n)`	Round to n decimal places.	`rank(x)`	Rank of elements.
`signif(x, n)`	Round to n significant figures.	`var(x)`	The variance.
`cor(x, y)`	Correlation.	`sd(x)`	The standard deviation.

Variable Assignment

```
> a <- 'apple'
> a
[1] 'apple'
```

The Environment

`ls()`	List all variables in the environment.
`rm(x)`	Remove x from the environment.
`rm(list = ls())`	Remove all variables from the environment.

You can use the environment panel in RStudio to browse variables in your environment.

Matrices

`m <- matrix(x, nrow = 3, ncol = 3)`
Create a matrix from x.

`m[2, ]` - Select a row

`m[ , 1]` - Select a column

`m[2, 3]` - Select an element

`t(m)`
Transpose

`m %*% n`
Matrix Multiplication

`solve(m, n)`
Find x in: m * x = n

Lists

`l <- list(x = 1:5, y = c('a', 'b'))`
A list is a collection of elements which can be of different types.

`l[[2]]`	`l[1]`	`l$x`	`l['y']`
Second element of l.	New list with only the first element.	Element named x.	New list with only element named y.

Also see the **dplyr** package.

Data Frames

`df <- data.frame(x = 1:3, y = c('a', 'b', 'c'))`
A special case of a list where all elements are the same length.

x	y
1	a
2	b
3	c

List subsetting

`df$x` `df[[2]]`

Understanding a data frame

`View(df)`	See the full data frame.
`head(df)`	See the first 6 rows.

Matrix subsetting



`df[ , 2]`

`df[2, ]`

`df[2, 2]`

`nrow(df)`
Number of rows.

`ncol(df)`
Number of columns.

`dim(df)`
Number of columns and rows.

`cbind` - Bind columns.

`rbind` - Bind rows.

Strings

Also see the **stringr** package.

`paste(x, y, sep = ' ')`	Join multiple vectors together.
`paste(x, collapse = ' ')`	Join elements of a vector together.
`grep(pattern, x)`	Find regular expression matches in x.
`gsub(pattern, replace, x)`	Replace matches in x with a string.
`toupper(x)`	Convert to uppercase.
`tolower(x)`	Convert to lowercase.
`nchar(x)`	Number of characters in a string.

Factors

`factor(x)`
Turn a vector into a factor. Can set the levels of the factor and the order.

`cut(x, breaks = 4)`
Turn a numeric vector into a factor by 'cutting' into sections.

Statistics

`lm(y ~ x, data=df)`
Linear model.

`glm(y ~ x, data=df)`
Generalised linear model.

`summary`
Get more detailed information out a model.

`t.test(x, y)`
Perform a t-test for difference between means.

`pairwise.t.test`
Perform a t-test for paired data.

`prop.test`
Test for a difference between proportions.

`aov`
Analysis of variance.

Distributions

	Random Variates	Density Function	Cumulative Distribution	Quantile
Normal	`rnorm`	`dnorm`	`pnorm`	`qnorm`
Poisson	`rpois`	`dpois`	`ppois`	`qpois`
Binomial	`rbinom`	`dbinom`	`pbinom`	`qbinom`
Uniform	`runif`	`dunif`	`punif`	`qunif`

Plotting

Also see the **ggplot2** package.



`plot(x)`
Values of x in order.

`plot(x, y)`
Values of x against y.



`hist(x)`
Histogram of x.

Dates

See the **lubridate** package.