String manipulation with stringr : : **CHEAT SHEET**

The **stringr** package provides a set of internally consistent tools for working with character strings, i.e. sequences of characters surrounded by quotation marks.

Detect Matches



str_detect(string, **pattern**) Detect the presence of a pattern match in a string. *str_detect(fruit, "a")*



str_which(string, **pattern**) Find the indexes of strings that contain a pattern match. *str_which(fruit, "a")*



str_count(string, **pattern**) Count the number of matches in a string. *str_count(fruit, "a")*

str_locate(string, **pattern**) Locate the positions of pattern matches in a string. Also **str_locate_all**. *str_locate(fruit, "a")*

Subset Strings



str_sub(string, start = 1L, end = -1L) Extract substrings from a character vector. *str_sub(fruit, 1, 3); str_sub(fruit, -2)*



str_subset(string, **pattern**) Return only the strings that contain a pattern match. *str_subset(fruit, "b")*

str_extract(string, **pattern**) Return the first pattern match found in each string, as a vector. Also **str_extract_all** to return every pattern match. *str_extract(fruit, "[aeiou]")*



str_match(string, **pattern**) Return the first pattern match found in each string, as a matrix with a column for each ( ) group in pattern. Also **str_match_all**. *str_match(sentences, "(a|the) ([^]+)")*

Manage Lengths



str_length(string) The width of strings (i.e. number of code points, which generally equals the number of characters). *str_length(fruit)*



str_pad(string, width, side = c("left", "right", "both"), pad = " ") Pad strings to constant width. *str_pad(fruit, 17)*



str_trunc(string, width, side = c("right", "left", "center"), ellipsis = "...") Truncate the width of strings, replacing content with ellipsis. *str_trunc(fruit, 3)*



str_trim(string, side = c("both", "left", "right")) Trim whitespace from the start and/or end of a string. *str_trim(fruit)*

Mutate Strings



str_sub() **<-** value. Replace substrings by identifying the substrings with str_sub() and assigning into the results. *str_sub(fruit, 1, 3) <- "str"*



str_replace(string, **pattern**, replacement) Replace the first matched pattern in each string. *str_replace(fruit, "a", "-")*



str_replace_all(string, **pattern**, replacement) Replace all matched patterns in each string. *str_replace_all(fruit, "a", "-")*



str_to_lower(string, locale = "en")[1] Convert strings to lower case. *str_to_lower(sentences)*



str_to_upper(string, locale = "en")[1] Convert strings to upper case. *str_to_upper(sentences)*



str_to_title(string, locale = "en")[1] Convert strings to title case. *str_to_title(sentences)*

Join and Split



str_c(..., sep = "", collapse = NULL) Join multiple strings into a single string. *str_c(letters, LETTERS)*



str_c(..., sep = "", **collapse = NULL**) Collapse a vector of strings into a single string. *str_c(letters, collapse = "")*

str_dup(string, times) Repeat strings times times. *str_dup(fruit, times = 2)*



str_split_fixed(string, **pattern**, n) Split a vector of strings into a matrix of substrings (splitting at occurrences of a pattern match). Also **str_split** to return a list of substrings. *str_split_fixed(fruit, " ", n=2)*



str_glue(…, .sep = "", .envir = parent.frame()) Create a string from strings and {expressions} to evaluate. *str_glue("Pi is {pi}")*



str_glue_data(.x, ..., .sep = "", .envir = parent.frame(), .na = "NA") Use a data frame, list, or environment to create a string from strings and {expressions} to evaluate. *str_glue_data(mtcars, "{rownames(mtcars)} has {hp} hp")*

Order Strings



str_order(x, decreasing = FALSE, na_last = TRUE, locale = "en", numeric = FALSE, ...)[1] Return the vector of indexes that sorts a character vector. *x[str_order(x)]*

str_sort(x, decreasing = FALSE, na_last = TRUE, locale = "en", numeric = FALSE, ...)[1] Sort a character vector. *str_sort(x)*

Helpers

str_conv(string, encoding) Override the encoding of a string. *str_conv(fruit,"ISO-8859-1")*



str_view(string, **pattern**, match = NA) View HTML rendering of first regex match in each string. *str_view(fruit, "[aeiou]")*

str_view_all(string, **pattern**, match = NA) View HTML rendering of all regex matches. *str_view_all(fruit, "[aeiou]")*

str_wrap(string, width = 80, indent = 0, exdent = 0) Wrap strings into nicely formatted paragraphs. *str_wrap(sentences, 20)*

[1] See bit.ly/ISO639-1 for a complete list of locales.

RStudio® is a trademark of RStudio, Inc. • CC BY SA RStudio • info@rstudio.com • 844-448-1212 • rstudio.com • Learn more at **stringr.tidyverse.org** • Diagrams from **@LVaudor** • stringr 1.2.0 • Updated: 2017-10

Need to Know

Pattern arguments in stringr are interpreted as regular expressions *after any special characters have been parsed.*

In R, you write regular expressions as *strings*, sequences of characters surrounded by quotes (**""**) or single quotes(**''**).

Some characters cannot be represented directly in an R string . These must be represented as **special characters**, sequences of characters that have a specific meaning., e.g.

Special Character	Represents
\\	\
\"	"
\n	new line

Run **?"'"** to see a complete list

Because of this, whenever a \ appears in a regular expression, you must write it as \\ in the string that represents the regular expression.

Use **writeLines**() to see how R views your string after all special characters have been parsed.

writeLines("\\.")
 # \.

writeLines("\\ is a backslash")
 # \ is a backslash

INTERPRETATION

Patterns in stringr are interpreted as regexs To change this default, wrap the pattern in one of:

regex(pattern, ignore_case = FALSE, multiline = FALSE, comments = FALSE, dotall = FALSE, ...) Modifies a regex to ignore cases, match end of lines as well of end of strings, allow R comments within regex's , and/or to have . match everything including \n.
str_detect("I", regex("i", TRUE))

fixed() Matches raw bytes but will miss some characters that can be represented in multiple ways (fast). *str_detect("\u0130", fixed("i"))*

coll() Matches raw bytes and will use locale specific collation rules to recognize characters that can be represented in multiple ways (slow). *str_detect("\u0130", coll("i", TRUE, locale = "tr"))*

boundary() Matches boundaries between characters, line_breaks, sentences, or words. *str_split(sentences, boundary("word"))*

Regular Expressions -

Regular expressions, or *regexps*, are a concise language for describing patterns in strings.

MATCH CHARACTERS

see <- function(rx) str_view_all("abc ABC 123\t.!?\\(){}\n", rx)

string (type this)	**regexp** (to mean this)	**matches** (which matches this)	**example**	
	a (etc.)	a (etc.)	see("a")	abc ABC 123 .!?\(){}
\\.	**\.**	.	see("\\.")	abc ABC 123 .!?\(){}
\\!	**\!**	!	see("\\!")	abc ABC 123 .!?\(){}
\\?	**\?**	?	see("\\?")	abc ABC 123 .!?\(){}
\\\\	****	\	see("\\\\")	abc ABC 123 .!?\(){}
\\(	**\(**	(	see("\\(")	abc ABC 123 .!?\(){}
\\)	**\)**	)	see("\\)")	abc ABC 123 .!?\(){}
\\{	**\{**	{	see("\\{")	abc ABC 123 .!?\(){}
\\}	**\}**	}	see("\\}")	abc ABC 123 .!?\(){}
\\n	**\n**	new line (return)	see("\\n")	abc ABC 123 .!?\(){}
\\t	**\t**	tab	see("\\t")	abc ABC 123 .!?\(){}
\\s	**\s**	any whitespace (**\S** *for non-whitespaces*)	see("\\s")	abc ABC 123 .!?\(){}
\\d	**\d**	any digit (**\D** *for non-digits*)	see("\\d")	abc ABC 123 .!?\(){}
\\w	**\w**	any word character (**\W** *for non-word chars*)	see("\\w")	abc ABC 123 .!?\(){}
\\b	**\b**	word boundaries	see("\\b")	abc ABC 123 .!?\(){}
	[:digit:] [1]	digits	see("[:digit:]")	abc ABC 123 .!?\(){}
	[:alpha:] [1]	letters	see("[:alpha:]")	abc ABC 123 .!?\(){}
	[:lower:] [1]	lowercase letters	see("[:lower:]")	abc ABC 123 .!?\(){}
	[:upper:] [1]	uppercase letters	see("[:upper:]")	abc ABC 123 .!?\(){}
	[:alnum:] [1]	letters and numbers	see("[:alnum:]")	abc ABC 123 .!?\(){}
	[:punct:] [1]	punctuation	see("[:punct:]")	abc ABC 123 .!?\(){}
	[:graph:] [1]	letters, numbers, and punctuation	see("[:graph:]")	abc ABC 123 .!?\(){}
	[:space:] [1]	space characters (i.e. \s)	see("[:space:]")	abc ABC 123 .!?\(){}
	[:blank:] [1]	space and tab (but not new line)	see("[:blank:]")	abc ABC 123 .!?\(){}
	.	every character except a new line	see(".")	abc ABC 123 .!?\(){}

[1] Many base R functions require classes to be wrapped in a second set of **[ ]**, e.g. **[[:digit:]]**

ALTERNATES

alt <- function(rx) str_view_all("abcde", rx)

regexp	**matches**	**example**	
ab|d	or	alt("ab|d")	abcde
[abe]	one of	alt("[abe]")	abcde
[^abe]	anything but	alt("[^abe]")	abcde
[a-c]	range	alt("[a-c]")	abcde

ANCHORS

anchor <- function(rx) str_view_all("aaa", rx)

regexp	**matches**	**example**	
^a	start of string	anchor("^a")	aaa
a$	end of string	anchor("a$")	aaa

LOOK AROUNDS

look <- function(rx) str_view_all("bacad", rx)



regexp	**matches**	**example**	
a(?=c)	followed by	look("a(?=c)")	bacad
a(?!c)	not followed by	look("a(?!c)")	bacad
(?<=b)a	preceded by	look("(?<=b)a")	bacad
(?<!b)a	not preceded by	look("(?<!b)a")	bacad

QUANTIFIERS

quant <- function(rx) str_view_all(".a.aa.aaa", rx)



regexp	**matches**	**example**	
a?	zero or one	quant("a?")	.a.aa.aaa
a*	zero or more	quant("a*")	.a.aa.aaa
a+	one or more	quant("a+")	.a.aa.aaa
a{n}	exactly **n**	quant("a{2}")	.a.aa.aaa
a{n,}	**n** or more	quant("a{2,}")	.a.aa.aaa
a{n, m}	between **n** and **m**	quant("a{2,4}")	.a.aa.aaa

GROUPS

ref <- function(rx) str_view_all("abbaab", rx)

Use parentheses to set precedent (order of evaluation) and create groups

regexp	**matches**	**example**	
(ab|d)e	sets precedence	alt("(ab|d)e")	abcde

Use an escaped number to refer to and duplicate parentheses groups that occur earlier in a pattern. Refer to each group by its order of appearance

string (type this)	**regexp** (to mean this)	**matches** (which matches this)	**example** (the result is the same as ref("abba"))	
\\1	**\1** (etc.)	first () group, etc.	ref("(a)(b)\\2\\1")	abbaab

[:space:]
↵ new line

[:blank:]
space
tab

.

[:graph:]

[:punct:]
. , : ; ? ! \ | / ` = * + - ^
_ ~ " ' [ ] { } ( ) < > @ # $

[:alnum:]

[:digit:]
0 1 2 3 4 5 6 7 8 9

[:alpha:]

[:lower:]
a b c d e f
g h i j k l
m n o p q r
s t u v w x
z

[:upper:]
A B C D E F
G H I J K L
M N O P Q R
S T U V W X
Z