

Lesson 6 - Boolean logic and iterations

Logical Computational Thinking

Stefano MARTINA

stefano.martina@gmail.com



Scuola Leonardo Da Vinci (Firenze)

15 October 2015



This work is licensed under a [Creative Commons Attribution-ShareAlike 4.0 International License](https://creativecommons.org/licenses/by-sa/4.0/).

Boolean logic

Predicate

A function

$$P : X \rightarrow \{true, false\}$$

from a certain set X (for instance $\mathbb{R} \times \mathbb{R}$) to a truth value. Can be: $<$, $>$, $<=$ (\leq), $>=$ (\geq), $==$ ($=$), $!=$ (\neq)

Logical connective

Technically predicates in the set: $\{true, false\} \times \{true, false\}$ ($\{true, false\}$ for the negation), can connect different expressions together. can be: $\&\&$ (\wedge), $||$ (\vee), $!$ (\neg).

a	b	$\neg a$	$a \wedge b$	$a \vee b$
0	0	1	0	0
0	1	1	0	1
1	0	0	0	1
1	1	0	1	1

Boolean expression

An expression that produce a boolean value when evaluated (true, false).

Can be composed from

- ✓ variables
- ✓ predicates
- ✓ connectives
- ✓ parenthesis

for instance:

- ✓ `a<3`
- ✓ `(a>5) && (a<10)`
- ✓ `(a<b) || !(a>=10 && b<=5)`

Iterations

