```java
import components.simplereader.SimpleReader;

/**
 * Put a short phrase describing the program here.
 *
 * @author Put your name here
 *
 */
public final class ABCDGuesser2 {

    /**
     * No argument constructor--private to prevent instantiation.
     */
    private ABCDGuesser2() {
    }

    /**
     * Main method.
     *
     * @param args
     *            the command line arguments
     */
    public static void main(String[] args) {
        SimpleReader in = new SimpleReader1L();
        SimpleWriter out = new SimpleWriter1L();
        double[] exp = { -5, -4, -3, -2, -1, -0.5, -0.333, -0.25, 0, 0.25,
                0.333, 0.5, 1, 2, 3, 4, 5 };
        double total = -1, closest = -999999999;
        double bestW = -1, bestX = -1, bestY = -1, bestZ = -1;

        // get u
        double u = getPositiveDouble(in, out);

        // get w x y z
        double w = getPositiveDoubleNotOne(in, out);
        double x = getPositiveDoubleNotOne(in, out);
        double y = getPositiveDoubleNotOne(in, out);
        double z = getPositiveDoubleNotOne(in, out);

        // big boy loop
        for (int i = 0; i <= 16; i++) {
            for (int j = 0; j <= 16; j++) {
                for (int k = 0; k <= 16; k++) {
                    for (int l = 0; l <= 16; l++) {
                        // does calculations
                        total = Math.pow(w, exp[i]);
                        total += Math.pow(x, exp[j]);
                        total += Math.pow(y, exp[k]);
                        total += Math.pow(z, exp[l]);

                        // if total is the closest to u so far
                        if (Math.abs(u - total) < Math.abs(u - closest)) {
                            closest = total;
                            bestW = exp[i];
                            bestX = exp[j];
                            bestY = exp[k];
                            bestZ = exp[l];
                        }
                    }
```

```
64                  }
65              }
66          }
67
68          // do some math
69          double percentError = Math.abs((closest - u) / u * 100);
70
71          // print results
72          System.out.println("u = " + u);
73          System.out.println("(" + w + "^" + bestW + ")" + " + " + "(" + x + "^"
74                  + bestX + ")" + " + " + "(" + y + "^" + bestY + ")" + " + "
75                  + "(" + z + "^" + bestZ + ")" + " = "
76                  + String.format("%.2f", closest));
77          System.out.println(
78                  "Percent Error: " + String.format("%.2f", percentError) + "%");
79
80          // close stuff
81          in.close();
82          out.close();
83      }
84
85      /**
86       * Repeatedly asks the user for a positive real number until the user enters
87       * one. Returns the positive real number.
88       *
89       * @param in
90       *             the input stream
91       * @param out
92       *             the output stream
93       * @return a positive real number entered by the user
94       */
95      private static double getPositiveDouble(SimpleReader in, SimpleWriter out) {
96          System.out.print("Enter a positive number: ");
97          String input = in.nextLine();
98          boolean looping = true;
99          double num = -1;
100
101         while (looping) {
102             if (FormatChecker.canParseInt(input)) {
103                 num = Integer.parseInt(input);
104                 if (num > 0) {
105                     looping = false;
106                 }
107             } else {
108                 System.out.print("Enter a positive number: ");
109                 input = in.nextLine();
110             }
111         }
112
113         return num;
114     }
115
116     /**
117      * Repeatedly asks the user for a positive real number not equal to 1.0
118      * until the user enters one. Returns the positive real number.
119      *
120      * @param in
121      *             the input stream
122      * @param out
```

```
123      *            the output stream
124      * @return a positive real number not equal to 1.0 entered by the user
125      */
126     private static double getPositiveDoubleNotOne(SimpleReader in,
127             SimpleWriter out) {
128         boolean looping = true;
129         double num = -1;
130 
131         while (looping) {
132             num = getPositiveDouble(in, out);
133             if (num != 1.0) {
134                 looping = false;
135             }
136         }
137 
138         return num;
139     }
140 
141 }
142 
```