



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

Angular Testing

3 - Asynchrony and Mocking

Parameterisable Tests 1/2

```
for (let { sentence, words } of [  
  { sentence: 'Veni vidi vici', words: 3 },  
  { sentence: 'Lorem ipsum', words: 2 },  
  { sentence: 'The brown 🐱 jumped over the lazy 🐶', words: 8 },  
  { sentence: 'Some space ', words: 2 }  
) {  
  it(`"${sentence}" should have ${words} words`, () => {  
    expect(sentence.split(' ').filter((word) => word)).toHaveLength(words);  
  });  
}
```



Parameterisable Tests 2/2

```
it.each([
  { sentence: 'Veni vidi vici', words: 3 },
  { sentence: 'Lorem ipsum', words: 2 },
  { sentence: 'The brown 🦊 jumped over the lazy 🐶', words: 8 },
  { sentence: 'Some space ', words: 2 }
])('$sentence' should have $words words', ({ sentence, words }) => {
  expect(sentence.split(' ').filter((word) => word)).toHaveLength(words);
});
```



Asynchrony



Potential Problems

- Expects not running
- Timeouts
- Cryptic error messages



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

Native Approaches

- done callback
- return Promise
- return `expect().resolves`
- `async/await`



done

```
it("should test with done", (done) => {  
  
  let a = 1;  
  
  Promise.resolve()  
  
    .then(() => {  
  
      a++;  
  
      expect(a).toBe(1);  
  
    })  
  
    .then(done, done);  
  
});
```



return the Promise

```
it("should return the promise", () => {
```

```
  let a = 1;
```

```
  return Promise.resolve().then(() => {
```

```
    a++;
```

```
    expect(a).toBe(2);
```

```
  });
```

```
});
```



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

return expect().resolves

```
it("should test with expect.resolves", () => {
```

```
  let a = 1;
```

```
  const promise = Promise.resolve().then(() => a + 1);
```

```
  return expect(promise).resolves.toBe(2);
```

```
});
```



Use async/await

```
it("should test with done", async () => {
```

```
  let a = 1;
```

```
  await Promise.resolve().then(() => {
```

```
    a++;
```

```
  });
```

```
  expect(a).toBe(2);
```

```
});
```



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

Angular-based Approaches

- **waitForAsync**: automatic done callback
- **fakeAsync**: transforms async to sync task
 - flushMicrotasks: run all microtasks
 - tick: move forward in time
 - flush: run all asynchronous tasks (skips periodic timers)



waitForAsync: Automatic done callback

```
test('async', waitForAsync(() => {  
  expect.hasAssertions();  
  let a = 1;  
  Promise.resolve().then(() => {  
    a++;  
    expect(a).toBe(2);  
  });  
  
  window.setTimeout(() => {  
    a++;  
    expect(a).toBe(3);  
  }, 1000);  
}))  
);
```



fakeAsync: Turn asynchrony into synchrony

```
test("microtasks", fakeAsync(() => {  
  let a = 1;  
  Promise.resolve().then(() => (a = 2));  
  expect(a).toBe(1);  
  
  flushMicrotasks();  
  expect(a).toBe(2);  
}));
```



fakeAsync

```
test("immediate macrotasks", fakeAsync(() => {  
  let a = 1;  
  window.setTimeout(() => (a = 2));  
  expect(a).toBe(1);  
  
  tick();  
  expect(a).toBe(2);  
}));
```



fakeAsync

```
test("delayed macrotasks", fakeAsync(() => {  
  let a = 1;  
  window.setTimeout(() => (a = 2), 2000);  
  expect(a).toBe(1);  
  
  tick(2000);  
  expect(a).toBe(2);  
}), 1000);
```



fakeAsync

```
test("delayed macrotasks", fakeAsync(() => {  
  let a = 1;  
  window.setTimeout(() => (a = 2), 2000);  
  expect(a).toBe(1);  
  
  flush();  
  expect(a).toBe(2);  
}), 1000);
```




Why fakeAsync over waitForAsync?

1. Run unreachable asynchronous tasks
2. Assertion at the end (AAA pattern)
3. No remaining macrotasks as "implicit" assertion




Mocking (Test Doubles)



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

Stub



Mock



Two Types (Academic)

1. Stub: Replaces a dependency
 - a. When dependency returns a value
 - b. e.g. HTTP Request
 - c. Is enough in most cases
 - d. Test doesn't verify the stub is called
2. Mock: Verifies a call to a dependency
 - a. A "side-effect only" dependency
 - b. Usage has to be verified
 - c. e.g. SnackBar, Router navigation
 - d. Test verifies the mock is called



```
export class ValidAddressLookuper {  
  constructor(  
    private addresses: () => AddressSource[],  
    private addressValidator: AddressValidatorService  
  ) {}  
  
  lookup(query: string): boolean {  
    return this.addresses()  
      .filter((addressSource) => this.addressValidator.isValidAddress(addressSource))  
      .some((address) => address.value.startsWith(query));  
  }  
}
```



Stub

```
it('should stub validator', () => {  
  const validator = { isValidAddress: () => true };  
  const lookuper = new ValidAddressLookuper(  
    () => [  
      {  
        value: 'Domgasse 5',  
        expiryDate: new Date(2000, 0, 1)  
      }  
    ],  
    validator as AddressValidatorService  
  );  
  
  expect(lookuper.lookup('Domgasse 5')).toBe(true);  
});
```



Mocking Functions

return value

arguments of functions

```
const validatorFn = jest.fn<boolean, [AddressSource]>(  
  (addressSource) => true  
)  
);
```

optional implementation



Mock

```
it('should mock validator', () => {  
  const validator = { isValidAddress: jest.fn<boolean, [AddressSource]>(() => true) };  
  const lookuper = new ValidAddressLookuper(  
    () => [  
      {  
        value: 'Domgasse 5',  
        expiryDate: new Date(2000, 0, 1)  
      }  
    ],  
    validator as AddressValidatorService  
  );  
  
  expect(lookuper.lookup('Domgasse 5')).toBe(true);  
});
```



Mock

```
it('should mock validator', () => {  
  const validator = { isValidAddress: jest.fn<boolean, [AddressSource]>(() => true) };  
  const lookuper = new ValidAddressLookuper(  
    () => [  
      {  
        value: 'Domgasse 5',  
        expiryDate: new Date(2000, 0, 1)  
      }  
    ],  
    validator as AddressValidatorService  
  );  
  
  lookuper.lookup('Domgasse 5')  
  
expect(lookuper.lookup('Domgasse 5')).toBe(true);  
});
```



Mock

```
it('should mock validator', () => {  
  const validator = { isValidAddress: jest.fn(() => true) };  
  const lookuper = new ValidAddressLookuper(  
    () => [  
      {  
        value: 'Domgasse 5',  
        expiryDate: new Date(2000, 0, 1)  
      }  
    ],  
    validator as AddressValidatorService  
  );  
  
  lookuper.lookup('Domgasse 5')  
  
  expect(validator.isValidAddress).toBeCalled();  
});
```



Mock

```
it('should mock validator', () => {  
  const validator = { isValidAddress: jest.fn(() => true) };  
  const lookuper = new ValidAddressLookuper(  
    () => [  
      {  
        value: 'Domgasse 5',  
        expiryDate: new Date(2000, 0, 1)  
      }  
    ],  
    validator as AddressValidatorService  
  );  
  
  lookuper.lookup('Domgasse 5')  
  
  expect(validator.isValidAddress).toBeCalledWith({  
    value: 'Domgasse 5',  
    expiryDate: new Date(2000, 0, 1)  
  });  
});
```



Mock

```
it('should mock validator', () => {  
  const validator = { isValidAddress: jest.fn<boolean, [AddressSource]>(() => true) };  
  const lookuper = new ValidAddressLookuper(  
    () => [  
      {  
        value: 'Domgasse 5',  
        expiryDate: new Date(2000, 0, 1)  
      }  
    ],  
    validator as AddressValidatorService  
  );  
  
  lookuper.lookup('Domgasse 5')  
  
  expect(validator.isValidAddress.mock.calls[0][0].value).toBe('Domgasse 5');  
});
```



Spying (ts-mockito)


```
it('should check with spied validator', () => {  
  const addressValidator = new AddressValidator();  
  const validatorSpy = spy(addressValidator);  
  // when(validatorSpy.isValidAddress('Domgasse 15')).thenReturn(true);  
  const addresses = ['Domgasse 15', '1010 Wien'];  
  const lookuper = new AddressLookuper(() => addresses, addressValidator);  
  
  lookuper.lookup('Domgasse 15');  
  
  verify(validatorSpy.isValidAddress(anyString())).once();  
});
```




Spying

```
it('should check with spied validator', () => {  
  const addressValidator = new AddressValidator();  
  const validatorSpy = jest.spyOn(addressValidator);  
  const addresses = ['Domgasse 15, 1010 Wien'];  
  const lookuper = new AddressLookuper(() => addresses, addressValidator);  
  
  lookuper.lookup('Domgasse 15');  
  
  expect(validatorSpy).toHaveBeenCalledWith('Domgasse 15, 1010 Wien');  
});
```





Stub



Component

TS

Mock



Component

TS

Spy



Component

TS



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

Lab Time

