

Neural Network and application in Finance

Assoc. Prof. Đỗ Phúc
Tri Nhan Data Science and Application Group
Year 2020

PGS.TS. Đỗ Phúc, 2020

1

Machine Learning

Neural Networks

Slides mostly adapted from Tom Mithcell,
Han and Kamber

PGS.TS. Đỗ Phúc, 2020

2

Artificial Neural Networks

- Computational models **inspired by the human brain**:
 - Algorithms that try to mimic the brain.
- Massively parallel, distributed system, made up of simple processing units (neurons)
- Synaptic connection strengths among neurons are used to store the acquired knowledge.
- Knowledge is acquired by the network from its environment through a learning process

PGS.TS. Đỗ Phúc, 2020

3

History

- late-1800's - Neural Networks appear as an analogy to biological systems
- 1960's and 70's - Simple neural networks appear
 - Fall out of favor because the perceptron is not effective by itself, and there were no good algorithms for multilayer nets
- 1986 - Backpropagation algorithm appears
 - Neural Networks have a resurgence in popularity
 - More computationally expensive

PGS.TS. Đỗ Phúc, 2020

4

Properties

- Inputs are flexible
 - any real values
 - Highly correlated or independent
- Target function may be discrete-valued, real-valued, or vectors of discrete or real values
 - Outputs are real numbers between 0 and 1
- Resistant to errors in the training data
- Long training time
- Fast evaluation
- The function produced can be difficult for humans to interpret

PGS.TS. Đỗ Phúc, 2020

5

When to consider neural networks

- Input is high-dimensional discrete or raw-valued
- Output is discrete or real-valued
- Output is a vector of values
- Possibly noisy data
- Form of target function is unknown
- Human readability of the result is not important


Examples:

- Speech phoneme recognition
- Image classification
- Financial prediction

PGS.TS. Đỗ Phúc, 2020

6

A Neuron (= a perceptron)



- The n -dimensional input vector x is mapped into variable y by means of the scalar product and a nonlinear function mapping

August 20, 2020

PGS.TS. Đỗ Phúc, 2020
Data Mining: Concepts and Techniques

7

Perceptron


- Basic unit in a neural network
- Linear separator
- Parts
 - N inputs, $x_1 \dots x_n$
 - Weights for each input, $w_1 \dots w_n$
 - A bias input x_0 (constant) and associated weight w_0
 - Weighted sum of inputs, $y = w_0 x_0 + w_1 x_1 + \dots + w_n x_n$
 - A threshold function or activation function,
 - i.e 1 if $y > t$, -1 if $y \leq t$

PGS.TS. Đỗ Phúc, 2020

8

Artificial Neural Networks (ANN)

- Model is an assembly of inter-connected nodes and weighted links
- Output node sums up each of its input value according to the weights of its links
- Compare output node against some threshold t



Perceptron Model

$$Y = I\left(\sum_i w_i x_i - t\right) \quad \text{or}$$


$$Y = \text{sign}\left(\sum_i w_i x_i - t\right)$$

PGS.TS. Đỗ Phúc, 2020

9

Different Network Topologies

- Single layer feed-forward networks
 - Input layer projecting into the output layer




PGS.TS. Đỗ Phúc, 2020

10

Different Network Topologies

- Multi-layer feed-forward networks
 - One or more hidden layers. Input projects only from previous layers onto a layer.




PGS.TS. Đỗ Phúc, 2020

11

Different Network Topologies

- Multi-layer feed-forward networks




PGS.TS. Đỗ Phúc, 2020

12

Different Network Topologies

• Recurrent networks

- A network with feedback, where some of its inputs are connected to some of its outputs (discrete time).



PGS.TS. Đỗ Phúc, 2020

13

Multilayer Networks

The class of functions representable by perceptrons is limited

$$\text{Out}(x) = g(\mathbf{w}^T \mathbf{x}) = g\left(\sum_j w_j x_j\right)$$




$\text{Out}(x) = g\left(\sum_j W_j g\left(\sum_k w_{jk} x_{jk}\right)\right)$ This is a nonlinear function
Of a linear combination
Of non linear functions
Of linear combinations of inputs

Copyright © 2001, 2003, Andrew W. Moore

PGS.TS. Đỗ Phúc, 2020

Neural Networks: Slide 51

A 1-HIDDEN LAYER NET

 $N_{\text{INPUTS}} = 2$ $N_{\text{HIDDEN}} = 3$ 

Copyright © 2001, 2003, Andrew W. Moore

PGS.TS. Đỗ Phúc, 2020

Neural Networks: Slide 52

Multi-layer Networks


- Linear units inappropriate
 - No more expressive than a single layer
- Introduce non-linearity
 - Threshold not differentiable
- Use sigmoid function

PGS.TS. Đỗ Phúc, 2020

16

The Sigmoid

$$g(h) = \frac{1}{1 + \exp(-h)}$$



Now we choose \mathbf{w} to minimize

$$\sum_{i=1}^R [v_i - \text{Out}(x_i)]^2 = \sum_{i=1}^R [v_i - g(\mathbf{w}^T \mathbf{x}_i)]^2$$


Copyright © 2001, 2003, Andrew W. Moore

PGS.TS. Đỗ Phúc, 2020

Neural Networks: Slide 45

17

Sigmoid Unit



$\sigma(x)$ is the sigmoid function/activation function (also linear, threshold)

$$\frac{1}{1 + e^{-x}}$$

Nice property: $\frac{d\sigma(x)}{dx} = \sigma(x)(1 - \sigma(x))$ Differentiable

We can derive gradient decent rules to train

- One sigmoid unit
- Multilayer networks of sigmoid units \rightarrow Backpropagation

PGS.TS. Đỗ Phúc, 2020

18

Backpropagation

$$\text{Out}(x) = g\left(\sum_j W_j g\left(\sum_k w_{jk} x_k\right)\right)$$

Find a set of weights $\{W_j\}, \{w_{jk}\}$
to minimize

$$\sum_i (y_i - \text{Out}(x_i))^2$$

by gradient descent.

That's it!
That's the backpropagation algorithm.

Backpropagation

- Iteratively process a set of training tuples & compare the network's prediction with the actual known target value
- For each training tuple, the weights are modified to **minimize the mean squared error** between the network's prediction and the actual target value
- Modifications are made in the **"backwards"** direction: from the output layer, through each hidden layer down to the first hidden layer, hence **"backpropagation"**
- Steps
 - Initialize weights (to small random #s) and biases in the network
 - Propagate the inputs forward (by applying activation function)
 - Backpropagate the error (by updating weights and biases)
 - Terminating condition (when error is very small, etc.)

How A Multi-Layer Neural Network Works?

- The **inputs** to the network correspond to the attributes measured for each training tuple
- Inputs are fed simultaneously into the units making up the **input layer**
- They are then weighted and fed simultaneously to a **hidden layer**
- The number of hidden layers is arbitrary, although usually only one
- The weighted outputs of the last hidden layer are input to units making up the **output layer**, which emits the network's prediction
- The network is **feed-forward** in that none of the weights cycles back to an input unit or to an output unit of a previous layer
- From a statistical point of view, networks perform **nonlinear regression**: Given enough hidden units and enough training samples, they can closely approximate any function


Neural Network as a Classifier

- **Weakness**
 - Long training time
 - Require a number of parameters typically best determined empirically, e.g., the network topology or "structure".
 - Poor interpretability: Difficult to interpret the symbolic meaning behind the learned weights and of "hidden units" in the network
- **Strength**
 - High tolerance to noisy data
 - Ability to classify untrained patterns
 - Well-suited for continuous-valued inputs and outputs
 - Successful on a wide array of real-world data
 - Algorithms are inherently parallel
 - Techniques have recently been developed for the extraction of rules from trained neural networks


Ứng dụng NN Dự báo bankruptcy

PGS.TS. Đỗ Phúc
Trí Nhân Data Science and Application Group
Year 2020

Dữ liệu: bankruptcy




Bankruptcy Prediction using NN




25

Bankruptcy Prediction using NN




26

Huấn luyện mạng NN




27

Vận hành mạng NN-fair bankruptcy



28

Vận hành mạng NN-strong bankruptcy



PGS.TS. Đỗ Phúc, 2020

29