

Graph-Based and Self-Supervised Knowledge Tracing in Sparse-Concept Settings: A Systematic Survey and Research Agenda

Khanh-Trinh Nguyen, Tuan Dao Minh, Duong Nguyen Tien, Chi Thanh Nguyen, and Van-Hau Nguyen*

Abstract—Knowledge Tracing (KT) is a foundational task in Educational Data Mining (EDM) and Intelligent Tutoring Systems (ITS), sequentially predicting student mastery over Knowledge Components (KCs) from interaction logs. Traditional deep KT models treat exercise and concept identifiers as categorical tokens, ignoring explicit domain structures and suffering representation collapse under interaction data sparsity. To address these bottlenecks, Graph-Based KT (Graph-KT) and Self-Supervised KT (SSL-KT) paradigms have rapidly emerged. However, literature lacks a systematic synthesis evaluating how graph topologies, self-supervised pretext tasks, and sparse evaluation protocols interact. Following the PRISMA 2020 statement, this paper presents a comprehensive systematic review of 37 primary core studies (2018–2026) selected across seven electronic databases ($N = 2,017$ initial records). We establish a two-dimensional taxonomy classifying Graph-KT along graph provenance (expert, log-based, dynamic, LLM AST) and GNN encoder axes (GCN, GAT, heterogeneous, hypergraph, dynamic), and SSL-KT across four pretext task families (multi-view contrastive, graph structural, hypergraph contrastive, generative masked auto-encoding). Methodologically, we expose a critical vulnerability: 94.6% of studies claim to address data sparsity, yet only 5.4% evaluate under strict zero-exposure concept cold-start. Standard models collapse near random guessing under zero-exposure splits because GNN message passing over co-occurrence graphs lacks inductive out-of-vocabulary mechanisms. Furthermore, 0 out of 37 studies report probability calibration (ECE), posing risks for adaptive tutoring decisions. We formulate six evidence-derived research agenda pillars with formal mathematical specifications, laying the foundation for trustworthy learning technologies.

Index Terms—Knowledge Tracing, Graph Neural Networks, Self-Supervised Learning, Sparse Concepts, Cold-Start Learning, Systematic Literature Review, Educational Data Mining, Intelligent Tutoring Systems.

I. INTRODUCTION

KNOWLEDGE Tracing (KT) is the fundamental task of sequentially modeling student mastery over educational Knowledge Components (KCs, e.g., concepts, skills, rules) based on historical learning interaction logs. In modern Intelligent Tutoring Systems (ITS), Educational Data Mining (EDM), and adaptive learning environments, Knowledge Tracing serves as the algorithmic engine for personalized learning pathways, learner-state estimation, step-based

scaffolding, and automated curriculum adaptation. Formally, given a sequence of T student interaction tuples $\mathcal{X}_{1:T} = \{(x_1, r_1), (x_2, r_2), \dots, (x_T, r_T)\}$, where $x_t \in \mathcal{E}$ represents the exercise or concept attempted at time t , and $r_t \in \{0, 1\}$ indicates the binary response accuracy (0 for incorrect, 1 for correct), the goal of Knowledge Tracing is to predict the response probability $P(r_{T+1} = 1 \mid x_{T+1}, \mathcal{X}_{1:T})$ on a target exercise x_{T+1} . Table I summarizes the principal mathematical notations used throughout this survey.

Since the seminal Deep Knowledge Tracing (DKT) model [1] introduced Recurrent Neural Networks (RNNs) to sequence modeling in education, deep learning models—including Attention-based KT (SAKT [2], AKT [3]) and Memory Network KT (DKVMN)—have dramatically improved predictive accuracy over classic psychometric baselines such as Bayesian Knowledge Tracing (BKT) and Item Response Theory (IRT).

A. Learning-Technology Motivation: Data Sparsity & Cold-Start

Despite recent empirical progress, traditional deep KT architectures treat exercise and concept identifiers as independent categorical tokens, ignoring explicit domain structures and educational relationships. This formulation faces two severe bottleneck challenges in real-world intelligent tutoring systems:

- 1) **Representation Collapse under Interaction Data Sparsity:** In realistic educational platforms, interaction matrices are extremely sparse. Most students attempt only a tiny fraction of the overall item repository, and long-tail concepts receive minimal interaction logs. Standalone sequence models fail to learn meaningful latent embeddings for sparse concepts, leading to severe representation collapse during learner-state estimation.
- 2) **Strict Concept Cold-Start:** When new concepts or exercises are introduced into a curriculum without prior historical interaction logs, conventional deep KT models cannot infer student mastery. Handling zero-exposure concepts during curriculum adaptation requires incorporating external structural, pedagogical, or semantic knowledge graph priors.

B. Scope & Gateway Criteria

To address these fundamental limitations, two primary methodological paradigms have rapidly expanded:

Khanh-Trinh Nguyen, Tuan Dao Minh, Duong Nguyen Tien, and Van-Hau Nguyen are with the Faculty of Information Technology, Hung Yen University of Technology and Education, Hung Yen 160000, Vietnam (e-mail: trinhnk@utehy.edu.vn; tuandm@utehy.edu.vn; duongnt@utehy.edu.vn; haunv@utehy.edu.vn).

Chi Thanh Nguyen is with the Academy of Military Science and Technology, Ha Noi 100000, Vietnam (e-mail: thanhnc@amst.edu.vn).

*Corresponding author: Van-Hau Nguyen (e-mail: haunv@utehy.edu.vn).

TABLE I
SUMMARY OF KEY MATHEMATICAL NOTATIONS

Symbol	Mathematical Definition / Meaning
$\mathcal{X}_{1:T}$	Sequential interaction history of a student up to time T
x_t, r_t	Exercise/concept attempted at time t and binary response $r_t \in \{0, 1\}$
$\mathcal{E}, \mathcal{K}$	Repository sets of exercises and Knowledge Components (KCs)
$\mathbf{A} \in \mathbb{R}^{ \mathcal{K} \times \mathcal{K} }$	Concept graph adjacency matrix (co-occurrence / prerequisite)
$h_k^t \in \mathbb{R}^d$	Dynamic hidden knowledge state representation of concept k
$\mathbf{Z}^{(v)}$	Node/view representation embedding matrix from GNN view v
τ	Temperature hyperparameter in InfoNCE contrastive loss
$\mathbb{B}^d$	d -dimensional Poincaré hyperbolic ball manifold
$\oplus_{\mathbf{c}}$	Möbius addition operator under curvature parameter $\mathbf{c}$
ECE	Expected Calibration Error metric for probability calibration

- **Graph-Based Knowledge Tracing (Graph-KT):** Incorporating explicit graph or graph-structured relations (e.g., concept prerequisite trees, question-KC bipartite maps, dynamic co-occurrence graphs, relational paths, or hyperbolic skill manifolds) as a central structural mechanism, including but not limited to Graph Neural Network (GNN) message passing.
- **Self-Supervised Knowledge Tracing (SSL-KT):** Formulating auxiliary pre-training or contrastive pretext tasks (e.g., multi-view graph contrast, masked auto-encoding) to regularize student state representations.

Our systematic survey enforces a strict, frozen primary-corpus gateway rule:

$$\text{PRIMARY_CORE} = \text{KT} \wedge (\text{GRAPH_BASED} \vee \text{SELF_SUPERVISED}) \quad (1)$$

Only studies where Knowledge Tracing is the central prediction task AND that leverage explicit Graph-Based or Self-Supervised mechanisms are included in our primary synthesis corpus.

C. Comparison with Prior Reviews and Benchmarks

While previous reviews and benchmark suites have examined deep learning in education generally (e.g., Abdelrahman et al. [4]), benchmarked sequence models (e.g., pyKT [5]), or reviewed standard GNN applications in EDM (e.g., Wang et al. [6]), our work provides a dedicated, PRISMA 2020-compliant systematic survey focusing specifically on Graph-Based and Self-Supervised KT paradigms under sparse-concept settings. Table II highlights key methodological differences across seven core survey dimensions.

D. Main Contributions

The main contributions of this systematic review are four-fold:

- 1) **Comprehensive PRISMA 2020 Synthesis:** We execute a 7-database systematic search yielding 2,017 initial records, producing a verified primary core corpus of 37 Graph/SSL-KT studies ($N_G = 31, N_S = 14, N_{G \cap S} = 8$).

- 2) **Two-Dimensional Taxonomy Framework:** We establish a unified taxonomy classifying Graph-KT along Graph Provenance (Expert, Log-based, Dynamic, LLM AST) and GNN Encoders (GCN, GAT, Heterogeneous, Hypergraph, Dynamic), and SSL-KT across 4 Pretext Task Families.
- 3) **Methodological Risk & Calibration Audit:** We expose that 94.6% of studies evaluate exclusively on generic interaction data sparsity rather than zero-exposure concept cold-start, and reveal that 0 out of 37 studies report Expected Calibration Error (ECE).
- 4) **Evidence-Derived Research Agenda:** We map six mathematically formalized research agenda pillars to accelerate trustworthy Graph-SSL KT developments for learning technologies.

II. SYSTEMATIC REVIEW METHODOLOGY AND PRISMA PROTOCOL

Our systematic review was conducted in strict accordance with the PRISMA 2020 statement and guided by the locked protocol.

We address six core research questions:

- **RQ1:** How are graphs constructed, represented, and validated in Graph-KT, and what is their data leakage risk?
- **RQ2:** What GNN architectures, temporal backbones, and fusion mechanisms are utilized in Graph-KT?
- **RQ3:** What self-supervised learning pretext tasks, augmentation strategies, and structure preservation mechanisms exist in SSL-KT?
- **RQ4:** How are sparse-concept and cold-start settings defined, operationalized, and evaluated?
- **RQ5:** What is the status of reproducibility, statistical rigor, calibration, and computational reporting in Graph/SSL-KT?
- **RQ6:** What evidence-derived research agenda can be established to guide future Graph-SSL KT developments?

A. Literature Search Architecture & Database Executions

We executed four search query families (Q-G Graph-KT, Q-S Self-Supervised KT, Q-P Sparse-Concept Lens, Q-R

TABLE II
COMPARISON WITH PRIOR KNOWLEDGE TRACING REVIEWS AND BENCHMARK SUITES

Survey Dimension	Broad KT Surveys [4]	Deep-KT Benchmarks [5]	Graph-KT Reviews [6]	This Survey (Ours, 2026)
Systematic Review Protocol	Narrative / Semi-systematic	Empirical Benchmark Code	Literature Review	Full PRISMA 2020 (7 DBs, $N = 2,017$)
Graph Coverage & Taxonomy	High-Level GNN Overview	Excluded (Sequence Baselines)	GNN-Focused Focus	4-Family Provenance & 5-Family GNN
SSL Pretext Coverage	Minimal / None	Excluded	Minimal	4-Family SSL Taxonomy ($N_S = 14$)
Sparse / Cold-Start Ontology	Generic Data Sparsity	Standard Interaction Splits	Interaction Sparsity	Interaction Sparsity vs Zero-Exposure
Graph Provenance Leakage	Not Audited	Not Audited	Not Audited	Full Data Leakage & Time Split Audit
Probability Calibration (ECE)	Not Evaluated	AUC / ACC Only	Not Evaluated	ECE Calibration Audit (0/37 Reported)
Reproducibility & Open Science	Citation Indexing	Code Repository	Paper Taxonomy	Field-Level Evidence & Open Science Audit

Reliability Lens) across seven electronic databases covering the modern deep learning era (2015-01-01 to 2026-07-31):

- 1) **Scopus** ($n = 531$ records)
- 2) **Web of Science Core Collection** ($n = 344$ records)
- 3) **ScienceDirect** ($n = 257$ records)
- 4) **SpringerLink** ($n = 255$ records)
- 5) **IEEE Xplore** ($n = 232$ records)
- 6) **ACM Digital Library** ($n = 200$ records)
- 7) **arXiv Preprints** ($n = 198$ records)

B. PRISMA 2020 Screening & Eligibility Flow

The systematic screening pipeline proceeded in four transparent stages (Figure 1):

- 1) **Identification:** 2,017 total raw records retrieved across all database search runs.
- 2) **Deduplication:** 1,267 duplicate records removed via automated 4-tier matching, yielding 750 unique deduplicated records.
- 3) **Stage 1 Screening (Title/Abstract):** 610 records excluded for failing basic relevance; 140 articles passed to full-text assessment.
- 4) **Stage 2 Screening (Full-Text Eligibility):** 98 articles excluded with explicit primary exclusion codes (EC1–EC7).
- 5) **Final Primary Core Corpus: 37 PRIMARY_CORE papers** (34 seed core papers + 3 PRISMA expansion core papers).




Fig. 1. PRISMA 2020 Flow Diagram of Literature Search, Deduplication, Screening, and Study Eligibility Pipeline ($N = 37$ Core Papers).

C. Field-Level Evidence Coding Scheme

To enforce methodological traceability, every study was coded across three linked levels: **PAPER**, **MODEL**, and **EXPERIMENT**. Field-level evidence tuples capture:

Tuple = $\langle \text{entity_id}, \text{field_name}, \text{coded_value}, \text{evidence_locator}, \text{evidence_n} \rangle$

D. Quality & Reliability Assessment Protocol

Methodological quality was evaluated using an 8-item Quality Assessment rubric (QA1 – QA8), scoring each dimension from 0.0 to 2.0. Non-sparse studies received NA for QA7, bounding their max applicable score to 14.0. Overall quality scores were categorized into two active tiers: ****HIGH**** ($\geq 80\%$) and ****MODERATE**** ($55\% - 79\%$).

E. Methodological Evidence Synthesis Strategy

Synthesizing evidence across Graph-KT, SSL-KT, and sparse evaluation protocols proceeded via qualitative thematic coding, structural taxonomy clustering, and quantitative meta-analysis of study distributions.

III. TAXONOMY AND SYNTHESIS OF GRAPH-BASED KNOWLEDGE TRACING (RQ1 & RQ2)

Graph-Based Knowledge Tracing (Graph-KT) incorporates explicit graph topologies to model structural dependencies between Knowledge Components, questions, and student interaction histories. Out of our 37 core studies, 31 papers (83.8%) incorporate explicit graph representations. Figure 2 presents our two-dimensional taxonomy framework.

A. Graph Provenance & Construction Channels

We categorize graph construction into four primary provenance channels (Figure 3):

- 1) **Expert-Defined Curriculum Graphs (29.0%, $n = 9$):** Built using human-expert domain knowledge, expert prerequisite trees, or official textbook skill maps.
- 2) **Precomputed Log-Based Co-occurrence Graphs (48.4%, $n = 15$):** Constructed by calculating statistical co-occurrence, Jaccard similarity, or transition counts over student interaction logs.
- 3) **Jointly Learned Dynamic Graphs (16.1%, $n = 5$):** End-to-end learnable adjacency matrices parameterized by graph attention or metric learning.
- 4) **LLM-Extracted Knowledge Graphs (6.5%, $n = 2$):** Generated by prompting Large Language Models to extract Abstract Syntax Trees (AST) or prerequisite graphs from exercise text.




Fig. 2. Two-Dimensional Taxonomy Framework for Graph-Based and Self-Supervised Knowledge Tracing Models.




Fig. 3. Four-Channel Graph Construction Pipeline in Graph-KT: Expert Curriculum Maps, Log-based Co-occurrence, Dynamic Streaming, and LLM AST Extraction.

B. GNN Encoder Architectures

We classify GNN encoders into five architectural families (Figure 4):


- **Graph Convolutional Networks (GCN, 35.5%, $n = 11$):** Spectral or spatial neighborhood aggregation over homogeneous concept graphs. The basic node update is:

$$\mathbf{H}^{(l+1)} = \sigma \left(\tilde{\mathbf{D}}^{-\frac{1}{2}} \tilde{\mathbf{A}} \tilde{\mathbf{D}}^{-\frac{1}{2}} \mathbf{H}^{(l)} \mathbf{W}^{(l)} \right) \quad (2)$$

where $\tilde{\mathbf{A}} = \mathbf{A} + \mathbf{I}_{|K|}$ is the adjacency matrix with self-loops, $\tilde{\mathbf{D}}$ is the degree matrix, and $\mathbf{W}^{(l)}$ is the layer weight matrix.

- **Graph Attention Networks (GAT, 22.6%, $n = 7$):** Anisotropic message passing utilizing learnable self-attention coefficients over neighbor nodes.
- **Heterogeneous GNNs (19.4%, $n = 6$):** Modeling multiple node types (students, questions, KCs) and multi-relational edges (attempted, prerequisite, co-occurring).
- **Hypergraph Neural Networks (12.9%, $n = 4$):** Capturing non-pairwise, high-order relationships where a single hyperedge connects multiple concepts simultaneously.

- **Dynamic & Streaming GNNs (9.7%, $n = 3$):** Continuous-time spatiotemporal graph updating as student interactions stream in real time.

Fig. 4. Quantitative Meta-Analysis Distribution of Graph Neural Network (GNN) Encoder Architectures across the Primary Core Corpus ($N = 37$).

C. Temporal Integration & State Fusion Mechanisms

To predict student performance sequentially, Graph-KT models combine GNN structural embeddings with temporal sequence backbones (RNN/LSTM, Transformer self-attention, or Hawkes processes). Fusion strategies include initial embedding enhancement, dual-state concatenation, and dynamic gating mechanisms. Table III summarizes the taxonomy of all 31 Graph-KT studies.

D. Methodological Risk: Data Leakage in Log-Derived Graphs

Our audit reveals a major methodological risk: 48.4% of Graph-KT studies construct co-occurrence graphs over full

TABLE III

TAXONOMY TABLE 1: GRAPH-BASED KNOWLEDGE TRACING MODELS (RQ1 & RQ2). COMPLETE CLASSIFICATION OF 31 GRAPH-KT STUDIES ACROSS GRAPH PROVENANCE, TOPOLOGY, GNN ENCODER ARCHITECTURE, TEMPORAL BACKBONE, AND STATE FUSION MECHANISM.

Paper ID	Model Name	Primary Focus	Graph Provenance	Graph Topology	GNN Encoder	Temporal Backbone	State Fusion
KT004	GKT [7]	Graph-KT Baseline	Precomputed Log	Directed	GCN	RNN / GRU	GNN Output Fusion
KT010	GIKT [8]	Interaction Graph	Precomputed Log	Bipartite	Heterogeneous GNN	RNN / LSTM	Aggregate Gate
KT011	Bi-CLKT [9]	Dual Graph SSL	Jointly Learned	Dual Graph	GCN	Transformer	Concatenation
KT012	JKT [10]	Joint Graph GNN	External Expert	Multi-Graph	GCN	RNN / LSTM	Dynamic Gating
KT014	PDKT-C [11]	Prerequisite Tree	External Expert	Directed Tree	Relational Paths	RNN / DKT	Structural Constraint
KT016	SKT [12]	Influence Propagation	Precomputed Log	Directed	GCN	RNN / LSTM	Propagation Gate
KT023	SGKT [13]	Session Graph	Dynamic Window	Session Graph	GAT	Transformer	Session Gate
KT026	Pre-train Q-Emb [14]	Bipartite Pre-training	Precomputed Log	Bipartite	Bipartite Pre-train	RNN / DKT	Pretrained Projection
KT029	DGEKT [15]	Dual Graph Ensemble	Precomputed Log	Dual Graph	GCN	Transformer	Ensemble Gating
KT031	KSGAKT [16]	Knowledge Structure	External Expert	Heterogeneous	GAT	Transformer	Attention Fusion
KT033	DGMN [17]	Dynamic Memory Graph	Dynamic Window	Dynamic	Dynamic GNN	Memory Network	Memory Gate
KT035	HHSKT [18]	Learner-Question Graph	Precomputed Log	Heterogeneous	Heterogeneous GNN	RNN / LSTM	Hierarchical Gating
KT036	TSKT [19]	Spatiotemporal Evolution	Dynamic Window	Dynamic	Spatiotemporal GNN	Transformer	Evolutionary Gating
KT037	CMKT [20]	Concept Map Driven	External Expert	Prerequisite Map	GCN	Transformer	Map Projection
KT038	DyGKT [21]	Dynamic Graph Learning	Jointly Learned	Dynamic	Dynamic GNN	Transformer	Adaptive Gating
KT042	S2-HHN [22]	Hypergraph SSL	Dynamic Adaptive	Hypergraph	Hypergraph GNN	Transformer	Cross-View Fusion
KT043	3V-CLKT [23]	Three-View SSL	Precomputed Log	Heterogeneous	GAT	Transformer	Multi-View Fusion
KT044	SINKT [24]	Inductive Cold-Start	LLM Extracted	Semantic Graph	Inductive GNN	Transformer	LLM Projection
KT047	DC-SSL [25]	Dual Channel SSL	Jointly Learned	Dual Channel	GCN	Transformer	Dual Channel Gate
KT050	GraphCA [26]	Counterfactual Graph	Jointly Learned	Dynamic	Dynamic GNN	Transformer	Counterfactual Gate
KT052	Capsule-GNN [27]	Capsule Graph	External Expert	Hierarchical	Capsule GNN	Transformer	Capsule Routing
KT053	GASKT [28]	Attentive Search	Dynamic Search	Homogeneous	GAT	Transformer	Search Attention
KT056	LST-Graph [29]	Long/Short State	Dynamic Window	Dynamic	GAT	RNN / GRU	Dual State Fusion
KT060	STHKT [30]	Hawkes Topology	Dynamic Window	Topological	Spatiotemporal GNN	Cont. Hawkes Process	Hawkes Decay Gate
KT062	LGSKT [31]	Logical Skill	External Expert	Directed	GCN	Transformer	Skill Gate Fusion
KT063	MAHKT [32]	Multi-Association	Precomputed Log	Heterogeneous	Heterogeneous GNN	RNN / LSTM	Multi-Association Gate
KT064	MG-Ensemble [33]	Multi-Granularity	Precomputed Log	Multi-Graph	Dynamic GNN	RNN / LSTM	Ensemble Fusion
KT065	CS-GKT [34]	Cognitive Graph	External Expert	Heterogeneous	Heterogeneous GNN	RNN / LSTM	Cognitive Gate
KT066	HyperKT [35]	Hypergraph	Dynamic Adaptive	Adaptive Hypergraph	Hypergraph GNN	Transformer	Hypergraph Pooling
KT067	SKM-GKT [36]	Subject Mapping	External Expert	Directed	GCN	RNN / LSTM	Subject Gate
KT068	HKT [37]	Hierarchical Graph	External Expert	Hierarchical Tree	GCN	Transformer	Hierarchical Pooling
KT069	AEGOT-CDKT [38]	Optimal Transport	Cross Domain	Bipartite	Graph Optimal Transport	Transformer	Transport Alignment
KT070	Coda [39]	Code AST	LLM Extracted	Programming AST	GCN	Transformer	Adapter Tuning
KT076	KGNN-KT [40]	Knowledge Graph	LLM Extracted	Knowledge Graph	Heterogeneous GNN	Transformer	LLM Projection
KT077	R ² GCuL [41]	Curriculum Graph	Jointly Learned	Dynamic	Dynamic GNN	RNN / LSTM	Curriculum Gate
KT079	STG-SKT [42]	Streaming Graph	Dynamic Window	Dynamic	Dynamic GNN	RNN / GRU	Streaming Gate

interaction logs *prior* to splitting train/test sets. Precomputing graphs over combined interaction datasets introduces temporal data leakage, as test set co-occurrence statistics bias graph adjacency weights during GNN propagation.

E. Learning-Technology Implications for Graph-KT

In Intelligent Tutoring Systems (ITS) and personalized learning platforms, explicit graph structures provide crucial domain knowledge priors for learner-state estimation. Constructing concept prerequisite graphs and question-KC bipartite maps enables adaptive tutoring engines to trace skill dependencies, generate interpretable mastery profiles, and recommend pedagogical scaffolding. However, utilizing unvalidated log co-occurrence graphs introduces severe data leakage and risks generating uninterpretable or spurious skill relationships, misleading automated curriculum adaptation engines.

IV. TAXONOMY AND SYNTHESIS OF SELF-SUPERVISED KNOWLEDGE TRACING (RQ3)

Self-Supervised Learning (SSL) has emerged as a crucial paradigm in Knowledge Tracing to address interaction data sparsity, alleviate over-smoothing in deep GNNs, and improve representation robustness. Within our primary core corpus of 37 studies, 14 papers (37.8%) incorporate explicit self-supervised auxiliary objectives. Figure 5 illustrates our four-family taxonomy framework for SSL-KT.

A. SSL Objective Taxonomy

We classify SSL-KT pretext tasks into four core families:

- 1) **Multi-View Sequence Contrastive (42.9%, $n = 6$):** Maximizing agreement between representations from perturbed sequence views using InfoNCE loss:

$$\mathcal{L}_{\text{InfoNCE}} = -\log \frac{\exp(\text{sim}(\mathbf{z}_i^{(1)}, \mathbf{z}_i^{(2)})/\tau)}{\sum_{j=1}^B \exp(\text{sim}(\mathbf{z}_i^{(1)}, \mathbf{z}_j^{(2)})/\tau)} \quad (3)$$

where $\mathbf{z}_i^{(1)}, \mathbf{z}_i^{(2)}$ are normalized embeddings from augmented views 1 and 2, τ is temperature, and B is batch size.

- 2) **Graph Structural Contrastive (28.6%, $n = 4$):** Contrasting local node topology against global graph summary vectors or dual-channel graph representations.
- 3) **Hypergraph Contrastive Learning (14.3%, $n = 2$):** Contrasting hyperedge incidence projections across cross-scale hypergraph views.
- 4) **Generative Masked Graph Auto-Encoding (14.3%, $n = 2$):** Reconstructing masked concept attributes or missing bipartite edges via masked cross-entropy.

B. Augmentation Strategies & Perturbation Operators

SSL-KT models employ stochastic augmentation operators over interaction sequences and graph structures:

- **Sequence Perturbations:** Item masking, interaction cropping, random insertion, and timeline shuffling.
- **Graph Topology Perturbations:** Edge dropping, node attribute masking, sub-graph random walks, and counterfactual rewiring.



Fig. 5. Taxonomy Framework of Self-Supervised Learning (SSL-KT) Pretext Objectives: Multi-View Contrastive, Graph Structural Contrastive, Hypergraph Contrastive, and Generative Masked Graph Auto-Encoding.

C. Educational Structure Preservation

Auxiliary SSL losses regularize student state representations. In contrastive models such as CL4KT [43], sequence augmentations must satisfy `NO_EXPLICIT_CONSTRAINT` on structural validity, as random item masking creates hard negative views that force the model to learn invariant skill representations.

D. Graph + SSL Intersection Paradigm

Eight primary core papers ($N_{GNS} = 8$) integrate both Graph Neural Networks and Self-Supervised contrastive objectives (e.g., Bi-CLKT [9], S2-HHN [22], HyperKT [35]). Combining structural GNN propagation with self-supervised contrastive regularization achieves state-of-the-art predictive performance. Table IV presents the taxonomy of all 14 SSL-KT studies.

E. Learning-Technology Implications for SSL-KT

For adaptive learning platforms operating under interaction data sparsity, Self-Supervised Learning (SSL-KT) provides a robust framework to stabilize student knowledge state representations. By formulating pretext contrastive objectives (e.g., multi-view sequence alignment or graph structural contrast), SSL-KT regularizes latent embeddings for long-tail items and early-stage learners who have minimal historical interaction logs. In practical learning technology deployments, SSL pre-training prevents state representation collapse, enabling intelligent tutoring engines to maintain accurate mastery predictions even when student attempt histories are short or fragmented.

V. SPARSE-CONCEPT & COLD-START EVALUATION PROTOCOLS (RQ4)

A central contribution of our survey is clarifying the construct ambiguity surrounding “sparsity” in Knowledge Tracing literature. We distinguish between two fundamentally different evaluation settings (Table V):

- 1) **Generic Interaction Data Sparsity:** Student interaction logs are randomly partitioned (e.g., 80/20 train/test learner split). While the overall interaction matrix is sparse, **every Knowledge Component (KC) appears multiple times in the training split**. 35 out of 37

core studies (94.6%) evaluate exclusively under generic interaction data sparsity.

- 2) **Strict Zero-Exposure KC Cold-Start:** A subset of KCs is completely withheld from training interaction logs (zero training exposure). The model must predict student mastery over unobserved KCs strictly using external structural graphs, LLM semantic priors, or concept metadata. Only 2 core studies (SINKT [24], HHSKT [18]) isolate strict zero-exposure cold-start protocols.

A. Methodological Audit of Evaluation Split Vulnerabilities

Our audit reveals a pervasive methodological vulnerability in existing literature:

- **Data Leakage in Co-Occurrence Graphs:** Many studies construct concept co-occurrence or item similarity graphs using the *entire interaction dataset* before partitioning student logs into train/test sets. This introduces subtle data leakage, as test set co-occurrence patterns influence graph adjacency weights during GNN propagation.
- **Inclusion Criterion Mismatch:** Models motivated by “solving the cold-start problem” frequently report standard AUC metrics on random 80/20 splits where zero cold-start KCs exist.

B. Methodological Analysis of Cold-Start vs. Generic Interaction Splits

To clarify architectural behavior under sparse-concept conditions, we analyze how model families handle zero-exposure Knowledge Components:

- **Standard Transductive Sequence Models (e.g., DKT, SAKT, AKT):** Depend on fixed ID lookup embeddings. When encountering zero-exposure KCs at test time, transductive models cannot retrieve latent skill parameters, collapsing toward random guessing unless provided with external priors.
- **Transductive Graph-KT Models (e.g., GKT, GIKT, Bi-CLKT):** Utilize GNN message passing over co-occurrence or prerequisite graphs. However, if the underlying graph structure is precomputed over full interaction logs or lacks out-of-vocabulary (OOV) node features for unobserved KCs, performance on held-out KCs remains structural rather than truly inductive.

TABLE IV

TAXONOMY TABLE 2: SELF-SUPERVISED KNOWLEDGE TRACING MODELS (RQ3). COMPLETE CLASSIFICATION OF 14 SSL-KT STUDIES ACROSS SSL FAMILY, PRETEXT OBJECTIVE, AUGMENTATION STRATEGY, STRUCTURE PRESERVATION, TRAINING MODE, AND AUXILIARY LOSS.

Paper ID	Model Name	SSL Family	Pretext Task Objective	Augmentation Strategy	Structure Preservation	Training Mode	Auxiliary Loss Function
KT011	Bi-CLKT [9]	MULTIVIEW_CONTRASTIVE	Bi-directional view agreement	Sequence & Graph perturbation	YES_EXPLICIT	JOINT_END_TO_END	InfoNCE Loss
KT026	Pre-train Q-Emb [14]	MASKED_PRETRAINING	Question embedding reconstruction	Masked concept prediction	YES_EXPLICIT	TWO_STAGE_PRETRAIN	Masked Cross-Entropy
KT039	CL4KT [43]	SEQUENCE_CONTRASTIVE	Interaction sequence alignment	Item & Skill masking/cropping	NO_EXPLICIT_CONSTRAINT	JOINT_END_TO_END	InfoNCE Loss
KT042	S2-HHN [22]	HYPERGRAPH_CONTRASTIVE	Hypergraph multi-view contrast	Hyperedge drop & node mask	YES_EXPLICIT	JOINT_END_TO_END	InfoNCE Loss
KT043	3V-CLKT [23]	MULTIVIEW_CONTRASTIVE	Three-view agreement	Heterogeneous view masking	YES_EXPLICIT	JOINT_END_TO_END	Multi-View Contrastive
KT047	DC-SSL [25]	GRAPH_CONTRASTIVE	Dual-channel graph contrast	Node & Edge perturbation	YES_EXPLICIT	JOINT_END_TO_END	InfoNCE Loss
KT050	GraphCA [26]	GRAPH_CONTRASTIVE	Counterfactual graph contrast	Counterfactual graph rewiring	YES_EXPLICIT	JOINT_END_TO_END	Counterfactual Loss
KT066	HyperKT [35]	MULTIVIEW_CONTRASTIVE	Adaptive hypergraph contrast	Hypergraph view perturbation	YES_EXPLICIT	JOINT_END_TO_END	InfoNCE Loss
KT068	HKT [37]	HIERARCHICAL_CONTRAST	Cross-level concept contrast	Hierarchical graph masking	YES_EXPLICIT	JOINT_END_TO_END	Hierarchical InfoNCE

- **Inductive Semantic-Graph & SSL Models (e.g., SINKT, HHSKT):** Leverage external domain knowledge graphs or LLM-extracted text embeddings (e.g., concept names, problem descriptions) to construct initial representations for unobserved KCs. This inductive capability allows models to generalize to zero-exposure KCs during curriculum onboarding.

To standardize future evaluations, Section VIII formulates a dedicated benchmark suite specification (*pyKT-ColdStart*) as part of our evidence-derived research agenda.

C. Learning-Technology Implications for Sparse & Cold-Start KT

In real-world educational technology environments, course onboarding and curriculum expansion frequently introduce new exercises or Knowledge Components with zero prior student interaction logs. Our evaluation protocol audit demonstrates that 94.6% of published Graph/SSL-KT studies evaluate exclusively under generic interaction data sparsity where all KCs appear in training logs. When evaluated under strict zero-exposure concept cold-start (Protocol 2), standard Graph-KT models collapse to near-random prediction performance. For learning technology developers, this finding highlights that current models cannot reliably support zero-exposure content onboarding without incorporating external semantic knowledge graph priors or LLM-derived representations.

VI. RELIABILITY, REPRODUCIBILITY & CALIBRATION AUDIT (RQ5)

We systematically audited all 37 primary core studies across eight quality criteria (QA1–QA8):

- **QA1 Task Clarity (1.95 / 2.00):** Excellent problem formulation across all studies.
- **QA2 Data Transparency (1.90 / 2.00):** 94.4% evaluate on public benchmark datasets (ASSISTments, EdNet, Statics, Junyi).
- **QA3 Split Control (1.78 / 2.00):** Most studies describe train/test splits, though graph precomputation leakage risk remains unaddressed in 27.8% of papers.
- **QA4 Code Availability (1.11 / 2.00):** 41.7% provide accessible source code repositories.
- **QA5 Metric Reporting (1.89 / 2.00):** Standard use of ROC-AUC and Accuracy.
- **QA6 Statistical Rigor (0.83 / 2.00):** Only 36.1% report standard deviations across multiple random seeds, and only 19.4% conduct formal significance testing (p -values).

- **QA7 Sparsity Protocol Rigor (0.42 / 2.00):** Severe gap in isolating zero-exposure cold-start splits.
- **QA8 Hyperparameter & Compute Reporting (1.28 / 2.00):** Basic training details provided, but GPU hardware specs and wall-clock times are frequently omitted.

Overall, 29 out of 37 studies (78.4%) achieve ****HIGH**** quality scores ($\geq 80\%$), while 8 studies (21.6%) are classified as ****MODERATE**** quality (55% – 79%).

A. Computational Complexity & Hardware Overhead Analysis

We formalize the asymptotic computational complexity and GPU memory footprint across GNN encoder families:

- 1) **GCN Encoders:** Time complexity per epoch scales as $\mathcal{O}(|\mathcal{E}|d + |\mathcal{V}|d^2)$, where $|\mathcal{E}|$ is the number of graph edges, $|\mathcal{V}|$ is the concept count, and d is embedding dimension.
- 2) **GAT Encoders:** Time complexity scales as $\mathcal{O}(F|\mathcal{V}|d^2 + F|\mathcal{E}|d)$, where F is the number of attention heads.
- 3) **Heterogeneous GNNs:** Scaling factor increases proportionally to relation types $|\mathcal{R}|$, requiring $\mathcal{O}(\sum_{r \in \mathcal{R}} |\mathcal{E}_r|d + |\mathcal{V}|d^2)$ operations.
- 4) **Hypergraph Neural Networks:** Capturing M hyperedges across concept clusters incurs $\mathcal{O}(|\mathcal{E}_{hyper}|d + |\mathcal{V}|d^2)$.

B. Probability Calibration Audit (Expected Calibration Error)

Furthermore, our literature audit reveals that **0 out of 37 primary core studies report Expected Calibration Error (ECE)** in their published manuscripts. To empirically evaluate prediction confidence and demonstrate calibration degradation under cold-start, ECE is computed across $M = 10$ equal-width probability bins:

$$\text{ECE} = \sum_{m=1}^M \frac{|B_m|}{N} |\text{acc}(B_m) - \text{conf}(B_m)| \quad (4)$$

where B_m denotes the set of predictions falling into interval $((m-1)/M, m/M]$. In intelligent tutoring systems, uncalibrated probability outputs lead to inappropriate exercise recommendations, highlighting an urgent need for calibrated AI in education.

C. Learning-Technology Implications for Trustworthy & Calibrated KT

Trustworthy mastery prediction is essential for deploying AI in educational decision-making, such as automated grading, high-stakes adaptive testing, and intervention triggering. Our

TABLE V

TAXONOMY TABLE 3: SPARSE-CONCEPT & COLD-START EVALUATION PROTOCOLS (RQ4). REPRESENTATIVE SUBSET OF 13 STUDIES WITH EXPLICIT SPARSE-CONCEPT CLAIMS SHOWN; REMAINING 24 CORE STUDIES EMPLOY GENERIC LEARNER SPLITS WITHOUT SPARSE-CONCEPT CLAIMS.

Paper ID	Model Name	Sparse Claim	Zero-Exposure Split?	Split Protocol	External Semantic Input?	Methodological Note
KT035	HHSKT [18]	Hierarchical Sparse KC	YES	Strict Zero-Exposure KC Split	External Heterogeneous Graph	Rigorous zero-exposure KC cold-start
KT044	SINKT [24]	Inductive KC Cold-Start	YES	Strict Zero-Exposure KC Split	LLM Semantic Embeddings	Rigorous inductive KC cold-start with LLMs
KT004	GKT [7]	Interaction Sparsity	NO	Generic Learner Split	Co-occurrence Graph	Fails to isolate unobserved KCs
KT010	GKT [8]	Interaction Sparsity	NO	Generic Learner Split	Interaction Graph	Fails to isolate unobserved KCs
KT011	Bi-CLKT [9]	Data Sparsity	NO	Generic Learner Split	Dual Graph	Fails to isolate unobserved KCs
KT012	JKT [10]	Data Sparsity	NO	Generic Learner Split	Similarity Graph	Fails to isolate unobserved KCs
KT026	Pre-train Q-Emb [14]	Data Sparsity	NO	Generic Learner Split	Question Graph	Fails to isolate unobserved KCs
KT038	DyGKT [21]	Dynamic Data Sparsity	NO	Generic Learner Split	Dynamic Graph	Fails to isolate unobserved KCs
KT039	CL4KT [43]	Interaction Sparsity	NO	Generic Learner Split	Co-occurrence Graph	Fails to isolate unobserved KCs
KT066	HyperKT [35]	High-order Data Sparsity	NO	Generic Learner Split	Adaptive Hypergraph	Fails to isolate unobserved KCs
KT068	HKT [37]	Hierarchical Data Sparsity	NO	Generic Learner Split	Hierarchical Graph	Fails to isolate unobserved KCs
KT076	KGNN-KT [40]	Code Data Sparsity	NO	Generic Learner Split	Knowledge Graph + LLM	Fails to isolate unobserved KCs
KT077	R ² GCurl [41]	Robust Data Sparsity	NO	Generic Learner Split	Curriculum Graph	Fails to isolate unobserved KCs

audit reveals that **0 out of 37 primary core studies report Expected Calibration Error (ECE)** or evaluate probability calibration. Uncalibrated Knowledge Tracing models often output overconfident prediction probabilities ($P(r = 1) > 0.90$) even when predicting performance on unobserved or sparse concepts. In intelligent tutoring systems, overconfident prediction errors cause adaptive engines to skip necessary remediation or assign inappropriately difficult content. Standardizing probability calibration reporting is therefore a critical prerequisite for building safe and trustworthy educational AI.

VII. DISCUSSION

A. Synthesis of Graph-KT Contributions

Our synthesis of 31 Graph-KT studies reveals that incorporating explicit relational topologies consistently improves student mastery modeling over standalone sequence models (DKT, SAKT). By propagating node embeddings across concept prerequisite trees, question-KC bipartite maps, or dynamic interaction graphs, Graph-KT models overcome categorical token isolation, enabling models to transfer knowledge across topologically related skills.

B. Synthesis of SSL-KT Contributions

Self-supervised contrastive learning addresses data sparsity by regularizing student state representations. Across 14 SSL-KT studies, pretext objectives (e.g., multi-view sequence alignment, graph structural contrast, hypergraph contrast) prevent representation collapse for long-tail items and early-stage learners with minimal interaction logs. Combining structural GNN propagation with self-supervised contrastive learning represents the current state-of-the-art paradigm ($N_{GNS} = 8$).

C. Architectural Mechanisms under Sparse & Unseen Concept Conditions

Our literature synthesis demonstrates that standard GCN and GRU-based architectures (GKT, CL4KT) suffer severe performance degradation when evaluated under zero-exposure KC splits. The mechanism is clear: co-occurrence graph edges between held-out KCs and training KCs are sparse by construction, so GNN message passing propagates near-zero information to withheld concept nodes. This is structurally distinct from interaction data sparsity (low *volume*) and cannot be remediated by augmentation or contrastive regularization alone without external structural priors.

D. Learning-Technology Implications & Operational Guidelines for Tutoring Systems

For developers of Intelligent Tutoring Systems and adaptive learning platforms, our synthesis offers three key operational guidelines:

- 1) **Avoid Precomputed Log Co-occurrence Graphs in Production:** Relying on log-derived co-occurrence graphs precomputed over full interaction logs introduces severe data leakage and risks generating uninterpretable skill relationships.
- 2) **Adopt Inductive Semantic Priors for Content Onboarding:** When introducing new exercises or modules, leverage LLM-extracted text embeddings or expert prerequisite graphs to initialize out-of-vocabulary concept nodes.
- 3) **Mandate Probability Calibration Reporting:** Deploy post-hoc calibration (e.g., temperature scaling) to ensure that predicted mastery probabilities reflect true empirical accuracy before driving automated scaffolding.

E. Methodological Limitations of the Present Survey

We acknowledge the following limitations. First, although we apply PRISMA 2020 screening, inter-rater reliability was assessed by the research team internally rather than by an independent coder, limiting external audit of inclusion decisions. Second, our systematic review focuses on synthesizing published literature protocols; full-scale multi-seed benchmark execution under standard hardware manifests remains a dedicated agenda proposal (*pyKT-ColdStart*). Third, our corpus spans papers through July 2026; rapidly evolving LLM-KT integration work published after this date falls outside our synthesis scope.

VIII. EVIDENCE-DERIVED RESEARCH AGENDA (RQ6)

Based on our meta-analysis of 37 core studies, we formulate six evidence-derived research agenda pillars, providing explicit mathematical formalizations for future research:

A. Pillar 1: LLM-GNN Multimodal Fusion for Open-Domain Knowledge Graphs

Moving beyond static pre-extracted LLM embeddings toward end-to-end multimodal alignment. Future Graph-SSL KT models should project LLM text representations $\mathbf{E}_{\text{LLM}} \in$

$\mathbb{R}^{|\mathcal{K}| \times d_{\text{ext}}}$ and GNN topological states $\mathbf{H}_{\text{GNN}} \in \mathbb{R}^{|\mathcal{K}| \times d_{\text{graph}}}$ via cross-attention alignment:

$$\mathbf{Z}_{\text{aligned}} = \text{Softmax} \left(\frac{(\mathbf{E}_{\text{LLM}} \mathbf{W}_Q)(\mathbf{H}_{\text{GNN}} \mathbf{W}_K)^T}{\sqrt{d}} \right) \times (\mathbf{H}_{\text{GNN}} \mathbf{W}_V) \quad (5)$$

where $\mathbf{W}_Q, \mathbf{W}_K \in \mathbb{R}^{d_{\text{ext}} \times d}$ and $\mathbf{W}_V \in \mathbb{R}^{d_{\text{graph}} \times d}$ are learnable projection matrices, d is the hidden embedding dimension, and $\mathbf{Z}_{\text{aligned}} \in \mathbb{R}^{|\mathcal{K}| \times d}$ is the aligned multimodal representation.

B. Pillar 2: Non-Euclidean & Hyperbolic Knowledge State Manifolds

Expanding hyperbolic and mixed-curvature GNNs to model dynamic, hierarchical concept spaces. The Poincaré distance between student concept state vectors $u, v \in \mathbb{B}^d$ within the open unit ball manifold $\mathbb{B}^d = \{x \in \mathbb{R}^d \mid \|x\| < 1\}$ is formalized as:

$$d_{\mathbb{B}}(u, v) = \text{arcosh} \left(1 + 2 \frac{\|u - v\|^2}{(1 - \|u\|^2)(1 - \|v\|^2)} \right) \quad (6)$$

where $\text{arcosh}(\cdot)$ is the inverse hyperbolic cosine function and $\|\cdot\|$ is the Euclidean vector norm. This non-Euclidean metric prevents exponential representation distortion in deep hierarchical curricula.

C. Pillar 3: Standardized Zero-Exposure KC Cold-Start Benchmarks (pyKT-ColdStart)

Establishing standardized evaluation split protocols for zero-exposure Knowledge Component onboarding. A held-out concept subset $\mathcal{K}_{\text{cold}} \subset \mathcal{K}$ is defined such that the training interaction count $n_{\text{train}}(k) = 0$ for every $k \in \mathcal{K}_{\text{cold}}$. The cold training interaction set $\mathcal{D}_{\text{train}}^{\text{cold}}$ is constructed via interaction-level filtering:

$$\mathcal{D}_{\text{train}}^{\text{cold}} = \{(x_t, r_t) \in \mathcal{D}_{\text{train}} \mid \text{KC}(x_t) \notin \mathcal{K}_{\text{cold}}\} \quad (7)$$

where $\text{KC}(x_t)$ maps exercise x_t to its constituent KCs. Models must infer response accuracy over $\mathcal{K}_{\text{cold}}$ at test time strictly using external structural graphs or semantic priors.

D. Pillar 4: Calibrated & Trustworthy Knowledge Tracing

Integrating post-hoc calibration techniques into GNN/SSL KT backbones to convert raw uncalibrated model logits z_i into calibrated mastery probabilities $\hat{p}_i$:

$$\hat{p}_i = \sigma \left(\frac{z_i}{T} \right) \quad (8)$$

where $\sigma(\cdot)$ is the sigmoid activation function. Following standard calibration procedure, the scalar temperature parameter $T > 0$ is fitted on a held-out validation set by minimizing negative log-likelihood (NLL / log-loss), after which Expected Calibration Error (ECE) and Brier score are evaluated on the test set.

E. Pillar 5: Continuous-Time Spatiotemporal Modeling via Neural ODEs

Combining Continuous-Time Neural ODEs with heterogeneous GNNs to model non-uniform learning intervals and continuous memory decay curves:

$$\begin{aligned} \frac{dh(t)}{dt} &= f_{\theta}(h(t), t), \\ h(t_{n+1}) &= h(t_n) + \int_{t_n}^{t_{n+1}} f_{\theta}(h(\tau), \tau) d\tau \end{aligned} \quad (9)$$

where $h(t) \in \mathbb{R}^d$ represents continuous latent student knowledge state at time t , $f_{\theta}(\cdot)$ is a neural network parameterized by weights θ modeling the continuous derivative $dh(t)/dt$, and t_n, t_{n+1} are consecutive interaction timestamps.

F. Pillar 6: Graph Counterfactual Augmentation & Causal Debiasing

Developing causal graph frameworks to disentangle intrinsic student learning capacity $Y \in \{0, 1\}$ (target outcome) from item popularity and historical attempt confounders X (treatment variable). Under the assumption that Z constitutes a sufficient set of observed confounding variables satisfying the backdoor criterion (unconfoundedness), the causal effect $P(Y \mid \text{do}(X = x))$ is identified via backdoor adjustment:

$$P(Y \mid \text{do}(X = x)) = \sum_z P(Y \mid X = x, Z = z) P(Z = z) \quad (10)$$

where Z blocks all spurious non-causal paths between treatment X and outcome Y .

IX. THREATS TO VALIDITY

A. Internal Validity

Search completeness: Despite executing four query families across seven databases, grey literature (workshop papers, technical reports, thesis dissertations) was excluded per protocol. Relevant work published in venues not indexed by the seven databases may be absent from our corpus.

Selection bias: The primary gateway criterion ($\text{PRIMARY_CORE} = \text{KT} \wedge (\text{GRAPH} \vee \text{SSL})$) was applied by three independent screeners. Borderline cases (e.g., models using attention-based graph structures without explicit GNN components) were adjudicated through consensus review. Residual selection uncertainty cannot be fully eliminated.

Coding reliability: QA scores (QA1–QA8) were assigned by the primary coder and cross-checked by one secondary coder for a 20% random sample; full double-coding of all 37 primary core papers was not performed due to resource constraints. A formal Cohen's κ calculation over the full corpus remains future work.

B. External Validity

Dataset generalizability: All 37 studies are evaluated on a narrow set of educational benchmarks (ASSISTments2009/2012/2017, EdNet, Statics2011, Junyi Academy).

Findings may not generalize to high-stakes assessment platforms, corporate learning systems, or non-English-language educational datasets.

Temporal scope: Our search covers 2015–2026. The rapid emergence of LLM-augmented KT after 2024 means that architectural paradigms and benchmark results are evolving faster than the typical 18–24 month survey publication cycle.

AUC as primary metric: Cross-paper AUC comparisons remain invalid as a league table due to heterogeneous dataset splits, preprocessing pipelines, and random seed policies. All quantitative comparisons in this survey are *within-study* unless explicitly noted as matched-protocol comparisons.

X. CONCLUSION

This systematic survey provides a comprehensive, PRISMA 2020-compliant synthesis of Graph-Based and Self-Supervised Knowledge Tracing (KT) under sparse-concept settings. Across 37 primary core studies published between 2018 and 2026 and identified through a 7-database search yielding 2,017 records, we established three original contributions.

Contribution 1 — Two-dimensional taxonomy. We classified all Graph-KT models along a graph provenance axis (Expert Curriculum, Precomputed Log-based, Jointly Learned, LLM-Extracted) and a GNN encoder axis (GCN, GAT, Heterogeneous, Hypergraph, Dynamic), and classified all SSL-KT models into four pretext objective families (Multi-View Contrastive, Graph Structural Contrastive, Hypergraph Contrastive, Generative Masked).

Contribution 2 — Evaluation split audit. We identified a pervasive methodological flaw: 94.6% of studies claim to address data sparsity, yet only 5.4% implement a strict zero-exposure KC cold-start protocol. Standard graph architectures collapse to near-random AUC under Protocol 2, demonstrating that the field’s empirical progress has been systematically measured under a lenient evaluation regime that does not reflect real-world curriculum cold-start conditions.

Contribution 3 — Evidence-derived research agenda. Six concrete future directions are proposed with formal mathematical specifications: LLM-GNN multimodal fusion, non-Euclidean hyperbolic state manifolds, standardized zero-exposure benchmarks (*pyKT-ColdStart*), calibrated trustworthy KT, continuous-time spatiotemporal Neural ODEs, and causal counterfactual graph debiasing.

We anticipate that this survey will serve as a rigorous reference for researchers entering the Graph-SSL KT space and as a methodological foundation for standardizing evaluation practices across the educational data mining community.

REFERENCES

- [1] C. Piech, J. Bassen, J. Huang, S. Ganguli, A. Sahai, L. Guibas, and J. Sohl-Dickstein, “Deep knowledge tracing,” in *Advances in Neural Information Processing Systems (NeurIPS)*, 2015, pp. 505–513.
- [2] S. Pandey and G. Karypis, “A self-attentive model for knowledge tracing,” in *Proceedings of the 12th International Conference on Educational Data Mining (EDM)*, 2019, pp. 384–389.
- [3] A. Ghosh, N. Heffernan, and A. Lan, “Context-aware attentive knowledge tracing,” in *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD)*, 2020, pp. 2330–2339.
- [4] G. Abdelrahman, Q. Wang, and B. P. Nunes, “Knowledge tracing: A survey,” *ACM Computing Surveys*, vol. 55, no. 11, pp. 1–37, 2023.
- [5] Z. Liu, Q. Liu, J. Chen, S. Huang, J. Tang, and W. Luo, “pykt: A python library to benchmark knowledge tracing,” in *Advances in Neural Information Processing Systems (NeurIPS) Datasets and Benchmarks Track*, vol. 35, 2022, pp. 1843–1855.
- [6] X. Wang, P. Chen, and Y. Lu, “Graph neural networks for knowledge tracing: A survey and comparative review,” *IEEE Transactions on Learning Technologies*, vol. 17, pp. 450–468, 2024.
- [7] H. Nakagawa, Y. Iwasawa, and Y. Matsuo, “Graph-based knowledge tracing: Modeling student proficiency using graph neural networks,” in *Proceedings of the IEEE/WIC/ACM International Conference on Web Intelligence (WI)*, 2019, pp. 156–163.
- [8] Y. Yang, J. Shen, Y. Qu, Y. Liu, K. Wang, Y. Zhu, W. Zhang, and Y. Yu, “Gikt: A graph-based interaction model for knowledge tracing,” in *Proceedings of the European Conference on Machine Learning and Principles and Practice of Knowledge Discovery in Databases (ECML-PKDD)*, 2021, pp. 299–315.
- [9] X. Song, J. Li, Q. Lei, W. Zhao, Y. Chen, and A. S. Mian, “Bi-clkt: Bi-graph contrastive learning based knowledge tracing,” *Knowledge-Based Systems*, vol. 241, p. 108274, 2022.
- [10] X. Song, J. Li, Y. Tang, T. Zhao, Y. Chen, and Z. Guan, “Jkt: A joint graph convolutional network based deep knowledge tracing,” *Information Sciences*, vol. 580, pp. 510–523, 2021.
- [11] P. Chen, Y. Lu, V. W. Zheng, and Y. Pian, “Prerequisite-driven deep knowledge tracing,” in *Proceedings of the IEEE International Conference on Data Mining (ICDM)*, 2018, pp. 39–48.
- [12] S. Tong, Q. Liu, W. Huang, Z. Huang, E. Chen, C. Liu, H. Ma, and S. Wang, “Structure-based knowledge tracing: An influence propagation view,” in *Proceedings of the IEEE International Conference on Data Mining (ICDM)*, 2020, pp. 541–550.
- [13] Z. Wu, L. Huang, Q. Huang, C. Huang, and Y. Tang, “Sgkt: Session graph-based knowledge tracing for student performance prediction,” *Expert Systems with Applications*, vol. 206, p. 117681, 2022.
- [14] Y. Liu, Y. Yang, X. Chen, J. Shen, H. Zhang, and Y. Yu, “Improving knowledge tracing via pre-training question embeddings,” in *Proceedings of the International Joint Conference on Artificial Intelligence (IJCAI)*, 2020, pp. 1577–1583.
- [15] C. Cui, Y. Yao, C. Zhang, H. Ma, Y. Ma, Z. Ren, C. Zhang, and J. Ko, “Dgekt: A dual graph ensemble learning method for knowledge tracing,” *ACM Transactions on Information Systems*, vol. 42, no. 3, pp. 78:1–78:25, 2024.
- [16] W. Gan, Y. Sun, and Y. Sun, “Knowledge structure enhanced graph representation learning model for attentive knowledge tracing,” *International Journal of Intelligent Systems*, vol. 37, no. 3, pp. 2012–2045, 2022.
- [17] G. Abdelrahman and Q. Wang, “Deep graph memory networks for forgetting-robust knowledge tracing,” *IEEE Transactions on Knowledge and Data Engineering*, vol. 35, no. 8, pp. 7844–7855, 2023.
- [18] Q. Ni, T. Wei, J. Zhao, L. He, and C. Zheng, “Hhskt: A learner-question interactions based heterogeneous graph neural network model for knowledge tracing,” *Expert Systems with Applications*, vol. 215, p. 119334, 2023.
- [19] H. Yang, S. Hu, J. Geng, T. Huang, J. Hu, H. Zhang, and Q. Zhu, “Heterogeneous graph-based knowledge tracing with spatiotemporal evolution,” *Expert Systems with Applications*, vol. 238, p. 122249, 2024.
- [20] Y. Lu, P. Chen, Y. Pian, and V. W. Zheng, “Cmkt: Concept map driven knowledge tracing,” *IEEE Transactions on Learning Technologies*, vol. 15, no. 4, pp. 467–480, 2022.
- [21] K. Cheng, L. Peng, P. Wang, J. Ye, L. Sun, and B. Du, “Dygt: Dynamic graph learning for knowledge tracing,” in *Proceedings of the ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD)*, 2024, pp. 409–420.
- [22] T. Wu and Q. Ling, “Self-supervised heterogeneous hypergraph network for knowledge tracing,” *Information Sciences*, vol. 624, pp. 200–216, 2023.
- [23] J. Sun, S. Du, Z. Liu, F. Yu, S. Liu, and X. Shen, “Weighted heterogeneous graph-based three-view contrastive learning for knowledge tracing in personalized e-learning systems,” *IEEE Transactions on Consumer Electronics*, vol. 70, no. 1, pp. 2838–2847, 2024.
- [24] L. Fu, H. Guan, K. Du, J. Lin, W. Xia, W. Zhang, R. Tang, Y. Wang, and Y. Yu, “Structure-aware inductive knowledge tracing with large language models,” in *Proceedings of the ACM International Conference on Information and Knowledge Management (CIKM)*, 2024, pp. 632–642.

- [25] Z. Wu and Y. Liu, "Dual-channel self-supervised learning for heterogeneous graph knowledge tracing," *Expert Systems with Applications*, vol. 231, p. 120212, 2023.
- [26] X. Wang, S. Zhao, L. Guo, L. Zhu, C. Cui, and L. Xu, "Graphca: Learning from graph counterfactual augmentation for knowledge tracing," *IEEE/CAA Journal of Automatica Sinica*, vol. 10, no. 11, pp. 2108–2123, 2023.
- [27] Z. He, W. Li, and Y. Yan, "Modeling knowledge proficiency using multi-hierarchical capsule graph neural network," *Applied Intelligence*, vol. 52, no. 7, pp. 7230–7247, 2022.
- [28] L. Wang and D. Wu, "Gaskt: A graph-based attentive knowledge-search model for knowledge tracing," in *Proceedings of the International Conference on Knowledge Science, Engineering and Management (KSEM)*, 2021, pp. 269–281.
- [29] G. Yu, Z. Xie, G. Zhou, Z. Zhao, and J. X. Huang, "Exploring long- and short-term knowledge state graph representations with adaptive fusion for knowledge tracing," *Information Processing & Management*, vol. 62, no. 3, p. 104074, 2025.
- [30] S. Li, S. Shen, Y. Su, X. Sun, J. Lu, Q. Mo, Z. Wu, and Q. Liu, "Sthkt: Spatiotemporal knowledge tracing with topological hawkes process," *Expert Systems with Applications*, vol. 259, p. 125248, 2025.
- [31] X. Sun, Q. Liu, K. Zhang, S. Shen, Y. Zhuang, and Y. Guo, "Lgskt: Integrating logical and grammatical skills for effective programming knowledge tracing," *Neural Networks*, vol. 185, p. 107164, 2025.
- [32] H. Yang, J. Hu, J. Chen, and T. Huang, "Mahkt: Knowledge tracing with multi-association heterogeneous graph embedding based on knowledge transfer," *Knowledge-Based Systems*, vol. 309, p. 112958, 2025.
- [33] J. Wang, H. Ma, M. Zhang, L. Zhang, and L. Chang, "Multi-granularity ensemble interaction graph modeling for knowledge tracing," *Knowledge-Based Systems*, vol. 309, p. 112834, 2025.
- [34] Q. Wu, W. Ji, G. Zhou, and Y. Yang, "Graph knowledge tracing in cognitive situation: Validation of classic assertions in cognitive psychology," *Knowledge-Based Systems*, vol. 315, p. 113281, 2025.
- [35] J. Li, Y. Deng, Y. Qin, S. Mao, and Y. Jiang, "Dual-channel adaptive scale hypergraph encoders with cross-view contrastive learning for knowledge tracing," *IEEE Transactions on Neural Networks and Learning Systems*, vol. 36, no. 4, pp. 6752–6766, 2025.
- [36] Z. Yang, J. Hu, S. Zhong, L. Yang, and G. Min, "Graph-based effective knowledge tracing via subject knowledge mapping," *Education and Information Technologies*, vol. 30, no. 7, pp. 9813–9840, 2025.
- [37] Q. Li, Z. Huang, J. Sun, X. Yuan, S. Liu, and Z. Yan, "Hkt: Hierarchical structure-based knowledge tracing," *Information Processing & Management*, vol. 62, no. 5, p. 104206, 2025.
- [38] Z. Wu, Y. Liu, J. Cen, Z. Zheng, and G. Xu, "A cross-domain knowledge tracing model based on graph optimal transport," *World Wide Web*, vol. 28, no. 1, p. 10, 2025.
- [39] W. Gao, Q. Liu, R. Li, H. Zhao, Z. Wang, X. Yue, J. Yao, and M. Zhang, "Denoising programming knowledge tracing with a code graph-based tuning adapter," in *Proceedings of the ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD)*, 2025, pp. 354–365.
- [40] D. Zhang, Q. Niu, T. Wang, Y. Hou, J. Wu, C. Zhang, and A. Stefanidis, "Kgmm-kt: Enhancing knowledge tracing in programming education through llm-extracted knowledge graphs," in *Proceedings of the International Conference on Intelligent Computing (ICIC)*, 2025, pp. 1–12.
- [41] T. Peng, Y. Pu, Y. Zhang, Y. Li, J. Ren, J. Luo, K. Zhang, H. Yuan, S. Wang, D. Yin, and W. Wu, "R²gcurl: Reinforced robust knowledge tracing via dynamic graph curriculum learning," *ACM Transactions on Information Systems*, vol. 44, pp. 1–32, 2026.
- [42] Y.-F. Wen, H. Liang, C. Yang, W.-B. Xie, Y. Du, X. Li, and Y.-L. Lee, "Spatio-temporal fusion in graph neural network for streaming knowledge tracing," in *Proceedings of the International Conference on Database Systems for Advanced Applications (DASFAA)*, 2026, pp. 150–162.
- [43] W. Lee, J. Chun, Y. Lee, K. Park, and S. Park, "Contrastive learning for knowledge tracing," in *Proceedings of the ACM Web Conference (WWW)*, 2022, pp. 2330–2338.

Khanh-Trinh Nguyen received the B.S. degree in Information Technology. He is currently pursuing advanced research in educational data mining, graph neural networks, and self-supervised learning at Hung Yen University of Technology and Education, Vietnam. His research interests include Knowledge Tracing, GNN representation learning, and Large Language Model applications in education.

Tuan Dao Minh received the B.S. degree in Computer Science. He is currently a researcher at Hung Yen University of Technology and Education, Vietnam. His research focuses on graph representation learning, self-supervised contrastive learning, and AI-assisted educational technology.

Duong Nguyen Tien received the B.S. degree in Software Engineering. He is currently a research assistant at Hung Yen University of Technology and Education, Vietnam. His research interests encompass deep learning for intelligent tutoring systems, hyperbolic neural manifolds, and systematic literature review methodologies.

Chi Thanh Nguyen received the Ph.D. degree in Computer Science. He is currently a Senior Researcher with the Academy of Military Science and Technology, Ha Noi, Vietnam. His research interests include graph neural networks, pattern recognition, spatial-temporal data mining, and trustworthy artificial intelligence.

Van-Hau Nguyen received the Ph.D. degree in Computer Science. He is currently an Associate Professor with the Faculty of Information Technology, Hung Yen University of Technology and Education, Vietnam. He has authored or co-authored numerous publications in international journals and conference proceedings. His primary research interests include machine learning, graph neural networks, educational data mining, self-supervised learning, and intelligent tutoring systems. Dr. Nguyen is the corresponding author of this paper.