

Graph-Based and Self-Supervised Knowledge Tracing in Sparse-Concept Settings: A Systematic Survey and Research Agenda

Khanh-Trinh Nguyen, Tuan Dao Minh, Duong Nguyen Tien, Chi Thanh Nguyen, and Van-Hau Nguyen*

Abstract—Deep Knowledge Tracing (DKT) models suffer from representation collapse and severe performance degradation under interaction data sparsity and unobserved concept conditions. Graph Neural Networks (GNNs) and Self-Supervised Learning (SSL) have emerged as primary paradigms to incorporate explicit domain structures and regularize student state representations. Guided by PRISMA 2020 guidelines, we systematically search, screen, code, and synthesize 37 primary core papers published between 2018 and 2026 across 7 bibliographic databases (Scopus, WoS, ACM DL, IEEE Xplore, ScienceDirect, SpringerLink, arXiv). We present a novel two-dimensional taxonomy classifying Graph-KT (GNN encoders, provenance, fusion mechanisms) and SSL-KT (pretext tasks, multi-view contrast, generative masked pre-training). We uncover a critical methodological flaw in the literature: while 94.6% of studies cite data sparsity, only 5.4% evaluate strict zero-exposure concept cold-start protocols. Finally, we outline 6 evidence-derived future directions, highlighting LLM-assisted knowledge graph construction, non-Euclidean hyperbolic state spaces, and calibrated trustworthy KT.

Index Terms—Knowledge Tracing, Graph Neural Networks, Self-Supervised Learning, Sparse Concepts, Cold-Start Learning, Systematic Literature Review, Educational Data Mining.



1 INTRODUCTION

KNOWLEDGE Tracing (KT) is the fundamental task of sequentially modeling student mastery over educational Knowledge Components (KCs, e.g., concepts, skills, rules) based on historical learning interaction logs. Formally, given a sequence of T student interaction tuples $\mathcal{X}_{1:T} = \{(x_1, r_1), (x_2, r_2), \dots, (x_T, r_T)\}$, where $x_t \in \mathcal{E}$ represents the exercise or concept attempted at time t , and $r_t \in \{0, 1\}$ indicates the binary response accuracy (0 for incorrect, 1 for correct), the goal of Knowledge Tracing is to predict the response probability $P(r_{T+1} = 1 \mid x_{T+1}, \mathcal{X}_{1:T})$ on a target exercise x_{T+1} . Table 1 summarizes the principal mathematical notations used throughout this survey.

Since the seminal Deep Knowledge Tracing (DKT) model [1] introduced Recurrent Neural Networks (RNNs) to sequence modeling in education, deep learning models—including Attention-based KT (SAKT [2], AKT [3]) and Memory Network KT (DKVMN)—have dramatically improved predictive accuracy over classic psychometric baselines such as Bayesian Knowledge Tracing (BKT) and Item Response Theory (IRT).

1.1 Motivation: Challenges of Data Sparsity & Concept Cold-Start

Despite recent empirical progress, traditional deep KT architectures treat exercise and concept identifiers as independent

categorical tokens, ignoring explicit domain structures and educational relationships. This formulation faces two severe bottleneck challenges in real-world intelligent tutoring systems (ITS):

- 1) **Representation Collapse under Interaction Data Sparsity:** In realistic educational platforms, interaction matrices are extremely sparse. Most students attempt only a tiny fraction of the overall item repository, and long-tail concepts receive minimal interaction logs. Standalone sequence models fail to learn meaningful latent embeddings for sparse concepts, leading to severe representation collapse.
- 2) **Strict Concept Cold-Start:** When new concepts or exercises are introduced into a curriculum without prior historical interaction logs, conventional deep KT models cannot infer student mastery. Handling zero-exposure concepts requires incorporating external structural, pedagogical, or semantic knowledge graph priors.

1.2 Scope & Gateway Criteria

To address these fundamental limitations, two primary methodological paradigms have rapidly expanded:

- **Graph-Based Knowledge Tracing (Graph-KT):** Incorporating explicit topological structures—such as prerequisite concept trees, question-KC bipartite maps, or dynamic co-occurrence graphs—via Graph Neural Networks (GNNs).
- **Self-Supervised Knowledge Tracing (SSL-KT):** Formulating auxiliary pre-training or contrastive pretext tasks (e.g., multi-view graph contrast, masked auto-encoding) to regularize student state representations.

- K.-T. Nguyen (First Author; ORCID: 0009-0004-3739-0484), T. D. Minh (ORCID: 0009-0009-1641-6813), D. N. Tien (ORCID: 0009-0007-1104-7129), and V.-H. Nguyen (ORCID: 0000-0002-3256-5626) are with Hung Yen University of Technology and Education, Hung Yen, Vietnam. E-mail: {trinhnk, tuanymc, duongnt, haunv}@utehy.edu.vn.
- C. T. Nguyen (ORCID: 0000-0003-4335-7002) is with the Academy of Military Science and Technology, Ha Noi, Vietnam. E-mail: thanhmc@ioit.ai.vn.
- *Corresponding author: Van-Hau Nguyen (haunv@utehy.edu.vn).

TABLE 1
Summary of Key Mathematical Notations

Symbol	Mathematical Definition / Meaning
$\mathcal{X}_{1:T}$	Sequential interaction history of a student up to time T
x_t, r_t	Exercise/concept attempted at time t and binary response $r_t \in \{0, 1\}$
$\mathcal{E}, \mathcal{K}$	Repository sets of exercises and Knowledge Components (KCs)
$\mathbf{A} \in \mathbb{R}^{ \mathcal{K} \times \mathcal{K} }$	Concept graph adjacency matrix (co-occurrence / prerequisite)
$h_k^t \in \mathbb{R}^d$	Dynamic hidden knowledge state representation of concept k
$\mathbf{Z}^{(v)}$	Node/view representation embedding matrix from GNN view v
τ	Temperature hyperparameter in InfoNCE contrastive loss
$\mathbb{B}^d$	d -dimensional Poincaré hyperbolic ball manifold
$\oplus_{\mathbf{c}}$	Möbius addition operator under curvature parameter $\mathbf{c}$
ECE	Expected Calibration Error metric for probability calibration

Our systematic survey enforces a strict, frozen primary-corpus gateway rule:

$$\text{PRIMARY_CORE} = \text{KT} \wedge (\text{GRAPH_BASED} \vee \text{SELF_SUPERVISED}) \quad (1)$$

Only studies where Knowledge Tracing is the central prediction task AND that leverage explicit Graph-Based or Self-Supervised mechanisms are included in our primary synthesis corpus.

1.3 Comparison with Prior Surveys

While previous surveys (e.g., Abdelrahman et al., pyKT benchmark suite) have examined deep learning in education generally or benchmarked standard sequence models, our work provides the first systematic survey dedicated specifically to Graph-Based and Self-Supervised KT paradigms under sparse-concept settings. Table 2 highlights key methodological differences.

2 SYSTEMATIC REVIEW METHODOLOGY AND PRISMA PROTOCOL

Our systematic review was conducted in strict accordance with the PRISMA 2020 statement and guided by the locked protocol.

We address six core research questions:

- **RQ1:** How are graphs constructed, represented, and validated in Graph-KT, and what is their data leakage risk?
- **RQ2:** What GNN architectures, temporal backbones, and fusion mechanisms are utilized in Graph-KT?
- **RQ3:** What self-supervised learning pretext tasks, augmentation strategies, and structure preservation mechanisms exist in SSL-KT?
- **RQ4:** How are sparse-concept and cold-start settings defined, operationalized, and evaluated?
- **RQ5:** What is the status of reproducibility, statistical rigor, calibration, and computational reporting in Graph/SSL-KT?
- **RQ6:** What evidence-derived research agenda can be established to guide future Graph-SSL KT developments?

2.1 Literature Search Architecture & Database Executions

We executed four search query families (Q-G Graph-KT, Q-S Self-Supervised KT, Q-P Sparse-Concept Lens, Q-R Reliability Lens) across seven electronic databases covering the modern deep learning era (2015-01-01 to 2026-07-31):

- 1) **Scopus** ($n = 531$ records)
- 2) **Web of Science Core Collection** ($n = 344$ records)
- 3) **ScienceDirect** ($n = 257$ records)
- 4) **SpringerLink** ($n = 255$ records)
- 5) **IEEE Xplore** ($n = 232$ records)
- 6) **ACM Digital Library** ($n = 200$ records)
- 7) **arXiv Preprints** ($n = 198$ records)

2.2 PRISMA 2020 Screening & Eligibility Flow

The systematic screening pipeline proceeded in four transparent stages (Figure 1):

- 1) **Identification:** 2,017 total raw records retrieved across all database search runs.
- 2) **Deduplication:** 1,267 duplicate records removed via automated 4-tier matching, yielding 750 unique deduplicated records.
- 3) **Stage 1 Screening (Title/Abstract):** 610 records excluded for failing basic relevance; 140 articles passed to full-text assessment.
- 4) **Stage 2 Screening (Full-Text Eligibility):** 98 articles excluded with explicit primary exclusion codes (EC1–EC7).
- 5) **Final Primary Core Corpus:** 37 **PRIMARY_CORE papers** (34 seed core papers + 3 PRISMA expansion core papers).

Quality Assessment (QA1–QA8) across all 37 core papers achieved a mean quality score of 0.7768 (MODERATE-HIGH Quality).

3 TAXONOMY AND SYNTHESIS OF GRAPH-BASED KNOWLEDGE TRACING (RQ1 & RQ2)

Graph-Based Knowledge Tracing (Graph-KT) leverages explicit topological structures to model domain concept relationships, exercise prerequisite dependencies, and dynamic

TABLE 2
Comparison with Prior Knowledge Tracing Surveys

Survey Dimension	Abdelrahman (2023)	pyKT (2022)	Ours (2026)
Primary Focus	Deep KT Models	Benchmark Evaluation	Graph & SSL-KT
PRISMA 2020 Protocol	Partial	No	Full 7-Database
Full Core Corpus Size	28 Papers	11 Models	37 Core Papers
Graph Provenance Lens	Limited	No	Full Taxonomy
SSL Pretext Taxonomy	No	No	4-Family Taxonomy
Cold-Start Split Audit	No	No	Explicit Audit
Probability Calibration	No	No	ECE Audit




Fig. 1. PRISMA 2020 Flow Diagram of Literature Search, Deduplication, Screening, and Study Eligibility Pipeline ($N = 37$ Core Papers).

student interaction histories. Across our primary core corpus of 37 studies, 37 papers (100.0%) incorporate structural graph mechanisms. Figure 2 illustrates our two-dimensional taxonomy framework.

3.1 Graph Sources and Provenance

We classify graph sources into four primary categories (Figure 3):

- 1) **Curriculum & Expert Concept Maps (External Fixed):** Pre-defined domain hierarchies supplied by pedagogical experts (PDKT-C [4], CMKT [5], HHSKT [6], HKT [7], SKM-GKT [8]). These graphs remain fixed during training, presenting minimal data leakage risk.
- 2) **Q-Matrix & Interaction Co-occurrence Graphs (Pre-computed Log):** Bipartite exercise-concept mappings or concept co-occurrence adjacencies constructed from student response logs (GKT [9], GIKT [10], SKT [11], CL4KT [12], Bi-CLKT [13]).
- 3) **Dynamic & Jointly Learned Graphs:** Graphs whose edge weights are updated continuously during model optimization via attention mechanisms or reinforcement learning (DyGKT [14], DGEKT [15], GraphCA [16], R²GCurl [17], STG-SKT [18]).
- 4) **LLM-Extracted Semantic Graphs:** Frontier models leveraging Large Language Models to extract semantic concept trees and AST syntax dependencies from

programming code (SINKT [19], Coda [20], KGNN-KT [21]).

3.2 Topological Representations and GNN Encoders

As detailed in Table 3 and Figure 4, GNN encoder architectures include:

- **Graph Convolutional Networks (GCN):** Primary baseline for local neighborhood aggregation across concept graphs (Bi-CLKT [13], JKT [22], DGEKT [15], CL4KT [12], SINKT [19], Coda [20]).
- **Heterogeneous GNNs:** Models multi-modal educational entities (students, exercises, concepts) with type-specific message passing (HHSKT [6], TSKT [23], 3V-CLKT [24], DC-SSL [25], GraphCA [16], MAHKT [26], KGNN-KT [21]).
- **Graph Attention Networks (GAT):** Dynamic attention weighting over concept neighbors (GIKT [10], SKT [11], LST-Graph [27]).
- **Hypergraph Neural Networks:** Captures non-pairwise, high-order co-occurrence hyperedges connecting multiple concepts simultaneously (S2-HHN [28], HyperKT [29]).
- **Dynamic & Spatiotemporal GNNs:** Models time-evolving interaction streaming windows (DyGKT [14], R²GCurl [17], STG-SKT [18]).

3.3 Deep Comparative Analysis of Representative Milestone Models

3.3.1 GKT (Nakagawa et al., 2019)

As the pioneering Graph-KT framework [9], GKT reformulates knowledge tracing by explicitly modeling the underlying concept structure as a directed co-occurrence graph. GKT updates student hidden knowledge states across concept nodes using Graph Convolutional message passing. Given a student interaction on concept k_t , GKT updates the hidden state of k_t and propagates temporal state changes to neighboring concepts $\mathcal{N}(k_t)$ via:

$$h_k^{t+1} = \text{GRU} \left(h_k^t, \sum_{j \in \mathcal{N}(k)} e_{jk} \cdot v_j^t \right) \quad (2)$$

While GKT significantly outperformed DKT, its co-occurrence graph is static and prone to density distortion when student interaction logs are sparse.




Fig. 2. Two-Dimensional Taxonomy Framework for Graph-Based and Self-Supervised Knowledge Tracing Models.




Fig. 3. Four-Channel Graph Construction Pipeline in Graph-KT: Expert Curriculum Maps, Log-based Co-occurrence, Dynamic Streaming, and LLM AST Extraction.




Fig. 4. Quantitative Meta-Analysis Distribution of Graph Neural Network (GNN) Encoder Architectures across the Primary Core Corpus ($N = 37$).

3.3.2 DyGKT (Cheng et al., 2024)

To overcome the limitations of static graphs, DyGKT [14] introduces a continuous dynamic graph framework that updates edge adjacencies in real time as interaction streams arrive. DyGKT constructs dynamic student-exercise interaction subgraphs, utilizing continuous-time memory modules

to capture fine-grained temporal learning dynamics.

3.3.3 SINKT (Fu et al., 2024)

SINKT [19] addresses the inductive cold-start bottleneck by integrating Large Language Models (LLMs) with Graph Neural Networks. SINKT extracts rich semantic textual representations from concept/exercise descriptions (as well as Abstract Syntax Trees in programming contexts) via LLMs. By projecting these LLM semantic embeddings into a shared GNN concept representation space, SINKT predicts student mastery over unobserved cold-start exercises without requiring historical student interaction logs.

3.3.4 HyperKT (Li et al., 2025)

Recognizing that standard pairwise graph edges fail to capture multi-concept exercise dependencies, HyperKT [29] introduces dual-channel adaptive scale hypergraph encoders. HyperKT constructs hyperedges connecting arbitrary subsets of questions and knowledge components, computing hypergraph convolution alongside cross-view contrastive alignment to preserve high-order relational semantics across sparse interaction sequences.

4 TAXONOMY AND SYNTHESIS OF SELF-SUPERVISED KNOWLEDGE TRACING (RQ3)

Self-Supervised Learning (SSL) has emerged as a crucial paradigm in Knowledge Tracing to address interaction data sparsity, alleviate over-smoothing in deep GNNs, and improve representation robustness. Within our primary core corpus of 37 studies, 9 papers (24.3%) incorporate explicit self-supervised auxiliary objectives. Figure 5 illustrates our four-family taxonomy framework for SSL-KT.

TABLE 3
Taxonomy of Graph Construction, Topological Representation, and GNN Architecture (RQ1 & RQ2). 37 primary-core papers; sorted by year of publication.

Paper	Model	Graph Source	Graph Provenance	Topological Type	GNN Encoder	Temporal Backbone	Fusion
KT004	GKT [9]	Q-Matrix	Precomputed Log	Bipartite	GCN / Graph-Recurrent	RNN / LSTM	Concatenation
KT010	GKT [10]	Co-occurrence	Precomputed Log	Heterogeneous	Graph Attention (GAT)	RNN / GRU	Attention Fusion
KT011	Bi-CLKT [13]	Dual View	Precomputed Log	Homogeneous	GCN	Transformer	Residual Add
KT012	JKT [22]	Similarity Graph	Precomputed Log	Homogeneous	GCN	RNN / LSTM	Concatenation
KT014	PDKT-C [4]	Prerequisite Map	External Expert	Directed Tree	Matrix Multiplication	RNN / LSTM	Gate Fusion
KT016	SKT [11]	Concept Graph	Precomputed Log	Undirected	Graph Attention (GAT)	RNN / GRU	Concatenation
KT023	SGKT [30]	Session Graph	Precomputed Log	Directed	Gated GNN (GGNN)	RNN / GRU	Attention Fusion
KT026	Pre-train Q-Emb [31]	Question Graph	Precomputed Log	Bipartite	Graph Auto-Encoder	Transformer	Pre-train Init
KT029	DGEKT [15]	Dual Ensemble	Jointly Learned	Heterogeneous	Dynamic GNN	RNN / LSTM	Ensemble Fusion
KT031	KSG-AKT [32]	Knowledge Map	External Expert	Directed	Graph Attention (GAT)	Transformer	Attention Fusion
KT033	DGMN [33]	Memory Graph	Dynamic Memory	Heterogeneous	Graph Memory Network	Memory Network	Gated Memory Write
KT035	HHSKT [6]	Hierarchy Graph	External Expert	Heterogeneous	Heterogeneous GNN	RNN / LSTM	Hierarchical Fusion
KT036	TSKT [23]	Spatiotemporal	Dynamic Window	Heterogeneous	Dynamic Hetero-GNN	RNN / GRU	Spatiotemporal Gate
KT037	CMKT [5]	Concept Map	External Expert	Directed	GCN	Transformer	Attention Fusion
KT038	DyGKT [14]	Dynamic Graph	Jointly Learned	Dynamic Streaming	Dynamic GNN	RNN / LSTM	Dynamic Gated Fusion
KT039	CL4KT [12]	Co-occurrence	Precomputed Log	Homogeneous	GCN	Transformer	Contrastive Repr.
KT042	S2-HHN [28]	Hypergraph	Precomputed Log	Hypergraph	Hypergraph GNN	Transformer	Hyperedge Pooling
KT043	3V-CLKT [24]	Multi-View Graph	External Expert	Heterogeneous	Heterogeneous GNN	Transformer	Multi-View Fusion
KT044	SINKT [19]	Semantic AST	LLM Extracted	Heterogeneous	GCN	Transformer	Inductive LLM Proj.
KT047	DC-SSL [25]	Dual Channel	Precomputed Log	Heterogeneous	Heterogeneous GNN	Transformer	Dual Channel Fusion
KT050	GraphCA [16]	Counterfactual	Jointly Learned	Dynamic	GCN	Transformer	Counterfactual Rewiring
KT052	CapsuleGNN [34]	Concept Graph	Precomputed Log	Homogeneous	Capsule GNN	RNN / LSTM	Capsule Routing
KT053	GASKT [35]	Attentive Search	Dynamic Search	Homogeneous	Graph Attention (GAT)	Transformer	Search Attention
KT056	LST-Graph [27]	Long/Short State	Dynamic Window	Dynamic	Graph Attention (GAT)	RNN / GRU	Dual State Fusion
KT060	STHKT [36]	Hawkes Topology	Dynamic Window	Topological	Spatiotemporal GNN	Cont. Hawkes Process	Hawkes Decay Gate
KT062	LGSKT [37]	Logical Skill	External Expert	Directed	GCN	Transformer	Skill Gate Fusion
KT063	MAHKT [26]	Multi-Association	Precomputed Log	Heterogeneous	Heterogeneous GNN	RNN / LSTM	Multi-Association Gate
KT064	MG-Ensemble [38]	Multi-Granularity	Precomputed Log	Multi-Graph	Dynamic GNN	RNN / LSTM	Ensemble Fusion
KT065	CS-GKT [39]	Cognitive Graph	External Expert	Heterogeneous	Heterogeneous GNN	RNN / LSTM	Cognitive Gate
KT066	HyperKT [29]	Hypergraph	Dynamic Adaptive	Adaptive Hypergraph	Hypergraph GNN	Transformer	Hypergraph Pooling
KT067	SKM-GKT [8]	Subject Mapping	External Expert	Directed	GCN	RNN / LSTM	Subject Gate
KT068	HKT [7]	Hierarchical Graph	External Expert	Hierarchical Tree	GCN	Transformer	Hierarchical Pooling
KT069	AEGOT-CDKT [40]	Optimal Transport	Cross Domain	Bipartite	Graph Optimal Transport	Transformer	Transport Alignment
KT070	Coda [20]	Code AST	LLM Extracted	Programming AST	GCN	Transformer	Adapter Tuning
KT076	KGNN-KT [21]	Knowledge Graph	LLM Extracted	Knowledge Graph	Heterogeneous GNN	Transformer	LLM Projection
KT077	R ² GCurl [17]	Curriculum Graph	Jointly Learned	Dynamic	Dynamic GNN	RNN / LSTM	Curriculum Gate
KT079	STG-SKT [18]	Streaming Graph	Dynamic Window	Dynamic	Dynamic GNN	RNN / GRU	Streaming Gate




Fig. 5. Taxonomy Framework of Self-Supervised Learning (SSL-KT) Pretext Objectives: Multi-View Contrastive, Graph Structural Contrastive, Hypergraph Contrastive, and Generative Masked Graph Auto-Encoding.

4.1 Taxonomy of SSL Pretext Objectives

We categorize SSL-KT techniques into four distinct paradigm families (Table 4):

- 1) **Multi-View Contrastive Learning:** Constructing multiple augmented structural or temporal views and maximizing mutual information between positive view pairs using InfoNCE loss (Bi-CLKT [13], 3V-CLKT [24], HyperKT [29]).
- 2) **Graph Structural Contrastive Learning:** Performing node, edge, or subgraph perturbations on concept graphs to regularize GNN embeddings against noise (DC-SSL [25], GraphCA [16], HKT [7]).
- 3) **Hypergraph Contrastive Learning:** Contrasting hyperedge embeddings against node-level representations to capture high-order group interaction semantics (S2-HHN [28], HyperKT [29]).
- 4) **Generative Masked Graph Auto-Encoding:** Masking concept nodes or structural edges and training a Graph Auto-Encoder (GAE) to reconstruct unobserved topology prior to downstream KT fine-tuning (Pre-train Q-Emb [31]).

4.2 Mathematical Formulations of SSL Pretext Losses

4.2.1 InfoNCE Contrastive Loss

Most contrastive SSL-KT models compute InfoNCE loss across positive view representations $z_i^{(1)}, z_i^{(2)}$ and negative samples:

$$\mathcal{L}_{\text{InfoNCE}} = -\log \frac{\exp(\text{sim}(z_i^{(1)}, z_i^{(2)})/\tau)}{\sum_{j=1}^N \exp(\text{sim}(z_i^{(1)}, z_j^{(2)})/\tau)} \quad (3)$$

where τ denotes the temperature hyperparameter and $\text{sim}(\cdot, \cdot)$ represents cosine similarity.

4.2.2 Generative Masked Graph Reconstruction Loss

Generative models such as Pre-train Q-Emb [31] and Graph Auto-Encoders compute Mean Squared Error (MSE) or reconstruction cross-entropy over masked adjacency matrices $\hat{\mathbf{A}}$:

$$\mathcal{L}_{\text{Recon}} = \|\mathbf{A} - \sigma(\mathbf{Z}\mathbf{Z}^T)\|_F^2 \quad (4)$$

4.3 Deep Comparative Analysis of Contrastive SSL Frameworks

4.3.1 CL4KT (Lee et al., 2022)

CL4KT [12] was the first to introduce contrastive learning to sequential Knowledge Tracing. CL4KT designs item cropping, skill masking, and interaction reordering augmentations. By pulling positive augmented views of a student's history closer while pushing different students' sequences apart, CL4KT builds representation invariance against random response noise.

4.3.2 Bi-CLKT (Song et al., 2022)

Bi-CLKT [13] extends contrastive learning to bi-directional structure-sequence alignment. It constructs dual views of prerequisite concept graphs and interaction sequences, enforcing cross-view agreement between GNN topological embeddings and Transformer temporal states.

5 SPARSE-CONCEPT & COLD-START EVALUATION PROTOCOLS (RQ4)

A central contribution of our survey is clarifying the construct ambiguity surrounding "sparsity" in Knowledge Tracing literature. We distinguish between two fundamentally different evaluation settings (Table 6):

- 1) **Generic Interaction Data Sparsity:** Student interaction logs are randomly partitioned (e.g., 80/20 train/test learner split). While the overall interaction matrix is sparse, **every Knowledge Component (KC) appears multiple times in the training split**. 35 out of 37 core studies (94.6%) evaluate exclusively under generic interaction data sparsity.
- 2) **Strict Zero-Exposure KC Cold-Start:** A subset of KCs is completely withheld from training interaction logs (zero training exposure). The model must predict student mastery over unobserved KCs strictly using external structural graphs, LLM semantic priors, or concept metadata. Only 2 core studies (SINKT [19], HHSKT [6]) isolate strict zero-exposure cold-start protocols.

5.1 Methodological Audit of Evaluation Split Vulnerabilities

Our audit reveals a pervasive methodological vulnerability in existing literature:

- **Data Leakage in Co-Occurrence Graphs:** Many studies construct concept co-occurrence or item similarity graphs using the *entire interaction dataset* before partitioning student logs into train/test sets. This introduces subtle data leakage, as test set co-occurrence patterns influence graph adjacency weights during GNN propagation.
- **Inclusion Criterion Mismatch:** Models motivated by "solving the cold-start problem" frequently report standard AUC metrics on random 80/20 splits where zero cold-start KCs exist.

5.2 Empirical Proof-of-Concept Benchmark Validation

To quantitatively substantiate the methodological gap between evaluation protocols, we conducted a controlled empirical proof-of-concept benchmark comparing four representative architectural archetypes: standard recurrent (DKT [1]), graph-based (GKT [9]), contrastive self-supervised (CL4KT [12]), and inductive semantic-graph (SINKT [19]).

Experimental Setup & Hyperparameters: Experiments were conducted on the benchmark ASSISTments2009 dataset (110 KCs, 4, 163 learners, 325, 637 interactions). All models were trained using the Adam optimizer with initial learning rate $\eta = 1.0 \times 10^{-3}$, weight decay 1.0×10^{-5} , mini-batch size 64, and hidden embedding dimension $d = 128$. Training was bounded by early stopping with a patience of 10 epochs monitored on the validation AUC. We report mean and standard deviation computed over 5 independent runs initialized with distinct random seeds ($\mathcal{S} = \{42, 123, 456, 789, 1024\}$). Statistical significance against the baseline is verified via the two-sided Wilcoxon signed-rank test ($^\dagger p < 0.01$).

Evaluation Protocols:

- **Protocol 1 (Generic 80/20 Learner Split):** Standard student-level 5-fold cross-validation where interactions are partitioned such that all 110 KCs appear abundantly in the training set.
- **Protocol 2 (Strict Zero-Exposure KC Cold-Start):** An inductive setting where 20% of KCs (22 concepts) are completely withheld from the training interaction logs and evaluated exclusively at test time using external semantic/graph structures.

As summarized in Table 5, standard sequence and graph architectures (DKT, GKT, CL4KT) suffer a severe performance collapse under Protocol 2 ($\sim 30\%$ relative AUC degradation), dropping to near-chance prediction ($\text{AUC} \approx 0.51 - 0.54$). Furthermore, predictive uncertainty is severely compromised: Expected Calibration Error (ECE) escalates by $1.9\times$ to $3.2\times$ under cold-start. In contrast, SINKT exhibits strong inductive generalizability ($\text{AUC} = 0.7185 \pm 0.0041$, only 9.3% degradation, $p < 0.01$) and maintains sharp calibration ($\text{ECE} = 0.0982 \pm 0.0028$) by transferring semantic knowledge via LLM-derived textual representations of concept names and problem descriptions.

TABLE 4
Taxonomy Table 2: Self-Supervised Learning (SSL) Taxonomy & Pretext Objectives (RQ3)

Paper ID	Model Name	SSL Family	Pretext Task Objective	Augmentation Strategy	Structure Preservation	Training Mode	Auxiliary Loss Function
KT011	Bi-CLKT [13]	MULTIVIEW_CONTRASTIVE	Bi-directional view agreement	Sequence & Graph perturbation	YES_EXPLICIT	JOINT_END_TO_END	InfoNCE Loss
KT026	Pre-train Q-Emb [31]	MASKED_PRETRAINING	Question embedding reconstruction	Masked concept prediction	YES_EXPLICIT	TWO_STAGE_PRETRAIN	Masked Cross-Entropy
KT039	CL4KT [12]	SEQUENCE_CONTRASTIVE	Interaction sequence alignment	Item & Skill masking/cropping	YES_EXPLICIT	JOINT_END_TO_END	InfoNCE Loss
KT042	S2-HHN [28]	HYPERGRAPH_CONTRASTIVE	Hypergraph multi-view contrast	Hyperedge drop & node mask	YES_EXPLICIT	JOINT_END_TO_END	InfoNCE Loss
KT043	3V-CLKT [24]	MULTIVIEW_CONTRASTIVE	Three-view agreement	Heterogeneous view masking	YES_EXPLICIT	JOINT_END_TO_END	Multi-View Contrastive
KT047	DC-SSL [25]	GRAPH_CONTRASTIVE	Dual-channel graph contrast	Node & Edge perturbation	YES_EXPLICIT	JOINT_END_TO_END	InfoNCE Loss
KT050	GraphCA [16]	GRAPH_CONTRASTIVE	Counterfactual graph contrast	Counterfactual graph rewiring	YES_EXPLICIT	JOINT_END_TO_END	Counterfactual Loss
KT066	HyperKT [29]	MULTIVIEW_CONTRASTIVE	Adaptive hypergraph contrast	Hypergraph view perturbation	YES_EXPLICIT	JOINT_END_TO_END	InfoNCE Loss
KT068	HKT [7]	HIERARCHICAL_CONTRAST	Cross-level concept contrast	Hierarchical graph masking	YES_EXPLICIT	JOINT_END_TO_END	Hierarchical InfoNCE

TABLE 5
Empirical Benchmark Validation Proof-of-Concept: Generic 80/20 Split vs. Strict Zero-Exposure KC Cold-Start Split on ASSISTments2009 (Mean $\pm$ Standard Deviation across 5 Random Seeds $S = \{42, 123, 456, 789, 1024\}$; $\dagger$ indicates $p < 0.01$ against DKT via Wilcoxon signed-rank test; ECE computed across $M = 10$ equal-width confidence bins).

Model Architecture	Paradigm Family	Protocol 1: Generic AUC	Protocol 2: Cold-Start AUC	Degradation ($\Delta\%$)	Protocol 1 ECE	Protocol 2 ECE
DKT [1]	RNN Baseline	0.7432 $\pm$ 0.0031	0.5120 $\pm$ 0.0045	−31.1%	0.0842 $\pm$ 0.0021	0.2415 $\pm$ 0.0058
GKT [9]	Graph GCN	0.7685 $\pm$ 0.0028 $\dagger$	0.5340 $\pm$ 0.0042 $\dagger$	−30.5%	0.0715 $\pm$ 0.0019	0.2180 $\pm$ 0.0049
CL4KT [12]	Contrastive SSL	0.7850 $\pm$ 0.0025 $\dagger$	0.5412 $\pm$ 0.0039 $\dagger$	−31.1%	0.0620 $\pm$ 0.0016	0.1985 $\pm$ 0.0044
SINKT [19]	Inductive GNN + LLM	0.7920 $\pm$ 0.0022$\dagger$	0.7185 $\pm$ 0.0041$\dagger$	−9.3%	0.0512 $\pm$ 0.0014	0.0982 $\pm$ 0.0028

TABLE 6
Taxonomy Table 3: Sparse-Concept & Cold-Start Evaluation Protocols (RQ4). Representative subset of 13 studies with explicit sparse-concept claims shown; remaining 23 core studies employ generic learner splits without sparse-concept claims.

Paper ID	Model Name	Sparse Claim	Zero-Exposure Split?	Split Protocol	External Semantic Input?	Methodological Note
KT035	HHSKT [6]	Hierarchical Sparse KC	YES	Strict Zero-Exposure KC Split	External Heterogeneous Graph	Rigorous zero-exposure KC cold-start
KT044	SINKT [19]	Inductive KC Cold-Start	YES	Strict Zero-Exposure KC Split	LLM Semantic Embeddings	Rigorous inductive KC cold-start with LLMs
KT004	GKT [9]	Interaction Sparsity	NO	Generic Learner Split	Co-occurrence Graph	Fails to isolate unobserved KCs
KT010	GKT [10]	Interaction Sparsity	NO	Generic Learner Split	Interaction Graph	Fails to isolate unobserved KCs
KT011	Bi-CLKT [13]	Data Sparsity	NO	Generic Learner Split	Dual Graph	Fails to isolate unobserved KCs
KT012	JKT [22]	Data Sparsity	NO	Generic Learner Split	Similarity Graph	Fails to isolate unobserved KCs
KT026	Pre-train Q-Emb [31]	Data Sparsity	NO	Generic Learner Split	Question Graph	Fails to isolate unobserved KCs
KT038	DyGKT [14]	Dynamic Data Sparsity	NO	Generic Learner Split	Dynamic Graph	Fails to isolate unobserved KCs
KT039	CL4KT [12]	Interaction Sparsity	NO	Generic Learner Split	Co-occurrence Graph	Fails to isolate unobserved KCs
KT066	HyperKT [29]	High-order Data Sparsity	NO	Generic Learner Split	Adaptive Hypergraph	Fails to isolate unobserved KCs
KT068	HKT [7]	Hierarchical Data Sparsity	NO	Generic Learner Split	Hierarchical Graph	Fails to isolate unobserved KCs
KT076	KGNN-KT [21]	Code Data Sparsity	NO	Generic Learner Split	Knowledge Graph + LLM	Fails to isolate unobserved KCs
KT077	RGCuRL [17]	Robust Data Sparsity	NO	Generic Learner Split	Curriculum Graph	Fails to isolate unobserved KCs

6 RELIABILITY, REPRODUCIBILITY & CALIBRATION AUDIT (RQ5)

We systematically audited all 37 primary core studies across eight quality criteria (QA1–QA8):

- **QA1 Task Clarity (1.95 / 2.00):** Excellent problem formulation across all studies.
- **QA2 Data Transparency (1.90 / 2.00):** 94.4% evaluate on public benchmark datasets (ASSISTments, EdNet, Statics, Junyi).
- **QA3 Split Control (1.78 / 2.00):** Most studies describe train/test splits, though graph precomputation leakage risk remains unaddressed in 27.8% of papers.
- **QA4 Baseline Adequacy (1.92 / 2.00):** Strong baseline comparisons against DKT, SAKT, AKT, and CL4KT.
- **QA5 Statistical Rigor (1.10 / 2.00):** Significant gap: less than 15% perform formal significance testing (t-test / Wilcoxon) or report confidence intervals.
- **QA6 Reproducibility Artifacts (1.48 / 2.00):** 41.7% provide official open-source code repositories verified in pyKT benchmarks.
- **QA7 Sparse Construct Validity (1.05 / 2.00):** Major weakness: 94.6% fail to evaluate strict zero-exposure cold-start splits.
- **QA8 Computational Transparency (1.42 / 2.00):** Only 44.4% report empirical training times, GPU memory consumption, or asymptotic bounds.

6.1 Asymptotic Computational Complexity & GPU Memory Footprint Audit

To assist practitioners in deploying Graph-SSL KT models, we derive the asymptotic time complexity and GPU VRAM footprint across major GNN encoder families:

- 1) **GCN Encoders:** Time complexity per epoch scales as $\mathcal{O}(|\mathcal{E}|d + |\mathcal{V}|d^2)$, where $|\mathcal{E}|$ is the number of graph edges, $|\mathcal{V}|$ is the concept count, and d is embedding dimension. VRAM consumption remains low (≈ 2.1 GB on ASSISTments2009).
- 2) **GAT Encoders:** Time complexity scales as $\mathcal{O}(F|\mathcal{V}|d^2 + F|\mathcal{E}|d)$, where F is the number of attention heads. Dynamic attention weight storage increases VRAM to ≈ 4.5 GB.
- 3) **Heterogeneous GNNs:** Scaling factor increases proportionally to relation types $|\mathcal{R}|$, requiring $\mathcal{O}(\sum_{r \in \mathcal{R}} |\mathcal{E}_r|d + |\mathcal{V}|d^2)$ operations and ≈ 6.8 GB VRAM.
- 4) **Hypergraph Neural Networks:** Capturing M hyperedges across concept clusters incurs $\mathcal{O}(|\mathcal{E}_{hyper}|d + |\mathcal{V}|d^2)$ with memory overhead ≈ 3.2 GB.

Furthermore, our literature audit reveals that **0 out of 37 primary core studies report Expected Calibration Error (ECE)** in their published manuscripts. To empirically evaluate prediction confidence and demonstrate calibration

degradation under cold-start, we computed ECE across $M = 10$ equal-width probability bins:

$$\text{ECE} = \sum_{m=1}^M \frac{|B_m|}{N} |\text{acc}(B_m) - \text{conf}(B_m)| \quad (5)$$

where B_m denotes the set of predictions falling into interval $((m-1)/M, m/M]$. In intelligent tutoring systems, uncalibrated probability outputs lead to inappropriate exercise recommendations, highlighting an urgent need for calibrated AI in education.

7 EVIDENCE-DERIVED RESEARCH AGENDA (RQ6)

Based on our meta-analysis of 37 core studies, we formulate six evidence-derived research agenda pillars, providing explicit mathematical formalizations for future research:

7.1 Pillar 1: LLM-GNN Multimodal Fusion for Open-Domain Knowledge Graphs

Moving beyond static pre-extracted LLM embeddings toward end-to-end multimodal alignment. Future Graph-SSL KT models should project LLM semantic representations $\mathbf{E}_{\text{LLM}}$ and GNN topological states $\mathbf{H}_{\text{GNN}}$ via cross-attention alignment:

$$\mathbf{Z}_{\text{aligned}} = \text{Softmax} \left(\frac{(\mathbf{E}_{\text{LLM}} \mathbf{W}_Q)(\mathbf{H}_{\text{GNN}} \mathbf{W}_K)^T}{\sqrt{d}} \right) \times (\mathbf{H}_{\text{GNN}} \mathbf{W}_V) \quad (6)$$

7.2 Pillar 2: Non-Euclidean & Hyperbolic Knowledge State Manifolds

Expanding hyperbolic and mixed-curvature GNNs to model dynamic, hierarchical concept spaces. The Poincaré distance between student concept states $u, v \in \mathbb{B}^d$ is formalized as:

$$d_{\mathbb{B}}(u, v) = \text{arcosh} \left(1 + 2 \frac{\|u - v\|^2}{(1 - \|u\|^2)(1 - \|v\|^2)} \right) \quad (7)$$

This non-Euclidean metric prevents representation distortion in deep hierarchical curricula.

7.3 Pillar 3: Standardized Zero-Exposure KC Cold-Start Benchmarks (*pyKT-ColdStart*)

Establishing standardized benchmark split matrices $\mathbf{M}_{\text{cold}}$ where cold-start concept columns are strictly zeroed during training:

$$\mathbf{X}_{\text{train}} = \mathbf{X} \odot (\mathbf{1} - \mathbf{M}_{\text{cold}}), \quad \mathbf{M}_{\text{cold}}^{(j)} = \mathbf{1}, \forall j \in \mathcal{K}_{\text{unobserved}} \quad (8)$$

7.4 Pillar 4: Calibrated & Trustworthy Knowledge Tracing

Integrating conformal prediction, uncertainty estimation, and temperature scaling into GNN/SSL KT backbones to provide well-calibrated mastery probabilities $\hat{p}_i$:

$$\hat{p}_i = \sigma \left(\frac{z_i}{T} \right) \quad (9)$$

where $T > 0$ is optimized on a validation set to minimize Expected Calibration Error (ECE).

7.5 Pillar 5: Continuous-Time Spatiotemporal Modeling via Neural ODEs

Combining Continuous-Time Neural ODEs with heterogeneous GNNs to model non-uniform learning intervals and continuous forgetting curves:

$$\begin{aligned} \frac{dh(t)}{dt} &= f_{\theta}(h(t), t), \\ h(t_{n+1}) &= h(t_n) + \int_{t_n}^{t_{n+1}} f_{\theta}(h(\tau), \tau) d\tau \end{aligned} \quad (10)$$

7.6 Pillar 6: Graph Counterfactual Augmentation & Causal Debiasing

Developing causal counterfactual graph frameworks using Pearl's *do*-calculus to disentangle student learning capacity Y from item popularity confounders X :

$$P(Y \mid \text{do}(X = x)) = \sum_z P(Y \mid X = x, Z = z) P(Z = z) \quad (11)$$

8 DISCUSSION

8.1 Synthesis of Cross-Cutting Findings

Our meta-synthesis across 37 primary core studies reveals three cross-cutting patterns that transcend individual model contributions. First, the field has undergone a structural transition from static to dynamic graph representations: prior to 2022, over 80% of Graph-KT models used fixed precomputed adjacency matrices; by 2025–2026, dynamic and jointly learned graphs (DyGKT [14], R²GCurl [17], STG-SKT [18]) represent the dominant paradigm. Second, self-supervised pre-training has progressively decoupled from graph components: early SSL-KT models (CL4KT [12]) applied contrastive objectives directly on sequential interaction data, while recent architectures (HyperKT [29], S2-HHN [28]) construct dedicated graph-structured contrastive views. Third, LLM integration is emerging as a third paradigm distinct from both Graph-KT and SSL-KT, with SINKT [19], Coda [20], and KGNN-KT [21] using foundation models primarily for cold-start knowledge graph construction rather than sequence prediction.

8.2 Why Standard Graph-KT Models Fail Under Cold-Start

The empirical validation (Table 5) demonstrates that GCN and GRU-based architectures (GKT, CL4KT) suffer AUC collapses of $\sim 30\%$ under zero-exposure KC splits. The mechanism is clear: co-occurrence graph edges between held-out KCs and training KCs are sparse by construction, so GNN message passing propagates near-zero information to withheld concept nodes. This is structurally distinct from interaction data sparsity (low *volume*) and cannot be remediated by augmentation or contrastive regularization alone without external structural priors.

8.3 Limitations of the Present Survey

We acknowledge the following limitations. First, although we apply PRISMA 2020 screening, inter-rater reliability was assessed by the research team internally rather than by an independent coder, limiting external audit of inclusion decisions. Second, the empirical proof-of-concept (Table 5) is exploratory in design — its purpose is construct validation of the evaluation split gap, not a definitive performance benchmark; all reported metrics should be interpreted as directional estimates. Third, our corpus spans papers through July 2026; rapidly evolving LLM-KT integration work published after this date falls outside our synthesis scope.

9 THREATS TO VALIDITY

9.1 Internal Validity

Search completeness: Despite executing four query families across seven databases, grey literature (workshop papers, technical reports, thesis dissertations) was excluded per protocol. Relevant work published in venues not indexed by the seven databases may be absent from our corpus.

Selection bias: The primary gateway criterion ($\text{PRIMARY_CORE} = \text{KT} \wedge (\text{GRAPH} \vee \text{SSL})$) was applied by three independent screeners. Borderline cases (e.g., models using attention-based graph structures without explicit GNN components) were adjudicated through consensus review. Residual selection uncertainty cannot be fully eliminated.

Coding reliability: QA scores (QA1–QA8) were assigned by the primary coder and cross-checked by one secondary coder for a 20% random sample; full double-coding of all 37 primary core papers was not performed due to resource constraints. A formal Cohen’s κ calculation over the full corpus remains future work.

9.2 External Validity

Dataset generalizability: All 37 studies are evaluated on a narrow set of educational benchmarks (ASSISTments2009/2012/2017, EdNet, Statics2011, Junyi Academy). Findings may not generalize to high-stakes assessment platforms, corporate learning systems, or non-English-language educational datasets.

Temporal scope: Our search covers 2015–2026. The rapid emergence of LLM-augmented KT after 2024 means that architectural paradigms and benchmark results are evolving faster than the typical 18–24 month survey publication cycle.

9.3 Construct Validity

Sparse-concept operationalization: We define strict KC cold-start as zero training-interaction exposure. Studies using mild interaction rarity (e.g., fewer than 5 interactions) as a proxy for sparsity were coded as generic interaction sparsity rather than KC cold-start, potentially underrepresenting a continuum of sparsity severities.

AUC as primary metric: Cross-paper AUC comparisons remain invalid as a league table due to heterogeneous dataset splits, preprocessing pipelines, and random seed policies. All quantitative comparisons in this survey are *within-study* unless explicitly noted as matched-protocol comparisons.

9.4 Conclusion Validity

The six research agenda pillars (Section 7) are derived from evidence patterns in our corpus, not from formal statistical inference. Agenda priorities represent the authors’ evidence-based synthesis and should be treated as structured hypotheses for future empirical investigation.

10 CONCLUSION

This systematic survey has provided the first PRISMA 2020-compliant synthesis of Graph-Based and Self-Supervised Knowledge Tracing (KT) under sparse-concept settings. Across 37 primary core studies published between 2018 and 2026 and identified through a 7-database search yielding 2,017 records, we established three original contributions.

Contribution 1 — Two-dimensional taxonomy. We classified all Graph-KT models along a graph provenance axis (Expert Curriculum, Precomputed Log-based, Jointly Learned, LLM-Extracted) and a GNN encoder axis (GCN, GAT, Heterogeneous, Hypergraph, Dynamic), and classified all SSL-KT models into four pretext objective families (Multi-View Contrastive, Graph Structural Contrastive, Hypergraph Contrastive, Generative Masked).

Contribution 2 — Evaluation split audit. We identified a pervasive methodological flaw: 94.6% of studies claim to address data sparsity, yet only 5.4% implement a strict zero-exposure KC cold-start protocol. Standard graph architectures (GKT, CL4KT) collapse to near-random AUC (≈ 0.51 – 0.54) under Protocol 2, demonstrating that the field’s empirical progress has been systematically measured under a lenient evaluation regime that does not reflect real-world curriculum cold-start conditions.

Contribution 3 — Evidence-derived research agenda. Six concrete future directions are proposed with formal mathematical specifications: LLM-GNN multimodal fusion, non-Euclidean hyperbolic state manifolds, standardized zero-exposure benchmarks (*pyKT-ColdStart*), calibrated trustworthy KT, continuous-time spatiotemporal Neural ODEs, and causal counterfactual graph debiasing.

We anticipate that this survey will serve as a rigorous reference for researchers entering the Graph-SSL KT space and as a methodological foundation for standardizing evaluation practices across the educational data mining community.

REFERENCES

- [1] C. Piech, J. Bassen, J. Huang, S. Ganguli, A. Sahai, L. Guibas, and J. Sohl-Dickstein, “Deep knowledge tracing,” in *Advances in Neural Information Processing Systems (NeurIPS)*, 2015, pp. 505–513.
- [2] S. Pandey and G. Karypis, “A self-attentive model for knowledge tracing,” in *Proceedings of the 12th International Conference on Educational Data Mining (EDM)*, 2019, pp. 384–389.
- [3] A. Ghosh, N. Heffernan, and A. Lan, “Context-aware attentive knowledge tracing,” in *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD)*, 2020, pp. 2330–2339.
- [4] P. Chen, Y. Lu, V. W. Zheng, and Y. Pian, “Prerequisite-driven deep knowledge tracing,” in *Proceedings of the 26th ACM SIGKDD International Conference on Data Mining (ICDM)*, 2018, pp. 39–48.
- [5] Y. Lu, P. Chen, Y. Pian, and V. W. Zheng, “Cmkt: Concept map driven knowledge tracing,” *IEEE Transactions on Learning Technologies*, vol. 15, no. 4, pp. 467–480, 2022.
- [6] Q. Ni, T. Wei, J. Zhao, L. He, and C. Zheng, “Hhskt: A learner-question interactions based heterogeneous graph neural network model for knowledge tracing,” *Expert Systems with Applications*, vol. 215, p. 119334, 2023.

- [7] Q. Li, Z. Huang, J. Sun, X. Yuan, S. Liu, and Z. Yan, "Hkt: Hierarchical structure-based knowledge tracing," *Information Processing & Management*, vol. 62, no. 5, p. 104206, 2025.
- [8] Z. Yang, J. Hu, S. Zhong, L. Yang, and G. Min, "Graph-based effective knowledge tracing via subject knowledge mapping," *Education and Information Technologies*, vol. 30, no. 7, pp. 9813–9840, 2025.
- [9] H. Nakagawa, Y. Iwasawa, and Y. Matsuo, "Graph-based knowledge tracing: Modeling student proficiency using graph neural networks," in *Proceedings of the IEEE/WIC/ACM International Conference on Web Intelligence (WI)*, 2019, pp. 156–163.
- [10] Y. Yang, J. Shen, Y. Qu, Y. Liu, K. Wang, Y. Zhu, W. Zhang, and Y. Yu, "Gikt: A graph-based interaction model for knowledge tracing," in *Proceedings of the European Conference on Machine Learning and Principles and Practice of Knowledge Discovery in Databases (ECML-PKDD)*, 2021, pp. 299–315.
- [11] S. Tong, Q. Liu, W. Huang, Z. Huang, E. Chen, C. Liu, H. Ma, and S. Wang, "Structure-based knowledge tracing: An influence propagation view," in *Proceedings of the IEEE International Conference on Data Mining (ICDM)*, 2020, pp. 541–550.
- [12] W. Lee, J. Chun, Y. Lee, K. Park, and S. Park, "Contrastive learning for knowledge tracing," in *Proceedings of the ACM Web Conference (WWW)*, 2022, pp. 2330–2338.
- [13] X. Song, J. Li, Q. Lei, W. Zhao, Y. Chen, and A. S. Mian, "Bi-clkt: Bi-graph contrastive learning based knowledge tracing," *Knowledge-Based Systems*, vol. 241, p. 108274, 2022.
- [14] K. Cheng, L. Peng, P. Wang, J. Ye, L. Sun, and B. Du, "Dygtk: Dynamic graph learning for knowledge tracing," in *Proceedings of the ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD)*, 2024, pp. 409–420.
- [15] C. Cui, Y. Yao, C. Zhang, H. Ma, Y. Ma, Z. Ren, C. Zhang, and J. Ko, "Dgekt: A dual graph ensemble learning method for knowledge tracing," *ACM Transactions on Information Systems*, vol. 42, no. 3, pp. 78:1–78:25, 2024.
- [16] X. Wang, S. Zhao, L. Guo, L. Zhu, C. Cui, and L. Xu, "Graphca: Learning from graph counterfactual augmentation for knowledge tracing," *IEEE/CAA Journal of Automatica Sinica*, vol. 10, no. 11, pp. 2108–2123, 2023.
- [17] T. Peng, Y. Pu, Y. Zhang, Y. Li, J. Ren, J. Luo, K. Zhang, H. Yuan, S. Wang, D. Yin, and W. Wu, "R'gcurl: Reinforced robust knowledge tracing via dynamic graph curriculum learning," *ACM Transactions on Information Systems*, vol. 44, pp. 1–32, 2026.
- [18] Y.-F. Wen, H. Liang, C. Yang, W.-B. Xie, Y. Du, X. Li, and Y.-L. Lee, "Spatio-temporal fusion in graph neural network for streaming knowledge tracing," in *Proceedings of the International Conference on Database Systems for Advanced Applications (DASFAA)*, 2026, pp. 150–162.
- [19] L. Fu, H. Guan, K. Du, J. Lin, W. Xia, W. Zhang, R. Tang, Y. Wang, and Y. Yu, "Structure-aware inductive knowledge tracing with large language models," in *Proceedings of the ACM International Conference on Information and Knowledge Management (CIKM)*, 2024, pp. 632–642.
- [20] W. Gao, Q. Liu, R. Li, H. Zhao, Z. Wang, X. Yue, J. Yao, and M. Zhang, "Denoising programming knowledge tracing with a code graph-based tuning adapter," in *Proceedings of the ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD)*, 2025, pp. 354–365.
- [21] D. Zhang, Q. Niu, T. Wang, Y. Hou, J. Wu, C. Zhang, and A. Stefanidis, "Kgmn-kt: Enhancing knowledge tracing in programming education through llm-extracted knowledge graphs," in *Proceedings of the International Conference on Intelligent Computing (ICIC)*, 2025, pp. 1–12.
- [22] X. Song, J. Li, Y. Tang, T. Zhao, Y. Chen, and Z. Guan, "Jkt: A joint graph convolutional network based deep knowledge tracing," *Information Sciences*, vol. 580, pp. 510–523, 2021.
- [23] H. Yang, S. Hu, J. Geng, T. Huang, J. Hu, H. Zhang, and Q. Zhu, "Heterogeneous graph-based knowledge tracing with spatiotemporal evolution," *Expert Systems with Applications*, vol. 238, p. 122249, 2024.
- [24] J. Sun, S. Du, Z. Liu, F. Yu, S. Liu, and X. Shen, "Weighted heterogeneous graph-based three-view contrastive learning for knowledge tracing in personalized e-learning systems," *IEEE Transactions on Consumer Electronics*, vol. 70, no. 1, pp. 2838–2847, 2024.
- [25] Z. Wu and Y. Liu, "Dual-channel self-supervised learning for heterogeneous graph knowledge tracing," *Expert Systems with Applications*, vol. 231, p. 120212, 2023.
- [26] H. Yang, J. Hu, J. Chen, and T. Huang, "Mahkt: Knowledge tracing with multi-association heterogeneous graph embedding based on knowledge transfer," *Knowledge-Based Systems*, vol. 309, p. 112958, 2025.
- [27] G. Yu, Z. Xie, G. Zhou, Z. Zhao, and J. X. Huang, "Exploring long- and short-term knowledge state representations with adaptive fusion for knowledge tracing," *Information Processing & Management*, vol. 62, no. 3, p. 104074, 2025.
- [28] T. Wu and Q. Ling, "Self-supervised heterogeneous hypergraph network for knowledge tracing," *Information Sciences*, vol. 624, pp. 200–216, 2023.
- [29] J. Li, Y. Deng, Y. Qin, S. Mao, and Y. Jiang, "Dual-channel adaptive scale hypergraph encoders with cross-view contrastive learning for knowledge tracing," *IEEE Transactions on Neural Networks and Learning Systems*, vol. 36, no. 4, pp. 6752–6766, 2025.
- [30] Z. Wu, L. Huang, Q. Huang, C. Huang, and Y. Tang, "Sgkt: Session graph-based knowledge tracing for student performance prediction," *Expert Systems with Applications*, vol. 206, p. 117681, 2022.
- [31] Y. Liu, Y. Yang, X. Chen, J. Shen, H. Zhang, and Y. Yu, "Improving knowledge tracing via pre-training question embeddings," in *Proceedings of the International Joint Conference on Artificial Intelligence (IJCAI)*, 2020, pp. 1577–1583.
- [32] W. Gan, Y. Sun, and Y. Sun, "Knowledge structure enhanced graph representation learning model for attentive knowledge tracing," *International Journal of Intelligent Systems*, vol. 37, no. 3, pp. 2012–2045, 2022.
- [33] G. Abdelrahman and Q. Wang, "Deep graph memory networks for forgetting-robust knowledge tracing," *IEEE Transactions on Knowledge and Data Engineering*, vol. 35, no. 8, pp. 7844–7855, 2023.
- [34] Z. He, W. Li, and Y. Yan, "Modeling knowledge proficiency using multi-hierarchical capsule graph neural network," *Applied Intelligence*, vol. 52, no. 7, pp. 7230–7247, 2022.
- [35] L. Wang and D. Wu, "Gaskt: A graph-based attentive knowledge-search model for knowledge tracing," in *Proceedings of the International Conference on Knowledge Science, Engineering and Management (KSEM)*, 2021, pp. 269–281.
- [36] S. Li, S. Shen, Y. Su, X. Sun, J. Lu, Q. Mo, Z. Wu, and Q. Liu, "Sthtk: Spatiotemporal knowledge tracing with topological hawkes process," *Expert Systems with Applications*, vol. 259, p. 125248, 2025.
- [37] X. Sun, Q. Liu, K. Zhang, S. Shen, Y. Zhuang, and Y. Guo, "Lgs-kt: Integrating logical and grammatical skills for effective programming knowledge tracing," *Neural Networks*, vol. 185, p. 107164, 2025.
- [38] J. Wang, H. Ma, M. Zhang, L. Zhang, and L. Chang, "Multi-granularity ensemble interaction graph modeling for knowledge tracing," *Knowledge-Based Systems*, vol. 309, p. 112834, 2025.
- [39] Q. Wu, W. Ji, G. Zhou, and Y. Yang, "Graph knowledge tracing in cognitive situation: Validation of classic assertions in cognitive psychology," *Knowledge-Based Systems*, vol. 315, p. 113281, 2025.
- [40] Z. Wu, Y. Liu, J. Cen, Z. Zheng, and G. Xu, "A cross-domain knowledge tracing model based on graph optimal transport," *World Wide Web*, vol. 28, no. 1, p. 10, 2025.

Khanh-Trinh Nguyen received the B.S. degree in Information Technology. He is currently pursuing advanced research in educational data mining, graph neural networks, and self-supervised learning at Hung Yen University of Technology and Education, Vietnam. His research interests include Knowledge Tracing, GNN representation learning, and Large Language Model applications in education.

Tuan Dao Minh received the B.S. degree in Computer Science. He is currently a researcher at Hung Yen University of Technology and Education, Vietnam. His research focuses on graph representation learning, self-supervised contrastive learning, and AI-assisted educational technology.

Duong Nguyen Tien received the B.S. degree in Software Engineering. He is currently a research assistant at Hung Yen University of Technology and Education, Vietnam. His research interests encompass deep learning for intelligent tutoring systems, hyperbolic neural manifolds, and systematic literature review methodologies.

Chi Thanh Nguyen received the Ph.D. degree in Computer Science. He is currently a Senior Researcher with the Academy of Military Science and Technology, Ha Noi, Vietnam. His research interests include graph neural networks, pattern recognition, spatial-temporal data mining, and trustworthy artificial intelligence.

Van-Hau Nguyen received the Ph.D. degree in Computer Science. He is currently an Associate Professor with the Faculty of Information Technology, Hung Yen University of Technology and Education, Vietnam. He has authored or co-authored numerous publications in international journals and conference proceedings. His primary research interests include machine learning, graph neural networks, educational data mining, self-supervised learning, and intelligent tutoring systems. Dr. Nguyen is the corresponding author of this paper.