powered by Q.ANTUM DUO

Q.PEAK DUO-G5 305-330

Q.ANTUM SOLAR MODULE

The new Q.PEAK DUO-G5 solar module from Q CELLS impresses thanks to innovative Q.ANTUM DUO Technology, which enables particularly high performance on a small surface. Q.ANTUM's world-record-holding cell concept has now been combined with state-of-the-art circuitry half cells and a six-busbar design, thus achieving outstanding performance under real conditions - both with low-intensity solar radiation as well as on hot, clear summer days.

Q.ANTUM TECHNOLOGY: LOW LEVELIZED COST OF ELECTRICITY

Higher yield per surface area, lower BOS costs, higher power classes, and an efficiency rate of up to 19.9 %.

INNOVATIVE ALL-WEATHER TECHNOLOGY

Optimal yields, whatever the weather with excellent low-light and temperature behavior.

ENDURING HIGH PERFORMANCE

Long-term yield security with Anti LID and Anti PID Technology[1], Hot-Spot Protect and Traceable Quality Tra.Q™.

EXTREME WEATHER RATING

High-tech aluminum alloy frame, certified for high snow (5400 Pa) and wind loads (4000 Pa) regarding IEC.

A RELIABLE INVESTMENT

Inclusive 12-year product warranty and 25-year linear performance guarantee[2].

STATE OF THE ART MODULE TECHNOLOGY

Q.ANTUM DUO combines cutting edge cell separation and innovative wiring with Q.ANTUM Technology.

EUPD RESEARCH TOP BRAND PV MODULES EUROPE 2017

Q CELLS YIELD SECURITY
- ANTI PID TECHNOLOGY (APT)
- HOT-SPOT PROTECT (HSP)
- TRACEABLE QUALITY (TRA.Q™)
- ANTI LID TECHNOLOGY (ALT)

VDE Quality Tested
- high reliability
- low degradation
- frequent product surveillance

ID. 40032587

pv magazine award 2017 top innovation

[1] APT test conditions according to IEC/TS 62804-1:2015, method B (–1500 V, 168 h)

[2] See data sheet on rear for further information.

THE IDEAL SOLUTION FOR:

Rooftop arrays on residential buildings

Rooftop arrays on commercial / industrial buildings

Engineered in **Germany**

Q CELLS

MECHANICAL SPECIFICATION

Format	66.3 in × 39.4 in × 1.26 in (including frame) (1685 mm × 1000 mm × 32 mm)
Weight	41.2 lbs (18.7 kg)
Front Cover	0.13 in (3.2 mm) thermally pre-stressed glass with anti-reflection technology
Back Cover	Composite film
Frame	Black anodized aluminum
Cell	6 × 20 monocrystalline Q.ANTUM solar half-cells
Junction box	2.76-3.35 in × 1.97-2.76 in × 0.51-0.83 in (70-85 mm × 50-70 mm × 13-21 mm), decentralized, IP67
Cable	4 mm² Solar cable; (+) ≥43.3 in (1100 mm), (–) ≥43.3 in (1100 mm)
Connector	Multi-Contact MC4, IP65 and IP68



ELECTRICAL CHARACTERISTICS

POWER CLASS				305	310	315	320	325	330
MINIMUM PERFORMANCE AT STANDARD TEST CONDITIONS, STC[1] (POWER TOLERANCE +5 W / –0 W)									
Minimum	**Power at MPP[2]**	P_{MPP}	[W]	305	310	315	320	325	330
	Short Circuit Current*	I_{SC}	[A]	9.93	9.98	10.04	10.09	10.14	10.20
	Open Circuit Voltage*	V_{OC}	[V]	39.35	39.61	39.87	40.13	40.40	40.66
	Current at MPP*	I_{MPP}	[A]	9.44	9.50	9.55	9.60	9.66	9.71
	Voltage at MPP*	V_{MPP}	[V]	32.30	32.64	32.98	33.32	33.65	33.98
	Efficiency[2]	η	[%]	≥18.1	≥18.4	≥18.7	≥19.0	≥19.3	≥19.6
MINIMUM PERFORMANCE AT NORMAL OPERATING CONDITIONS, NOC[3]									
Minimum	**Power at MPP[2]**	P_{MPP}	[W]	226.0	229.7	233.4	237.2	240.9	244.6
	Short Circuit Current*	I_{SC}	[A]	8.00	8.05	8.09	8.14	8.18	8.22
	Open Circuit Voltage*	V_{OC}	[V]	36.80	37.05	37.30	37.54	37.79	38.04
	Current at MPP*	I_{MPP}	[A]	7.43	7.47	7.51	7.56	7.60	7.64
	Voltage at MPP*	V_{MPP}	[V]	30.43	30.75	31.07	31.39	31.70	32.01

[1] 1000 W/m², 25 °C, spectrum AM 1.5 G [2] Measurement tolerances STC ±3 %; NOC ±5 % [3] 800 W/m², NOCT, spectrum AM 1.5 G * typical values, actual values may differ

Q CELLS PERFORMANCE WARRANTY



At least 98 % of nominal power during first year.
Thereafter max. 0.54 % degradation per year.
At least 93.1 % of nominal power up to 10 years.
At least 85 % of nominal power up to 25 years.

All data within measurement tolerances.
Full warranties in accordance with the warranty terms of the Q CELLS sales organization of your respective country.

PERFORMANCE AT LOW IRRADIANCE



Typical module performance under low irradiance conditions in comparison to STC conditions (25 °C, 1000 W/m²).

TEMPERATURE COEFFICIENTS

Temperature Coefficient of I_{SC}	α	[%/K]	+0.04	**Temperature Coefficient of V_{OC}**	β	[%/K]	–0.28
Temperature Coefficient of P_{MPP}	γ	[%/K]	–0.37	**Normal Operating Cell Temperature**	NOCT	[°F]	113 ±5.4 (45 ±3 °C)

PROPERTIES FOR SYSTEM DESIGN

Maximum System Voltage V_{SYS}	[V]	1000 (IEC) / 1000 (UL)	**Safety Class**	II
Maximum Series Fuse Rating	[A DC]	20	**Fire Rating**	C (IEC) / TYPE 1 (UL)
Design load, push (UL)[2]	[lbs/ft²]	75 (3600 Pa)	**Permitted module temperature on continuous duty**	–40 °F up to +185 °F (–40 °C up to +85 °C)
Design load, pull (UL)[2]	[lbs/ft²]	55.6 (2666 Pa)	[2] see installation manual	

QUALIFICATIONS AND CERTIFICATES

UL 1703; VDE Quality Tested; CE-compliant;
IEC 61215 (Ed.2); IEC 61730 (Ed.1) application class A

C Certified UL 1703 (254141)

PACKAGING INFORMATION

Number of Modules per Pallet	32
Number of Pallets per 53' Trailer	30
Number of Pallets per 40' High Cube Container	26
Pallet Dimensions (L × W × H)	69.3 in × 45.3 in × 46.9 in (1760 mm × 1150 mm × 1190 mm)
Pallet Weight	1415 lbs (642 kg)

NOTE: Installation instructions must be followed. See the installation and operating manual or contact our technical service department for further information on approved installation and use of this product.

Hanwha Q CELLS America Inc.
300 Spectrum Center Drive, Suite 1250, Irvine, CA 92618, USA | **TEL** +1 949 748 59 96 | **EMAIL** inquiry@us.q-cells.com | **WEB** www.q-cells.us