CertainTeed Solar **US-SERIES** SOLAR MODULES



See reverse for product specifications





Mono-Crystalline Type:

CT290Mxx-02

CT295Mxx-02

CT300Mxx-02

CT305Mxx-02



Features and Benefits

High Quality/ High Power

- 300W Black backsheet, 305W White backsheet
- UL listed (UL 1703)
- Output power tolerance +3/-0%
- PID Free

Limited Warranty*


- 10-year product warranty
- 25-year linear power output warranty

*See CertainTeed's limited warranty for details





Power Output Warranty








		290W	295W	300W	305W
Nominal Output (Pmpp)	W	290	295	300	305
Voltage at Pmax (Vmpp)	V	32.00	32.24	32.48	32.73
Current at Pmax (Impp)	Α	9.06	9.15	9.24	9.32
Open Circuit Current (Voc)	V	39.77	40.11	40.45	40.79
Short Circuit Current (Isc)	Α	9.62	9.77	9.91	10.06
Output Tolerance	%		<< 0/-	+3%>>	
No. of Cells & Connections		<<	60 in series with	3 bypass diodes -	>>
Cell Type			<< 6" Mono	crystalline ———>>	
Module Efficiency	%	17.7	18.1	18.4	18.7
Temperature Coefficient of Pmpp	%/C		<<0	.38>>	
Temperature Coefficient of Voc	%/C		<<0	.28>>	
Temperature Coefficient of Isc	%/C		<<0	.04>>	



Mechanical Characteristics

Laminate	Glass: 3.2mm high transmission tempered, anti-reflective Encapsulant: EVA Backsheet: Weatherproof film (black/white)
Frame	Anodized aluminum (Black)
Junction Box	IP68, IEC certified, UL listed
Output Cables	4mm² (12AWG) cables 1.0m (39.4") length
Connectors	Polarized MC4 compatible Weatherproof, IEC certified, UL listed
Weight	19.0 kg (41.9 lbs)







Nominal Operating Cell Temperature (NOCT)	46° C + 2
Operating Temperature	-40 to 85° C
Maximum System Voltage	1,000v
Series Fuse Rating	15 A
Fire Performance	Type 2
Maximum Wind Load	30 lbs/ft ²



