

# Heavy Duty Safety Switches

Selection

3  
SAFETY  
SWITCHES



System	Ampere Rating	Indoor - Type 1			Outdoor - Type 3R			Horsepower Ratings							
		Catalog Number	Ship. Wgt.	List Price \$	Catalog Number	Ship. Wgt.	List Price \$	240 Volt		480 Volt		600 Volt		250V DC	600V DC
								1-Phase	3-Phase	1-Phase	3-Phase	1-Phase	3-Phase		

## 600 Volt Non-Fusible<sup>④</sup>

### 2-Pole<sup>③</sup>

### 480 Volt AC / 600 Volt AC / 600 Volt DC

	30	HNF261	12	299.00	HNF261R	13	532.00	—	—	7 1/2	—	10	—	5	15
	60	HNF262	19	532.00	HNF262R	20	930.00	—	—	20	—	25	—	10	30
	100	HNF263	24	823.00	HNF263R	25	1323.00	—	—	30	—	40	—	20	50
	400	HNF265■	109	2893.00	HNF265R	113	4075.00	15	—	50	—	50	—	40	50
	600	HNF266■	111	5102.00	HNF266R■	115	8134.00	15	—	50	—	50	—	50	50

### 3-Pole

### 480 Volt AC / 600 Volt AC / 250 Volt DC

	30	HNF361	12	299.00	HNF361R	13	532.00	5	10	7 1/2	20	10	30	5	—
	30	—	—	—	HNF361RL <sup>⑤</sup>	19	900.00	5	10	7 1/2	20	10	30	5	—
	60	HNF362H <sup>②</sup>	11	523.00	HNF362RH <sup>②</sup>	11	923.00	10	20	20	50	20	40	10	—
	60	HNF362 <sup>②⑦</sup>	18	532.00	HNF362R <sup>①</sup>	19	936.00	10	20	20	50	25	60	10	30 <sup>②</sup>
	60	—	—	—	HNF362RL <sup>⑤</sup>	24	1301.00	10	20	20	50	25	60	10	30 <sup>②</sup>
	100	HNF363 <sup>②⑦</sup>	23	864.00	HNF363R <sup>①</sup>	24	1338.00	15	40	30	75	40	100	20	50 <sup>②</sup>
	200	HNF364 <sup>①</sup>	46	1314.00	HNF364R <sup>①</sup>	47	1616.00	15	60	50	125	50	150	40	50
	400	HNF365	114	3068.00	HNF365R	118	4107.00	15	125	50	250	50	350	50	—
	600	HNF366	116	5467.00	HNF366R	120	8147.00	15	200	50	400	50	500	50	—
	800	HNF367	295	10779.00	HNF367R	295	14209.00	15	250	50	500	50	500	50	—
	1200	HNF368	305	14642.00	HNF368R	307	18567.00	15	250	50	500	50	500	50	—

## 600 Volt Non-Fusible<sup>④</sup>

### 2-Pole<sup>③</sup>

### 480 Volt AC / 600 Volt AC / 600 Volt DC

	Type 4 / 4X Stainless		Type 12 Industrial <sup>⑤</sup>												
	30	HNF261S	13	2153.00	HNF261J	13	641.00	—	—	7 1/2	—	10	—	5	15
	60	HNF262S	20	2521.00	HNF262J	20	806.00	—	—	20	—	25	—	10	30
	100	HNF263S■	25	5137.00	HNF263J■	25	1153.00	—	—	30	—	40	—	20	50
	400	HNF265S■	113	13612.00	HNF265J■	114	3902.00	15	—	50	—	—	—	40	50
	600	HNF266S■	115	19606.00	HNF266J■	120	6557.00	15	—	50	—	—	—	50	50

### 3-Pole

### 480 Volt AC / 600 Volt AC / 250 Volt DC

	30	HNF361S	13	2186.00	HNF361J	13	670.00	5	10	7 1/2	20	10	30	5	—
	60	HNF362SH <sup>②</sup>	15	2537.00	HNF362JH <sup>②</sup>	14	930.00	10	20	20	50	20	40	10	—
	60	HNF362S <sup>②⑦</sup>	19	2563.00	HNF362J <sup>①</sup>	19	946.00	10	20	20	50	25	60	10	30 <sup>②</sup>
	100	HNF363S <sup>②⑦</sup>	24	5198.00	HNF363J <sup>①</sup>	24	1338.00	15	40	30	75	40	100	20	50 <sup>②</sup>
	200	HNF364S <sup>①</sup>	47	7078.00	HNF364J <sup>①</sup>	47	1692.00	15	60	50	125	50	150	40	50
	400	HNF365S	118	14729.00	HNF365J	119	4152.00	15	125	50	250	50	350	50	50
	600	HNF366S	120	21589.00	HNF366J	120	8150.00	15	200	50	400	50	500	50	50
	800	HNF367S	295	30951.00	HNF367J■	295	14224.00	15	250	50	500	50	500	50	50
	1200	HNF368S■	310	34305.00	HNF368J■	310	18684.00	15	250	50	500	50	500	50	50

■ Built to order. Allow 2-3 weeks for delivery.

① Also rated 600V DC.

② Compact switch (11.1"H, 6.6"W box less cover and handle).  
Short circuit withstand rating—100,000 RMS sym. amps.

③ Use 3-Pole switch for 200A application.

④ Suitable for use as service entrance equipment except for  
1200 when used on a 480 or 600V grounded wye system.  
⑤ Also rated type 3S / 3R.

⑥ Indicates oversized enclosure (30A switch in a 60A enclosure or a 60A switch in a 100A enclosure).

⑦ 600V DC and 600V DC horsepower rating shown requires (2) poles to be connected in series.