

ALL-FLASH® NO-CALK® ROOF FLASHINGS




TECHNICAL SPECIFICATION

Engineering Specification: Oatey All-Flash No-Calk Roof Flashings can be used in commercial and residential applications where a watertight seal for roof penetrations around the plumbing vent pipe is required.

Job Reference





(All dimensions in inches)

- ♦ Plastic Base Roof Flashing slides over D
- ♦ Metal Base Roof Flashing slides over DWV pipe for pitch to 40°
- Patented All-Flash collar has tear-away ring allowing flashing to seal different pipe diameters
- Plastic base flashings are made of rigid thermoplastic
- Aluminum base flashings are made of .032 stamped aluminum
- Galvanized base flashings are made of 24 gauge galvanized steel
- Non-fading sealing collar
- Approved for Type B installations
- ♦ Not for hot-mopped or built-up roofs
- Do not use paint or petroleum based products on plastic bases or rubber collars

| ✓ | Product No. | Description | Length (L) | Width (W) | PACK | CARTON WEIGHT |
|---|----------------|---|---------------|--------------|------|------------------|
| | 11919 | 1-1/2" – 3" Thermoplastic No-Calk Roof Flashing | 15 | 11-1/4 | 12 | 9 lbs. |
| | 11920 | 3"- 4" Thermoplastic No-Calk Roof Flashing | 16 | 12 | 12 | 9 lbs. |
| | 11937 | 1-1/2" – 3" Thermoplastic No-Calk Roof Flashing | 15 | 11-1/4 | 6 | 4 lbs. |
| | 11938 | 3"- 4" Thermoplastic No-Calk Roof Flashing | 16 | 12 | 6 | 5 lbs. |
| | 12403 | 1-1/2" – 3" Copper No-Calk Roof Flashing | 14-1/2 | 11 | 12 | 10 lbs. |
| | 12404 | 3" - 4" Copper No-Calk Roof Flashing | 15-1/2 | 12 | 12 | 12 lbs. |
| | 12945 | 1-1/2" – 3" Aluminum No-Calk Roof Flashing | 14-1/2 | 11 | 12 | 7 lbs. |
| | 12956 | 3" - 4" Aluminum No-Calk Roof Flashing | 15-1/2 | 12 | 12 | 13 lbs. |
| | 12976 | 1-1/2" – 3" Aluminum No-Calk Roof Flashing | 14-1/2 | 11 | 6 | 4 lbs. |
| | 12977 | 3" - 4" Aluminum No-Calk Roof Flashing | 15-1/2 | 12 | 6 | 7 lbs. |
| | 11871 | 1-1/2" – 3" Galvanized No-Calk Roof Flashing | 14-1/2 | 11 | 12 | 17 lbs. |
| | 11877 | 3" – 4" Galvanized No-Calk Roof Flashing | 15-1/2 | 12 | 12 | 23 lbs. |
| | 11815 | 1-1/2" – 3" Galvanized No-Calk Roof Flashing | 14-1/2 | 11 | 6 | 4 lbs. |
| | 11816 | 3" – 4" Galvanized No-Calk Roof Flashing | 15-1/2 | 12 | 6 | 12 lbs. |
| | 11957 | 1-1/2" – 3" Large Base Galvanized No-Calk Roof | 18 | 18 | 12 | 23 lbs. |
| | | Flashing | | | | |
| | 11958 | 3" – 4" Large Base Galvanized No-Calk Roof Flashing | 18 | 18 | 12 | 26 lbs. |
| | 12974 | 1-1/2" – 3" Large Base Aluminum No-Calk Roof Flashing | 18 | 18 | 12 | 20 lbs. |
| | 12975 | 3" - 4" Large Base Aluminum No-Calk Roof Flashing | 18 | 18 | 12 | 20 lbs. |





Data is subject to manufacturing tolerances.