

Heavy Duty Safety Switches

Selection

3
SAFETY
SWITCHES



System	Ampere Rating	Indoor — Type 1			Outdoor — Type 3R			Horsepower Ratings ^②							250 Volt DC
		Catalog Number	List Price \$	Ship Wt.* Std. Pkg.	Catalog Number	List Price \$	Ship Wt.* Std. Pkg.	240V AC							
								1-Phase, 2-Wire		2-Phase, 4-Wire		3-Phase, 3-Wire			
								Std.	Max.	Std.	Max.	Std.	Max.		

240 Volt Fusible^③

2-Pole, 2-Fuse, and Solid Neutral^③ (Also used for 2-Pole, 2-Wire Applications) 240 Volt AC/250 Volt DC

	30	HF221N	257.00	12	HF221NR	487.00	13	1½	3	—	—	3	7½	5
	60	HF222N	512.00	18	HF222NR	914.00	19	3	10	—	—	7½	15	10
	100	HF223N	781.00	23	HF223NR	1174.00	24	7½	15	—	—	15	30	20
	200	HF224N	1391.00	47	HF224NR	1700.00	48	15	—	—	—	25	60	40
	400	HF225NH ^①	3390.00	129	HF225NRH ^①	4536.00	131	15	—	—	—	50	125	50
	400	HF225N	3416.00	153	HF225NR	4559.00	157	15	—	—	—	50	125	50
	600	HF226NH ^①	6237.00	133	HF226NRH ^①	8317.00	135	15	—	—	—	75	200	50
	600	HF226N	6266.00	155	HF226NR	8351.00	159	15	—	—	—	75	200	50
	800	HF227N	11116.00	365	HF227NR	13270.00	365	—	—	—	—	100	250	50
	1200	HF228N	13688.00	385	HF228NR	18454.00	385	—	—	—	—	100	250	50

3-Pole, 3-Fuse, and Solid Neutral (Also used for 3-Pole, 3-Wire Applications) 240 Volt AC/250 Volt DC

	30	HF321N	323.00	14	HF321NR	620.00	15	1½	3	—	—	3	7½	5
	60	HF322N	547.00	19	HF322NR	979.00	20	3	10	—	—	7½	15	10
	100	HF323N	906.00	25	HF323NR	1400.00	26	7½	15	—	—	15	30	20
	200	HF324N	1570.00	49	HF324NR	1906.00	50	15	—	—	—	25	60	40
	400	HF325NH ^①	4161.00	137	HF325NRH ^①	4643.00	138	15	—	—	—	50	125	50
	400	HF325N	4183.00	158	HF325NR	4183.00	162	15	—	—	—	50	125	50
	600	HF326NH ^①	7073.00	139	HF326NRH ^①	9354.00	142	15	—	—	—	75	200	50
	600	HF326N	7104.00	161	HF326NR	9389.00	165	15	—	—	—	75	200	50
	800	HF327N	13591.00	375	HF327NR	17377.00	375	—	—	—	—	100	250	50
	1200	HF328N	16946.00	395	HF328NR	21095.00	388	—	—	—	—	100	250	50

240 Volt Fusible^③

2-Pole, 2-Fuse^④ Type 4/4X Stainless Type 12 Industrial^⑤ 240 Volt AC/250 Volt DC

	30	HF221S	2216.00	13	HF221J	729.00	13	1½	3	—	—	3	7½	5
	60	HF222S	2507.00	19	HF222J	881.00	19	3	10	—	—	7½	15	10
	100	HF223S	4952.00	24	HF223J	1274.00	24	7½	15	—	—	15	30	20
	200	HF224S	7519.00	48	HF224J	2017.00	48	15	—	—	—	25	60	40

3-Pole, 3-Fuse^④ (Also used for 2-Pole, 2-Wire Applications in 400–800A Ratings) 240 Volt AC/250 Volt DC

	30	HF321S	2307.00	14	HF321J	767.00	14	1½	3	—	—	3	7½	—
	60	HF322S	2707.00	20	HF322J	939.00	20	3	10	—	—	7½	15	10
	100	HF323S	5759.00	25	HF323J	1414.00	25	7½	15	—	—	15	30	20
	200	HF324S	7965.00	49	HF324J	2185.00	49	15	—	—	—	25	60	40
	400	HF325S	16315.00	154	HF325J	4741.00	110	15	—	—	—	50	125	50
	600	HF326S	23672.00	157	HF326J	8957.00	161	15	—	—	—	75	200	50
	800	HF327S	31830.00	370	HF327J	16792.00	365	—	—	—	—	100	250	50

■ Built to order. Allow 2–3 weeks for delivery.

* In pounds (lbs).

① Height reduced switch (45.25 rather than 56 inches in height) for use with 500MCM or smaller conductors.

② Dual horsepower ratings: Std.- applies when non-time delay fuses are installed. Max.- applies when time-delay fuses are installed.

③ These switches are UL-listed for application on grounded B-phase systems and are suitable for 3-phase motor applications.

④ When a neutral is required use a field installed neutral kit.

⑤ Suitable for use as service entrance equipment.

⑥ Also rated Type 3S/3R.