POLARIS · TRIPSURE

Hotel API

Integration Guide

REST API reference for hotel search, pricing, booking, and post-booking management

Prepared for	TripAgent
Provided by	Polaris Commerce Pvt Ltd
Document version	1.0
Status	Confidential — for partner integration use only

1. Introduction

This document describes the Tripsure Hotel API — a RESTful web service that lets partners search for hotels, retrieve rich property and room content, verify live prices, and place, view, and cancel bookings. It is intended for the OnArrival engineering team building the hotel booking experience on behalf of Jupiter.

The API follows a stateful, token-based booking flow. Each step produces identifiers (tokens, doc keys, booking codes, reference numbers) that are passed forward into the next call. Following the sequence in Section 5 is required — for example, a booking cannot be created without first creating an itinerary, which in turn depends on a prior price check.

Conventions used in this document

- **Placeholders —** values shown in curly braces such as {{token}} are placeholders you replace with real values obtained from earlier responses.
- **Payloads —** all request and response bodies are JSON with Content-Type: application/json.
- **Dates —** all timestamps and dates use ISO 8601. Dates are YYYY-MM-DD; datetimes include timezone offset.
- **Currency —** monetary amounts are in the currency of the request (default INR) unless stated otherwise.

2. Environment and Base URL

The API is served from a single base URL. It is supplied to you during onboarding; substitute it wherever the placeholder below appears.

Placeholder	Purpose
`{{BASE_URL}}`	Base host for all endpoints — location autosuggest, hotel listing and details, price check, itinerary, booking, cancellation, invoice, and health check.

> **Note**
> All endpoints share the same base URL. Prepend {{BASE_URL}} to every path shown in the reference sections below.

3. Authentication and Required Headers

Every request is authenticated with a tenant identifier and an API key supplied via HTTP headers. These credentials are issued to OnArrival during onboarding and must be kept secret; never expose them in client-side code.

Header	Required	Description

x-tenant-id	Yes	Your tenant identifier issued by Tripsure.
x-api-key	Yes	Secret API key that authenticates the tenant. Send on every request.
x-trace-id	Recommended	A correlation ID that identifies the entire user journey. Generate one value (e.g. a UUID) [ona-3518-a845c375] at the start of the flow (City Suggestion) and reuse it on every subsequent call through to all post-booking operations. Echoed back in responses.
Content-Type	For POST	Must be application/json for all requests that send a body.
Accept-Encoding	Recommended	Send gzip to receive compressed responses. Strongly advised for Hotel Listing, whose responses are large; the client must handle decompression.

> **Tip — traceability**
> Use a single **x-trace-id** for the whole user flow — generate it at City Suggestion and reuse it on every call up to and including all post-booking operations.
> Store it on your side against the order so a support ticket can be traced end to end. Quoting the trace ID lets Tripsure follow the complete user journey and reconcile the order quickly.

4. Response Envelope and Error Handling

Most endpoints return a consistent JSON envelope. Business data is carried in the response object; status information is carried in the sibling fields.

```
{
  "response": { ... },          // endpoint-specific payload (null on error)
  "error": null,                 // human-readable error text, or null on success
  "code": 200,                   // numeric status
  "internalErrorCode": null,     // provider/business error code when applicable
  "statusCode": "OK"            // textual status
}
```

HTTP and business status codes

Code	Meaning	Typical handling
`200 OK`	Success	Read the response and continue the flow.
`400 Bad Request`	Validation or business rule failure	Inspect error and internalErrorCode; correct the request and retry.
`401 / 403`	Authentication failure	Verify **x-tenant-id** and **x-api-key**.
`404 Not Found`	Unknown reference	Check the partnerReferenceId / order reference in the URL.
`429 Too Many Requests`	Rate limit exceeded	Back off and retry; see rate-limit headers below.
`5xx`	Upstream/server error	Retry idempotent reads; contact support with the trace ID.

Known business error codes

internalErrorCode	Example message	Cause
`4020`	Invalid PAN number	The PAN supplied at itinerary creation is malformed.
`4020`	PAN name does not match customer name	The PAN holder name differs from the customer name provided.

Rate limiting

Responses include standard rate-limit headers so you can throttle proactively: X-RateLimit-Limit, X-RateLimit-Remaining, and X-RateLimit-Reset (a Unix timestamp indicating when the window resets). Design your integration to honour these headers and back off on 429 responses.

5. End-to-End Booking Flow

The endpoints are designed to be called in the following order. Each step yields identifiers consumed by later steps.

Step	Endpoint	What it does

1	City Suggestion	Resolve a user's text query into a location (id, coordinates, type).
2	Hotel Listing	Search available hotels for the location and stay dates. Returns hotel results plus a search token / docKey.
3	Hotel Details	Fetch full content and room/rate options for a chosen hotel using the token and docKey.
4	Price Check	Re-validate the live price and cancellation policy for a selected room rate before booking.
5	Create Itinerary	Lock the selection with guest details and PAN/GST; returns a partnerReferenceId and order reference.
6	Book Room	Confirm the booking against the itinerary and the collected amount.
7	Booking Details / Cancel / Invoice	Retrieve status, compute cancellation fees, cancel, or download the tax invoice.

Identifier chain

- **token** and **docKey** come from Listing → used by Details and Price Check.
- **roomTypeId**, **roomTypeCode** (rate plan) and bookingCode come from Details/Price Check → used by Create Itinerary.
- **partnerReferenceId** and **orderRefNum** come from Create Itinerary → used by Book Room and all post-booking calls.

6. Endpoint Reference

6.1 City Suggestion (Location Autosuggest)

Resolves free-text input into structured location suggestions, including popular sub-locations, points of interest, and hotels. Use the first / chosen suggestion's id, name, type and coordinates to drive the Hotel Listing call.

```
GET   {{BASE_URL}}/api/hotel/locations/autosuggest?q={query}
```

Query parameters

Parameter	Description
q	Required. The user's search text, e.g. goa.

Sample response (trimmed)

```
{
  "response": {
    "locationSuggestions": [
      {
        "id": "328959",
        "name": "Goa",
        "fullName": "Goa, India",
        "type": "State",
        "country": "IN",
        "coordinates": { "lat": 15.498995, "lon": 73.828214 },
        "popular_locations": [ { "id": "334152", "name": "North Goa", ... } ],
        "popular_poi":       [ { "id": "329890", "name": "Calangute Beach", ... } ],
        "popular_hotels":    [ { "id": "...", "name": "...", ... } ]
      }
    ]
  }
}
```

Key response fields

Field	Description
locationSuggestions[]	Ordered list of matches; the first is the best match.
id	Location identifier — pass as locationSuggestion.id in Hotel Listing.
name / fullName	Display name and fully qualified name of the location.
type	Location granularity: State, City, PointOfInterest, or Hotel.
coordinates.lat / .lon	Geographic centre — pass as lat / lon in Hotel Listing.
popular_locations / popular_poi / popular_hotels	Suggested drill-downs for building richer search UIs.

6.2 Hotel Listing (Search)

Searches for available hotels at a resolved location for the given stay dates and room/occupancy configuration. The response provides the hotel results together with the search token and doc key used by subsequent Details and Price Check calls.

```
POST   {{BASE_URL}}/api/hotel/listing
```

Request body

```
{
  "checkIn": "2026-08-05",
  "checkOut": "2026-08-06",
  "rooms": [
    { "numberOfAdults": "2", "numberOfChildren": "1", "childrenAge": "3" }
  ],
  "city": "Goa",
  "locationSuggestion": {
    "id": "328959",
    "name": "Goa",
    "type": "State",
    "lat": 15.498995,
    "lon": 73.828214
  },
  "state": "Goa",
  "countryName": "IN",
  "circularSearch": false,
  "nationalityCode": "IN",
  "countryCode": "IN",
  "partnerCall": true,
  "currency": "INR",
  "fetchFromCache": false
}
```

Request fields

Field	Description
checkIn / checkOut	Required. Stay dates in YYYY-MM-DD.
rooms[]	Required. One object per room. Multiple rooms = multiple objects.
rooms[].numberOfAdults	Adults in the room (as a string).
rooms[].numberOfChildren	Children in the room (as a string); 0 if none.
rooms[].childrenAge	Comma-separated ages when children are present.
locationSuggestion	The chosen suggestion from City Suggestion (id, name, type, lat, lon).
city / state / countryName	Location descriptors from the suggestion.

`nationalityCode / countryCode`	Guest nationality and country (ISO code), e.g. IN.
`partnerCall`	Set true for partner (server-to-server) integrations.
`currency`	Requested pricing currency, e.g. INR. [default INR]
`fetchFromCache`	false to force a fresh availability search.

Carry forward

From the listing response, retain the search **token** and **docKey** for the hotel(s) the user is interested in, plus the **hotelId**. These are required by Hotel Details and Price Check.

Performance — enable compression

Hotel Listing responses can be large. Send the Accept-Encoding: gzip header on this request and implement gzip decompression on the client so responses transfer quickly over the network.

6.3 Hotel Details

Returns full property content — descriptions, amenities, images, policies, nearby attractions — and the bookable room groups with rate breakdowns and cancellation rules for the searched dates.

POST {{BASE_URL}}/api/hotel/details

Request body

```
{
  "docKey": "{{docKey}}",
  "token": "{{token}}",
  "hotelId": "{{hotelId}}",
  "contentOnly": false,
  "provider": "{{provider}}"
}
```

Request fields

Field	Description
docKey	Required. Document key from the Hotel Listing response.
token	Required. Search token from the Hotel Listing response.
hotelId	Required. Identifier of the hotel to expand.
contentOnly	true returns static content only (no live rates); false returns content plus room rates.
provider	Supplier/provider code associated with the hotel from the listing.

Sample response (structure, trimmed)

```
{
  "response": {
    "partnerName": "Tripsure",
    "validResponse": true,
    "token": "...",
    "hotelInfo": {
      "hotelName": "...", "address": "...", "city": "...", "state": "...",
      "latitude": "...", "longitude": "...",
      "hotelAmenities": [ { "amenity": "...", "category": "..." } ],
      "imageInfo":      [ { "largeImageUrl": "...", "caption": "..." } ],
      "policies":       [ { "name": "...", "content": "..." } ],
      "roomGroups": [
        {
          "standardRoomIds": ["1"],
          "options": [
            {
              "recommendationId": "...",
              "totalRate": 4027,
              "standardRooms": [
                {
                  "rateBreakdown": { "baseFare": 3451, "tax": 576, "total": 4027 },
                  "roomType": {
```

```
                  "roomTitle": "Superior Room,1 Queen Bed,NonSmoking",
                  "roomTypeId": "…", "roomTypeCode": "…", "bookingCode": "…",
                  "refundable": true, "isPANMandatory": false
                },
                "cancellationPolicy": "…", "cancellationRules": [ … ]
              }
            ]
          }
        ]
      }
    ]
  }
}
```

Key response fields

Field	Description
hotelInfo	Property-level content object.
hotelInfo.roomGroups[].options[]	Bookable rate options for a standard room.
…roomType.roomTypeId	Room type identifier — required by Create Itinerary.
…roomType.roomTypeCode	Rate-plan identifier — passed as roomRatePlanId / roomTypeCode in Create Itinerary.
…roomType.bookingCode	Rate booking code — required by Price Check and Create Itinerary.
…rateBreakdown.total	Total price for the option; feeds bookingAmount.
…roomType.isPANMandatory / isPassportMandatory	Indicates whether PAN / passport is required to book this rate.
…cancellationRules	Machine-readable cancellation windows (amount/percentage with start/end).

6.4 Price Check

Re-validates the live price and cancellation policy for a chosen room rate immediately before booking. **Always** call this after the user selects a room and before creating an itinerary, so price changes are surfaced to the customer.

```
POST   {{BASE_URL}}/api/hotel/priceCheck
```

Request body

```
{
  "hotelId": "{{hotelId}}",
  "docKey": "{{docKey}}",
  "token": "{{token}}",
  "bookingCode": "{{bookingCode}}"
}
```

Request fields

Field	Description
hotelId	Required. Hotel identifier.
docKey	Required. Document key from Hotel Listing.
token	Required. Search token from Hotel Listing.
bookingCode	Required. Rate booking code from Hotel Details for the selected option.

Sample response (trimmed)

```
{
  "response": {
    "hotelId": "39972858",
    "checkIn": "2026-08-05", "checkOut": "2026-08-06",
    "roomRates": [
      {
        "rateBreakdown": { "baseFare": 3451, "tax": 576, "total": 4027 },
        "roomType": {
          "roomTitle": "Superior Room,1 Queen Bed,NonSmoking",
          "roomTypeId": "…", "roomTypeCode": "…", "bookingCode": "…",
          "refundable": true, "refundability": "Refundable",
          "isPANMandatory": false, "isPassportMandatory": false
        },
        "cancellation": "This booking is Refundable. Free Cancellation …",
        "cancellationRules": [ { "rules": [ { "value": 0, "valueType": "Amount", … } ] } ],
        "inclusions": [ "Free breakfast,Free self parking" ]
      }
    ],
    "panCardRequired": false,
    "customerAddressRequired": false,
```

```
    "changeInPrice": false
  },
  "code": 200, "statusCode": "OK"
}
```

Key response fields

Field	Description
`roomRates[].rateBreakdown.total`	Confirmed total to charge; use as bookingAmount.
`changeInPrice`	true if the price changed since Hotel Details — show the customer the change before booking.
`panCardRequired / customerAddressRequired`	When panCardRequired is true, a PAN must be supplied as panCardNumber in Create Itinerary; customerAddressRequired indicates full address is needed.
`cancellationRules / cancellation`	Structured and human-readable cancellation policy.
`checkInInstructions`	Property check-in rules, mandatory/optional fees, and accepted cards.
`inclusions`	Rate inclusions such as breakfast or parking.

Show the customer what changed

Compare the Price Check response against the Hotel Details data and surface any differences before proceeding — in particular the price (changeInPrice), the cancellation policy, and the hotel name and room names. This lets the customer confirm the final details before an itinerary is created.

PAN handling

If **panCardRequired** is true, you must collect a PAN and pass **panCardNumber** in Create Itinerary.
PAN is generally requested when an Indian customer books an international hotel.
The client only needs to validate that the PAN is in the correct format — it does not need to verify the PAN holder's name against the PAN number. Tripsure performs that check.

6.5 Create Itinerary

Locks the selected rate together with guest, contact, PAN and optional GST details. A successful call returns a partnerReferenceId and order reference that identifies the pending booking.

```
POST   {{BASE_URL}}/api/hotel/booking/create-itinerary
```

Request body

```
{
  "orderRefNum": "{{orderRefNum}}",
  "hotelId": "{{hotelId}}",
  "searchToken": "{{token}}",
  "checkIn": "2026-08-05",
  "checkOut": "2026-08-06",
  "rooms": [
    {
      "room": 1,
      "numberOfAdults": "2",
      "numberOfChildren": "1",
      "childrenAge": "3",
      "roomTypeId": "{{roomTypeId}}",
      "roomRatePlanId": "{{roomTypeCode}}",
      "bookingCode": "{{bookingCode}}"
    }
  ],
  "bookingCode": "{{bookingCode}}",
  "roomTypeCode": "{{roomTypeCode}}",
  "bookingAmount": 4027,
  "couponCode": "",
  "mobileCountryCode": "91",
  "orderId": "{{orderRefNum}}",
  "customerInfo": {
    "title": "Mr", "firstName": "Concierge", "lastName": "User",
    "type": "Adult", "mobile": "8873044319", "email": "guest@example.com",
    "streetAddress1": "", "city": "", "state": "", "postalCode": "", "age": 0
  },
  "country": "IN",
  "panCardNumber": "ABCDE1234F",
  "gst": { "gstNumber": "", "name": "", "address": "", "state": "", "city": "", "pincode":
"" }
}
```

Request fields

Field	Description
`orderRefNum / orderId`	Your order reference for this transaction.
`hotelId`	Hotel being booked.
`searchToken`	Search token from Hotel Listing.
`checkIn / checkOut`	Stay dates (YYYY-MM-DD).

rooms[].roomTypeId	Room type id from Details / Price Check.
rooms[].roomRatePlanId	Rate-plan id (roomTypeCode) for the room.
rooms[].bookingCode	Rate booking code for the room.
bookingAmount	Confirmed total from Price Check.
customerInfo	Lead guest details: title, first/last name, mobile, email, and address when required.
mobileCountryCode / country	Contact country code (e.g. 91) and guest country (e.g. IN).
panCardNumber	Required only when the Price Check response returned panCardRequired: true (typically an Indian customer booking an international hotel). Validate the PAN format on the client; name-to-PAN verification is done by Polaris Tripsure.
gst	Optional GST billing details for business invoices.
couponCode	Optional promotional code; empty string if none.

Success response


```
{
  "response": {
    "orderRefNum": "SBCGf53ccdfc",
    "partnerReferenceId": "e1ac32b9-09bc-4b1d-be4d-7798e816b309",
    "amount": 4027,
    "totalRate": 4026.03,
    "bookingAmount": 4027,
    "isChangeInPrice": false,
    "panCardRequired": false,
    "token": "30c23eca-c2d6-4c13-83eb-4d207d222f17",
    "rateBreakdown": { "baseFare": 3451.30, "tax": 574.73, "total": 4026.03 },
    "message": "Itinerary Created Successfully"
  },
  "code": 200, "statusCode": "OK"
}
```


Validation error responses


```
// Invalid PAN
{ "response": { "message": "Invalid PAN number" },
  "error": "Invalid PAN number", "code": 400,
  "statusCode": "Bad Request", "internalErrorCode": 4020 }

// PAN name mismatch
{ "response": { "message": "PAN name … does not match customer name" },
  "error": "PAN name … does not match customer name",
```

```
  "code": 400, "statusCode": "Bad Request", "internalErrorCode": 4020 }
```

Carry forward

Retain **partnerReferenceId** and **orderRefNum** from the success response — they are required to confirm the booking (Book Room) and for every post-booking operation.
Also check **isChangeInPrice**; if true, reconfirm the new amount before proceeding.

6.6 Book Room (Confirm Booking)

Confirms the pending itinerary into a firm booking. Send the order reference, the partner reference returned by Create Itinerary, and the amount collected from the customer.

```
POST   {{BASE_URL}}/api/hotel/booking/create
```

Request body

```
{
  "orderRefNum": "{{orderRefNum}}",
  "partnerReferenceId": "{{partnerRefId}}",
  "amountCollected": 4027
}
```

Request fields

Field	Description
`orderRefNum`	Order reference from Create Itinerary.
`partnerReferenceId`	Partner reference id from Create Itinerary.
`amountCollected`	Amount actually collected from the customer; must match the confirmed booking amount.

Collect payment first

Collect the amount from the customer before sending the Book Room request. amountCollected must reflect the amount actually taken and match the confirmed booking amount.

Handle slow or timed-out responses

The Book Room call may take a while to complete. Until it returns a terminal status (Confirmed or Failed), or if it times out or is slow to respond, keep the booking in a processing / pending state on your side rather than treating it as failed. Do not blindly retry — the call is non-idempotent and a retry can create a duplicate booking.

Always reconfirm via Booking Details

Immediately after the Book Room request, call the Booking Details API with the partnerReferenceId to reconfirm the outcome. Use its status to move the order from processing to the correct terminal state.

6.7 Booking Details

Retrieves the current status and full details of a booking by its partner reference id. Use this to reconcile bookings and to confirm outcomes after any uncertain Book Room call.

```
GET   {{BASE_URL}}/api/hotel/booking/{partnerReferenceId}
```

Path parameter

Parameter	Description
`partnerReferenceId`	Required. The partner reference id returned by Create Itinerary.

7. Post Booking Endpoints

7.1 Cancellation Fee

Returns the applicable cancellation charge for a booking as of now, based on the rate's cancellation rules. Call this before cancelling so the customer can be shown the refund/penalty.

```
GET    {{BASE_URL}}/api/hotel/booking/{partnerReferenceId}/cancellation-fee
```

Path parameter

Parameter	Description
`partnerReferenceId`	Required. The booking's partner reference id.

7.2 Cancel Booking

Cancels a confirmed booking. The refund/penalty follows the rate's cancellation policy at the time of cancellation. Confirm the fee via the Cancellation Fee endpoint first.

```
POST    {{BASE_URL}}/api/hotel/booking/{partnerReferenceId}/cancel
```

Path parameter

Parameter	Description
`partnerReferenceId`	Required. The booking's partner reference id.

7.2 Download Tax Invoice

Retrieves the tax invoice for a booking. Pass regenerate=true to force the invoice to be regenerated rather than served from cache.

```
GET
{{BASE_URL}}/api/hotel/booking/{partnerReferenceId}/tax-invoice?regenerate=true
```

Parameters

Parameter	Description
`partnerReferenceId`	Required (path). The booking's partner reference id.

`regenerate`	Optional (query). true to regenerate the invoice instead of returning a cached copy.

7. Endpoint Quick Reference

All paths below are relative to {{BASE_URL}}.

Method & Path	Purpose
`GET /api/hotel/locations/autosuggest`	Location autosuggest
`POST /api/hotel/listing`	Hotel search
`POST /api/hotel/details`	Hotel content & room rates
`POST /api/hotel/priceCheck`	Live price re-validation
`POST /api/hotel/booking/create-itinerary`	Lock selection + guest details
`POST /api/hotel/booking/create`	Confirm booking
`GET /api/hotel/booking/{ref}`	Booking details / status
`GET /api/hotel/booking/{ref}/cancellation-fee`	Cancellation fee quote
`POST /api/hotel/booking/{ref}/cancel`	Cancel booking
`GET /api/hotel/booking/{ref}/tax-invoice`	Download tax invoice
`GET /api/hotel/healthCheck`	Health check

8. Integration Notes and Best Practices

- **Follow the flow —** call endpoints in the documented order; identifiers from each step are prerequisites for the next.
- **Enable compression —** send Accept-Encoding: gzip and decompress on the client, especially for the large Hotel Listing responses, for faster network transfer.
- **Re-validate and show changes —** always Price Check immediately before Create Itinerary and show the customer any changes in price, cancellation policy, and hotel/room names versus the Hotel Details data.
- **PAN handling —** pass panCardNumber in Create Itinerary only when Price Check returns panCardRequired: true — typically Indian customers booking international hotels. Validate only the PAN format; Tripsure verifies the name against the PAN.
- **Collect payment first —** collect the amount from the customer before sending the Book Room request, and set amountCollected to the amount actually taken.
- **Handle pending bookings —** keep a booking in processing / pending if the Book Room is slow or times out, until it returns a terminal status (Confirmed or Failed). Do not blindly retry — the call is non-idempotent.
- **Always reconfirm —** call Booking Details immediately after Book Room to reconfirm the status and drive the order to its terminal state.
- **Trace the journey —** use one x-trace-id for the entire user flow (from City Suggestion through all post-booking calls) and store it against your order for support and reconciliation.
- **Handle rate limits —** respect X-RateLimit-* headers and back off on HTTP 429.
- **Protect credentials —** never expose x-api-key in browser or mobile clients; keep all calls server-to-server.

9. Support

For credentials, environment URLs, or integration assistance, contact your Tripsure onboarding representative.
When reporting an issue, always include the relevant x-trace-id, the endpoint, the request timestamp, and the partnerReferenceId or orderRefNum where applicable.

This document is confidential and provided solely for the purpose of integrating with the Tripsure Hotel API. © Polaris Commerce Pvt Ltd.