Form no: GrSD-10.3 /SC/600
(Rev)no/ Date:(o1)1st April 2021

NEPAL AIRLINES CORPORATION
GROUND SUPPORT DEPARTMENT
GSE PLANNING

GE 618/19/20/21/ 22/ 23/24/25

Equipment –Conveyer Belt Loader
Model No: 2020/07-NBL
Serial No: - T62958-65

Engine: -Perkins

Check: **D** (2000 hrs.)
Scheduled Check hour:
Check completed

hour:

Job No:
Date:

……AD

……BS

Material Required:

SN	Materials	Part No/Grade	Quantity	Remarks
1	Engine oil	SAE 15 W 40	9Lts	
2	Engine oil filter	5000102-001	1	
3	Fuel filter	5000102-002	1	
4	Air filter	5133125	1	
5	Hydraulic filter	6800082	1	
6	Transmission filter	5200075-001	1	
7	Hydraulic oil	ISO 111 58	75L	
8	Transmission oil	DEXRON II D	7 ltr	
9	Brake oil	Dot 4	0.75L	
10	Differential oil	SAE 85W 90	5 L	
11	Grease	Ronex	As Reqd	

Note: In remarks column, mark **"R"** for replaced items, **"NA"** for not available, **"NR"** for not replaced items & **"NN"** for not necessary with reason.

Job allocated to:

SN	Name	Signature	SN	Name	Signature
1					
2					

Job Description (Please tick for the completed job): -

1. Drain and refill engine oil.
2. Replace oil filter.
3. Replace fuel filter.
4. Drain water and sediments from the fuel tank via drain valve on the bottom of the fuel tank.
5. Check condition of drive belt and adjust belt tension. Replace the belt if there is presence of server wear and crack. Correct tension for new belt is 400N to 489 N. Correct Tension for used belt after more than 30 minutes of operation is 267 N to 356 N.

6. Check and clean radiator cooling system and also check leakage of coolant cap and cap gasket.
7. Check 3D censer function and condition.
8. Replace engine crankcase breather.
9. Check the fuel injector for proper functioning.
10. Visually inspect the water pump for leaks. Renew the water pump seal the water pump of there is an excessive leakage of coolant.
11. Check the alternator battery charging system and fan belt tension.
12. Check valve clearance. (Inlet:0.2 mm Exhaust:0.2 mm)
13. Check condition of mounting and its bolts of engine, transmission, starter motor, and alternator, radiator and hydraulic pump.
14. Lubricate engine control linkage.
15. Check /Lubricate battery terminal connections, battery condition, and battery cabinet /Tray and carry out necessary job if required.
16. Clean air cleaner, replace if necessary.
17. Hydraulic system
    a) Drain and refill hydraulic fluid.
    b) Check alignment of hydraulic pump mounting.
    c) Check the condition of the rigid and flexible pipes.
    d) Extend each screw jack to its maximum. Check for any leakage or scratch. Clean the shafts.
    e) Check the hydraulic flaps for tightness.
    f) Replace hydraulic filters.
    g) Check the calibration of the limiters.
    h) Tighten all connections and retaining clips.
18. Drain and refill transmission oil.
19. Replace transmission filter.
20. Check for the proper functioning of steering system. Adjust the steering, wheel play 10 to 30 mm.
21. Test wiping and washing system.
22. Change wipers if not working.
23. Check & adjust paring breaks.
24. Check all external and internal operator cabin lights, horn hazard/beacon lights, and its switches.
25. Check all limit switches and interlock system for smooth operation.
26. Check all electrical switches for proper function.
27. Check the condition of flexible brake pipes.
28. Check tyre pressure 4.5 bar (50 PSI).
29. Check wheel nut tightening to ensure 235 lbs./ 32 mdaN.
30. Drain the braking circuit.
31. Check the steering track rods ends for play.
32. Drain and refill differential oil.
33. Perform plate brake carrier tightening.
34. Check leaks on wheel cylinder and check Wearing on brake pads.

35. Apply axle end knee greasing.
36. Check dented body parts and report to I/C GSEM for further necessary dent/paint works.
37. Check foot brake and replace lining/ brake pad if necessary.
38. Check visibility of equipment identification number, safety Warning signs and instructions including EEE and RA logo.
39. Check validity and condition of fire extinguisher and its mounting.
40. Check the condition of boom/change and repair it if damage.
41. Grease all nipples.
42. Wash and steam clean the equipment.

Estimated Time:
Job started Time:
Job finished Time:
Job completed by:
Labour cost:

Equipment test driven by:
Equipment released by:
I/C Maintenance:
Completion date:
Material cost:

Check sheet received by:
GSE planning:
Date:

Technical Bulletin:

If necessary draw attentions of I/C GSEM, I/C GSEP, I/C R and D (tick mark for concerned I/C and furnish your outlooks in following text box pertaining overall operational and maintenance aspects of the equipment such as:

1. Further job to be accomplished other than mentioned in this check sheet.
2. Residual jobs due to any circumstances that has to be carry out in next following check.
3. Any particular systems, aggregates and parts to be kept under surveillance during operation of the equipment.
4. Any particular system, aggregates and parts to be monitor/repair modification/replace on next scheduled maintenance.
5. Amendments to be done in this check sheet.

	GSEM		GSEO		GSEP		R AND D		OTHER

Note: -

Technicians may also submit available supportive documents, if deemed relevant, along with this check sheet in order to authenticate the outlooks.

Source of reference

This check sheet has been issued /revised from GSE Planning on the basic of following:

1. Maintenance service manual of OEM.
2. Previous check sheets.
3. Maintenance practices.
4. ISAGO standards, requirements and recommended practices.
5. Recommendations of different auditors/ airlines.
6. Recommendations of the regulating body.
7. Recommendations of QA department in course of Quality Audits.
8. Recommendations of CS Division.

Bulletin Issued By
GSE planning