

Providing space heating and domestic hot water generation for hydronically-heated small commercial premises needing boiler replacements.

Fractional Forge — Project a_compact_commercial_airsource_heat_pump

Generated: 2026-05-05

Economics Dashboard

VERDICT: PENDING

EST. UNIT COST

Not computed

[D] Algorithmic Estimate

TARGET COST CEILING

£4,500.00

[A] Brief Constraint

NON-RECURRING ENG. (NRE)

Not computed

[D] Modelled

TOTAL ADDRESSABLE MARKET

Not computed

[B] Research

SUBSYSTEM MODULES

0

[D] Decomposition

BOM LINE ITEMS

0

[D] Parts Generated

MARKET CAGR

Not computed

[C] Analyst consensus

SPATIAL ALLOCATION

Infeasible

[D] Solver verification

Source Grading Key

- [A] Primary datasheet or direct constraint
- [B] Supplier quote or high-confidence research
- [C] Trade journal or secondary source
- [D] Algorithmic estimate or LLM extraction
- [E] LLM assumption or unverified hypothesis

Feasibility Gate Assessment

The following automated checks verify the integrity and completeness of the engineering specification before detailed analysis.

Check	Status	Reason	Evidence
1. Market TAM/SAM/SOM Defined	FAIL	Missing market data	Not computed
2. Regulatory Standards Identified	PASS	Standards found	5 standards
3. Cost Ceiling Specified	PASS	Target provided	£4,500.00
4. Spatial Envelope Provided	WARN	No dimensions	Not computed
5. Modules Decomposed	FAIL	Decomposition failed	0 modules
6. BOM Cost Within Ceiling	PASS	Compared unit cost to ceiling	Not computed
7. Risk Matrix Saturated	FAIL	FMEA rows generated	Risks exist

Methodology Note

The feasibility gate ensures that prior to consuming significant computational resources and compiling sub-component analyses, the foundational constraints exist and align with a viable physical interpretation. Failure on any PASS/FAIL criteria halts downstream generation.

Data Sources

[System] Internal gate checks

Overall Section Grade: A

1. Brief & Requirements [A]

1.1 Mission & Use Case

Mission

To accelerate the decarbonization of small UK commercial buildings by delivering a highly efficient, single-unit 30kW R290 heat pump at a disruptive price point.

Use Case

Providing space heating and domestic hot water generation for hydronically-heated small commercial premises needing boiler replacements.

1.2 Market Context & Timing [B]

The progressive UK F-Gas phase-down, upcoming commercial boiler bans, and strong ESG initiatives have created an urgent market vacuum for affordable, low-GWP, high-capacity heating systems.

Small to medium enterprise (SME) office buildings, light commercial retail stores, boutique hospitality venues, and commercial mechanical contractors.

Data Sources

[User Input] Original brief provided

[LLM Output] Research synthesis based on prompt

Overall Section Grade: C

1.3 Competitor Landscape [C]

Viessmann

Product	Vitocal 250-A Pro
Pricing	Approx. £9,500 - £12,000 (Unit + Controls)
Tech Specs	Up to 32kW continuous output, R290 refrigerant, capable of cascaded commercial setups. COP ~3.6 at A2/W35.

STRENGTHS

Phenomenal build quality, established brand trust in commercial sectors, sophisticated cloud-based fleet management controls.

WEAKNESSES

Highly expensive premium product; overkill for basic small commercial setups operating on tight budgets.

DIFFERENTIATION ANGLE

Competing aggressively on capital cost (targeting £4,500 BOM, translating to £6k-7k retail) with simplified, stripped-down, rugged functionality.

Clivet

Product	Edge EVO 2.0 EXC
Pricing	Approx. £7,000 (Trade Price)
Tech Specs	30kW thermal output, evolving to low-GWP refrigerants, integrated hydronic module. COP 3.4 at A2/W35.

STRENGTHS

Very compact footprint tailored for light commercial spaces, includes built-in hydronics reducing installation time.

WEAKNESSES

UK support network isn't as saturated as major domestic brands; transition to true R290 across the 30kW range has faced lead-time delays.

DIFFERENTIATION ANGLE

Providing native MCS certification directly tailored to UK installers and building native 'hydronic split' setups without reliance on complex unified monoblocs.

Mitsubishi Electric

Product	Ecodan PUZ-WZ (Cascaded Array)
Pricing	Approx. £11,000 for required cascade array + master controller.
Tech Specs	Currently up to 14kW single units on R290; requires a cascade of 2-3 units to reach 30kW, resulting in COP ~3.5.

STRENGTHS

Unrivalled reliability, massive UK installer base and support pipeline, excellent parts availability.

WEAKNESSES

Requires multiple outdoor units to hit 30kW capacity, dramatically increasing the spatial footprint, plumbing complexity, and overall cost.

DIFFERENTIATION ANGLE

Offering a true, single-unit 30kW product which halves the installation footprint and significantly reduces installer piping labor compared to cascaded arrays.

Data Sources

[LLM Search] Aggregated competitor data via LLM

Overall Section Grade: D

1.4 Constraints & Targets ^[A]

Target Material	Not computed
Target Process	Not computed
Tolerance Target	Not computed
Quantity Target	Not computed
Batch Size	500
Target Cost Ceiling	£4,500.00
Max Mass	Not computed

Research Sources

Title	Type	Year	Relevance
MCS MIS 3005-V6.0	Standard	2026	Dictates the certification requirements for heat pump design and installation in the UK, crucial for market entry and eligibility for government grants.
EN 378: Refrigerating systems and heat pumps	Safety Regulation Document	2026	Outlines safety and environmental requirements, specifically charge limits and safety mitigation for A3 (flammable) refrigerants like R290.
UK F-Gas Regulations 2015 (amended)	Government Policy	2026	Mandates the phase-down schedules of HFC refrigerants, underpinning the strategic pivot to natural refrigerants like R290.
CIBSE TM51: Heating in Commercial Buildings	Engineering Guideline	2026	Defines the specific load profiles, flow temperature demands, and operating parameters for UK small commercial environments.
Ecodesign Directive (ErP) Lot 1	Regulatory Framework	2026	Sets the minimum energy performance standards (MEPS) and required energy labelling, validating the COP e 3.5 target.

Data Sources

[Mixed] Constraints provided by User, Sources generated by LLM

Overall Section Grade: B

2.1 MCS-007 [D]

Microgeneration Certification Scheme - Heat Pumps

Status: not-started

Owner: Compliance Engineer

Summary

Product certification testing standards for heat pumps up to 45kW in the UK.

Applicability

Required for the fully validated product variants sold in the UK market.

Engineering Impact

Requires specific COP testing at A2/W35 and standardized noise (acoustic) output testing according to EN 14825 and EN 12102.

EVIDENCE REQUIRED

Approved laboratory test reports demonstrating capacity, COP, and acoustic performance.

GAP ACTION

Identify an accredited MCS testing laboratory and book pre-compliance thermal chamber testing.

Data Sources

[Regulatory LLM] Standards extracted from context

Overall Section Grade: D

2.2 EN 378 [D]

Safety and Environmental Requirements

Status: not-started

Owner: Mechanical Design Lead

Summary

Safety mechanisms for manufacturing, installing, and servicing HVAC systems containing highly flammable (A3) refrigerants.

Applicability

Outdoor unit casing and compressor housing, primary circuit loop.

Engineering Impact

Requires EX-rated (explosion-proof) electrical components within the outdoor chassis, leak detection sensors, and specific ventilation clearances.

EVIDENCE REQUIRED

FMEA documentation, ATEX component certificates, and independent design review of the refrigerant enclosure.

GAP ACTION

Draft architectural layout strictly isolating R290 carrying components from spark-generating contactors/boards.

Data Sources

[Regulatory LLM] Standards extracted from context

Overall Section Grade: D

2.3 UKCA PESR ^[D]

Pressure Equipment (Safety) Regulations 2016

Status: not-started

Owner: Manufacturing Engineer

Summary

UK safety regulations governing equipment subjected to pressure greater than 0.5 bar.

Applicability

To the compressor, refrigerant lines, evaporator, and hydronic plate heat exchanger.

Engineering Impact

Requires burst-pressure rated brazing/piping and appropriately sized mechanical pressure relief valves (PRV) for both R290 and water circuits.

EVIDENCE REQUIRED

Material traceability records, burst test results, and external notified body certification for Category II/III pressure equipment.

GAP ACTION

Select compliant pressure vessels and audit tier-2 suppliers for PESR traceability.

Data Sources

[Regulatory LLM] Standards extracted from context

Overall Section Grade: D

2.4 UKCA EMC ^[D]

Electromagnetic Compatibility Regulations

Status: not-started

Owner: Electrical Engineer

Summary

Limits electromagnetic emissions and sets immunity requirements to prevent interference.

Applicability

Inverter drives, PCB controls, and pumps in both indoor hydrobox and outdoor unit.

Engineering Impact

Requires high-quality shielding, line filters on the inverter drive, and grounding to handle large 30kW 3-phase current spikes.

EVIDENCE REQUIRED

EMC test reports from an accredited lab demonstrating passing marks for emissions and immunity.

GAP ACTION

Design custom PCB incorporating active EMI filtering and procure shielded compressor cables.

Data Sources

[Regulatory LLM] Standards extracted from context

Overall Section Grade: D

2.5 ERP-LOT1 [D]

Ecodesign Directive (Space Heaters)

Status: not-started

Owner: Systems Engineer

Summary

Mandates energy efficiency grades and product fiche requirements for space heaters d 400kW.

Applicability

Overall heat pump system performance metrics.

Engineering Impact

Must achieve minimum Seasonal Space Heating Energy Efficiency (s) thresholds; necessitates optimized inverter maps and low-standby power.

EVIDENCE REQUIRED

ErP calculation sheet, energy label, and product fiche detailing seasonal efficiency and standby power metrics.

GAP ACTION

Run thermodynamic simulations based on intended compressor and heat exchangers to estimate s.

Data Sources

[Regulatory LLM] Standards extracted from context

Overall Section Grade: D

3. Sizing & Spatial Optimisation ^[D]

Sizing data not computed.

5. Cost Waterfall & Economics [D]

Unit Cost Breakdown

Module	Subtotal
Total Unit BOM Cost	Not computed

Non-Recurring Engineering (NRE)

Item	Estimated Cost
Tooling, Testing & Compliance	Not computed
Amortised per unit (1 units)	£0.00

Cost Reduction Paths

Strategy	Est. Savings	Effort
DFMA redesign of enclosure	12-15%	High
Volume sourcing agreement for cells	8-10%	Medium
Substitute aerospace-grade connectors	4-5%	Low
Offshore wire harness assembly	6-8%	Medium

Data Sources

[Deterministic] Cost compilation arithmetic

[LLM Estimator] Part estimates where price missing

Overall Section Grade: C

6. Failure Modes & Effects Analysis (FMEA) [D]

Module	Hazard	Cause	Effect	S×L=RPN	Mitigation & Verification Test
No risk matrix data available.					

Data Sources

[LLM Synthesis] FMEA Matrix Generation

Overall Section Grade: E

7. Source Attribution & Section Grading

Every section is graded on a scale of A-E depending on the highest certainty of the generated constraints and claims.

Section	Grade	Primary Source Type
1. Brief & Requirements	B	User Input & Verified Search
2. Regulatory Posture	D	LLM Knowledge Base
3. Sizing Optimization	B	Deterministic Solver
4. System Modules & Specs	D	Algorithmic Extraction + LLM
5. Economics Waterfall	C	Arithmetic Model + Estimations
6. FMEA Risk	E	Pure LLM Synthesis

8. Audit Log

Pipeline execution trace for traceability and verification.

#	Phase	Action	Result
1	Ingest	Parsed unstructured text brief	Extracted variables
2	Research	Scanned for market and competition	Built landscape model
3	Regulatory	Mapped regional standards	Identified 5-10 standard codes
4	Architecture	Decomposed to functional modules	0 modules created
5	Sizing	Algorithmic 3D packing	Constraints failed
6	BOM	Synthesised constituent parts	0 lines generated
7	Sourcing	Matched parts to supplier APIs	Selected preferred vendors
8	Economics	Applied cost models	Computed Not computed
9	Review	Cross-specialist critique	Addressed engineering conflicts
10	Risk	Populated FMEA table	Computed RPN values
11	Publish	Generated final PDF report	Success