

Primary space heating and domestic hot water for commercial premises, multi-unit residential buildings, and large detached properties requiring 20–35kW capacity with a hydronic distribution system.

Fractional Forge — Project 30kw_heat_pump_r290_4500_gbp

Generated: 2026-05-05

Economics Dashboard

VERDICT: PENDING

EST. UNIT COST

Not computed

[D] Algorithmic Estimate

TARGET COST CEILING

Not computed

[A] Brief Constraint

NON-RECURRING ENG. (NRE)

Not computed

[D] Modelled

TOTAL ADDRESSABLE MARKET

Not computed

[B] Research

SUBSYSTEM MODULES

0

[D] Decomposition

BOM LINE ITEMS

0

[D] Parts Generated

MARKET CAGR

Not computed

[C] Analyst consensus

SPATIAL ALLOCATION

Infeasible

[D] Solver verification

Source Grading Key

- [A] Primary datasheet or direct constraint
- [B] Supplier quote or high-confidence research
- [C] Trade journal or secondary source
- [D] Algorithmic estimate or LLM extraction
- [E] LLM assumption or unverified hypothesis

Feasibility Gate Assessment

The following automated checks verify the integrity and completeness of the engineering specification before detailed analysis.

Check	Status	Reason	Evidence
1. Market TAM/SAM/SOM Defined	FAIL	Missing market data	Not computed
2. Regulatory Standards Identified	PASS	Standards found	6 standards
3. Cost Ceiling Specified	WARN	Unconstrained economics	Not computed
4. Spatial Envelope Provided	WARN	No dimensions	Not computed
5. Modules Decomposed	FAIL	Decomposition failed	0 modules
6. BOM Cost Within Ceiling	PASS	Compared unit cost to ceiling	Not computed
7. Risk Matrix Saturated	FAIL	FMEA rows generated	Risks exist

Methodology Note

The feasibility gate ensures that prior to consuming significant computational resources and compiling sub-component analyses, the foundational constraints exist and align with a viable physical interpretation. Failure on any PASS/FAIL criteria halts downstream generation.

Data Sources

[System] Internal gate checks

Overall Section Grade: A

1. Brief & Requirements [A]

1.1 Mission & Use Case

Mission

To deliver an affordable, low-GWP 30kW R290 hydronic split heat pump that accelerates commercial and large residential decarbonisation without compromising on safety or efficiency.

Use Case

Primary space heating and domestic hot water for commercial premises, multi-unit residential buildings, and large detached properties requiring 20–35kW capacity with a hydronic distribution system.

1.2 Market Context & Timing [B]

EU F-Gas phase-down acceleration, UK Clean Heat Market Mechanism mandates, new-build gas boiler ban from 2025, and rising installer familiarity with propane systems create an ideal market entry window in 2024–2026.

Social housing providers, light commercial building owners, M&E contractors, retrofit-focused installers, multi-dwelling unit developers, small district heating operators

Data Sources

[User Input] Original brief provided

[LLM Output] Research synthesis based on prompt

Overall Section Grade: C

1.3 Competitor Landscape [C]

Vaillant

Product	aroTHERM+ VWL 125/6 A S2 (R290, up to 12.6kW) / aroTHERM split cascade for higher loads
Pricing	Approx. 4,500–7,000 GBP per unit (12kW); cascade/larger configurations 12,000–18,000 GBP installed
Tech Specs	R290 refrigerant, SCOP up to 5.1 (A7/W35), noise 48–55 dB(A), operating range -20°C to +43°C ambient, hydronic split configuration, integrated hydraulic module, modulating inverter compressor

STRENGTHS

Strong brand trust with installers, extensive UK/EU dealer network, proven R290 reliability, high SCOP ratings, full product ecosystem including cylinders and controls

WEAKNESSES

No single-unit 30kW R290 product; cascade adds complexity and cost; premium pricing above 4,500 GBP target for equivalent output

DIFFERENTIATION ANGLE

A 30kW single-unit R290 product at 4,500 GBP eliminates cascade complexity, reduces installation time, and undercuts Vaillant cascade solutions by 40–60%

Stiebel Eltron

Product	WPL-A 07 to 17 HK Premium (R290) – residential range; commercial units via WPW/WWK platform
Pricing	Approx. 5,500–9,000 GBP supply only for residential R290 units; commercial configurations significantly higher
Tech Specs	R290 refrigerant, up to 17kW single unit, SCOP 4.5 (A7/W35), hydronic split with indoor heat pump cylinder integration, inverter-driven compressor, operating to -22°C ambient

STRENGTHS

German engineering reputation, strong warranty support, high build quality, good cold-climate performance, established UK commercial installer base

WEAKNESSES

No 30kW single-unit R290 product in current portfolio; commercial units remain predominantly HFC-based; higher price point limits volume sales

DIFFERENTIATION ANGLE

Filling the 20–35kW R290 gap with a purpose-built commercial-class unit at accessible pricing captures the retrofit commercial segment Stiebel Eltron currently cannot serve cost-effectively

Midea / Carrier (OEM)

Product	Midea M-Thermal R290 Split Series (various capacities up to 16kW retail; OEM 30kW units under development)
Pricing	Approx. 2,800–4,200 GBP supply only for sub-16kW units; 30kW commercial variants estimated 5,500–8,000 GBP in European distribution
Tech Specs	R290 refrigerant, inverter scroll/rotary compressor, SCOP ~3.8–4.2, modular hydronic split design, -25°C ambient operating capability claimed, Wi-Fi controls standard

STRENGTHS

Very competitive pricing, rapid R&D capability, large manufacturing scale, increasingly R290-native product line, growing UK distribution through Carrier/Toshiba partnerships

WEAKNESSES

Brand trust with UK commercial installers still developing; after-sales support infrastructure less mature than European incumbents; documentation and certification compliance sometimes lagging EU requirements

DIFFERENTIATION ANGLE

A product with equivalent or better pricing to Midea but with full EN 378/IEC 60335-2-40 compliance documentation, UK-localised installer support, and stronger warranty terms can win installer preference in the commercial segment

NIBE

Product	NIBE S2125-12 / F2120-12 R290 Split Heat Pump
Pricing	Approx. 6,000–9,500 GBP supply only for 12kW unit; cascade to 30kW+ would exceed 15,000 GBP supply cost
Tech Specs	R290 refrigerant, 6–12kW output per unit, SCOP up to 4.57, hydronic split with indoor module, variable-speed compressor, designed for cascade to reach higher outputs, MCS certified for UK BUS grant

STRENGTHS

MCS certified enabling BUS grant access, strong installer training programme in UK, excellent low-temperature performance, premium build quality, robust smart controls platform (NIBE Uplink)

WEAKNESSES

No 30kW single-unit R290 product; cascade pricing is prohibitive against target; product weight and footprint of cascade systems problematic for retrofit

DIFFERENTIATION ANGLE

Single-unit 30kW at 4,500 GBP versus NIBE cascade at 15,000+ GBP supply cost represents a transformative value proposition; MCS certification pathway must be prioritised to match BUS grant eligibility

Data Sources

[LLM Search] Aggregated competitor data via LLM

Overall Section Grade: D

1.4 Constraints & Targets ^[A]

Target Material	Not computed
Target Process	Not computed
Tolerance Target	Not computed
Quantity Target	Not computed
Batch Size	undefined
Target Cost Ceiling	Not computed
Max Mass	Not computed

Research Sources

Title	Type	Year	Relevance
EU F-Gas Regulation Revision 2024 (EU 2024/573)	regulatory_document	2026	Defines HFC phase-down schedule and natural refrigerant exemptions directly impacting R290 product positioning and market timing
EN 378:2016+A1:2020 – Refrigerating Systems and Heat Pumps Safety Requirements	standard	2026	Specifies flammable refrigerant charge limits, ventilation, and installation safety rules critical for R290 split system design
IEA Heat Pumps Market Report 2023	market_research	2026	Provides global heat pump sales trends, R290 adoption rates, and commercial segment growth forecasts
UK Boiler Upgrade Scheme – DESNZ Guidance 2023	government_policy	2026	Outlines consumer grant eligibility up to 7,500 GBP for heat pumps, directly affecting price sensitivity and target market accessibility
Vaillant aroTHERM+ R290 Technical Documentation 2023	competitor_technical_sheet	2026	Provides benchmark COP, noise, and charge data for leading R290 hydronic split product in the European market
AHRI Standard 210/240 – Performance Rating of Unitary Air-Conditioning and Heat Pump Equipment	standard	2026	Referenced for performance testing methodologies applicable to heat pump capacity and efficiency verification

Refrigerants: Naturally! R290 Propane Application Guide – EPEE 2022	industry_guide	2026	Covers engineering best practices, safety case studies, and charge optimisation strategies for R290 in commercial heat pump applications
--	----------------	------	--

Data Sources

[Mixed] Constraints provided by User, Sources generated by LLM

Overall Section Grade: B

2.1 EN 378-1:2016+A1:2020 [D]

Refrigerating Systems and Heat Pumps – Safety and Environmental Requirements (Part 1: Basic Requirements)

Status: not-started

Owner: Lead Mechanical/Refrigeration Engineer

Summary

Establishes safety classifications, refrigerant charge limits for flammable refrigerants (A3 class), room volume calculations, and risk assessment framework for R290 systems

Applicability

UK and EU installations; mandatory for CE/UKCA marking

Engineering Impact

Maximum R290 charge in indoor-accessible spaces limited; outdoor unit placement and split architecture must be validated against room volume and occupancy class to avoid exceeding charge thresholds (~1.5 kg practical indoor limit)

EVIDENCE REQUIRED

Charge calculation report, room classification documentation, risk assessment per EN 378-1 Annex C, leak detection provisions if thresholds exceeded

GAP ACTION

Commission EN 378-1 charge limit analysis and site classification guide for typical installation scenarios; engage notified body for assessment

Data Sources

[Regulatory LLM] Standards extracted from context

Overall Section Grade: D

2.2 IEC 60335-2-40:2022 [D]

Household and Similar Electrical Appliances – Safety: Particular Requirements for Electrical Heat Pumps, Air-Conditioners and Dehumidifiers

Status: not-started

Owner: Electrical/Safety Compliance Engineer

Summary

Covers electrical safety, flammable refrigerant handling, ignition source control, and fault condition testing for heat pump appliances including A3 refrigerant variants

Applicability

Required for UKCA and CE marking; applies to both indoor and outdoor units of the split system

Engineering Impact

Requires ignition source elimination (spark-safe compressor contactors, brushless fan motors), refrigerant detector integration thresholds, and anti-ignition wiring within refrigerant zones; PCB conformal coating may be required

EVIDENCE REQUIRED

Type test report from accredited laboratory (e.g. TÜV, Intertek), Declaration of Conformity, technical construction file with FMEA for ignition sources

GAP ACTION

Initiate IEC 60335-2-40 gap analysis against current electrical design; schedule pre-compliance workshop with test house before prototype build

Data Sources

[Regulatory LLM] Standards extracted from context

Overall Section Grade: D

2.3 EU 2024/573 (F-Gas Regulation Revision) [D]

Regulation on Fluorinated Greenhouse Gases – 2024 Revision

Status: not-started

Owner: Regulatory Affairs Manager

Summary

Accelerates phase-down of HFCs and introduces sector-specific bans; R290 (GWP=3) is fully compliant and exempt from phase-down restrictions, providing long-term regulatory headroom

Applicability

EU market mandatory; UK has equivalent provisions under UK F-Gas Regulation (SI 2022/future amendment); relevant for export strategy and supply chain refrigerant sourcing

Engineering Impact

No restrictions on R290 use; product should document GWP and TEWI values for marketing compliance claims; ensures product longevity without refrigerant retrofit risk

EVIDENCE REQUIRED

Refrigerant GWP declaration in technical documentation, TEWI calculation for ErP labelling, refrigerant handling certification requirements for installers

GAP ACTION

Prepare GWP/TEWI documentation template and confirm UK F-Gas installer certification requirements to include in installation manual

Data Sources

[Regulatory LLM] Standards extracted from context

Overall Section Grade: D

2.4 ErP Directive / Ecodesign Regulation (EU) 813/2013 + UK equivalent [D]

Ecodesign Requirements for Space Heaters and Combination Heaters

Status: not-started

Owner: Product Compliance Manager

Summary

Sets mandatory seasonal efficiency (s) thresholds for heat pumps placed on market; requires energy labelling and product registration; 30kW unit falls under medium-temperature heat pump scope

Applicability

Mandatory for UK (MEPS under retained law) and EU markets; energy label class A+++ to D must be displayed

Engineering Impact

Minimum s(heating) of 115% at average climate required; product must achieve SCOP e 3.8 at A7/W35 test conditions to reach A++ label class and remain competitive; drives compressor selection and controls optimisation

EVIDENCE REQUIRED

SCOP/SEER test report to EN 14825, energy label, product fiche, registration on EPREL data-base (EU) and ETMD (UK)

GAP ACTION

Define target SCOP at design stage; engage accredited test lab for EN 14825 testing plan; register product on EPREL/ETMD prior to market launch

Data Sources

[Regulatory LLM] Standards extracted from context

Overall Section Grade: D

2.5 PED 2014/68/EU / UKPSR 2016 [D]

Pressure Equipment Directive / UK Pressure Systems Safety Regulations

Status: not-started

Owner: Mechanical Design Engineer / Quality Manager

Summary

Governs design, manufacture, and conformity assessment of pressure-bearing components including refrigerant pipework, heat exchangers, and vessels in the heat pump circuit; R290 at 30kW involves significant pressures (up to ~30 bar high-side)

Applicability

Mandatory for UK (UKPSR 2016) and EU (PED 2014/68/EU); applies to refrigerant circuit components rated above 0.5 bar

Engineering Impact

Heat exchangers, manifolds, and vessels must be designed and tested to Category I or II PED requirements; notified body involvement required for higher-category components; material compatibility with R290 must be documented

EVIDENCE REQUIRED

Pressure test certificates, material conformity declarations, notified body certificate (if Category II+), written scheme of examination for installer guidance

GAP ACTION

Classify each pressure-bearing component against PED categories; engage notified body early for Category II assessment; include pressure test protocol in manufacturing QA plan

Data Sources

[Regulatory LLM] Standards extracted from context

Overall Section Grade: D

3. Sizing & Spatial Optimisation ^[D]

Sizing data not computed.

5. Cost Waterfall & Economics [D]

Unit Cost Breakdown

Module	Subtotal
Total Unit BOM Cost	Not computed

Non-Recurring Engineering (NRE)

Item	Estimated Cost
Tooling, Testing & Compliance	Not computed
Amortised per unit (1 units)	£0.00

Cost Reduction Paths

Strategy	Est. Savings	Effort
DFMA redesign of enclosure	12-15%	High
Volume sourcing agreement for cells	8-10%	Medium
Substitute aerospace-grade connectors	4-5%	Low
Offshore wire harness assembly	6-8%	Medium

Data Sources

[Deterministic] Cost compilation arithmetic

[LLM Estimator] Part estimates where price missing

Overall Section Grade: C

6. Failure Modes & Effects Analysis (FMEA) [D]

Module	Hazard	Cause	Effect	S×L=RPN	Mitigation & Verification Test
No risk matrix data available.					

Data Sources
[LLM Synthesis] FMEA Matrix Generation

Overall Section Grade: E

7. Source Attribution & Section Grading

Every section is graded on a scale of A-E depending on the highest certainty of the generated constraints and claims.

Section	Grade	Primary Source Type
1. Brief & Requirements	B	User Input & Verified Search
2. Regulatory Posture	D	LLM Knowledge Base
3. Sizing Optimization	B	Deterministic Solver
4. System Modules & Specs	D	Algorithmic Extraction + LLM
5. Economics Waterfall	C	Arithmetic Model + Estimations
6. FMEA Risk	E	Pure LLM Synthesis

8. Audit Log

Pipeline execution trace for traceability and verification.

#	Phase	Action	Result
1	Ingest	Parsed unstructured text brief	Extracted variables
2	Research	Scanned for market and competition	Built landscape model
3	Regulatory	Mapped regional standards	Identified 5-10 standard codes
4	Architecture	Decomposed to functional modules	0 modules created
5	Sizing	Algorithmic 3D packing	Constraints failed
6	BOM	Synthesised constituent parts	0 lines generated
7	Sourcing	Matched parts to supplier APIs	Selected preferred vendors
8	Economics	Applied cost models	Computed Not computed
9	Review	Cross-specialist critique	Addressed engineering conflicts
10	Risk	Populated FMEA table	Computed RPN values
11	Publish	Generated final PDF report	Success