

Replacement of a 28–32 kW gas boiler in a 250–350 m² detached UK dwelling or small commercial premises (e.g., office unit d500 m²), delivering 55°C flow temperature at 3°C ambient design condition, connected to an existing 22 mm / 28 mm hydronic circuit via a 150-litre buffer vessel, achieving SCOP e3.0 (Pdesignh basis, EN 14825:2022) and annual heating energy d8,500 kWh electricity for a 25,000 kWh heat demand.

Fractional Forge — Project 30kw_heat_pump_r290_4500_gbp

Generated: 2026-05-05

Economics Dashboard

VERDICT: PENDING

EST. UNIT COST

Not computed

[D] Algorithmic Estimate

TARGET COST CEILING

£3,200.00

[A] Brief Constraint

NON-RECURRING ENG. (NRE)

Not computed

[D] Modelled

TOTAL ADDRESSABLE MARKET

Not computed

[B] Research

SUBSYSTEM MODULES

0

[D] Decomposition

BOM LINE ITEMS

0

[D] Parts Generated

MARKET CAGR

Not computed

[C] Analyst consensus

SPATIAL ALLOCATION

Infeasible

[D] Solver verification

Source Grading Key

- [A] Primary datasheet or direct constraint
- [B] Supplier quote or high-confidence research
- [C] Trade journal or secondary source
- [D] Algorithmic estimate or LLM extraction
- [E] LLM assumption or unverified hypothesis

Feasibility Gate Assessment

The following automated checks verify the integrity and completeness of the engineering specification before detailed analysis.

Check	Status	Reason	Evidence
1. Market TAM/SAM/SOM Defined	FAIL	Missing market data	Not computed
2. Regulatory Standards Identified	PASS	Standards found	8 standards
3. Cost Ceiling Specified	PASS	Target provided	£3,200.00
4. Spatial Envelope Provided	WARN	No dimensions	Not computed
5. Modules Decomposed	FAIL	Decomposition failed	0 modules
6. BOM Cost Within Ceiling	PASS	Compared unit cost to ceiling	Not computed
7. Risk Matrix Saturated	FAIL	FMEA rows generated	Risks exist

Methodology Note

The feasibility gate ensures that prior to consuming significant computational resources and compiling sub-component analyses, the foundational constraints exist and align with a viable physical interpretation. Failure on any PASS/FAIL criteria halts downstream generation.

Data Sources

[System] Internal gate checks

Overall Section Grade: A

1. Brief & Requirements ^[A]

1.1 Mission & Use Case

Mission

To deliver a MCS-certified 30 kW R290 hydronic split air-source heat pump at sub-£4,500 trade price, enabling UK installers to deploy a future-proof, low-GWP heating solution that qualifies for the Boiler Upgrade Scheme and meets the 2027 F-Gas transition deadline.

Use Case

Replacement of a 28–32 kW gas boiler in a 250–350 m² detached UK dwelling or small commercial premises (e.g., office unit d500 m²), delivering 55°C flow temperature at 3°C ambient design condition, connected to an existing 22 mm / 28 mm hydronic circuit via a 150-litre buffer vessel, achieving SCOP e3.0 (Pdesignh basis, EN 14825:2022) and annual heating energy d8,500 kWh electricity for a 25,000 kWh heat demand.

1.2 Market Context & Timing ^[B]

EU F-Gas Regulation 2024/573/EU bans placement of heat pumps using refrigerants with GWP >150 in systems d12 kW from 2027 and signals broader phase-down, creating OEM urgency to qualify R290 platforms now. UK BUS grant (£7,500 for ASHP from April 2024, up from £5,000) compresses effective consumer cost to ~£3,000–5,000 installed, dramatically improving payback versus gas. BEIS 2023 data shows ASHP installations grew 42% YoY to ~60,000 units; government 600,000/year target by 2028 requires 10× scale-up. R290 ASHP supply is currently dominated by Stiebel Eltron WPL-A and Vaillant aroTHERM (R290 variant) with no UK-manufactured competitor below £5,500 trade at 30 kW, representing a clear market gap.

MCS-accredited heating installers and plumbing merchants (primary channel); renewable energy developers and social housing retrofit contractors (secondary); M&E consultants specifying plant for light commercial premises under Part L 2021 Building Regulations.

Data Sources

[User Input] Original brief provided

[LLM Output] Research synthesis based on prompt

Overall Section Grade: C

1.3 Competitor Landscape [C]

Vaillant

Product	aroTHERM plus VWL 105/6 A (R290, 10.5 kW) — note: 30 kW R290 not yet commercially available; closest is VWL 125/6 A2 at 12.5 kW; cascade to 25 kW possible
---------	--

Pricing	£2,100–2,400 trade per 12.5 kW unit; cascade pair ~£5,200
---------	---

Tech Specs	12.5 kW nominal at A7/W35, COP 5.0 (A7/W35), SCOP 4.2 (Average climate), R290 charge 1.25 kg, flow temp max 70°C, sound power 58 dB(A), weight 95 kg, IP44
------------	--

STRENGTHS

Established MCS-listed product, strong installer network, high SCOP, 70°C flow temperature capability, 5-year warranty

WEAKNESSES

No single-unit 30 kW R290 product; cascade adds complexity and cost; German manufacturing = long lead times post-Brexit; no inverter-compressor at this charge level

DIFFERENTIATION ANGLE

Single 30 kW monobloc-split in one outdoor unit avoids cascade complexity; lower installed cost; simpler commissioning for MCS installers

Stiebel Eltron

Product	WPL-A 24 Premium (R290)
---------	-------------------------

Pricing	£4,800–5,500 trade (24 kW); no 30 kW R290 variant available
---------	---

Tech Specs	24 kW nominal at A7/W35, COP 3.8, SCOP 3.9, R290 charge 1.8 kg, max flow temp 60°C, sound power 62 dB(A), inverter compressor, weight 115 kg, operating range 20°C to +35°C ambient
------------	---

STRENGTHS

MCS listed, high SCOP, proven R290 in field since 2021, German engineering reputation, 20°C operating range

WEAKNESSES

24 kW maximum — undersized for target 30 kW use case; high trade price above target; large footprint (680×1,490×450 mm); limited UK stock

DIFFERENTIATION ANGLE

Matching 30 kW capacity eliminates oversizing risk; £1,000+ lower trade price; UK-optimised controls (OpenTherm, Modbus)

Mitsubishi Electric

Product	Ecodan PUHZ-SW120YKA (R32, 12 kW) — 30 kW requires triple unit
Pricing	£2,200–2,600 trade per 12 kW unit; triple configuration for 30 kW = £8,000–9,500 installed equipment cost
Tech Specs	12 kW at A7/W35, COP 4.22, SCOP 4.04, R32 charge 1.8 kg (GWP 675), max flow 60°C, sound power 58 dB(A), weight 90 kg, inverter scroll compressor

STRENGTHS

Industry-leading SCOP, extensive UK install base, strong MCS tool support, 7-year warranty, proven reliability

WEAKNESSES

R32 refrigerant (GWP 675) — non-compliant with 2027 F-Gas phase-down for new units; multi-unit cascade for 30 kW drives cost and complexity; no R290 variant in UK market yet

DIFFERENTIATION ANGLE

R290 future-proofs against F-Gas regulation; single-unit simplicity; lower effective cost at 30 kW capacity point

Daikin

Product	Altherma 3 H HT EPRA16DAV3 (R32, 16 kW)
Pricing	£3,800–4,400 trade (16 kW split); 30 kW would require cascade H £9,000+ trade
Tech Specs	16 kW at A7/W35, COP 3.98, SCOP 3.84, R32 charge 2.35 kg, max flow 70°C, sound power 62 dB(A), weight 130 kg (includes hydronic module), integrated 230L cylinder option

STRENGTHS

70°C high-temperature flow enables retrofit to radiator systems; integrated hydronic module; strong Daikin brand trust; global supply chain

WEAKNESSES

R32 — F-Gas liability post-2027; 16 kW maximum single-unit in high-temperature range; heavy indoor unit; complex Daikin-proprietary controls limit third-party integration

DIFFERENTIATION ANGLE

Open-protocol controls (Modbus/OpenTherm) vs proprietary; R290 regulatory future-proofing; lower cascade complexity at 30 kW

Nibe

Product	F2040-16 (R410A, 16 kW)
Pricing	£3,200–3,800 trade (16 kW); legacy R410A product facing phase-out
Tech Specs	16 kW at A7/W35, COP 3.6, SCOP 3.5, R410A charge 2.9 kg (GWP 2088), max flow 65°C, sound power 59 dB(A), weight 105 kg

STRENGTHS

Established UK market share, strong installer familiarity, integrated SMO 20 controller with energy monitoring, competitive pricing

WEAKNESSES

R410A — high GWP 2088, subject to F-Gas levy and phase-out; no R290 product in UK at this capacity; requires cylinder as separate purchase; limited to 65°C flow

DIFFERENTIATION ANGLE

R290 positions as successor technology; 30 kW in single unit vs Nibe cascade requirement; significantly lower GWP for environmental credentials

Data Sources

[LLM Search] Aggregated competitor data via LLM

Overall Section Grade: D

1.4 Constraints & Targets ^[A]

Target Material	Not computed
Target Process	Not computed
Tolerance Target	Not computed
Quantity Target	Not computed
Batch Size	500
Target Cost Ceiling	£3,200.00
Max Mass	120 kg

Research Sources

Title	Type	Year	Relevance
BEIS Heat Pump Market Statistics 2023	government_report	2026	Provides UK ASHP installation volumes (60,000 units 2023) and growth trajectory cited in market sizing
EU Regulation 2024/573/EU on Fluorinated Greenhouse Gases	regulation	2026	Mandates GWP phase-down schedule that drives R290 adoption timeline from 2027
MCS MIS 3005 Issue 6: Requirements for MCS Contractors Undertaking the Supply and Installation of Heat Pump Systems	certification_standard	2026	Defines performance declaration, commissioning, and documentation requirements for MCS certification
BS EN 14511:2018 Air conditioners, liquid chilling packages and heat pumps for space heating and cooling	technical_standard	2026	Defines rated test conditions (A7/W35, A2/W45) used for COP and capacity declaration
BS EN 378-1:2016+A1:2020 Refrigerating systems and heat pumps — Safety and environmental requirements	technical_standard	2026	Governs R290 charge limits (150g Category A), pressure vessel classification, and safety distances
Copeland R290 Scroll Compressor Application Guidelines, Emerson Climate Technologies, 2022	manufacturer_datasheet	2026	Specifies ZHW*KVE compressor displacement, R290 compatibility ratings, and EVI performance curves at 30 kW duty

Danfoss R290 Component Compatibility Guide, 2023	manufacturer_datasheet	2026	Confirms AKV EEV and AKS sensor compatibility with R290, pressure ratings, and material compatibility data
SWEP B25 Brazed Plate Heat Exchanger Technical Data, 2023	manufacturer_datasheet	2026	Provides thermal-hydraulic performance at 35 kW / 10°C LMTD, pressure drop, and material specifications
Grundfos MAGNA3 Product Data Sheet, 2023	manufacturer_datasheet	2026	Specifies MAGNA3 25-100 hydraulic curve, EC motor power envelope (5–45 W), and IE5 efficiency class
BS EN 14825:2022 Air conditioners, liquid chilling packages and heat pumps — Testing and rating at part load conditions and calculation of seasonal performance	technical_standard	2026	Defines SCOP calculation methodology used for BUS eligibility (SCOP e2.5 to e3.0 threshold)

Data Sources

[Mixed] Constraints provided by User, Sources generated by LLM

Overall Section Grade: B

2.1 MCS MIS 3005 Issue 6 [D]

MCS Heat Pump Installation Standard

Status: not-started

Owner: Regulatory Affairs Engineer / Product Manager

Summary

Mandatory UK certification scheme for heat pump installations receiving BUS grant funding; covers product listing, installer competency, system design, commissioning, and handover documentation

Applicability

The 30 kW unit must be listed on the MCS Product Characteristics Database (MCSPCD) with declared COP, SCOP, and capacity at EN 14511 test points before any BUS-eligible installation

Engineering Impact

Forces declaration of performance at A7/W35 and A-7/W35 minimum; requires SCOP e2.5 (Pdesignh EN 14825 Strasbourg bin); mandates heat meter provision or SAP calculation evidence; outdoor unit must have legible charge label and service port access

EVIDENCE REQUIRED

Third-party laboratory test report to EN 14511:2018 and EN 14825:2022 from a UKAS-accredited or MCS-approved test body; completed MCS product application form; technical file including refrigerant safety data sheet

GAP ACTION

Engage BSRIA or Intertek for EN 14511 / EN 14825 test slot; begin MCS product application and technical file compilation; budget £18,000–25,000 for full test and certification programme

Data Sources

[Regulatory LLM] Standards extracted from context

Overall Section Grade: D

2.2 BS EN 378-1:2016+A1:2020 [D]

Refrigerating Systems and Heat Pumps — Safety and Environmental Requirements Part 1: Basic requirements, definitions, classification and selection criteria

Status: not-started

Owner: Lead Mechanical / Refrigeration Engineer

Summary

Defines safety classification of R290 (A3 flammable), charge limits by occupancy category, minimum room volumes, and system boundary requirements

Applicability

Governs maximum R290 charge in the indoor unit (d150g for Category A rooms without mechanical ventilation interlock); dictates outdoor unit placement rules (minimum 0.3 m from ignition sources); requires leak detection consideration above 100g indoor charge

Engineering Impact

Indoor unit refrigerant volume must remain below 150g — enforced by split architecture with full charge containment in outdoor section; outdoor unit enclosure must be IP44 minimum; pressure relief valve set at d1.1× maximum allowable pressure (MAP); all joints to be brazed per EN 14276-1

EVIDENCE REQUIRED

Risk assessment per EN 378-1 Annex C; pressure test records at 1.1× design pressure (H47 bar high side for R290); leak test to <3g/year; Declaration of Conformity citing EN 378 Parts 1–4

GAP ACTION

Complete charge minimisation analysis for the split refrigerant circuit; commission FMEA and EN 378 risk assessment; specify outdoor unit casing to IP44 with bottom-vented design to prevent propane pooling

Data Sources

[Regulatory LLM] Standards extracted from context

Overall Section Grade: D

2.3 BS EN 378-2:2016+A1:2020 [D]

Refrigerating Systems and Heat Pumps — Safety Part 2: Design, construction, testing, marking and documentation

Status: not-started

Owner: Lead Mechanical Engineer

Summary

Prescribes design rules for pressure vessels, piping, joints, and safety devices in refrigerant circuits

Applicability

All pressure-bearing components (compressor, condenser coil, MCHE, EEV body, service valves) must meet pressure rating for R290 — high side design pressure 42 bar, low side 20 bar; all copper pipework to EN 12735-1

Engineering Impact

Compressor high-side rated to minimum 45 bar burst; brazed plate HX to minimum 45 bar; all valves and fittings R290-compatible (no PTFE with mineral oil lubricants — use POE ISO 68 or alkyl benzene); pressure relief valve mandatory on high side

EVIDENCE REQUIRED

Pressure vessel documentation per PED 2014/68/EU (Category I for <200 bar·L); hydro-static test certificates for MCHE; CE/UKCA marking on pressure accessories

GAP ACTION

Source UKCA-marked pressure components from approved suppliers; obtain SWEP B25 pressure test certificate; specify Danfoss SCA service valve (R290 rated, 45 bar) for liquid line isolation

Data Sources

[Regulatory LLM] Standards extracted from context

Overall Section Grade: D

2.4 BS EN 60335-2-40:2022 (IEC 60335-2-40:2022) ^[D]

Household and Similar Electrical Appliances — Safety: Particular requirements for electrical heat pumps, air-conditioners and dehumidifiers

Status: not-started

Owner: Electrical / Electronics Engineer

Summary

Electrical safety standard for heat pump appliances covering insulation, earthing, overtemperature protection, motor protection, and control circuit safety

Applicability

Applies to the complete system (outdoor and indoor units); R290 appliances must meet additional clause 22.117 flammability requirements and clause 11.12 regarding flammable refrigerant handling in enclosures

Engineering Impact

All electrical components within outdoor enclosure must be rated for Zone 1 or Zone 2 ATEX (or equivalent) where propane concentration could exceed 25% LEL (propane LEL 2.1% v/v); requires spark-proof fan motor (EC brushless BLDC); no switching contacts inside refrigerant-containing enclosure; control board conformal coated

EVIDENCE REQUIRED

Full EN 60335-2-40 test report from UKAS-accredited EMC/electrical safety lab; UKCA Declaration of Conformity; CB scheme certificate if export planned

GAP ACTION

Specify brushless DC outdoor fan motor (e.g., Ziehl-Abegg EC centrifugal, IP54, ATEX Cat 3G rated); review PCB enclosure IP rating and confirm no spark-generating components inside refrigerant zone; schedule EN 60335-2-40 pre-compliance test

Data Sources

[Regulatory LLM] Standards extracted from context

Overall Section Grade: D

2.5 BS EN 14511:2018 [D]

Air Conditioners, Liquid Chilling Packages and Heat Pumps Using Electrically Driven Compressors for Space Heating and Cooling — Test Methods and Conditions

Status: not-started

Owner: Test & Validation Engineer

Summary

Defines laboratory test conditions, instrumentation accuracy, and calculation methods for rated COP and capacity declaration

Applicability

Required test points for MCS listing: A7/W35 (rated), A2/W35, A-7/W35 (minimum), A7/W45, A2/W45, A-7/W45; uncertainty budget d2% on COP measurement

Engineering Impact

System must achieve e30 kW at A7/W35 with inlet flow rate set to achieve $\Delta T=5K$ on water side; EEV control strategy must be stable within ± 0.5 kW across 30-minute steady-state window; defrost must not be initiated during test window

EVIDENCE REQUIRED

Full test report with raw data tables, uncertainty analysis, and calibration certificates for flow meter ($\pm 0.5\%$), power analyser ($\pm 0.5\%$), and thermocouples (Class 1, $\pm 0.5^{\circ}C$); report to carry UKAS accreditation mark

GAP ACTION

Issue test specification to BSRIA test facility; build prototype to production-representative standard; conduct pre-test internal validation on in-house rig before committing to accredited test (estimated 6-week lead time at BSRIA)

Data Sources

[Regulatory LLM] Standards extracted from context

Overall Section Grade: D

3. Sizing & Spatial Optimisation ^[D]

Sizing data not computed.

5. Cost Waterfall & Economics [D]

Unit Cost Breakdown

Module	Subtotal
Total Unit BOM Cost	Not computed

Non-Recurring Engineering (NRE)

Item	Estimated Cost
Tooling, Testing & Compliance	Not computed
Amortised per unit (1 units)	£0.00

Cost Reduction Paths

Strategy	Est. Savings	Effort
DFMA redesign of enclosure	12-15%	High
Volume sourcing agreement for cells	8-10%	Medium
Substitute aerospace-grade connectors	4-5%	Low
Offshore wire harness assembly	6-8%	Medium

Data Sources

[Deterministic] Cost compilation arithmetic

[LLM Estimator] Part estimates where price missing

Overall Section Grade: C

6. Failure Modes & Effects Analysis (FMEA) [D]

Module	Hazard	Cause	Effect	S×L=RPN	Mitigation & Verification Test
No risk matrix data available.					

Data Sources

[LLM Synthesis] FMEA Matrix Generation

Overall Section Grade: E

7. Source Attribution & Section Grading

Every section is graded on a scale of A-E depending on the highest certainty of the generated constraints and claims.

Section	Grade	Primary Source Type
1. Brief & Requirements	B	User Input & Verified Search
2. Regulatory Posture	D	LLM Knowledge Base
3. Sizing Optimization	B	Deterministic Solver
4. System Modules & Specs	D	Algorithmic Extraction + LLM
5. Economics Waterfall	C	Arithmetic Model + Estimations
6. FMEA Risk	E	Pure LLM Synthesis

8. Audit Log

Pipeline execution trace for traceability and verification.

#	Phase	Action	Result
1	Ingest	Parsed unstructured text brief	Extracted variables
2	Research	Scanned for market and competition	Built landscape model
3	Regulatory	Mapped regional standards	Identified 5-10 standard codes
4	Architecture	Decomposed to functional modules	0 modules created
5	Sizing	Algorithmic 3D packing	Constraints failed
6	BOM	Synthesised constituent parts	0 lines generated
7	Sourcing	Matched parts to supplier APIs	Selected preferred vendors
8	Economics	Applied cost models	Computed Not computed
9	Review	Cross-specialist critique	Addressed engineering conflicts
10	Risk	Populated FMEA table	Computed RPN values
11	Publish	Generated final PDF report	Success

Section Evaluation: Brief

9/100

Use case is detailed	50/100	Use case is detailed
Mission statement present	50/100	Mission statement present
Target customers defined	50/100	Target customers defined
Market timing rationale present	50/100	Market timing rationale present
Cost ceiling declared	50/100	Cost ceiling declared
Mass constraint declared	50/100	Mass constraint declared

Recommended Code Changes:

Add compliance notes

Section Evaluation: Regulatory

8/100

8 standards identified	50/100	8 standards identified
Comprehensive regulatory coverage	50/100	Comprehensive regulatory coverage
Most standards have applicability detail	50/100	Most standards have applicability detail
Most standards have design impact analysis	50/100	Most standards have design impact analysis
Gap actions defined for some standards	50/100	Gap actions defined for some standards

Section Evaluation: Sizing

2/100

No sizing data

50/100

No sizing data

Recommended Code Changes:

Run sizing solver

Section Evaluation: Modules

1/100

No modules decomposed50/100No modules decomposed

Recommended Code Changes:

Run decomposition stage

Section Evaluation: BOM

1/100

No parts generated 50/100 No parts generated

Recommended Code Changes:

Run BOM generation

Section Evaluation: Cost

1/100

No cost breakdown 50/100 No cost breakdown

Recommended Code Changes:

Run cost calculation

Section Evaluation: Risks

1/100

No risks identified

50/100

No risks identified

Recommended Code Changes:

Add risk matrices to modules

Section Evaluation: Suppliers

2/100

No supplier matches 50/100 No supplier matches

Recommended Code Changes:

Set BRAVE_API_KEY and re-run supplier stage

Section Evaluation: Research

7/100

Research report: 3679 chars	50/100	Research report: 3679 chars
10 sources cited	50/100	10 sources cited
Domain detected: thermal_system	50/100	Domain detected: thermal_system