



element₁₄

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

MCL053AT

ΕN

This Datasheet is presented by the manufacturer

DE

Dieses Datenblatt wird vom Hersteller bereitgestellt

FR

Cette fiche technique est présentée par le fabricant

LED Orange, 5mm







Specifications:

Dice material : GaAsP on GaP

Emitted colour : Orange

Lens colour : Orange Transparent

Peak wavelength : 635nm Viewing angle : 16° Luminous intensity (IV) : 50mcd

Absolute Maximum Ratings (T_a = 25°C)

Reverse Voltage	5V		
Reverse Current	10μA (V _R = 5V)		
Operating Temperature Range	-40°C to 85°C		
Storage Temperature Range	-40°C to 100°C		
Lead Soldering Temperature Range 1.6mm (1/16 inch) from body	260°C for 5 Seconds		

Electrical/Optical Characteristics at $T_a = 25$ °C


Parameter	Symbol	Minimum	Typical	Maximum	Unit	Test
Luminous Intensity	IV	30	50	75	mcd	IF = 20mA
Viewing Angle	2θ 1/2	-	16	-	degrees	
Peak Emission Wavelength	λP	-	635	-		-
Dominant Wavelength	λD	-	625	-	nm	-
Spectral Line Half-Width	Δλ	-	45	-		-
Forward Voltage	VF	1.6	2	2.6	V	IF = 20mA
Power Dissipation	Pd	-	-	85	-	-
Peak Forward Current (Duty 1/10 at 1KHz)	IF (Peak)	-	-	100	-	-
Recommended Operating Current	IF (Rec)	-	20	-	mA	-




LED Orange, 5mm




Orange (GaAsP/CaP λ P = 635nm)






Forward Current Derating Curve

Orange (GaAsP/CaP λ P = 635nm)







Luminous Intensity vs. Ambient Temperature

LED Orange, 5mm







Dimensions: Millimetres (Inches)

Part Number Table

Description	Part Number		
LED, 5mm, 16°, Orange	MCL053AT		

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com







element₁₄

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

MCL053AT

ΕN

This Datasheet is presented by the manufacturer

DE

Dieses Datenblatt wird vom Hersteller bereitgestellt

FR

Cette fiche technique est présentée par le fabricant