

EXPLORING PASSWORD-AUTHENTICATED KEY-EXCHANGE ALGORITHMS

A PROJECT REPORT SUBMITTED TO THE UNIVERSITY OF MANCHESTER
FOR THE DEGREE OF BACHELORS OF SCIENCE
IN THE FACULTY OF SCIENCE AND ENGINEERING

2023

Sam Leonard
f41751sl
Supervisor: Professor Bernardo Magri

Department of Computer Science

Declaration

No portion of the work referred to in this project report has been submitted in support of an application for another degree or qualification of this or any other university or other institute of learning.

Copyright

- i. The author of this project report (including any appendices and/or schedules to this thesis) owns certain copyright or related rights in it (the “Copyright”) and s/he has given The University of Manchester certain rights to use such Copyright, including for administrative purposes.
- ii. Copies of this thesis, either in full or in extracts and whether in hard or electronic copy, may be made **only** in accordance with the Copyright, Designs and Patents Act 1988 (as amended) and regulations issued under it or, where appropriate, in accordance with licensing agreements which the University has from time to time. This page must form part of any such copies made.
- iii. The ownership of certain Copyright, patents, designs, trade marks and other intellectual property (the “Intellectual Property”) and any reproductions of copyright works in the thesis, for example graphs and tables (“Reproductions”), which may be described in this thesis, may not be owned by the author and may be owned by third parties. Such Intellectual Property and Reproductions cannot and must not be made available for use without the prior written permission of the owner(s) of the relevant Intellectual Property and/or Reproductions.
- iv. Further information on the conditions under which disclosure, publication and commercialisation of this thesis, the Copyright and any Intellectual Property and/or Reproductions described in it may take place is available in the University IP Policy (see <http://documents.manchester.ac.uk/DocuInfo.aspx?DocID=24420>), in any relevant Thesis restriction declarations deposited in the University Library, The University Library’s regulations (see <http://www.library.manchester.ac.uk/about/regulations/>) and in The University’s policy on presentation of Theses

Abstract

Exploring Password-Authenticated Key-Exchange Algorithms

Sam Leonard, Supervisor: Professor Bernardo Magri

Password Authenticated Key Exchange (PAKE) algorithms are a niche kind of cryptography where parties seek to establish a strong shared key, from a low entropy secret such as a password. This makes the particularly attractive to some domains, such as Industrial Internet of Things (IIOT). However many PAKE algorithms are unsuitable for Internet of Things (IOT) applications, due to their heavy computational requirements. Augmented Composable Password Authenticated Connection Establishment (AuCPace) is a new PAKE protocol which aims to make PAKEs accessible to IIOT by utilising Elliptic Curve Cryptography (ECC), Verifier based PAKEs (V-PAKEs) and a novel augmented approach. This project aims to provide an approachable and developer-focused implementation of AuCPace in Rust and to contribute this implementation back to RustCrypto to promote wider adoption of PAKE algorithms.

Acknowledgements

I would like to thank everyone at absolutely onderful supervisor, RustCrypto, Crypto Hack and my CTF Team (0rganizers). Without your help none of this would have been possible.

Contents

1	Context	7
1.1	Background on PAKEs	7
1.1.1	What is a PAKE?	7
1.1.2	A brief history of PAKE algorithms	7
1.2	Elliptic Curve Cryptography	7
1.3	Modern PAKEs	7
1.4	AuCPace	7
1.5	Who are RustCrypto?	7
2	Design	8
2.1	Why Rust?	8
2.2	Developer Focussed Design	8
3	Implementation	9
3.1	Overview of RustCrypto and Dalek Cryptography	9
4	Testing	10
4.1	Creating Test Vectors	10
5	Reflection and Conclusion	11
5.1	Achievements	11
5.2	Reflection	11
5.3	Future Work	11
	Glossary	12
A	Python implementation of EKE	14
B	Python implementation of SRP	17

Chapter 1

Context

1.1 Background on PAKEs

1.1.1 What is a PAKE?

[PAKEs](#) are interactive, two party cryptographic protocols where each party shares knowledge of a password (a low entropy secret) and seeks to obtain a strong shared key e.g. for use later with a symmetric cipher. Critically an eavesdropper who can listen in to all messages of the key negotiation cannot learn enough information to bruteforce the password. Another way of phrasing this is that brute force attacks on the key must be "online".

1.1.2 A brief history of PAKE algorithms

The first [PAKE](#) algorithm was Bellovin and Merritt's EKE scheme[[BM92](#)].

1.2 Elliptic Curve Cryptography

1.3 Modern PAKEs

1.4 AuCPace

1.5 Who are RustCrypto?

Chapter 2

Design

2.1 Why Rust?

2.2 Developer Focussed Design

Chapter 3

Implementation

3.1 Overview of RustCrypto and Dalek Cryptography

Chapter 4

Testing

4.1 Creating Test Vectors

Chapter 5

Reflection and Conclusion

5.1 Achievements

5.2 Reflection

5.3 Future Work

Glossary

AuCPace Augmented Composable Password Authenticated Connection Establishment. [4](#)

DH Diffie Hellman. [17](#)

ECC Elliptic Curve Cryptography. [4](#)

IIOT Industrial Internet of Things. [4](#)

IOT Internet of Things. [4](#)

Online Cryptography Online cryptography is where interactions with the cryptosystem are only possible via real-time interactions with the server. Primarily this is to prevent offline computation. . [7](#)

PAKE Password Authenticated Key Exchange. [4](#), [7](#)

SRP Secure Remote Password. [17](#)

V-PAKE Verifier based PAKE. [4](#)

Bibliography

- [AP05] Michel Abdalla and David Pointcheval. Simple password-based encrypted key exchange protocols. In Alfred Menezes, editor, *Topics in Cryptology – CT-RSA 2005*, pages 191–208, Berlin, Heidelberg, 2005. Springer Berlin Heidelberg.
- [BM92] Steven Michael Bellovin and Michael Merritt. Encrypted key exchange: Password-based protocols secure against dictionary attacks, May 1992.
- [CNPR20] Cas Cremers, Moni Naor, Shahar Paz, and Eyal Ronen. Chip and crisp: Protecting all parties against compromise through identity-binding pakes. Cryptology ePrint Archive, Paper 2020/529, 2020. <https://eprint.iacr.org/2020/529>.
- [GJK21] Yanqi Gu, Stanislaw Jarecki, and Hugo Krawczyk. Khape: Asymmetric pake from key-hiding key exchange. Cryptology ePrint Archive, Paper 2021/873, 2021. <https://eprint.iacr.org/2021/873>.
- [Gre18a] Matthew Green, Oct 2018. <https://blog.cryptographyengineering.com/2018/10/19/lets-talk-about-pake/>.
- [Gre18b] Matthew Green. Should you use srp?, 2018. <https://blog.cryptographyengineering.com/should-you-use-srp/>.
- [Ham15] Mike Hamburg. Decaf: Eliminating cofactors through point compression. Cryptology ePrint Archive, Paper 2015/673, 2015. <https://eprint.iacr.org/2015/673>.
- [HL18] Björn Haase and Benoît Labrique. Aucpace: Efficient verifier-based pake protocol tailored for the iiot. Cryptology ePrint Archive, Paper 2018/286, 2018. <https://eprint.iacr.org/2018/286>.
- [JKX18] Stanislaw Jarecki, Hugo Krawczyk, and Jiayu Xu. Opaque: An asymmetric pake protocol secure against pre-computation attacks. Cryptology ePrint Archive, Paper 2018/163, 2018. <https://eprint.iacr.org/2018/163>.
- [Wu00] Tom Wu. The srp authentication and key exchange system, September 2000. Request for Comments (RFC) 2945.

Appendix A

Python implementation of EKE

While researching Bellovin and Merritt's EKE scheme[BM92], I created a full implementation of the scheme in Python. The full code can be found at https://github.com/tritoke/eke_python. The core negotiation functions for the client and server have been included below:

Listing 1: Client Negotiate

```
def negotiate(self):
    # generate random public key Ea
    Ea = RSA.gen()

    # instantiate AES with the password
    P = AES.new(self.password.ljust(16).encode(), AES.MODE_ECB)

    # send a negotiate command
    self.send_json(
        action="negotiate",
        username=self.username,
        enc_pub_key=b64e(P.encrypt(Ea.encode_public_key())),
        modulus=Ea.n
    )

    # receive and decrypt R
    self.recv_json()
    key = 12b(Ea.decrypt(b2l(P.decrypt(b64d(self.data["enc_secret_key"]
    ↪ ])))))
    R = AES.new(key, AES.MODE_ECB)

    # send first challenge
    challengeA = randbytes(16)
    self.send_json(challenge_a=b64e(R.encrypt(challengeA)))

    # receive challenge response
    self.recv_json()
    challenge_response =
    ↪ R.decrypt(b64d(self.data["challenge_response"]))
```

```

assert challenge_response[:16] == challengeA, "Challenge A failed."

challengeB = challenge_response[16:]

# response with challengeB
self.send_json(challenge_b=b64e(R.encrypt(challengeB)))

# receive success message
self.recv_json()
assert self.data["success"], self.data.get("message",
    → "ChallengeB failed.")

# store the shared key
self.R = R

```

Listing 2: Server Negotiate

```

def handle_eke_negotiate_key(self):
    # decrypt Ea using P
    P = AES.new(self.database[self.data["username"]].ljust(16).encode('
    → ),
    → AES.MODE_ECB)
    e = b2l(P.decrypt(b64d(self.data["enc_pub_key"])))

    # e is always odd, but we add 1 with 50% probability
    if e % 2 == 0:
        e -= 1

    # generate secret key R
    R = randbytes(16)
    Ea = RSA.from_pub_key(e, self.data["modulus"])
    self.send_json(enc_secret_key=b64e(P.encrypt(l2b(Ea.encrypt(b2l(R)
    → )))))
    x = b64e(P.encrypt(l2b(Ea.encrypt(b2l(R)))))

    # transform R into a cipher instance
    R = AES.new(R, AES.MODE_ECB)

    # receive encrypted challengeA and generate challengeB
    self.recv_json()
    challengeA = R.decrypt(b64d(self.data["challenge_a"]))
    challengeB = randbytes(16)

    # send challengeA + challengeB
    self.send_json(challenge_response=b64e(R.encrypt(challengeA+challe
    → ngeB)))

```

```
# receive challengeB back again
self.recv_json()
success = R.decrypt(b64d(self.data["challenge_b"])) == challengeB

self.send_json(success=success)
self.R = R
```


Appendix B

Python implementation of SRP

While conducting my initial research on PAKEs I came across [Secure Remote Password \(SRP\)](#)[Wu00]. SRP is the first protocol I looked at which took the approach of encoding values as [Diffie Hellman \(DH\)](#) group elements. To understand this approach better I chose to create a toy implementation. The full code can be found at https://github.com/tritoke/srp_python. The core negotiation functions for the client and server have been included below:

Listing 3: Client Negotiate

```
def negotiate(self):
    # send a negotiate command
    self.send_json(action="negotiate", username=self.username)

    # receive the salt back from the server
    self.recv_json()
    s = int(self.data["salt"])
    x = H(s, H(f"{self.username}:{self.password}"))

    # generate an ephemeral key pair and send the public key to the
    ↪ server
    a = strong_rand(KEYSIZE_BITS)
    A = pow(g, a, N)
    self.send_json(user_public_ephemeral_key=A)

    # receive the servers public ephemeral key back
    self.recv_json()
    B = self.data["server_public_ephemeral_key"]

    # calculate u and S
    u = H(A, B)
    S = pow((B - 3 * pow(g, x, N)), a + u * x, N)

    # calculate M1
    M1 = H(A, B, S)
    self.send_json(verification_message=M1)
```

```

# receive M2
self.recv_json()
M2 = self.data["verification_message"]

if M2 != H(A, M1, S):
    print("Failed to agree on shared key.")

K = H(S)

return K

```

Listing 4: Server Negotiate

```

def handle_srp_negotiate_key(self):
    # receive the username I from the client
    # lookup data in database
    user = self.data["username"]
    I = b2l(user.encode())

    if (db_record := self.database.get(user)) is None:
        self.send_json(success=False,
            ↪ message=f"Failed to find user in DB.")
        return

    s = db_record["salt"]
    v = db_record["verifier"]

    # send s to the client
    self.send_json(salt=s)

    # receive A from the user
    self.recv_json()
    A = self.data["user_public_ephemeral_key"]

    # calculate B
    b = strong_rand(KEYSIZE_BITS)
    B = 3 * v + pow(g, b, N)

    # send B to the client
    self.send_json(server_public_ephemeral_key=B)

    # calculate u and S
    u = H(A, B)
    S = pow(A * pow(v, u, N), b, N)

    # receive M1 from the client
    self.recv_json()
    M1 = self.data["verification_message"]

```

```

# verify M1
if M1 != H(A, B, S):
    self.send_json(success=False,
        ↪ message=f"Failed to agree shared key.")
    return

# calculate M2
M2 = H(A, M1, S)
self.send_json(verification_message=M2)

# calculate key
K = H(S)

# log the derived key - not part of the protocol
print(f"Derived K={K:X}")

# encrypt our final message to the client using our shared key
key = 12b(K)
nonce = get_random_bytes(16)

cipher = AES.new(key, AES.MODE_GCM, nonce=nonce)
ct, mac = cipher.encrypt_and_digest(f_
    ↪ "Successfully agreed shared key for {user}.".encode())

# notify the client of the success
self.send_json(success=True, nonce=b64e(nonce),
    ↪ enc_message=b64e(ct), tag=b64e(mac))

```