A Level Computer Science Non-Examined Assessment (NEA)

Sam Leonard

Contents

1 Analysis

1.1 Identification and Background to the Problem

The problem my project tries to solve is how to look at devices on a network from a "black box" perspective and gain information about what services are running. Services are programs whose entire purpose is to provide a *service* to other programs. For example a server hosting a website would be running a service whose purpose is to send the webpage to people who try to connect to the website.

There are a number of steps a device has to go through from when it is turned on until it can connect to the internet. There are many more steps than those listed below, but the most important ones are.

1. Loading networking drivers

2. Starting Dynamic Host Configuration Protocol (DHCP) daemon

3. Broadcasting DHCP request for an IP address

4. Obtaining assigned an IP address

Starting from a Linux computer being switched on, the first step is that the kernel needs to load the networking drivers. The kernel is the basis for the operating system, it is what interacts with the hardware in the most fundamental way. Drivers are small bits of code which the kernel can load in order to interact with certain hardware modules. These can range from graphics drivers for games to use graphics cards, to networking drivers which interact with the Network Interface Card (NIC).

Once the kernel has loaded the required drivers and the system has booted, the networking 'daemons' must be started. In Linux, a daemon is a program that runs all the time in the background to serve a specific purpose or utility. For example, when I start my laptop, the following daemons start: upowerd (power management), systemd (manages the creation of all processes), dbus-daemon (manages inter-process communication), iwd (manages my WiFi connections) and finally Dynamic Host Configuration Protocol Client Daemon (DHCPCD), which manages all interactions with the network around DHCP.

Once the daemons are all started, the DHCP client can issue commands to the daemon for it to carry out. The DHCP client is simply a daemon that runs in the background to carry out any interactions between the current machine and the DHCP server. The DHCP server is normally the WiFi router or network switch for the local network and it manages a list of which computer has which IP address and negotiates with new computers trying to join a network to get them a free IP address. The DHCP client starts the DHCP address negotiation

with the server by sending a discover message with the address 255.255.255.255, which is the IP limited broadcast address, which means that whatever is listening at the other end will forward this packet on to everyone on the subnet. When the DHCP server (normally the router, sometimes a separate machine) on the subnet receives this message it reserves a free IP address for that client and then responds with a DHCP offer that contains the address the server is offering, the length of time the address is valid for and the subnet mask of the network. The client must then respond with a DHCP request message to request the offered address, this is in case of multiple DHCP servers offering addresses. Finally the DHCP server responds with a DHCP acknowledge message showing that it has received the request (see Figure 1).

Figure 1: *A block diagram showing the relationship between different elements of a DHCP negotiation.*

Figure 2 shows a packet capture from my laptop where I turned WiFi off, started Wireshark listening and plugged in an Ethernet cable. Wireshark is a program which intercepts all the network communications on a single computer and records them to a file.[1] It also displays them to the user, and is capable of performing an analysis and dissection of each the protocols used. This means that I can record the DHCP negotiation shown below and show it to you using Wireshark to get all the information out of the packets being sent over the wire. For a definition of packets see Page 6.

For the sake of clarity, the Figure displays Wireshark showing only the DHCP packets, so that the DHCP negotiation can be clearly seen, including the 255.255.255.255 limited broadcast destination address and the 0.0.0.0 unassigned address in the source column.

No.	Time	Source	Destination	Protocol	Info
6	0.983737378	0.0.0.0	255.255.255.255	DHCP	DHCP Discover
32	4.239092378	192.168.1.1	192.168.1.47	DHCP	DHCP Offer
34	4.239420587	0.0.0.0	255.255.255.255	DHCP	DHCP Request
36	4.241743101	192.168.1.1	192.168.1.47	DHCP	DHCP ACK

Figure 2: *DHCP address negotiation.*

All computer networking is encapsulated in the Open Systems Interconnection model (OSI model) which has 7 layers:

7. Application: Applications Programming Interface (API)s, etc...

6. Presentation: encryption/decryption, encoding/decoding, decompression etc...

5. Session: Managing sessions, PHP Hypertext Processor (PHP) session IDs etc...

4. Transport: TCP and UDP among others.

3. Network: ICMP and IP among others.

2. Data Link: MAC addressing, Ethernet protocol etc...

1. Physical: The physical Ethernet cabling/NIC.

Figure 3: *OSI model diagram, source: https://www.electronicdesign.com.*

Each of these layers is essential to the running of the internet but a single communication might not include all of the layers. These communications are all based on the most fundamental part of the internet: the packet.

Packets are sequences of ones and zeros sent between computers which are used to transfer data as well as to control how networks function. They consist of different layers of information; the innermost layer contains the data being transferred, and the other layers specify where the packet should go next. When packets are sent between computers, a certain number of layers are stripped off by, each computer so that it knows where to send the packet next, at which point it will add all the layers back again, this time with the instructions needed to go from the current computer to the next one on its route. Each of these layers actually consists of a number of fields at the start, called a header; some layers also append a footer to the end of the packet. The actual data being transferred in the packet can be anything. As an example, HyperText Transfer Protocol (HTTP) transfers websites using HyperText Markup Language (HTML) files and images. In particular, there are two pieces of information stored in headers which together define the final destination of the packet: the IP address and the port number. The IP address defines the destination machine and the port number defines which "port" on the remote machine the packet should be sent to. Ports are essential entrances to a computer; for example, if a computer were a hotel, the IP address would be the address of the hotel, and the port number would be the room inside the hotel. There are 65535 ports and 0 is a special reserved port. There are this many ports because the port field in Transmission Control Protocol (TCP) and User Datagram Protocol (UDP) is 16 bits long and the maximum value for a 16 bit unsigned integer in 65535. Both TCP and UDP use ports; TCP ports are mainly used for transferring data where reliability is a concern, as TCP has built in checks for packet loss whereas UDP does not. For this reason, UDP is used for purposes where speed is more important and missing some data is inconsequential, such as video streaming and playing online games.

I would like to illustrate how ports and packets work using the example of getting a very simple static HTML page with an image inside. The code for the page is shown in Listing 1. In Figure 4 you can see how the page renders. However, far more interesting is how the browser retrieved the page. In Figure 5 you can see the full sequence of packets that were exchanged for the browser to get the resources it needed to render the page. The page is hosted using Python3's http.server module, which is a quick and easy way to serve HTML pages and other content locally, without the hassle of setting up a full blown web server such as Nginx or Apache. Python's http.server makes the current directory open on port 8000. From there, navigating to /example.html will render the page. Breaking Figure 5 down, packet one shows the browser receiving the request from the user to display `http://192.168.1.47:8000/example.html` and attempting to connect to 192.168.1.47 on port 8000. Packets two and three show the negotiation of this request through to the full connection being made. The browser now makes an HTTP GET request for the page example.html over the established TCP connection, as shown in packet 4. The server then acknowledges the request and sends a packet with the PSH flag set, as shown in packets 6 and 7. The PSH flag in the TCP header is used to notify the client that

the server is ready to push the data (in this case example.html) to the client. The browser then sends back an acknowledgement and the server sends the page as shown in packets 7 and 8. Finally, the browser sends an acknowledgement of having received the page before initiating a graceful session teardown by sending a FIN ACK packet, which indicates the end of a session. Having received the FIN ACK packet, the server acknowledges this by sending an ACK packet back to the client, completing the graceful teardown. This process is repeated when the browser parses the HTML and identifies there is an image which it needs to get from the server as well. Because the image is a large file, it takes more packets to transfer the required data. In Figure 6 you can see a ladder diagram which shows the entire transaction symbolically. I have also colour coded Figure 6 with green arrow heads to the initial handshakes, blue for the HTTP protocol transactions and red for the TCP connection teardown packets.

The OSI model described in Figure 3 can be seen in action in Figures 4, 5 and 7. Figure 4 shows levels 6 and 7 of the OSI model. Levels 4 and 5 can be seen in figure 5 in the form of the TCP session negotiation and transferring the picture and example.html. Level 3/2/1 are shown in Figure 7 where you can see the IP layer information along with Ethernet II and finally frame 4 which is the bytes that went down the wire.

Figure 4: *A basic static HTML webpage.*

Figure 5: *A full chain of packets that shows retrieving a basic webpage from the server.*

Figure 6: *A ladder diagram showing the transaction in Figure 5.*

Figure 7: *A look inside a TCP packet.*

Listing 1: *example.html*

```html
1   <!DOCTYPE html>
2   <html>
3   <head>
4   <title>Wow I can add titles</title>
5   </head>
6   <body>
7
8   <h1>This is a really big heading</h1>
9   <p>wow para</p>
10  <p>graphs a</p>
11  <p>re amazi</p>
12  <p>ng</p>
13    <script type="text/javascript">
14      function imgtog() {
15        if (document.getElementById("img").style.display == "none") {
16          document.getElementById("img").style = "block"
17        } else {
18          document.getElementById("img").style.display = "none"
19        }
20      }
21
22    </script>
23
```

```
24  <img id="img" src="document/screenshots/packet_drop.png">
25
26  <button onclick="imgtog()">Toggle image</button>
27
28
29  </body>
30  </html>
```

1.2   Analysis of problem

To reiterate, the problem my project tries to solve is how to look at devices on a network from a "black box" perspective and gain information about what services are running. The difficulty with looking at a network from the outside is that the purpose of the network is to allow communication within the network, thus very little is exposed externally. This presents a challenge, as we want to know not only what machines are on the network, but also what services are running on each machine. This is not always possible, owing to the limited information that services reveal about themselves. Firewalls also play a large part in making network scanning difficult, as sometimes they simply drop packets instead of sending a TCP RST packet (reset connection packet). Dropping a packet means that when a packet is received, no response is sent back – as if the connection was just "dropped". When firewalls drop packets, it becomes exponentially more difficult to determine the state of any port on the target machine, as you don't know whether your packet was corrupted, or lost in transit, or if it was just dropped.

To demonstrate this I will show three things:

1. A successful connection over TCP.

2. An attempted connection to a closed port.

3. An attempted connection with a firewall rule to drop packets.

1.2.1   Successful connection over TCP

For a TCP connection to be established there is a three-way handshake between the communicating machines. Initially, the machine trying to establish the connection sends a TCP SYN packet to the other machine. This packet holds a dual purpose:[2] to ask for a connection, and, if it is accepted, to SYNchronise the sequence numbers being used to detect whether packets have been lost in transport. The receiving machine then replies with a TCP SYN ACK, which confirms the starting sequence number with SYN, and ACKnowledges the connection request. The sending machine then acknowledges this by sending a final

TCP ACK packet back. This connection initialisation is shown in Figure 8 by packets one, two and three. Data transfer can then commence by sending a TCP packet with the PSH and ACK flags set, along with the data in the data portion of the packet. This is shown in Figure 11, where Wireshark allows us to take a look inside the packet to see the data being sent, along with the PSH and ACK flags being set.

The code I used to generate these packet captures is shown in Figures 9 and 10. Breaking the code down, Figure 10 shows me initialising a socket object,[3] then I bind it to localhost (127.0.0.1) port 12345. Localhost is just an address which allows connections between programs running on the same computer to be looped back onto the current machine, hence its alternative name: the loopback address. The next line of code instructs the machine to listen for incoming connections. The program accepts the connection in Figure 9, line 3. I then tell the program to listen for up to 1024 bytes in the data part of any TCP packets sent. The program in Figure 9 then sends some data which we then see printed to the screen in Figure 10, both programs then close the connection.

No.	Time	Source	Destination	Protocol	Info
1	0.000000000	127.0.0.1	127.0.0.1	TCP	47710 → 12345 [SYN] Seq=0
2	0.000019294	127.0.0.1	127.0.0.1	TCP	12345 → 47710 [SYN, ACK]
3	0.000033431	127.0.0.1	127.0.0.1	TCP	47710 → 12345 [ACK] Seq=1
4	53.378941809	127.0.0.1	127.0.0.1	TCP	47710 → 12345 [PSH, ACK]
5	53.378958066	127.0.0.1	127.0.0.1	TCP	12345 → 47710 [ACK] Seq=1
6	65.928944995	127.0.0.1	127.0.0.1	TCP	12345 → 47710 [FIN, ACK]
7	65.936113471	127.0.0.1	127.0.0.1	TCP	47710 → 12345 [ACK] Seq=3
8	85.536923935	127.0.0.1	127.0.0.1	TCP	47710 → 12345 [FIN, ACK]
9	85.536940026	127.0.0.1	127.0.0.1	TCP	12345 → 47710 [ACK] Seq=2

Figure 8: *Packets starting a TCP session, transferring some data then ending it.*

```
In [1]: import socket

In [2]: sender = socket.socket(socket.AF_INET, socket.SOCK_STREAM)

In [3]: sender.connect(("127.0.0.1", 12345))

In [4]: sender.send(b"hi I'm data what's your name? "*10)
Out[4]: 300

In [5]: sender.close()
```

Figure 9: *Transferring some basic text data over a TCP connection.*

```
In [1]: import socket

In [2]: receiver = socket.socket(socket.AF_INET, socket.SOCK_STREAM)

In [3]: receiver.bind(("127.0.0.1", 12345))

In [4]: receiver.listen(1)

In [5]: connection, address = receiver.accept()

In [6]: connection.recv(1024)
Out[6]: b"hi I'm data what's your name? hi I'm data what's your name? hi I'm data what's your name? hi I'm
 data what's your name? hi I'm data what's your name? hi I'm data what's your name? hi I'm data what's you
r name? hi I'm data what's your name? hi I'm data what's your name? hi I'm data what's your name? "

In [7]: connection.close()
```

Figure 10: *Receiving some basic text data over a TCP connection.*

13

No.	Time	Source	Destination	Protocol	Info
1	0.000000000	127.0.0.1	127.0.0.1	TCP	47710 → 12345 [SYN] Seq=0
2	0.000019294	127.0.0.1	127.0.0.1	TCP	12345 → 47710 [SYN, ACK]
3	0.000033431	127.0.0.1	127.0.0.1	TCP	47710 → 12345 [ACK] Seq=1
4	53.378941809	127.0.0.1	127.0.0.1	TCP	47710 → 12345 [PSH, ACK]
5	53.378958066	127.0.0.1	127.0.0.1	TCP	12345 → 47710 [ACK] Seq=1
6	65.928944995	127.0.0.1	127.0.0.1	TCP	12345 → 47710 [FIN, ACK]
7	65.936113471	127.0.0.1	127.0.0.1	TCP	47710 → 12345 [ACK] Seq=3
8	85.536923935	127.0.0.1	127.0.0.1	TCP	47710 → 12345 [FIN, ACK]
9	85.536940026	127.0.0.1	127.0.0.1	TCP	12345 → 47710 [ACK] Seq=2

> Frame 4: 366 bytes on wire (2928 bits), 366 bytes captured (2928 bits) o
> Ethernet II, Src: 00:00:00_00:00:00 (00:00:00:00:00:00), Dst: 00:00:00_0(
> Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
> Transmission Control Protocol, Src Port: 47710, Dst Port: 12345, Seq: 1,
> Data (300 bytes)

```
0000   00 00 00 00 00 00 00 00   00 00 00 00 08 00 45 00   ········ ······E·
0010   01 60 70 81 40 00 40 06   cb 14 7f 00 00 01 7f 00   ·`p·@·@· ········
0020   00 01 ba 5e 30 39 09 d1   70 b2 e9 c6 d7 ad 80 18   ···^09·· p·······
0030   01 56 ff 54 00 00 01 01   08 0a 1a 7c 9a 84 1a 7b   ·V·T···· ···|···{
0040   ca 01 68 69 20 49 27 6d   20 64 61 74 61 20 77 68   ··hi I'm  data wh
0050   61 74 27 73 20 79 6f 75   72 20 6e 61 6d 65 3f 20   at's you r name?
0060   68 69 20 49 27 6d 20 64   61 74 61 20 77 68 61 74   hi I'm d ata what
0070   27 73 20 79 6f 75 72 20   6e 61 6d 65 3f 20 68 69   's your  name? hi
0080   20 49 27 6d 20 64 61 74   61 20 77 68 61 74 27 73    I'm dat a what's
0090   20 79 6f 75 72 20 6e 61   6d 65 3f 20 68 69 20 49    your na me? hi I
00a0   27 6d 20 64 61 74 61 20   77 68 61 74 27 73 20 79   'm data  what's y
00b0   6f 75 72 20 6e 61 6d 65   3f 20 68 69 20 49 27 6d   our name ? hi I'm
00c0   20 64 61 74 61 20 77 68   61 74 27 73 20 79 6f 75    data wh at's you
00d0   72 20 6e 61 6d 65 3f 20   68 69 20 49 27 6d 20 64   r name?  hi I'm d
00e0   61 74 61 20 77 68 61 74   27 73 20 79 6f 75 72 20   ata what 's your
00f0   6e 61 6d 65 3f 20 68 69   20 49 27 6d 20 64 61 74   name? hi  I'm dat
0100   61 20 77 68 61 74 27 73   20 79 6f 75 72 20 6e 61   a what's  your na
0110   6d 65 3f 20 68 69 20 49   27 6d 20 64 61 74 61 20   me? hi I 'm data
0120   77 68 61 74 27 73 20 79   6f 75 72 20 6e 61 6d 65   what's y our name
0130   3f 20 68 69 20 49 27 6d   20 64 61 74 61 20 77 68   ? hi I'm  data wh
0140   61 74 27 73 20 79 6f 75   72 20 6e 61 6d 65 3f 20   at's you r name?
0150   68 69 20 49 27 6d 20 64   61 74 61 20 77 68 61 74   hi I'm d ata what
0160   27 73 20 79 6f 75 72 20   6e 61 6d 65 3f 20         's your  name?
```

Figure 11: *Highlighted packet carrying the data being transferred in Figure 9.*

1.2.2   An attempted connection to a closed port

In Figure 12 shows my program beginning by sending the same TCP SYN packet as we saw in the attempted connection to an open port discussed above. The difference comes in the next packet with the TCP RST flag being sent back. This flag resets the connection,[2] or if the connection is not yet established, as in this case, it means that the port is closed, hence why the packet is highlighted red in Figure 12. The code used to generate this is shown in Figure 13; line two shows the initialisation of a socket object. In line 3 the program tries to connect to port 12345 on localhost again, except this time we get a connection refused error back. This shows us that the remote host sent a TCP RST packet back,

which is reflected in Figure 12.

No. ▼	Time	Source	Destination	Protocol	Info
1	0.000000000	127.0.0.1	127.0.0.1	TCP	56196 → 12345 [SYN] Seq=0 Win=43690 Len=
2	0.000009524	127.0.0.1	127.0.0.1	TCP	12345 → 56196 [RST, ACK] Seq=1 Ack=1 Win
3	6.808420598	127.0.0.1	127.0.0.1	TCP	56198 → 12345 [SYN] Seq=0 Win=43690 Len=
4	7.830566490	127.0.0.1	127.0.0.1	TCP	[TCP Retransmission] 56198 → 12345 [SYN]
5	9.842573743	127.0.0.1	127.0.0.1	TCP	[TCP Retransmission] 56198 → 12345 [SYN]
6	13.942571238	127.0.0.1	127.0.0.1	TCP	[TCP Retransmission] 56198 → 12345 [SYN]
7	22.130575535	127.0.0.1	127.0.0.1	TCP	[TCP Retransmission] 56198 → 12345 [SYN]
8	38.258578004	127.0.0.1	127.0.0.1	TCP	[TCP Retransmission] 56198 → 12345 [SYN]

Figure 12: *Attempted connection to a closed port with and without firewall rule to drop packets.*

```
In [1]: import socket

In [2]: a = socket.socket(socket.AF_INET, socket.SOCK_STREAM)

In [3]: a.connect(("127.0.0.1", 12345))
---------------------------------------------------------------------------
ConnectionRefusedError                    Traceback (most recent call last)
<ipython-input-3-fbc96d60b5f2> in <module>
----> 1 a.connect(("127.0.0.1", 12345))

ConnectionRefusedError: [Errno 111] Connection refused

In [4]: a.connect(("127.0.0.1", 12345))
^C---------------------------------------------------------------------------
KeyboardInterrupt                         Traceback (most recent call last)
```

Figure 13: *The code used to produce firewall packet dropping example in Figure 12.*

1.2.3 An attempted connection with a firewall rule to drop packets

I would like to commence this section by explaining a bit about firewalls and how they work. Firewalls are essentially the gatekeepers of the internet; they decide whether or not a packet is passed on. Firewalls work by a set of rules which decide what to do with a particular packet. Such a rule might be that it is coming from a certain IP address or has a particular destination port. The actions taken after the packet has had its fate decided by the rules can be one of the following three (on iptables on Linux): ACCEPT, DROP and RETURN. ACCEPT does exactly what you think it would and lets the packet through; DROP simply drops the packet and sends no reply whatsoever: RETURN is more complicated and has no effect on how port scanning is done, and as such we will ignore it. A common set of rules for something like a webserver would be to DROP all incoming packets and then allow exceptions for certain ports i.e. port 80 for HTTP or 443 for HyperText Transfer Protocol Secure (HTTPS). For

demonstration purposes I will be using a Linux utility called iptables for implementing all firewall rules on my system. Packet number three in Figure 12 corresponds to line 4 of the code in Figure 13, the difference being that in Figure 13 I have enabled a firewall rule to drop all packets from the address 127.0.0.1, using the iptables command as so: `iptables -I INPUT -s 127.0.0.1 -j DROP`. This command directs that all packets arriving (`-I INPUT`) with source address 127.0.0.1 (`-s 127.0.0.1`) are dropped, with no response sent (`-j DROP`).[4] With this firewall rule in place you can see in Figure 12, packet 3 receives no response, and as such Python assumes that the packet just got lost and tries to send the packet again repeatedly. This continued for more than 30 seconds before I stopped it, as shown by the time column in Figure 12, and the final `KeyboardInterrupt` in Figure 13. The amount of time that a system will continue trying to reconnect depends on the OS and other factors, but the minimum time is 100 seconds, as specified by RFC 1122.[5] On most systems, the timeout is between 13 and 30 minutes, according to the Linux manual page on TCP reproduced below.[6]

```
man 7 tcp:
tcp_retries2 (integer; default: 15; since Linux 2.2)
  The maximum number of times a TCP packet is retransmitted in
  established state before giving up. The default value is 15,
  which corresponds to a duration of approximately between 13 to
  30 minutes, depending on the retransmission timeout. The RFC
  1122 specified minimum limit of 100 seconds is typically deemed
  too short.
```

1.2.4 Project aims and methods

Having explained firewalls, how they affect port scanning and other things above, I will now explain what I am actually trying to achieve with my project and how I am going to do it. I am trying to make a tool similar to nmap,[7] which will be able to detect the state of ports on remote machines (as in whether the port is open/closed or filtered etc.); detect which hosts are up on a subnet; and detect what services are listening behind any of the ports. I am going to be writing in Python version 3.7.2, as it is the latest stable release of Python 3, and has many features such as f-strings which are not in even fairly recent versions such as 3.5. F-strings allow for a clear and consistent string formatting syntax, which I will use extensively. I have chosen Python in particular, because it is very readable and has extensive low level bindings to kernel syscalls with the socket module allowing me to write code quickly that is easily understandable and has a clear purpose. Python enables me to use low level networking functions, and even change the behaviour at this low level with `socket.setsockopt`. As well as this, the socket module allows me to open sockets that communicate using many different protocols such as TCP, UDP and Internet Control Message Protocol (ICMP). These features combine to make Python a great language for

writing networking software with a high level of abstraction. In regards to the OSI model, my code will sit with the user interface at level 7 specifying what to do at a high level, and the actual scanning takes place at levels 3, 4 and 5, with host detection being at level 3. Port scanning will be taking place at level 4 for TCP SYN scanning and UDP scanning, whereas `connect()` scanning and version detection will sit at level 5. Finally, I will look at what is actually handling all of the networking on my machine. My machine runs Linux, and as such all networking is handled by system calls to the Linux kernel. For example, the `socket.connect` method is just a call to the underlying Linux kernel's connect syscall, but presents a kinder call signature to the user, as the Python socket library does some processing before the syscall is made.

1.3 Success Criteria

1. Probe another computer's networking from a black box perspective.

2. To help the user with usage/help messages when prompted.

3. Translate Classless Inter-Domain Routing (CIDR)-specified subnets into a list of domains.

4. Send ICMP ECHO requests to determine whether a machine is active or not.

5. Perform any scan type without first checking whether the host is up.

6. Detect whether a TCP port is open (can be connected to).

7. Detect whether a TCP port is closed (will refuse connections).

8. Detect whether a TCP port is filtered (a firewall is preventing or monitoring access).

9. Detect whether a UDP port is open (can be connected to).

10. Detect whether a UDP port is closed (will refuse connections).

11. Detect whether a UDP port is filtered (a firewall is preventing or monitoring access).

12. Detect the operating system of another machine on the network solely from sending packets to the machine and interpreting the responses.

13. Detect what service is listening behind a port.

14. Detect the version of the service running behind a port.

1.4 Description of existing solutions

Nmap is currently the most popular tool for doing port scanning and host enumeration. It supports the scanning types for determining information about remote hosts.

- TCP: SYN
- TCP: `Connect()`
- TCP: ACK
- TCP: Window
- TCP: Maimon
- TCP: Null
- TCP: FIN
- TCP: Xmas
- UDP
- Zombie host/idle
- Stream Control Transmission Protocol (SCTP): INIT
- SCTP: COOKIE-ECHO
- IP protocol scan
- File Transfer Protocol (FTP): bounce scan

As well as supporting a vast array of scanning types, Nmap can also perform service and version detection, and operating system detection via custom probes. It also has script scanning, which allows the user to write a script specifying exactly how they want to scan, e.g. to circumvent port knocking (where packets must be sent to a sequence of ports in order before access to the finalportis allowed). It supports a plethora of options to avoid firewalls or Intrusion Detection System (IDS), such as sending packets with spoofed checksums/source addresses, and sending decoy probes. Nmap can do many more things than I have listed above, and indeed there is an entire book on using nmap (https://nmap.org/book/). Figure 14 shows the logical structure behind nmap scanning a network.

Figure 14: *A flow chart showing how nmap does scanning.*

The following paragraphs discuss an example nmap scan I did on my home network I did for this project. The command I used was:
`nmap -sC -sV -oA networkscan 192.168.1.0/24`. The purpose of the command line flags was to enable script scanning `-sc`, enable version detection

`-sV`, and then output all results in all the common formats: XML, nmap and greppable, using the base name `networkscan`. The program outputs to three files: `networkscan.(nmap,gnmap,xml)`. Before I go into what each file contains, I will explain some terminology: something is greppable if it can be easily searched with the Linux utility `grep`.[8] Grep stands for Globally search a Regular Expression and Print, which instructs the computer to search the specified file for lines that contain a certain word or pattern; for example, the command to find all lines with the word "hi" in them in the file "document" would be `grep 'hi' document`.

Returning to the files nmap created: `networkscan.nmap` contains what would usually be printed by nmap, while the scan is being run. It looks like this:

```
# Nmap 7.70 scan initiated Wed Apr 10 19:36:18 2019 as:
    nmap -sC -sV -oA /home/tritoke/thing 192.168.1.0/24
Nmap scan report for router.asus.com (192.168.1.1)
Host is up (1.0s latency).
Not shown: 995 closed ports
PORT     STATE SERVICE     VERSION
53/tcp   open  domain      (generic dns response: NOTIMP)
| fingerprint-strings:
|   DNSVersionBindReqTCP:
|     version
|_    bind
80/tcp   open  http        ASUS WRT http admin
|_http-server-header: httpd/2.0
|_http-title: Site doesn't have a title (text/html).
515/tcp  open  printer
8443/tcp open  ssl/http    ASUS WRT http admin
|_http-server-header: httpd/2.0
|_http-title: Site doesn't have a title (text/html).
| ssl-cert: Subject: commonName=192.168.1.1/countryName=US
| Not valid before: 2018-05-05T05:05:17
|_Not valid after:  2028-05-05T05:05:17
9100/tcp open  jetdirect?
1 service unrecognized despite returning data.
  If you know the service/version,
please submit the following fingerprint at
https://nmap.org/cgi-bin/submit.cgi?new-service :
SF-Port53-TCP:V=7.70%I=7%D=4/10%Time=5CAE3DC5%P=x86_64-pc-Linux
-gnu%r(DNSVSF:ersionBindReqTCP,20,"\0\x1e\0\x06\x85\x85\0\x01\0
\0\0\0\0\0\x07version\SF:x04bind\0\0\x10\0\x03")%r(DNSStatusReq
uestTCP,E,"\0\x0c\0\0\x90\x04\0\0SF:\0\0\0\0\0\0");
Service Info: CPE: cpe:/o:asus:wrt_firmware
```

The above is the report for only one device on the network. In it, you can see information such as which ports are open, and what services are running

behind them. As this example device is network router, you can see port 8443, which nmap has recognised to be hosting the ASUS web admin, from which you can configure the router. There follows some other associated information extracted from the server. Most of this extra information is derived from the -sC flag, which enables script scanning, and allows advanced interaction with running services specifically to gain more information by providing specialised probing per protocol. We can also see at the end an unrecognised service. Nmap shows us the data it returned and asks us to submit a new service report at a given URL if we recognise the service. This system of submitting fingerprints of services explains why nmap is so good at recognising services: it has a lot of data to look at and learn from in regards to service fingerprinting.

Networkscan.gnmap contains exactly the same information as networkscan.nmap, but the output is formatted to enable easy searching with the grep utility. I reproduce part of the output file below:

```
# Nmap 7.70 scan initiated Wed Apr 10 19:36:18 2019 as:
    nmap -sC -sV -oA /home/tritoke/networkscan 192.168.1.0/24
Host: 192.168.1.1 (router.asus.com) Status:
Host: 192.168.1.1 (router.asus.com) Ports: 53/open/tcp//domain//
    (generic dns response: NOTIMP)/, 80/open/tcp//http//ASUS
    WRT http admin/,515/open/tcp//printer///,
    8443/open/tcp//ssl| http//ASUS WRT http
    admin/,9100/open/tcp//jetdirect?///
    Ignored State: closed (995)
Host: 192.168.1.8 (android-25a97e36c2e74456)  Status: Up
Host: 192.168.1.8 (android-25a97e36c2e74456)  Ports: 5060/
    filtered/tcp//sip/// Ignored State: closed (999)
```

As you can see above, all of the information is on a single line for each type of scan. This is useful: for example, if you want to scan a large number of hosts and just want to know which hosts are up you could use grep 'Status: Up' networkscan.gnmap which outputs this:

```
$ grep 'Status: Up' networkscan.gnmap
Host: 192.168.1.1 (router.asus.com) Status: Up
Host: 192.168.1.8 (android-25a97e36c2e74456) Status: Up
Host: 192.168.1.10 (diskstation) Status: Up
Host: 192.168.1.88 () Status: Up
Host: 192.168.1.88 () Status: Up
Host: 192.168.1.117 () Status: Up
Host: 192.168.1.159 (groot) Status: Up
Host: 192.168.1.159 (groot) Status: Up
Host: 192.168.1.176 (ET0021B7C01F2E) Status: Up
```

This shows the hosts which are online and their host names. Other ways to use the greppable output format would be to search for which ports are open

on only one machine, or which hosts have a webserver running on them or a vulnerable version of a mail server etc. In general, the `.gnmap` output is useful for when you want to use grep to filter results.

Finally, we have the eXtensible Markup Language (XML) format file, `networkscan.xml` part of which is reproduced below:

```xml
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE nmaprun>
<?xml-stylesheet href="file:///usr/bin/../share/nmap/nmap.xsl"
    type="text/xsl"?>
<!-- Nmap 7.70 scan initiated Wed Apr 10 19:36:18 2019 as: nmap -sC -sV
    -oA /home/tritoke/thing 192.168.1.0/24 -->
<nmaprun scanner="nmap" args="nmap -sC -sV -oA /home/tritoke/thing
    192.168.1.0/24" start="1554921378" startstr="Wed Apr 10 19:36:18
    2019" version="7.70" xmloutputversion="1.04">
<verbose level="0"/>
<debugging level="0"/>
<host starttime="1554921379" endtime="1554923187"><status state="up"
    reason="syn-ack" reason_ttl="0"/>
<address addr="192.168.1.1" addrtype="ipv4"/>
<hostnames>
<hostname name="router.asus.com" type="PTR"/>
</hostnames>
<ports><extraports state="closed" count="995">
<extrareasons reason="conn-refused" count="995"/>
</extraports>
<port protocol="tcp" portid="53"><state state="open" reason="syn-ack"
    reason_ttl="0"/><service name="domain" extrainfo="generic dns
    response: NOTIMP"
    servicefp="SF-Port53-TCP:V=7.70%I=7%D=4/10%Time=5CAE3DC5%P=x86_64
-pc-Linux-gnu%r(DNSVersionBindReqTCP,20,&quot;\0\x1e\0\x06\x85\x85\0
\x01\0\0\0\0\0\0\x07version\x04bind\0\0\x10\0\x03&quot;)%r
(DNSStatusRequestTCP,E,&quot;\0\x0c\0\0\x90\x04\0\0\0\0\0\0\0\0&quot;);"
    method="probed" conf="10"/><script id="fingerprint-strings"
    output="&#xa; DNSVersionBindReqTCP: &#xa; version&#xa; bind"><elem
    key="DNSVersionBindReqTCP">&#xa; version&#xa; bind</elem>
</script></port>
```

It can be seen that this file is extremely verbose. It contains the reason why each port has the state it does, as well as a vast amount of other data that the other scans did not include. The consequence is that this output format is not very easy for humans to read, meaning that this format is available because it is easier for other programs to parse than the other formats. As well as this the extra information can be good if you really need to dive into why a port was marked as closed etc. or the exact bytes that a service replied with.

In terms of where nmap lives in the software stack, it is an application at level 7 when the user interacts, with it but uses several libraries that interact at level 2, which it uses to get the raw headers of the packets being sent and thus gain

information from them (see Figure 15). Nmap has virtually no competitors in the Linux ecosystem, other than possibly Angry IP Scanner, which is another open source network scanner, except it has a much smaller user base.

Figure 15: *A block diagram showing how nmap sits in the software stack.*

Before describing my program in detail I would like to explain some terminology I will use: "parse the arguments" means taking the string of text that the user enters after the program name i.e. `program <text>`. It is these texts that represent the arguments. Parsing the arguments means turning those strings into useful information that the program can use. For example, my program will allow people to enter the port number(s) they want to scan. I want them to be able to do this by specifying a range of ports. If the user specifies `10-20`, this would mean ports 10, 11, ..., 20. Thus an example of parsing would be the turning of `10-20` into the list of numbers from 10 to 20 as shown in Algorithm 1 below. "Probes" refer to the actual packets being sent to the server; I will refer to anything sent from my code to another machine as being a "probe". I will use the term "hosts" to mean the other machines on the network that we are scanning.

Algorithm 1 *This is an example algorithm for parsing the port range argument I gave as an example above, extended by allowing for comma separated lists of ports intermixed with ranges.*

```
1: procedure PORT PARSER
2:     argument ← string after program name
3:     chunks ← argument split on ','
4:     ports ← empty list
5:     for chunk in chunks do
6:         if chunk contains "-" then                  ▷ a range chunk
7:             numbers ← chunk split on "-"
8:             for port ← numbers[0],numbers[1] do
9:                 Append port to ports
10:        else                                          ▷ a single number chunk
11:            Append chunk to ports
       return ports
```

1.5   Prospective Users

The prospective users of my program would be system administrators, penetration testers or network engineers. In my particular case, prospective users would be my school's system administrators. It would allow them to see an outsider's perspective on, for example, the server running the school's website page, or to see if any of the programs on the servers were leaking information through banners etc. Banners are short strings of text which a service or program will send to identify itself when it receives a new connection. They often contain information such as protocol version etc., which allows the connecting client to know how to communicate with the service. However, they can also reveal too much information, such as the version number of the service running. If the service version is old, then it is likely that bugs will have been found in that version of the program. This information could allow an attacker to gain access to the server by exploiting the vulnerability in that service. This can obviously be prevented by keeping services up to date; however, that is not always possible, so as a best practice banners should reveal the minimum amount of information possible such that the client can interact with the service.

I plan to use my school's system administrators users in order to gain some feedback as to the usability and performance of my program.

1.6   Data Dictionary

While my program is running it will need to store many different things in memory:

- The list of hosts to scan

- The list of ports to scan on each host

- The state of each port we are scanning on each host

- The packet received by the listening socket (temporarily before processing)

- The probes to be used for version detection

I am going to try to estimate the amount of RAM my program will use, based on scanning a CIDR-specified subnet of 192.168.1.0/24, and the most common 1000 ports of each machine. For the purpose of RAM estimation I will not consider version detection, as I am unsure of how I will implement it currently. To measure the size of an object in Python we can use the `getsizeof` function provided by the `sys` module. I also have a file called 'hosts' which contains the addresses specified by 192.168.1.0/24 and a file 'ping_bytes' which contains 4 captured packets from the ping command which I captured during an early exploratory testing phase.

Listing 2: *Some testing I did on the size of Python objects.*

```
>>> with open("hosts", "r") as f
...     hosts = f.read().splitlines()
...
>>> import sys
>>> sys.getsizeof(hosts)
2216
>>> ports = list(range(1000))
>>> sys.getsizeof(ports)
9112
>>> len(hosts)*sys.getsizeof(ports) / 2**10 # 2*10 is one kibibyte
2278.0
>>> sys.getsizeof(True)
28
>>> len(hosts)*(sys.getsizeof(True)) / 2**10
7.0
>>> pings[0]
'45 00 00 54 0f 82 40 00 40 01 2d 25 7f 00 00 01 7f 00 00 01 08 00 41 c5
    02 4f 00 01 cd ef 0f 5c de 9b 0d 00 08 09 0a 0b 0c 0d 0e 0f 10 11
    12 13 14 15 16 17 18 19 1a 1b 1c 1d 1e 1f 20 21 22 23 24 25 26 27
    28 29 2a 2b 2c 2d 2e 2f 30 31 32 33 34 35 36 37'
>>> from binascii import unhexlify
>>> ping = unhexlify(pings[0].replace(" ", "")) # turn the string of
    numbers into a bytes object
>>> sys.getsizeof(ping)
117
>>> len(hosts)*sys.getsizeof(ping) / 2**10
29.25
>>> 2278.0 + 7.0 + 29.25 + 2.22
2316.47
```

As shown above in Listing 2, we can see that by far the most space intensive item stored by our program will be the port numbers for each host, making up just over than ninety eight percent of the total space used by the mock data I created. However, a total of 2.3 mebibytes is not a huge amount of data by any means.

Holding	Data type	Space used /Kib	Percentage of total
ports	List[int]	2278	98.34
hosts	List[str]	2.22	0.1
port state	List[bool]	7	0.3
packets	List[bytes]	29.25	1.26

1.7   Data Flow Diagram

In my application there will be three-way information flow:

1. Sending packets out from my application

2. Receiving packets back from the targets

3. Transferring data between functions

My program will only hold information in memory and provides no utility for saving the information from scans. This is because on the target systems (Linux/Unix based machines), the shell which is used to run commands has a very simple way of placing output in files by use of Unix "pipes", which are how Unix-based operating systems handle interprocess communications. If nmap did not have a dedicated saving utility, the following command could be used to save the output of nmap to a text file called outputfile:
`nmap 192.168.1.0 > outputfile`. Thus, in my application, for the sake of simplicity, this is the method I will use to save output.

Figure 16 below shows the proposed data flow in my program.

Figure 16: *A data flow digram for information in my application.*

1.8 Description of Solution Details

As already stated above on page 16, I will be using Python version 3.7.2 for
my project because I am already familiar with Python's syntax and its socket

library has a very nice high level API for making system calls to the kernel's low level networking functions. This makes it ideal for a networking project like mine, as it allows me to prototype easily, and explore many ideas about how I could implement my solution in a time-efficient manner.

I decided to start my project by researching how to write code for receiving and sending ICMP `echo requests` (i.e. pings). ICMP sits at layer 3 of the OSI model. This means that it functions at a layer below that to which you are normally given access in the socket module. Sending an ICMP `echo request` requires a raw socket. A raw socket is one which will return everything contained by the ethernet/wifi frame, including the raw Internet Protocol (IP) headers. The bytes object received from a raw socket thus requires unpacking to extract relevant information. The struct module provides a convenient API for converting between packed values, because there is usually a difference in endianness between the network and the local machine which requires translation.

Interactions with the socket module are mainly through the pack and unpack functions. For each of these functions it is necessary to provide a format specifier defining how to unpack/pack the bytes/values. In Listing 3, you can see an example of me using the `struct.pack` function to pack the values which comprise an ICMP `echo request` into a packet and sending it the localhost address (127.0.0.1). This program is effectively the complement to the program in Listing 4, which uses `struct.unpack` to unpack value from the received ICMP packet before printing the fields out to the terminal. Listing 3 makes use of an IP checksum function which I wrote (see Listing 5 below). In Figure 17, you can see the output when I run the command `ping 127.0.0.1` which the code in Listing 4 is listening for packets.

Algorithm 2 *The psuedocode representation of Listing 3.*

1: $socket \leftarrow$ new ICMP socket
2: $ID \leftarrow$ process ID $\&$ $0xFFFF$
3: $dummy\ header \leftarrow \text{PACK}(\text{"bbHHh"}, 8, 0, 0, ID, 1)$
4: $time \leftarrow \text{PACK}(\text{TIME}(\text{now}))$
5: $data \leftarrow time + \text{"A"} \times (192 - \text{LENGTH}(time))$
6: $checksum \leftarrow \text{IPCHECKSUM}(dummy\ header + data)$
7: $header \leftarrow \text{PACK}(\text{"bbHHh"}, 8, 0, checksum, ID, 1)$
8: $packet \leftarrow header + data$
9: $\text{SOCKET.SEND}(packet)$

Listing 3: *A prototype for sending ICMP echo request packets.*

```python
#!/usr/bin/Python3.7
import socket
import struct
import os
import time
```

```python
6    import array
7
8    from os import getcwd, getpid
9    import sys
10   sys.path.append("../modules/")
11
12   import ip_utils
13
14
15   ICMP_ECHO_REQUEST = 8
16
17   # opens a raw socket for the ICMP protocol
18   ping_sock = socket.socket(socket.AF_INET, socket.SOCK_RAW,
           socket.IPPROTO_ICMP)
19   # allows manual IP header creation
20   # ping_sock.setsockopt(socket.SOL_IP, socket.IP_HDRINCL, 1)
21
22   ID = os.getpid() & 0xFFFF
23
24   # the two zeros are the code and the dummy checksum, the one is the
           sequence number
25   dummy_header = struct.pack("bbHHh", ICMP_ECHO_REQUEST, 0, 0, ID, 1)
26
27   data = struct.pack("d", time.time()) + bytes((192 -
           struct.calcsize("d")) * "A", "ascii")
28
29   checksum = ip_utils.ip_checksum(dummy_header+data)
30
31   header = struct.pack("bbHHh", ICMP_ECHO_REQUEST, 0, checksum, ID, 1)
32
33   packet = header + data
34
35   ping_sock.sendto(packet, ("127.0.0.1", 1))
```

Algorithm 3 *Psuedocode for the code in Listing 4.*

1: $socket \leftarrow$ new ICMP socket
2: $packet \leftarrow$ SOCKET.RECEIVE("one packet")
3: $data \leftarrow$ UNPACK($packet$)
4: PRINT($data$)

Listing 4: *A prototype for receiving ICMP echo request packets.*

```python
1    #!/usr/bin/Python3.7
2
3    import socket
4    import struct
5    import time
```

```python
from typing import List

# socket object using an IPV4 address, using only raw socket access, set
#     ICMP protocol
ping_sock = socket.socket(socket.AF_INET, socket.SOCK_RAW,
    socket.IPPROTO_ICMP)

packets: List[bytes] = []

while len(packets) < 1:
    recPacket, addr = ping_sock.recvfrom(1024)
    ip_header = recPacket[:20]
    icmp_header = recPacket[20:28]

    ip_hp_ip_v, ip_dscp_ip_ecn, ip_len, ip_id, ip_flgs_ip_off, ip_ttl,
        ip_p, ip_sum, ip_src, ip_dst = struct.unpack('!BBHHHBBHII',
        ip_header)

    hl_v = f"{ip_hp_ip_v:08b}"
    ip_v = int(hl_v[:4], 2)
    ip_hl = int(hl_v[4:], 2)
    dscp_ecn = f"{ip_dscp_ip_ecn:08b}"
    ip_dscp = int(dscp_ecn[:6], 2)
    ip_ecn = int(dscp_ecn[6:], 2)
    flgs_off = f"{ip_flgs_ip_off:016b}"
    ip_flgs = int(flgs_off[:3],2)
    ip_off = int(flgs_off[3:], 2)
    src_addr = socket.inet_ntoa(struct.pack('!I', ip_src))
    dst_addr = socket.inet_ntoa(struct.pack('!I', ip_dst))

    print("IP header:")
    print(f"Version: [{ip_v}]\nInternet Header Length:
        [{ip_hl}]\nDifferentiated Services Point Code:
        [{ip_dscp}]\nExplicit Congestion Notification: [{ip_ecn}]\nTotal
        Length: [{ip_len}]\nIdentification: [{ip_id:04x}]\nFlags:
        [{ip_flgs:03b}]\nFragment Offset: [{ip_off}]\nTime To Live:
        [{ip_ttl}]\nProtocol: [{ip_p}]\nHeader Checksum:
        [{ip_sum:04x}]\nSource Address: [{src_addr}]\nDestination
        Address: [{dst_addr}]\n")

    msg_type, code, checksum, p_id, sequence = struct.unpack('!bbHHh',
        icmp_header)
    print("ICMP header:")
    print(f"Type: [{msg_type}]\nCode: [{code}]\nChecksum:
        [{checksum:04x}]\nProcess ID: [{p_id:04x}]\nSequence:
        [{sequence}]"
    packets.append(recPacket)
open("current_packet", "w").write("\n".join(" ".join(map(lambda x:
    "{x:02x}", map(int, i))) for i in packets))
```

```
 1: function IP_CHECKSUM(data)
 2:     if LENGTH(data) is odd then
 3:         data.append(0)
 4:     total ← 0
 5:     for i in 0,2,LENGTH(data) do
 6:         total ← total + data[i] << 8
 7:         total ← total + data[i+1]
 8:     carried ← (total − (total & 0xFFFF)) >> 16
 9:     total ← total & 0xFFFF
10:     total ← total + carried
11:     if total > 0xFFFF then
12:         total ← total & 0xFFFF
13:         total ← total + 1
14:     total ← INVERT(total) return total
```

Listing 5: *A function for calculating the IP checksum for a set of bytes.*

```python
 1  def ip_checksum(packet: bytes) -> int:
 2      """
 3      ip_checksum function takes in a packet
 4      and returns the checksum.
 5      """
 6      if len(packet) % 2 == 1:
 7          # if the length of the packet is odd, add a NULL byte
 8          # to the end as padding to make it even in length
 9          packet += b"\0"
10
11      total = 0
12      for first, second in (
13              packet[i:i+2]
14              for i in range(0, len(packet), 2)
15      ):
16          total += (first << 8) + second
17
18      # calculate the number of times a
19      # carry bit was added and add it back on
20      carried = (total - (total & 0xFFFF)) >> 16
21      total &= 0xFFFF
22      total += carried
23
24      if total > 0xFFFF:
25          # adding the carries generated a carry
26          total &= 0xFFFF
27          total += 1
28
29      # invert the checksum and take the last 16 bits
```

```
30        return (~total & 0xFFFF)
```

```
flags: [0]
fragment offset: [0]
ttl: [64]
prot: [1]
checksum: [28457]
source address: [127.0.0.1]
destination address: [127.0.0.1]

type: [0]
code: [0]
checksum: [9703]
p_id: [39682]
sequence: [256]


version: [4]
header length: [5]
dscp: [0]
ecn: [0]
total length: [21504]
identification: [21075]
flags: [0]
fragment offset: [64]
ttl: [64]
prot: [1]
checksum: [21737]
source address: [127.0.0.1]
destination address: [127.0.0.1]

type: [8]
code: [0]
checksum: [7566]
p_id: [39682]
sequence: [512]


version: [4]
header length: [5]
dscp: [0]
ecn: [0]
total length: [21504]
identification: [21331]
flags: [0]
fragment offset: [0]
ttl: [64]
prot: [1]
checksum: [21545]
source address: [127.0.0.1]
destination address: [127.0.0.1]

type: [0]
code: [0]
checksum: [7574]
p_id: [39682]
sequence: [512]
```

Figure 17: *Dissecting an ICMP echo request packet.*

Figure 18: *Screenshot of Wireshark showing a successful send of an ICMP echo request packet.*

Figure 19: *Screenshot showing me first successfully dissecting an ICMP echo request packet.*

Having written a prototype program which was capable of sending an ICMP `echo request` and another prototype which was capable of receiving and unpacking it. Having done these prototypes I identified that it would be best to abstract the code for dissecting all the headers i.e. ICMP, TCP and IP into classes where I can just pass the received packet into the class and have the class dissect it for me. This will also give me access to some of the benefits of classes, such as the `__repr__` method, which is called when you print classes out and allows control over what is printed out. Before embarking on the final program, I decided to write a prototype ping scanner, as this would allow me to get a feel for making a scanner, and to further exploring low level protocol interactions.

Listing 6: *An attempt at making a ping scanner.*

```
1  #!/usr/bin/Python3.7
2  from os import getcwd, getpid
3  import sys
4  sys.path.append("../modules/")
5
```

```
6   import ip_utils
7
8   import socket
9   from functools import partial
10  from itertools import repeat
11  from multiprocessing import Pool
12  from contextlib import closing
13  from math import log10, floor
14  from typing import List, Tuple
15  import struct
16  import time
17
18
19  def round_significant_figures(x: float, n: int) -> float:
20      """
21      rounds x to n significant figures.
22      round_significant_figures(1234, 2) = 1200.0
23      """
24      return round(x, n-(1+int(floor(log10(abs(x))))))
25
26
27  def recieved_ping_from_addresses(ID: int, timeout: float) ->
        List[Tuple[str, float, int]]:
28      """
29      Takes in a process id and a timeout and returns the list of
            addresses which sent
30      ICMP ECHO REPLY packets with the packed id matching ID in the time
            given by timeout.
31      """
32      ping_sock = socket.socket(socket.AF_INET, socket.SOCK_RAW,
            socket.IPPROTO_ICMP)
33      time_remaining = timeout
34      addresses = []
35      while True:
36          time_waiting = ip_utils.wait_for_socket(ping_sock,
                time_remaining)
37          if time_waiting == -1:
38              break
39          time_recieved = time.time()
40          recPacket, addr = ping_sock.recvfrom(1024)
41          ip_header = recPacket[:20]
42          ip_hp_ip_v, ip_dscp_ip_ecn, ip_len, ip_id, ip_flgs_ip_off,
                ip_ttl, ip_p, ip_sum, ip_src, ip_dst =
                struct.unpack('!BBHHHBBHII', ip_header)
43          icmp_header = recPacket[20:28]
44          msg_type, code, checksum, p_id, sequence =
                struct.unpack('bbHHh', icmp_header)
45          time_remaining -= time_waiting
46          time_sent = struct.unpack("d",
                recPacket[28:28+struct.calcsize("d")])[0]
```

```
47          time_taken = time_recieved - time_sent
48          if p_id == ID:
49              addresses.append((str(addr[0]), float(time_taken),
                    int(ip_ttl)))
50          elif time_remaining <= 0:
51              break
52          else:
53              continue
54      return addresses


57  with closing(socket.socket(socket.AF_INET, socket.SOCK_RAW,
        socket.IPPROTO_ICMP)) as ping_sock:
58      addresses = ip_utils.ip_range("192.168.1.0/24")
59      local_ip = ip_utils.get_local_ip()
60      if addresses is not None:
61          addresses_to_scan = filter(lambda x: x!=local_ip, addresses)
62      else:
63          print("error with ip range specification")
64          exit()
65      p = Pool(1)
66      ID = getpid()&0xFFFF
67      replied = p.apply_async(recieved_ping_from_addresses, (ID, 2))
68      for address in zip(addresses_to_scan, repeat(1)):
69          try:
70              packet = ip_utils.make_icmp_packet(ID)
71              ping_sock.sendto(packet, address)
72          except PermissionError:
73              pass
74      p.close()
75      p.join()
76      hosts_up = replied.get()
77      print("\n".join(map(lambda x: f"host: [{x[0]}]\tresponded to an ICMP
            ECHO REQUEST in {round_significant_figures(x[1], 2):<10}
            seconds, ttl: [{x[2]}]", hosts_up)))
```

Figure 20: *Screenshot of Wireshark showing a successful ping scan.*

Listing 7: *The output of from the ping scanner on the run which generated the PCAP file in figure 20*

```
1  $ sudo ./ping_scan.py
2  host: [192.168.1.1]   responded to an ICMP ECHO REQUEST in 0.00037
       seconds, ttl: [64]
3  host: [192.168.1.35] responded to an ICMP ECHO REQUEST in 0.00042
       seconds, ttl: [128]
4  host: [192.168.1.37] responded to an ICMP ECHO REQUEST in 0.002 seconds,
       ttl: [64]
5  host: [192.168.1.117] responded to an ICMP ECHO REQUEST in 0.0017
       seconds, ttl: [64]
6  host: [192.168.1.176] responded to an ICMP ECHO REQUEST in 0.0014
       seconds, ttl: [254]
7  host: [192.168.1.14] responded to an ICMP ECHO REQUEST in 0.0072
       seconds, ttl: [64]
8  host: [192.168.1.246] responded to an ICMP ECHO REQUEST in 0.049
       seconds, ttl: [64]
9  host: [192.168.1.8] responded to an ICMP ECHO REQUEST in 0.099 seconds,
       ttl: [64]
```

Completion of these prototypes has given me an understanding of how I will structure the rest of my scanners, how to interact with Python's socket programming interface and how I can use the struct module to make and dissect

38

packets. My general plan for the scanners will be to start a process that listens for responses for a set amount of time and then starts sending the packets in a different process, before waiting for the listening process to get all the responses back and collecting the results from that process.

1.9 Acceptable Limitations

My original concept included dedicated operating system detection as an option. However, if I find that time is short having implemented version detection, it will be an acceptable limitation to omit operating system detection. This is because version detection can provide some indication of the operating system in use, by virtue of the fact that some services are restricted to certain operating systems. For example, if the scanner detected that the service ActiveSync was in use, this would indicate that the system being scanned was a Windows system, which is reflected in the match directive and attached CPE information for ActiveSync:

```
match activesync m|^.\0\x01\0[^\0]\0[^\0]\0[^\0]\0[^\0]\0[^\0]\0.
*\0\0\0$|s p/Microsoft ActiveSync/ o/Windows/ cpe:/a:microsoft:ac
tivesync/ cpe:/o:microsoft:windows/a
```

1.10 Test Strategy

I am going to use two different methods to test my program:

1. Unit testing
2. Wireshark

I will employ two separate testing strategies because they are good at different things, both of which I need in order to show that my project works. First, I will use unit testing to test some general purpose functions, which are pure functions (are independent of the current state of the machine).

I will use Wireshark to test those parts of the program which involve the use of impure functions and low level networking. Wireshark makes this easy by allowing capture of all the packets going over the wire. As well as this, it has a vast array of packet decoders (2231 in my install), which it can use to dissect almost any packet that is on the network. Wireshark will allow me to see my scanners sending packets, and to check whether the parsers I have written for the various protocol are working. I can also check that the checksums in each of the various protocols are valid as Wireshark is capable of performing checksum verification for a wide variety of protocols.

I will be running these tests on my laptop, which is a Thinkpad T480 running Arch Linux with kernel version 5.0.7. I have installed the following versions of

each of the programs I will be using to test my code: Wireshark 3.1.0, Python 3.7.2 and PyTest 4.3.1. I am also using pyenv version 1.2.9 to manage the version of Python in my Python environment. I plan not to use any modules outside of the Python standard library, so that my program is as portable as possible and its functionality is as reproducible as possible.

2 Design

2.1 Overall System Design (High Level Overview)

There are two types of scanning implemented for different scan types in my program.

- `Connect()`
- Version
- Listener / Sender

`Connect()` scanning is the simplest, in that it takes in a list of ports and simply calls `socket.connect` it and sees whether it can connect or not. The ports are marked accordingly as open or closed.

Version scanning is very similar to `Connect()` scanning in that it takes in a list of ports and connects to them, except it then sends a probe to the target to elicit a response and gain some information about the service running behind the port.

Listener / sender scanning does exactly what it says on the tin: it sets up a "listener" in another process to listen for responses from the host which the "sender" is sending packets to. It can then differentiate between open, open|filtered, filtered and closed ports, based on whether it receives a packet back and what flags are set in the received packet. Flags are parts of TCP packets that constitute a one byte long section, which store "flags" where each bit in the byte represents a different flag.

2.2 Design of User Interface

I am designing my system to have a similar interface to the most common tool currently used: nmap. This is because I believe that having a familiar interface will not only make it easier for someone who is familiar with nmap to use my tool, it also has the advantage that anything learnt using either tool is applicable to both, which benefits everyone.

Based on this perception, I plan to use the same option flags as nmap, as well as similar help messages and an almost identical call signature (how the program is used on the command line).
Running `./netscan.py <options> <target specification>` should be almost identical to `nmap <options> <target specification>` in terms of which scan types will be run, which hosts will be scanned and which ports are scanned. Below, you can see a concept help message, for my program with all the arguments I plan to implement.

```
usage: netscan.py <options> <target specification>

required arguments:      target specification

optional arguments:      -h, --help -Pn, -sL, -sn, -sS,
                         -sT, -sU, -sV, -p, --ports, -O
                         --exclude_ports
```

The above shows clearly which are required arguments, and which are optional
ones. It also shows that some some arguments can be called with either a short
format e.g. -p or with a more verbose format --ports. This allows the user to
be clearer if they are using the tool as part of an automated script to perform
scanning, as it should easier to recall the function of the more verbose flags. If
the user enters erroneous data, they should be greeted by a ValueError, which
will explain exactly what the issue was with their input, and will print out the
argument that caused the error.

2.3   System Algorithms

Figure 21: *The logic for how I will do Ping Scanning.*

Figure 22: *The logic for how I will do TCP connect Scanning.*

Figure 23: *The logic for how I will do TCP SYN scanning.*

Figure 24: *The logic behind how UDP scanning works.*

Figure 25: *The logic behind how version detection works.*

2.4 Input data validation

I plan to perform data validation in all of the functions in the fundamental modules which will hold the basic functionality for my project, such as the scanning functions. This is because my project will revolve heavily around these functions and they will need to be as error free as possible. Adding input validation to these core functions will enable me to find errors in my code earlier. For example, passing a function a list of strings instead of just a string might work in some cases, but the function will have a completely different result. These types of programming errors can be quite hard to debug, as although they may not generate errors very often but on occasions they will still break the application. Although data validation helps when programming, it will mainly be there to guide the user by showing them where in their arguments the problem is. This is far more useful than some programs, which simply exit with no information, beyond the fact that error occurred.

An example for a Python ValueError could be trying to turn the string `"tacos"` into an integer. This will result in the following error message:
`ValueError: invalid literal for int() with base 10: 'tacos'`
This informs you that you have tried to turn `"tacos"` into an integer with base 10, which is invalid. This is a clear and helpful error message, because it tells you what you tried to do that went wrong, and which argument was the one that caused the error.

2.5 Algorithm for complex structures

Algorithm 4 *My algorithm for turning a CIDR-specified subnet into a list of actual IP addresses*

1: **procedure** IP_RANGE
2:     $network\_bits \leftarrow$ number of network bits specified
3:     $ip \leftarrow$ base IP address
4:     $mask \leftarrow 0$
5:     **for** $maskbit \leftarrow (32 - network\_bits), 31$ **do**
6:         $mask \leftarrow mask + 2^{maskbit}$
7:     $lower\_bound \leftarrow ip$ AND $mask$ ▷ zero the last 32-$network\_bits$
8:     $upper\_bound \leftarrow ip$ OR ($mask$ XOR 0xFFFFFFFF)   ▷ turn the last 32-$network\_bits$ to ones
9:     $addresses \leftarrow$ empty list
10:     **for** $address \leftarrow lower\_bound, upper\_bound$ **do**
11:         append CONVERT_TO_DOT($address$) to $addresses$
        return $addresses$

Algorithm 5 *My algorithm for pretty-printing a dictionary of lists ofportnumbers such that ranges are specified as start-end instead of start,start+1,...,end*

1: **procedure** COLLAPSE
2:     *port_dictionary* ← dictionary of lists ofportnumbers
3:     *key_results* ← empty list   ▷ stores the formatted result for each key
4:     **for** *key* in *port_dictionary* **do**
5:         *ports* ← *port_dict*[*key*]
6:         *result* ← *key* + ":{"
7:     **if** *ports* is empty **then**
8:         *new_sequence* ← $FALSE$
9:         **for** $index \leftarrow 1, (\text{length of } ports) - 1$ **do**
10:            $port = ports[index]$
11:            **if** $index = 0$ **then**
12:            $result \leftarrow result + ports[0]$ ▷ append the first element
13:            **if** $ports[index{+}1] = port + 1$ **then**
14:            $result \leftarrow result +$ "-"   ▷ begin a new sequence
15:            **else**
16:            $result \leftarrow result +$ ","   ▷ not a sequence
17:            **else if** $port + 1 \neq ports[index{+}1]$ **then**   ▷ break in sequence
18:            $result \leftarrow result + port +$ ","
19:            *new_sequence* ← $TRUE$
20:            **else if** $port + 1 = ports[index{+}1]$ & *new_sequence* **then**
21:            $result \leftarrow result +$ "-"
22:            *new_sequence* ← $FALSE$
23:         $result \leftarrow result + ports[(\text{length of } ports)\text{-}1] +$ "}"
24:         append *result* to *key_results*
        return "{" + (*key_results* separated by ", ") + "}"

---

3 Technical Solution

I have placed all of my code in Appendix A. I will be going through each of the items in this appendix and explaining what they do.

Appendix A.1 contains all the code which I wrote while in an early experimentation phase where I was testing out how I was planning to make and structure the project.

Appendix A.2 contains all the code which I wrote while writing the initial prototype of my ping scanner which uses ICMP `echo request` messages to detect hosts which are online on a given subnet. This is used to meet success criterion 4.

Appendix A.3 contains all the code which I wrote while writing a tool to translate a CIDR-specified subnet into the list of IP addresses for that subnet. It uses logic to exclude the broadcast address and host addresses for each subnet. This is used to meet success criterion 3.

Appendix A.4 contains all of the prototypes for TCP-based scanning, which are contained in the sub-appendices A.4.1 and A.4.2. Appendix A.4.1 contains all of the code which I created whilst prototyping connect scanning. It satisfies success criteria 6 and 7. Appendix A.4.2 contains all of the code I wrote while prototyping TCP SYN scanning. It satisfies success criteria 6, 7 and 8.

Appendix A.5 contains all of the code I wrote while prototyping UDP scanning. It satisfies success criteria 9, 10 and 11.

Appendix A.6 contains all of the code I wrote while prototyping version detection scanning. It satisfies success criteria 13 and 14.

Appendix A.7 contains all of the modules I wrote to help with creating my main application, described later. These modules mainly contain code which I reuse often, such as code to calculate an ip checksum, or validate an IP address.

Appendix A.8 contains a script I wrote which will run each of the prototype applications I made. This doesn't satisfy any of the success criteria, but was very useful for solving issues I had with importing Python modules, where owing to the directory structure everything has to be started from the root of the directory structure, otherwise errors occur. My solution for eliminating the errors was to run everything at the root of the directory structure, as this can call the `main()` function defined in each of the modules, and can also import all of the modules in the modules directory.

Appendix A.9 contains the code for my final application. This satisfies all of the success criteria apart from 12, which as previously discussed, is alternatively completed via version detection scanning.

Appendix A.10 contains all of the code for my unit tests which I run using `Python -m pytest`. It automatically runs each function, and delivers verbose information on each one. I have deliberately named all of the test functions in a very verbose way and I only test one thing in each function. This means that

it is much easier for me to read from the name of a failed test exactly what went wrong with what function and what argument caused it. An example of this can be seen in Figure 26, where I have changed one of the tests so that it fails. You can see that the output of the test shows me a clear difference between what was expected on one side of the assertion statement and then what actually happened on the other side. In this case, it shows that in the left set there is an extra element "192.168.1.1" and in the right an extra element "192.168.1.0". This is very helpful for preventing regressions in the code. Until I wrote these unit tests, I found that I would write a new feature and accidentally break another piece of functionality as a consequence.

Figure 26: *A screenshot of running pytest with a deliberately broken test.*

4 Testing

4.1 Test Plan

I will be testing my application using a combination of unit tests, and Wireshark where applicable. Unit tests are more suitable for doing tests on specific functions to make sure that regressions don't occur while developing the application. A regression is a when a feature or change that was implemented into the program has accidental consequences that cause the application to break. I will use Wireshark to show the scanning portion of my code, and when external connections are made/custom packets created. Section 4.2 contains the tests using Wireshark; the unit tests are in Appendix A.10.

The Wireshark testing will require Wireshark and iptables. I will need to set up Wireshark in listen mode on the right interface so that it captures the packets that my program is sending. From there I will be able to inspect the sent packets and determine whether they fit what was expected in the test description or whether they don't match at all. For filtered packet tests I will need to run the command `iptables -I INPUT -s 127.0.0.1 -j DROP` and scan the localhost address, and after the test I will need to run the command `iptables -F` to flush all the iptables rules to prevent any confusion in future caused by an firewall rule that shouldn't be there.

To running the unit tests will require Python 3.7.2 and pytest 4.3.1. To run the tests I will need to run `python -m pytest` inside the Code directory. This will call pytest, which will find the tests inside the tests directory and run them. It will then display the number of tests that passed along with lots of information on the tests that failed, such as what the arguments were etc. Pytest does this via introspection of the comparison and assert commands. This means that it uses its own versions of those commands which allow it to get more information out about what went wrong, such as which element in a list was the one that caused the comparison to return false etc.

4.2 Testing Evidence

4.2.1 Printing a usage message when run without parameters

To show this I will run my program passing it no parameters. This should print out a message of the form: `USAGE: ./<program> <required> <parameters>` where everything in angle brackets should be replaced by what is necessary for my program. In Figure 27 you can see me run `./netscan.py` with no parameters and it prints out the required usage message telling me that I am missing the target_spec parameter, this shows that it passed this test. This shows success criterion 2.

Figure 27: *Screenshot showing my program being run without parameters.*

4.2.2 Printing a help message when passed -h

To show this I will run my program with the **-h** flag. This should print out a message showing each of the options as well as what each of them do. It should also print out whether they are positional arguments or optional arguments and if an argument can have two forms then it should print out both forms of the flag, i.e. **-p --ports**. In Figure 28 you can see me run my program with the **-h** flag and it proceeds to print of a help message with messages with what each option is for as well as short and long form of arguments, this shows my program passed this test. This shows success criterion 2.

Figure 28: *Screenshot showing my program being run with the -h flag.*

4.2.3 Printing a help message when passed -help

To show this I will run my program with the `--help` flag. This should produce the same output as with `-h`. This shows the same message as in the test of `-h`. To prove this, if I take the sha1sum of the output for both flags, we can see that the hashes are identical and therefore the originals were also identical; this is shown in Figure 30. This shows success criterion 2.

```
networkScanner/Code on ゴ master [!?] venv:(net_scanner) pyenv:(🐍 net_scanner)
→ ./netscan.py --help
usage: netscan.py [-h] [-Pn] [-sL] [-sn] [-sS] [-sT] [-sU] [-sV] [-p PORTS]
                  [--exclude_ports EXCLUDE_PORTS]
                  target_spec

positional arguments:
  target_spec          specify what to scan, i.e. 192.168.1.0/24

optional arguments:
  -h, --help           show this help message and exit
  -Pn                  assume hosts are up
  -sL                  list targets
  -sn                  disable port scanning
  -sS                  TCP SYN scan
  -sT                  TCP connect scan
  -sU                  UDP scan
  -sV                  version scan
  -p PORTS, --ports PORTS
                       scan specified ports
  --exclude_ports EXCLUDE_PORTS
                       ports to exclude from the scan
```

Figure 29: *Screenshot showing my program being run with the help flag.*

```
networkScanner/Code on ゴ master [!?] venv:(net_scanner) pyenv:(🐍 net_scanner)
→ ./netscan.py --help | sha1sum
47b52bb86cbe927e2c1a9521e4c55c2369f541a5  -

networkScanner/Code on ゴ master [!?] venv:(net_scanner) pyenv:(🐍 net_scanner)
→ ./netscan.py -h | sha1sum
47b52bb86cbe927e2c1a9521e4c55c2369f541a5  -
```

Figure 30: *Screenshot showing the hashes of the two help messages.*

4.2.4 Scanning a subnet with ICMP echo request messages

To show this I will run my program with the `-sn` flag and specify the subnet of my local network `192.168.178.0/24`. This should produce a list of all the

hosts which are up on the network. In Figure 31 you can see you can see my program's output showing that the hosts:

- 192.168.178.60

- 192.168.178.56

- 192.168.178.30

- 192.168.178.1

all responded with ICMP echo reply messages. This is reflected in a packet capture I took while performing the scan. A section of this scan is shown in Figure 32, where you can see some of ICMP echo request messages my program sent, along with some of the requests to hosts that don't exist. Note the different addresses in the source and destination fields, and the Echo (ping) request vs reply in the info column. This meets success criteria 1 and 4.


```
networkScanner/Code on  master [!?] venv:(net_scanner) pyenv:( net_scanner) took 13s
→ sudo ./netscan.py 192.168.178.0/24 -sn
host: [192.168.178.60]  responded to an ICMP ECHO REQUEST in 0.00011s   ttl: [64]
host: [192.168.178.56]  responded to an ICMP ECHO REQUEST in 0.28s      ttl: [64]
host: [192.168.178.30]  responded to an ICMP ECHO REQUEST in 0.027s     ttl: [64]
host: [192.168.178.1]   responded to an ICMP ECHO REQUEST in 0.031s     ttl: [64]
```

Figure 31: *Screenshot showing the output of a scan of my local network.*

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000000	192.168.178.60	192.168.178.30	ICMP	234	Echo (ping) request
2	0.000749915	192.168.178.60	192.168.178.56	ICMP	234	Echo (ping) request
3	0.004504662	192.168.178.60	192.168.178.20	ICMP	234	Echo (ping) request
4	0.004830456	192.168.178.60	192.168.178.48	ICMP	234	Echo (ping) request
5	0.005289695	192.168.178.60	192.168.178.1	ICMP	234	Echo (ping) request
6	0.026946346	192.168.178.30	192.168.178.60	ICMP	234	Echo (ping) reply
7	0.036125893	192.168.178.1	192.168.178.60	ICMP	234	Echo (ping) reply
8	0.281829344	192.168.178.56	192.168.178.60	ICMP	234	Echo (ping) reply
9	0.282171289	192.168.178.60	192.168.178.51	ICMP	234	Echo (ping) request
10	2.329937472	192.168.178.60	192.168.178.21	ICMP	234	Echo (ping) request
11	2.330018351	192.168.178.60	192.168.178.35	ICMP	234	Echo (ping) request

Figure 32: *Screenshot showing a selection of the packets being sent by this scan.*

4.2.5 Translating a CIDR-specified subnet into a list of IP addresses

To show this I will run my program with the `-sL` flag and I will specify a small subnet of `192.168.1.0/28` (I have chosen such a small subnet such that it will fit on my terminal and therefore in a screenshot). I expect the list of addresses to be `192.168.1.1 - 192.168.1.14`. To prove that my program

works, I will screenshot the output when run with the stated parameters and I will use a website to translate the same subnet and show that it displays the same addresses as my program. In Figure 33, you can see that the output from my program matches the expected list of IP addresses from `192.168.1.1` to `192.168.1.14` which is also shown by the screen shot of the same subnet translated by the ipcalc utility on Linux. This proves my program works and covers success criterion 3.

Figure 33: *Screenshot showing the output of my program when asked to translate the subnet 192.168.1.0/28.*

Figure 34: *Screenshot showing the range displayed by the ipcalc utility when asked to calculate the same subnet.*

4.2.6 Scanning without first checking whether hosts are up.

To show this I will perform a TCP scan on a small subnet where I know there are no hosts and show that the scan continues despite there actually being no

host on the other end. To do this I will pass the `-Pn` flag and I will specify the subnet `192.168.43.0/28` which I know has no has no hosts on it. I will also specify `-p 12345` to only scan port 12345 so that there are fewer requests in the packet capture. Finally I will specify `-sS` to do TCP SYN SCANNING. I expect to see a multiple of 14 Address Resolution Protocol (ARP) messages. This is because I don't know how many times my NIC will retry at getting the destination Media Access Control (MAC) address. It needs the destination MAC address to send the packet to its destination as we are scanning a private IP range of my router. In Figure 35 you can see the output of my program when run with the specified flags, you can see that as expected it showed that there were no open ports on those machines as they don't exist. In Figure 36 you can see the packet capture of the packets my code sent, however, there are only ARP messages, this is because we are scanning in the private IP range of my router which was the only way I could guarantee that there was no machine at the other end. However, this is as expected, as well as this we can see 42 ARP requests, which is 3×14 ARP requests, which would indicate each scan made three ARP requests before giving up. This shows my program can perform scans without first checking if the host is up, showing success criterion 5.

Figure 35: *Screenshot showing the output from my code when asked to port scan a subnet with no machines behind the addresses.*

Figure 36: *Screenshot showing the ARP requests my NIC sent to attempt to determine where to send the attempted connection packets.*

4.2.7 Detecting whether a TCP port is open

To show this I will perform a TCP `Connect()` scan on my local machine while running a script which will listen on port 12345 for any connections and send back a message. I will pass my program the flags `-sT` and `-p 12345` as well as specifying localhost to scan (127.0.0.1). I expect to see a TCP SYN-ACK handshake between my program and the script and then my program to output that the port is open. In Figure 39 you can see the expected TCP SYN-ACK handshake performed by my program and the script in Figure 37. You can see the output of my program in Figure 38; as expected it outputs that port 12345 is open. This shows success criteria 1 and 6.

Figure 37: *Screenshot showing the script I ran to accept a connection on localhost port 12345.*

Figure 38: *Screenshot showing the output of my script when run with the specified flags and while the script in Figure 37 was running.*

Figure 39: *Screenshot showing the packet capture of the TCP SYN-ACK handshake performed by the scan in Figure 38 with the script in 37.*

4.2.8 Detecting whether a TCP port is closed

To show this, I will perform a TCP `Connect()` scan on my local machine, except that instead of running a script to catch the request, I will just let it try to connect to the closed port. I expect to see a TCP SYN packet sent to the port, and then a RST ACK packet sent back; my program should output no open ports. I will pass my program the same options as in the test for a TCP open port. In Figure 41, you can see the attempted connection to 127.0.0.1 port 12345, along with the RST ACK packet afterwards, indicating the port

is closed. This is reflected in Figure 40 with no open ports, showing success criteria 1 and 7.

Figure 40: *Screenshot showing the output of my program when run with the specified options.*

Figure 41: *Screenshot showing the packet capture of the TCP SYN-RST closed port indication caused by the scan in Figure 40.*

4.2.9 Detecting whether a TCP port is filtered

To show this I will perform a TCP SYN scan on localhost port 12345, except that I will also introduce a firewall rule to drop all requests to localhost. I expect this to produce no response to the initial SYN packet sent by my program, and my program to output that port as filtered. To test this, I will run my program with the flags `-sS,-p 12345,-Pn`. This will instruct it to perform a TCP SYN scan on port 12345 and not to check that the host is up before beginning the scan. I will also introduce a firewall rule using the Linux iptables utility to drop all requests to localhost as so: `iptables -I INPUT -s 127.0.0.1 -j DROP`. The output of my program is shown in Figure 42. It can be seen that port 12345 is displayed as filtered, and in the packet capture shown in Figure 43, you can see that there is no response to our initial packet, which corresponds to what I thought would happen with an iptables rule in place to drop packets. This shows success criteria 1 and 8.

Figure 42: *Screenshot showing the output of my program when run with the specified options and a firewall in place to drop all packets to 127.0.0.1.*

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000000	127.0.0.1	127.0.0.1	TCP	58	38337 → 12345 [SYN]

Figure 43: *Screenshot showing the packet capture of the scan in Figure 42*

4.2.10 Detecting whether a UDP port is open

To show this I will perform a UDP scan on a script I had already written while developing UDP scanning. This can be seen in Listing 8. I expect to see my program output port 12345 as open, and in the packet capture, I expect to see two UDP packets followed by two response UDP packets from my listener program. I will test this using the following flags: `-Pn,-p 12345,-sU`. These translate to scanning port 12345 over UDP and not checking the host is up beforehand. In Figure 44, you can see the output of my program when run as specified, and you can see that it correctly detects port 12345 as being open. In Figure 45, you can see the packet capture of my program being run. However, the output was not precisely as expected, as I did not foresee the ICMP destination unreachable messages, which were sent by the kernel in response to the UDP probe. However, apart from those messages, the capture shows the program detecting the UDP port was open, as expected. This meets success criteria 1 and 9.

Listing 8: *Script to open port 12345 to UDP.*

```python
import socket
from contextlib import closing

with closing(
        socket.socket(
            socket.AF_INET,
            socket.SOCK_DGRAM
        )
) as s:
    s.bind(("127.0.0.1", 12345))
    print("opened port 12345 on localhost")
    while True:
        data, addr = s.recvfrom(1024)
        s.sendto(bytes("Well hello there good sir.", "utf-8"), addr)
```

62

Figure 44: *Screenshot showing the output of my program when run with the options specified above, and the script in Listing 8 is running.*

Figure 45: *screenshot showing the packet capture of the scan in Figure 44*

4.2.11 Detecting whether a UDP port is closed

To show this I will perform a UDP scan on a port which has no service listening behind it. I expect my program to print out no filtered ports and no open ports, showing that the port was closed. In the packet capture, I expect to see three UDP packets and three response ICMP packets. To test this, I will use my program with the following flags: `-p 12345,-Pn,-sU` which perform a UDP port scan without first checking if the host is up. In Figure 46, you can see the output of my program when run with the options specified above. There are no ports displayed as either open or filtered. This shows that my program successfully identified the port as closed. This shows success criteria 1 and 10.

Figure 46: *screenshot showing the output of my program when scanning with the options specified above.*

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000000	127.0.0.1	127.0.0.1	UDP	92	50615 → 12345 Len=50
2	0.000014482	127.0.0.1	127.0.0.1	ICMP	120	Destination unreachable (Port unreachable)
3	0.000024645	127.0.0.1	127.0.0.1	UDP	92	50615 → 12345 Len=50
4	0.000027543	127.0.0.1	127.0.0.1	ICMP	120	Destination unreachable (Port unreachable)
5	4.028510366	127.0.0.1	127.0.0.1	UDP	92	50615 → 12345 Len=50
6	4.028548735	127.0.0.1	127.0.0.1	ICMP	120	Destination unreachable (Port unreachable)

Figure 47: *screenshot showing the packet capture of the scan in Figure 46*

4.2.12 Detecting whether a UDP port is filtered

To show this I will use my program to perform a UDP scan on my local machine with a firewall rule to drop any ports sent to the localhost address. I expect to see my program to output the port as filtered and in the packet capture I expect to see three UDP packets with no response to any of them. In Figure 48 you can see my program correctly identifies the port as being filtered, and in Figure 49 you can see the packet capture of the scan which also as expected shows the three UDP packets with no reply packets. This shows the program meeting success criteria 1 and 11.

Figure 48: *screenshot showing the output of my program when scanning with the options specified above.*

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000000	127.0.0.1	127.0.0.1	UDP	92	41279 → 12345 Len=50
2	0.000008961	127.0.0.1	127.0.0.1	UDP	92	41279 → 12345 Len=50
3	4.026639713	127.0.0.1	127.0.0.1	UDP	92	41279 → 12345 Len=50

Figure 49: *screenshot showing the packet capture of the scan in Figure 48*

4.2.13 Detecting the operating system of another machine

I haven't directly added this as a feature to my project, largely because I discovered on implementing version scanning that this had the substantially the same effect. I found that in most instances it was possible to detect an operating system-dependent service and thereby deduce which operating system that machine was running. For example, if a machine is open on TCP port 22, and

Secure SHell (SSH) is detected to be running behind that port, then the machine is most likely running Linux, as Remote Desktop Protocol (RDP) is more commonly used for this purpose on Windows machines. It would become even more likely that the target machine runs Linux if the scan reveals some further information such as the Common Platform Enumeration (CPE). In Figure 50 you can see a scan of my machine where I have SSH running. My program reveals that the version is 7.9 and the vendor is openbsd, which is a Unix-like operating system. This shows that my SSH version is Unix-based and therefore that my machine is likely running Linux, which is the case. This partially completes success criterion 12.

```
networkScanner/Code on  master [×!?] venv:(net_scanner) pyenv:( net_scanner)
→ sudo ./netscan.py 127.0.0.1 -sV

Scan report for: 127.0.0.1
Open ports:
22/TCP      ssh
vendorproductname: OpenSSH
version: 7.9
info: protocol 2.0

CPE:
applications
vendor: openbsd
product: openssh
version: 7.9
update:
edition:
language:

Filtered ports:
```

Figure 50: *screenshot showing a version scan of my local machine.*

4.2.14 Detecting the service and its version running behind a port

To show this I will use my program to perform a version detection scan on my local machine while I am running SSH. I expect to see my program identify that SSH is running on TCP port 22 and that it detects it as OpenSSH version 7.9. To test this I will run my program with the -sV flag to indicate version detection and I will run it against the localhost address. In Figure 14 you can see that my program successfully identified SSH as running on TCP port 22 as well as the expected identification of OpenSSH version 7.9 operating on protocol version 2. It also identified some CPE information such as OpenSSH coming from the openbsd distribution. This meets success criteria 1, 13 and 14.

Figure 51: *screenshot showing a version scan of my local machine running ssh.*

4.2.15   User enters invalid ip address

To show this I will run my program with the `target_spec` option being `300.300.300.300` which is an invalid IPv4 address, because each of the octets is not between 0 and 255. I expect to see my program raise a Python ValueError saying that this is an invalid dot form IP address, and displaying `300.300.300.300` as the invalid IP address. In Figure 52 you can see my program's output for this invalid IP address. This shows a successful pass as it correctly identifies the invalid IP and displays the error and the argument that caused the error to the user.

Figure 52: *Screenshot showing the output from an invalid IP address being used.*

4.2.16   User enters invalid number of network bits

To show this I will run my program and ask it to list the IP addresses specified by the subnet `192.168.1.0/33`. IP addresses are only 32 bits, long so specifying 33 network bits has no meaning, and thus is invalid data. I expect my program

to raise a ValueError and print out that it was an invalid number of network bits that caused the error, along with 33 being the network bits. In Figure 53 you can see that my program successfully identified the invalid number of network bits, raised the expected error, and printed the expected information.

Figure 53: *Screenshot showing the output of my program when passed an invalid number of network bits.*

4.2.17   User enters an invalid port number to scan

To show this I will run my program with the argument `-p 99999`. Because port numbers can only go up to 65535, this is erroneous data, and as such should generate an error message specifying that you have tried to scan an invalid destination port. In Figure 54 you can see that my program successfully identified 99999 as an invalid destination port and printed the correct error message accordingly.

Figure 54: *Screenshot of my program showing the output from an invalid port number.*

4.2.18   User enters an invalid number of network bits and a bad IP address

To show this I will run my program with both an invalid IP address and an invalid port number. I expect this to raise a ValueError for the invalid IP address. This is because the IP addresses are checked first, and thus an invalid IP address would be caught before an error could be raised for an invalid port number. To show this I will pass my program the following arguments:
`192.168.1.a -p a`. In Figure 55 you can see that my program catches the

invalid IP address and raises the correct ValueError as expected, thus it passed
the test.

Figure 55: *screenshot of my program showing the output from an invalid ip and
an invalid port number.*

4.3   Test Table

Test No.	Test Data	Expectation	Result	Fig	Success Criteria
1		usage message	Pass	27	2
2	-h	help message	Pass	28	2
3	--help	help message	Pass	29	2
4	-sL	print addresses	Pass	33	3
5	-sn	ping scan	Pass	31	4
6	-Pn	assume host up	Pass	35	5
7	-sS|sT	TCP port open	Pass	38	6
8	-sS|sT	TCP port closed	Pass	40	7
9	-sS	TCP port filtered	Pass	42	8
10	-sU	UDP port open	Pass	44	9
11	-sU	UDP port closed	Pass	46	10
12	-sU	UDP port filtered	Pass	48	11
13	-sV	OS detection	Partial	50	12
14	-sV	service detection	Pass	50	13
15	-sV	version detection	Pass	50	14
16		invalid IP	Pass	52	
17		invalid subnet	Pass	53	
18		invalid port & IP	Pass	54	

5 Evaluation

5.1 Reflection on final outcome

Overall, I am very happy with how my program has turned out. At the beginning of this project, I did not believe I could do anywhere near as much as I have done. My rationale for choosing this project was to learn more about low level networking, and networking in general, because these were areas where I felt my knowledge was deficient. I greatly enjoyed learning about various aspects of networking structure and protocols. For instance, I found it fascinating to discover that the order that bytes are packed into the packet matters enormously, and to learn how users are automatically assigned an IP address on joining a network.

There were many areas where I encountered difficulty while developing this program. The first problem was understanding what a packet is, and how I send one that I have made myself using Python. There seemed to be very little in the way of documentation, so I ended up reading many peoples' answers to questions on the Stack Overflow website, where they had encountered similar problems. Once I discovered that I could simply open a socket in raw mode and use the `socket.sendto` method to send any arbitrary bytes to an address and Python would handle the IP header, it became easier to make progress. The next major problem was getting the checksum correct for TCP packets, because they use a pseudo-header, which is sort of a header made from fields in the IP header that are not in the TCP header. They are used to calculate the checksum for the TCP header. Figuring out how to pack these properly, and in what endianness, turned out to be one of the biggest difficulties in getting TCP SYN scanning working. I had a completely different problem when it came to implementing UDP scanning. This is because when a UDP packet arrives and is destined for a closed port, an ICMP destination unreachable message is sent back, and on Linux systems these are time-limited to a maximum of one per second. Thus, I had to come up with a strategy that could deal with problem. In the end, I added a maximum wait time for each packet sent, and instructed the program to listen for that length of time to determine if an ICMP destination unreachable message was received. Implementing version scanning came with its own difficulties. Parsing the file which defines the probes and all the directives which are needed to interpret the service's response was challenging, as was matching the returned data using a regular expression that was parsed from a file.

5.2 Evaluation against objectives, end user feedback

When I set out on this project I intended to make a program which was able to scan other computers on a network from a black box perspective in a way similar to nmap. Before commencing, I set out 14 pre-specified criteria against which

the performance of my program could be measured. As has been demonstrated above, the program fully meets 13 of the 14 criteria, and partially meets the remaining criterion. I believe therefore that my program has substantially met all the objectives set out at the beginning.

5.3 Potential improvements

I believe that I could improve my program if it were to have a dedicated option for operating system detection. It is clear that as a single individual, it would not be feasible for me to collect the required number of operating system signatures myself. Therefore, in order to implement this feature, I would need use another of the files from nmap: nmao-os-db, which contains a database of TCP/IP stack fingerprints that show how the TCP and IP protocols are implemented in virtually all currently-used operating systems, as well as in different versions of Linux and different service packs and versions of Windows.

A Technical Solution

A.1 icmp_ping

Listing 9: *A prototype program for sending ICMP ECHO REQEST packets*

```python
#!/usr/bin/env python
import socket
import struct
import os
import time
from modules.ip_utils import ip_checksum


def main() -> None:
    ICMP_ECHO_REQUEST = 8

    # opens a raw socket for the ICMP protocol
    ping_sock = socket.socket(
        socket.AF_INET,
        socket.SOCK_RAW,
        socket.IPPROTO_ICMP
    )
    # allows manual IP header creation
    # ping_sock.setsockopt(socket.SOL_IP, socket.IP_HDRINCL, 1)

    ID = os.getpid() & 0xFFFF

    # the two zeros are the code and the dummy checksum, the one is the
    # sequence number
    dummy_header = struct.pack("bbHHh", ICMP_ECHO_REQUEST, 0, 0, ID, 1)

    data = struct.pack(
        "d", time.time()
    ) + bytes(
        (192 - struct.calcsize("d")) * "A",
        "ascii"
    )
    # the data to send in the packet
    checksum = socket.htons(ip_checksum(dummy_header + data))
    # calculates the checksum for the packet and psuedo header
    header = struct.pack("bbHHh", ICMP_ECHO_REQUEST, 0, checksum, ID, 1)
    # packs the packet header
    packet = header + data
    # concatonates the header and the data to form the final packet.
    ping_sock.sendto(packet, ("127.0.0.1", 1))
    # sends the packet to localhost
```

```python
#!/usr/bin/env python
from modules import headers
import socket
from typing import List


def main() -> None:
    # socket object using an IPV4 address, using only raw socket access,
        set
    # ICMP protocol
    ping_sock = socket.socket(
        socket.AF_INET,
        socket.SOCK_RAW,
        socket.IPPROTO_ICMP
    )

    packets: List[bytes] = []

    while len(packets) < 1:
        recPacket, addr = ping_sock.recvfrom(1024)
        ip = headers.ip(recPacket[:20])
        icmp = headers.icmp(recPacket[20:28])

        print(ip)
        print()
        print(icmp)
        print("\n")

        packets.append(recPacket)
```

A.2 ping_scanner

Listing 11: *A prototype program for performing 'ping' scans*

```python
#!/usr/bin/env python
from modules import headers
from modules import ip_utils
import socket
import struct
import time
from contextlib import closing
from itertools import repeat
from math import log10, floor
from multiprocessing import Pool
from os import getpid
from typing import Set, Tuple

```

```python
14
15  def sig_figs(x: float, n: int) -> float:
16      """
17      rounds x to n significant figures.
18      sig_figs(1234, 2) = 1200.0
19      """
20      return round(x, n - (1 + int(floor(log10(abs(x))))))
21
22
23  def ping_listener(
24          ID: int,
25          timeout: float
26  ) -> Set[Tuple[str, float, headers.ip]]:
27      """
28      Takes in a process id and a timeout and returns
29      a list of addresses which sent ICMP ECHO REPLY
30      packets with the packed id matching ID in the time given by timeout.
31      """
32      ping_sock = socket.socket(
33          socket.AF_INET,
34          socket.SOCK_RAW,
35          socket.IPPROTO_ICMP
36      )
37      # opens a raw socket for sending ICMP protocol packets
38      time_remaining = timeout
39      addresses = set()
40      while True:
41          time_waiting = ip_utils.wait_for_socket(ping_sock,
42                  time_remaining)
43          # time_waiting stores the time the socket took to become readable
43      # or returns minus one if it ran out of time
44
45          if time_waiting == -1:
46              break
47          time_recieved = time.time()
48          # store the time the packet was recieved
49          recPacket, addr = ping_sock.recvfrom(1024)
50          # recieve the packet
51          ip = headers.ip(recPacket[:20])
52          # unpack the IP header into its respective components
53          icmp = headers.icmp(recPacket[20:28])
54          # unpack the time from the packet.
55          time_sent = struct.unpack(
56              "d",
57              recPacket[28:28 + struct.calcsize("d")]
58          )[0]
59          # unpack the value for when the packet was sent
60          time_taken: float = time_recieved - time_sent
61          # calculate the round trip time taken for the packet
62          if icmp.id == ID:
```

73

```
63              # if the ping was sent from this machine then add it to the
                    list of
64              # responses
65              ip_address, port = addr
66              addresses.add((ip_address, time_taken, ip))
67          elif time_remaining <= 0:
68              break
69          else:
70              continue
71      # return a list of all the addesses that replied to our ICMP echo
          request.
72      return addresses


def main() -> None:
75  def main() -> None:
76      with closing(
77              socket.socket(
78                  socket.AF_INET,
79                  socket.SOCK_RAW,
80                  socket.IPPROTO_ICMP
81              )
82      ) as ping_sock:
83          ip_addresses = ["127.0.0.1"] # ip_utils.ip_range("192.168.43.0",
                24)
84          # generate the range of IP addresses to scan.
85          # get the local ip address
86          addresses = [
87              ip
88              for ip in ip_addresses
89              if (
90                  not ip.endswith(".0")
91                  and not ip.endswith(".255")
92              )
93          ]

95          # initialise a process pool
96          p = Pool(1)
97          # get the local process id for use in creating packets.
98          ID = getpid() & 0xFFFF
99          # run the listeners.ping function asynchronously
100         replied = p.apply_async(ping_listener, (ID, 5))
101         time.sleep(0.01)
102         for address in zip(addresses, repeat(1)):
103             try:
104                 packet = ip_utils.make_icmp_packet(ID)
105                 ping_sock.sendto(packet, address)
106             except PermissionError:
107                 ip_utils.eprint("raw sockets require root priveleges,
                        exiting")
108                 exit()
```

```
109        p.close()
110        p.join()
111        # close and join the process pool to so that all the values
112        # have been returned and the pool closed
113        hosts_up = replied.get()
114        # get the list of addresses that replied to the echo request
               from the
115        # listener function
116        print("\n".join(
117            f"host: [{host}]\t" +
118            "responded to an ICMP ECHO REQUEST in " +
119            f"{str(sig_figs(taken, 2))+'s':<10s} " +
120            f"ttl: [{ip_head.time_to_live}]"
121            for host, taken, ip_head in hosts_up
122        ))
```

A.3   subnet_to_addresses

Listing 12: *A program which translates a CIDR specified subnet into a list of addresses and prints them out in sorted order*

```
1   #!/usr/bin/env python
2   import re
3   from modules.ip_utils import ip_range, dot_to_long
4
5
6   if __name__ == '__main__':
7       from argparse import ArgumentParser
8       parser = ArgumentParser()
9       parser.add_argument(
10          "ip_subnet",
11          help="The CIDR form ip/subnet that you wish to print" +
12              "the IP addresses specified by."
13      )
14      args = parser.parse_args()
15      CIDR_regex = re.compile(r"(\d{1,3}\.\d{1,3}\.\d{1,3}\.\d{1,3}/\d+)")
16      search = CIDR_regex.search(args.ip_subnet)
17      if search:
18          ip, network_bits = search.group(1).split("/")
19          print("\n".join(
20              sorted(
21                  ip_range(ip, int(network_bits)),
22                  key=dot_to_long
23              )
24          ))
```

A.4 tcp_scan

A.4.1 connect_scan

Listing 13: *prototype TCP connect scanner only attempting to detect the state of port 22*

```python
#!/usr/bin/python3
from contextlib import closing
import socket
LOCAL_IP = "192.168.1.159"
PORT = 22


address = ("127.0.0.1", 22)

with closing(
        socket.socket(
            socket.AF_INET,
            socket.SOCK_STREAM
        )
) as s:
    try:
        s.connect(address)
        print(f"connection on port {PORT} succedded")
    except ConnectionRefusedError:
        print(f"port {PORT} is closed")
```

Listing 14: *A program that performs TCP connect scanning*

```python
#!/usr/bin/python3

from typing import List, Set


def connect_scan(address: str, ports: Set[int]) -> List[int]:
    import socket
    from contextlib import closing
    open_ports: List[int] = []
    for port in ports:
        # loop through each port in the list of ports to scan
        try:
            with closing(
                    socket.socket(
                        socket.AF_INET,
                        socket.SOCK_STREAM
                    )
            ) as s:
                # open an IPV4 TCP socket
                s.connect((address, port))
```

76

```
21                    # attempt to connect the newly created socket to the
                          target
22                    # address and port
23                    open_ports.append(port)
24                    # if the connection was successful then add the port to
                          the
25                    # list of open ports
26        except ConnectionRefusedError:
27            pass
28    return open_ports


31  def main() -> None:
32      open_ports = connect_scan("192.168.43.225", set(range(65535)))
33      print("\n".join(map(lambda x: f"port: [{x}]\tis open", open_ports)))
```

A.4.2 syn_scan

Listing 15: *A prototype program that tries to detect the state of port 22 via TCP SYN scanning (aka half open scanning)*

```
1   #!/usr/bin/python3.7
2   from contextlib import closing
3   import socket
4   import ip_utils
5
6   dest_port = 22
7   src_port = ip_utils.get_free_port()
8   local_ip = ip_utils.get_local_ip()
9   dest_ip = "192.168.1.159"
10  local_ip = dest_ip = "127.0.0.1"
11  loc_long = ip_utils.dot_to_long(local_ip)
12
13  SYN = 2
14  RST = 4
15
16
17
18  with closing(
19          socket.socket(
20              socket.AF_INET,
21              socket.SOCK_RAW,
22              socket.IPPROTO_TCP
23          )
24  ) as s:
25      tcp_packet = ip_utils.make_tcp_packet(
26          src_port,
27          dest_port,
```

```
28          local_ip,
29          dest_ip,
30          SYN
31      )
32      if tcp_packet is not None:
33          s.sendto(tcp_packet, (dest_ip, dest_port))
34      else:
35          print(f"Couldn't make TCP packet with supplied arguments:",
36              f"source port: [{src_port}]",
37              f"destination port: [{dest_port}]",
38              f"local ip: [{local_ip}]",
39              f"destination ip: [{dest_ip}]",
40              f"SYN flag: [{SYN}]",
41              sep="\n")
```

Listing 16: *A program that performs TCP SYN scanning (aka half open scanning)*

```
1  #!/usr/bin/python3.7
2  from modules import headers
3  from modules import ip_utils
4  import socket
5  from contextlib import closing
6  from multiprocessing import Pool
7  from typing import List, Set, Tuple
8
9
10 def syn_listener(address: Tuple[str, int], timeout: float) -> List[int]:
11     """
12     This function is run asynchronously and listens for
13     TCP ACK responses to the sent TCP SYN msg.
14     """
15     print(f"address: [{address}]\ntimeout: [{timeout}]")
16     open_ports: List[int] = []
17     with closing(
18             socket.socket(
19                 socket.AF_INET,
20                 socket.SOCK_RAW,
21                 socket.IPPROTO_TCP
22             )) as s:
23         s.bind(address)
24         # bind the raw socket to the listening address
25         time_remaining = timeout
26         print("started listening")
27         while True:
28             time_taken = ip_utils.wait_for_socket(s, time_remaining)
29             # wait for the socket to become readable
30             if time_taken == -1:
31                 break
32             else:
```

```
33            time_remaining -= time_taken
34        packet = s.recv(1024)
35        # recieve the packet data
36        tcp = headers.tcp(packet[20:40])
37        if tcp.flags == 0b00010010: # syn ack
38            print(tcp)
39            open_ports.append(tcp.source)
40            # check that the header contained the TCP ACK flag and if
                  it
41            # did append it
42        else:
43            continue
44    print("finished listening")
45    return open_ports


48 def syn_scan(dest_ip: str, portlist: Set[int]) -> List[int]:
49    src_port = ip_utils.get_free_port()
50    # request a local port to connect from
51    local_ip = ip_utils.get_local_ip()
52    p = Pool(1)
53    listener = p.apply_async(syn_listener, ((local_ip, src_port), 5))
54    # start the TCP ACK listener in the background
55    print("starting scan")
56    for port in portlist:
57        packet = ip_utils.make_tcp_packet(src_port, port, local_ip,
              dest_ip, 2)
58        # create a TCP packet with the syn flag
59        with closing(
60                socket.socket(
61                    socket.AF_INET,
62                    socket.SOCK_RAW,
63                    socket.IPPROTO_TCP
64                )
65        ) as s:
66            s.sendto(packet, (dest_ip, port))
67            # send the packet to its destination

69    print("finished scan")
70    p.close()
71    p.join()
72    open_ports = listener.get()
73    # collect the list of ports that responded to the TCP SYN message
74    print(open_ports)
75    return open_ports


78 def main() -> None:
79    dest_ip = "127.0.0.1"
80    syn_scan(dest_ip, set(range(2**16)))
```

A.5 udp_scan

Listing 17: *A prototype program to detect whether UDP port 53 is open on a target machine*

```python
#!/usr/bin/ python
from contextlib import closing
import ip_utils
import socket

dest_ip = "192.168.1.1"
dest_port = 68
local_ip = ip_utils.get_local_ip()
local_port = ip_utils.get_free_port()

local_ip = dest_ip = "127.0.0.1"

address = (dest_ip, dest_port)

with closing(
        socket.socket(
            socket.AF_INET,
            socket.SOCK_RAW,
            socket.IPPROTO_UDP
        )) as s:
    try:
        pkt = ip_utils.make_udp_packet(
            local_port,
            dest_port,
            local_ip,
            dest_ip
        )
        if pkt is not None:
            packet = bytes(pkt)
            s.sendto(packet, address)
        else:
            print(
                "Error making packet.",
                f"local port: [{local_port}]",
                f"destination port: [{dest_port}]",
                f"local ip: [{local_ip}]",
                f"destination ip: [{dest_ip}]",
                sep="\n"
            )
    except socket.error:
        raise
```

Listing 18: *A program for performing scans on UDP ports.*

```python
#!/usr/bin/env python
from modules import headers
from modules import ip_utils
import socket
import time
from collections import defaultdict
from contextlib import closing
from multiprocessing import Pool
from typing import Set, DefaultDict


def udp_listener(dest_ip: str, timeout: float) -> Set[int]:
    """
    This listener detects UDP packets from dest_ip in the given timespan,
    all ports that send direct replies are marked as being open.
    Returns a list of open ports.
    """

    time_remaining = timeout
    ports: Set[int] = set()
    with socket.socket(
            socket.AF_INET,
            socket.SOCK_RAW,
            socket.IPPROTO_UDP
    ) as s:
        while True:
            time_taken = ip_utils.wait_for_socket(s, time_remaining)
            if time_taken == -1:
                break
            else:
                time_remaining -= time_taken
            packet = s.recv(1024)
            ip = headers.ip(packet[:20])
            udp = headers.udp(packet[20:28])
            # unpack the UDP header
            if dest_ip == ip.source and ip.protocol == 17:
                ports.add(udp.src)

    return ports


def icmp_listener(src_ip: str, timeout: float = 2) -> int:
    """
    This listener detects ICMP destination unreachable
    packets and returns the icmp code.
    This is later used to mark them as either close, open|filtered,
        filtered.
    3 -> closed
```

```python
48          0|1|2|9|10|13 -> filtered
49          -1 -> error with arguments
50          open|filtered means that they are either open or
51          filtered but return nothing.
52          """
53
54          ping_sock = socket.socket(
55              socket.AF_INET,
56              socket.SOCK_RAW,
57              socket.IPPROTO_ICMP
58          )
59          # open raw socket to listen for ICMP destination unrechable packets
60          time_remaining = timeout
61          code = -1
62          while True:
63              time_waiting = ip_utils.wait_for_socket(ping_sock,
64                  time_remaining)
65              # wait for socket to be readable
66              if time_waiting == -1:
67                  break
68              else:
69                  time_remaining -= time_waiting
70              recPacket, addr = ping_sock.recvfrom(1024)
71              # recieve the packet
72              ip = headers.ip(recPacket[:20])
73              icmp = headers.icmp(recPacket[20:28])
74              valid_codes = [0, 1, 2, 3, 9, 10, 13]
75              if (
76                      ip.source == src_ip
77                      and icmp.type == 3
78                      and icmp.code in valid_codes
79              ):
80                  code = icmp.code
81                  break
82              elif time_remaining <= 0:
83                  break
84              else:
85                  continue
86          ping_sock.close()
87      return code


def udp_scan(
        dest_ip: str,
        ports_to_scan: Set[int]
) -> DefaultDict[str, Set[int]]:
    """
    Takes in a destination IP address in either dot or long form and
    a list of ports to scan. Sends UDP packets to each port specified
    in portlist and uses the listeners to mark them as open,
```

```
            open|filtered,
 97     filtered, closed they are marked open|filtered if no response is
 98     recieved at all.
 99     """
100
101     local_ip = ip_utils.get_local_ip()
102     local_port = ip_utils.get_free_port()
103     # get local ip address and port number
104     ports: DefaultDict[str, Set[int]] = defaultdict(set)
105     ports["REMAINING"] = ports_to_scan
106     p = Pool(1)
107     udp_listen = p.apply_async(udp_listener, (dest_ip, 4))
108     # start the UDP listener
109     with closing(
110             socket.socket(
111                 socket.AF_INET,
112                 socket.SOCK_RAW,
113                 socket.IPPROTO_UDP
114             )
115     ) as s:
116         for _ in range(2):
117             # repeat 3 times because UDP scanning comes
118             # with a high chance of packet loss
119             for dest_port in ports["REMAINING"]:
120                 try:
121                     packet = ip_utils.make_udp_packet(
122                         local_port,
123                         dest_port,
124                         local_ip,
125                         dest_ip
126                     )
127                     # create the UDP packet to send
128                     s.sendto(packet, (dest_ip, dest_port))
129                     # send the packet to the currently scanning address
130                 except socket.error:
131                     packet_bytes = " ".join(map(hex, packet))
132                     print(
133                         "The socket modules sendto method with the
                                following",
134                         "argument resulting in a socket error.",
135                         f"\npacket: [{packet_bytes}]\n",
136                         "address: [{dest_ip, dest_port}])"
137                     )
138
139     p.close()
140     p.join()
141
142     ports["OPEN"].update(udp_listen.get())
143
144     ports["REMAINING"] -= ports["OPEN"]
```

```
145        # only scan the ports which we know are not open
146        with closing(
147                socket.socket(
148                    socket.AF_INET,
149                    socket.SOCK_RAW,
150                    socket.IPPROTO_UDP
151                )
152        ) as s:
153            for dest_port in ports["REMAINING"]:
154                try:
155                    packet = ip_utils.make_udp_packet(
156                        local_port,
157                        dest_port,
158                        local_ip,
159                        dest_ip
160                    )
161                    # make a new UDP packet
162                    p = Pool(1)
163                    icmp_listen = p.apply_async(icmp_listener, (dest_ip,))
164                    # start the ICMP listener
165                    time.sleep(1)
166                    s.sendto(packet, (dest_ip, dest_port))
167                    # send packet
168                    p.close()
169                    p.join()
170                    icmp_code = icmp_listen.get()
171                    # recieve ICMP code from the ICMP listener
172                    if icmp_code in {0, 1, 2, 9, 10, 13}:
173                        ports["FILTERED"].add(dest_port)
174                    elif icmp_code == 3:
175                        ports["CLOSED"].add(dest_port)
176                except socket.error:
177                    packet_bytes = " ".join(map("{:02x}".format, packet))
178                    ip_utils.eprint(
179                        "The socket modules sendto method with the following",
180                        "argument resulting in a socket error.",
181                        f"\npacket: [{packet_bytes}]\n",
182                        "address: [{dest_ip, dest_port}])"
183                    )
184        # this creates a new set which contains all the elements that
185        # are in the list of ports to be scanned but have not yet
186        # been classified
187        ports["OPEN|FILTERED"] = (
188            ports["REMAINING"]
189            - ports["OPEN"]
190            - ports["FILTERED"]
191            - ports["CLOSED"]
192        )
193        # set comprehension to update the list of open filtered ports
194        return ports
```

```
195
196
197  def main() -> None:
198      ports = udp_scan("127.0.0.1", {22, 68, 53, 6969})
199      print(f"Open ports: {ports['OPEN']}")
200      print(f"Open or filtered ports: {ports['OPEN|FILTERED']}")
201      print(f"Filtered ports: {ports['FILTERED']}")
202      print(f"Closed ports: {ports['CLOSED']}")
```

Listing 19: *A program I made to open a port via UDP for testing my UDP scanner.*

```
1   #!/usr/bin/env python
2
3   import socket
4   from contextlib import closing
5
6   with closing(
7           socket.socket(
8               socket.AF_INET,
9               socket.SOCK_DGRAM
10          )
11  ) as s:
12      s.bind(("127.0.0.1", 12345))
13      print("opened port 12345 on localhost")
14      while True:
15          data, addr = s.recvfrom(1024)
16          s.sendto(bytes("Well hello there good sir.", "utf-8"), addr)
```

A.6   version_detection

Listing 20: *A program which does version detection on services.*

```
1   #!/usr/bin/env python
2   from typing import Dict, Set, Pattern, Tuple, DefaultDict
3   from functools import reduce
4   from collections import defaultdict
5   from modules import directives
6   import re
7   import operator
8
9   # type annotaion for the container which
10  # holds the probes. I have abstracted it from
11  # the function definition because multiple functions
12  # depend on it and they weren't all getting updated
13  # if I needed to change the function signature.
14  PROBE_CONTAINER = DefaultDict[str, Dict[str, directives.Probe]]
15
```

```python
16
17  def parse_ports(portstring: str) -> DefaultDict[str, Set[int]]:
18      """
19      This function takes in a port directive
20      and returns a set of the ports specified.
21      A set is used because it is O(1) for contains
22      operations as opposed for O(N) for lists.
23      """
24      # matches both the num-num port range format
25      # and the plain num port specification
26      # num-num form must come first otherwise it breaks.
27      proto_regex = re.compile(r"([ TU]):?([0-9,-]+)")
28      # THE SPACE IS IMPORTANT!!!
29      # it allows ports specified before TCP/UDP ports
30      # to be specified globally as in for all protocols.
31
32      pair_regex = re.compile(r"(\d+)-(\d+)")
33      single_regex = re.compile(r"(\d+)")
34      ports: DefaultDict[str, Set[int]] = defaultdict(set)
35      # searches contains the result of trying the pair_regex
36      # search against all of the command seperated
37      # port strings
38
39      for protocol, portstring in proto_regex.findall(portstring):
40          pairs = pair_regex.findall(portstring)
41          # for each pair of numbers in the pairs list
42          # seperate each number and cast them to int
43          # then generate the range of numbers from x[0]
44          # to x[1]+1 then cast this range to a list
45          # and "reduce" the list of lists by joining them
46          # with operator.ior (inclusive or) and then let
47          # ports be the set of all the ports in that list.
48          proto_map = {
49              " ": "ANY",
50              "U": "UDP",
51              "T": "TCP"
52          }
53          if pairs:
54              def pair_to_ports(pair: Tuple[int, int]) -> Set[int]:
55                  """
56                  a function to go from a port pair i.e. (80-85)
57                  to the set of specified ports: {80,81,82,83,84,85}
58                  """
59                  start, end = pair
60                  return set(range(start, end+1))
61              # ports contains the set of all ANY/TCP/UDP specified ports
62              ports[proto_map[protocol]] = set(reduce(
63                  operator.ior,
64                  map(pair_to_ports, pairs)
65              ))
```

```
66
67          singles = single_regex.findall(portstring)
68          # for each of the ports that are specified on their own
69          # cast them to int and update the set of all ports with
70          # that list.
71          ports[proto_map[protocol]].update(map(int, singles))
72
73      return ports
74
75
76  def parse_probes(probe_file: str) -> PROBE_CONTAINER:
77      """
78      Extracts all of the probe directives from the
79      file pointed to by probe_file.
80      """
81      # lines contains each line of the file which doesn't
82      # start with a # and is not empty.
83      lines = [
84          line
85          for line in open(probe_file).read().splitlines()
86          if line and not line.startswith("#")
87      ]
88
89      # list holding each of the probe directives.
90      probes: PROBE_CONTAINER = defaultdict(dict)
91
92      regexes: Dict[str, Pattern] = {
93          "probe":       re.compile(r"Probe (TCP|UDP) (\S+) q\|(.*)\|"),
94          "match":       re.compile(" ".join([
95              r"(?P<type>softmatch|match)",
96              r"(?P<service>\S+)",
97              r"m([@/%=|])(?P<regex>.+?)\3(?P<flags>[si]*)"
98          ])),
99          "rarity":      re.compile(r"rarity (\d+)"),
100         "totalwaitms": re.compile(r"totalwaitms (\d+)"),
101         "tcpwrappedms": re.compile(r"tcpwrappedms (\d+)"),
102         "fallback":    re.compile(r"fallback (\S+)"),
103         "ports":       re.compile(r"ports (\S+)"),
104         "exclude":     re.compile(r"Exclude T:(\S+)")
105     }
106
107     # parse the probes out from the file
108     for line in lines:
109         # add any ports to be excluded to the base probe class
110         if line.startswith("Exclude"):
111             search = regexes["exclude"].search(line)
112             if search:
113                 # parse the ports from the grouped output of
114                 # a search with the regex defined above.
```

```
115              for protocol, ports in
                   parse_ports(search.group(1)).items():
116                  directives.Probe.exclude[protocol].update(ports)
117          else:
118              print(line)
119              input()
120
121      # new probe directive
122      if line.startswith("Probe"):
123          # parse line into probe protocol, name and probestring
124          search = regexes["probe"].search(line)
125          if search:
126              try:
127                  proto, name, string = search.groups()
128              except ValueError:
129                  print(line)
130                  raise
131              probes[name][proto] = directives.Probe(proto, name,
                   string)
132              # assign current_probe to the most recently added probe
133              current_probe = probes[name][proto]
134          else:
135              print(line)
136              input()
137
138      # new match directive
139      elif line.startswith("match") or line.startswith("softmatch"):
140          search = regexes["match"].search(line)
141          if search:
142              # the remainder of the string after the match
143              version_info = line[search.end()+1:]
144              # escape the curly braces so the regex engine doesn't
145              # consider them to be special characters
146              pattern = bytes(search.group("regex"), "utf-8")
147              # these replace the literal \n, \r and \t
148              # strings with their actual characters
149              # i.e. \n -> newline character
150              pattern = pattern.replace(b"\\n", b"\n")
151              pattern = pattern.replace(b"\\r", b"\r")
152              pattern = pattern.replace(b"\\t", b"\t")
153              matcher = directives.Match(
154                  search.group("service"),
155                  pattern,
156                  search.group("flags"),
157                  version_info
158              )
159              if search.group("type") == "match":
160                  current_probe.matches.add(matcher)
161              else:
162                  current_probe.softmatches.add(matcher)
```

```
163
164                else:
165                    print(line)
166                    input()
167
168            # new ports directive
169            elif line.startswith("ports"):
170                search = regexes["ports"].search(line)
171                if search:
172                    for protocol, ports in
                            parse_ports(search.group(1)).items():
173                        current_probe.ports[protocol].update(ports)
174                else:
175                    print(line)
176                    input()
177            # new totalwaitms directive
178            elif line.startswith("totalwaitms"):
179                search = regexes["totalwaitms"].search(line)
180                if search:
181                    current_probe.totalwaitms = int(search.group(1))
182                else:
183                    print(line)
184                    input()
185
186            # new rarity directive
187            elif line.startswith("rarity"):
188                search = regexes["rarity"].search(line)
189                if search:
190                    current_probe.rarity = int(search.group(1))
191                else:
192                    print(line)
193                    input()
194
195            # new fallback directive
196            elif line.startswith("fallback"):
197                search = regexes["fallback"].search(line)
198                if search:
199                    current_probe.fallback = set(search.group(1).split(","))
200                else:
201                    print(line)
202                    input()
203        return probes
204
205
206    def version_detect_scan(
207            target: directives.Target,
208            probes: PROBE_CONTAINER
209    ) -> directives.Target:
210        for probe_dict in probes.values():
211            for proto in probe_dict:
```

```
212             target = probe_dict[proto].scan(target)
213         return target
214
215
216 def main() -> None:
217     print("reached here")
218     probes = parse_probes("./version_detection/nmap-service-probes")
219     open_ports: DefaultDict[str, Set[int]] = defaultdict(set)
220     open_filtered_ports: DefaultDict[str, Set[int]] = defaultdict(set)
221     open_filtered_ports["TCP"].add(22)
222     open_ports["TCP"].update([1, 2, 3, 4, 5, 6, 8, 65,
223                             20, 21, 23, 24, 25])
224
225     target = directives.Target(
226         "127.0.0.1",
227         open_ports,
228         open_filtered_ports
229     )
230     target.open_ports["TCP"].update([1, 2, 3])
231     print("BEFORE")
232     print(target)
233     scanned = version_detect_scan(target, probes)
234     print("AFTER")
235     print(scanned)
```

A.7   modules

Listing 21: *A Python module I wrote for parsing and holding the version detection probes from the nmap_service_probes file.*

```
1  #!/usr/bin/env python
2  from collections import defaultdict
3  from contextlib import closing
4  from dataclasses import dataclass, field
5  from functools import reduce
6  from string import whitespace, printable
7  from typing import (
8      DefaultDict,
9      Dict,
10     Set,
11     List,
12     Pattern,
13     Match as RE_Match,
14     Tuple
15 )
16 from . import ip_utils
17 import operator
18 import re
```

```python
import socket
import struct


class Match:
    """
    This is a class for both Matches and
    Softmatches as they are actually the same
    thing except that softmatches have less information.
    """
    options_to_flags = {
        "i": re.IGNORECASE,
        "s": re.DOTALL
    }
    letter_to_name = {
        "p": "vendorproductname",
        "v": "version",
        "i": "info",
        "h": "hostname",
        "o": "operatingsystem",
        "d": "devicetype"
    }
    cpe_part_map: Dict[str, str] = {
        "a": "applications",
        "h": "hardware platforms",
        "o": "operating systems"
    }
    # look into match.expand when looking at the substring version info
        things.

    def __init__(
            self,
            service: str,
            pattern: bytes,
            pattern_options: str,
            version_info: str
    ):
        self.version_info: Dict[str, str] = dict()
        self.cpes: Dict[str, Dict[str, str]] = dict()
        self.service: str = service
        # bitwise or is used to combine flags
        # pattern options will never be anything but a
        # combination of s and i.
        # the default value of re.V1 is so that
        # re uses the newer matching engine.
        flags = reduce(
            operator.ior,
            [
                self.options_to_flags[opt]
                for opt in pattern_options
```

```
68              ],
69              0
70          )
71          try:
72              self.pattern: Pattern = re.compile(
73                  pattern,
74                  flags=flags
75              )
76          except Exception as e:
77              print("Regex failed to compile:")
78              print(e)
79              print(pattern)
80              input()
81
82          vinfo_regex = re.compile(r"([pvihod]|cpe:)([/|])(.+?)\2([a]*)")
83          cpe_regex = re.compile(
84              ":?".join((
85                  "(?P<part>[aho])",
86                  "(?P<vendor>[^:]*)",
87                  "(?P<product>[^:]*)",
88                  "(?P<version>[^:]*)",
89                  "(?P<update>[^:]*)",
90                  "(?P<edition>[^:]*)",
91                  "(?P<language>[^:]*)"
92              ))
93          )
94
95          for fieldname, _, val, opts in vinfo_regex.findall(version_info):
96              if fieldname == "cpe:":
97                  search = cpe_regex.search(val)
98                  if search:
99                      part = search.group("part")
100                     # this next bit is so that the bytes produced by the
                            regex
101                     # are turned to strings
102                     self.cpes[Match.cpe_part_map[part]] = {
103                         key: value
104                         for key, value
105                         in search.groupdict().items()
106                     }
107             else:
108                 self.version_info[
109                     Match.letter_to_name[fieldname]
110                 ] = val
111
112     def __repr__(self) -> str:
113         return "Match(" + ", ".join((
114                 f"service={self.service}",
115                 f"pattern={self.pattern}",
116                 f"version_info={self.version_info}",
```

```
117                    f"cpes={self.cpes}"
118                )) + ")"
119
120    def matches(self, string: bytes) -> bool:
121        def replace_groups(
122                string: str,
123                original_match: RE_Match
124        ) -> str:
125            """
126            This function takes in a string and the original
127            regex search performed on the data recieved and
128            replaces all of the $i, $SUBST, $I, $P occurances
129            with the relavant formatted text that they produce.
130            """
131            def remove_unprintable(
132                    group: int,
133                    original_match: RE_Match
134            ) -> bytes:
135                """
136                Mirrors the P function from nmap which
137                is used to print only printable characters.
138                i.e. W\OO\OR\OK\OG\OR\OO\OU\OP -> WORKGROUP
139                """
140                return b"".join(
141                    i for i in original_match.group(group)
142                    if ord(i) in (
143                        set(printable)
144                        - set(whitespace)
145                        | {" "}
146                    )
147                )
148                # if i in the set of all printable characters,
149                # excluding those of which that are whitespace characters
150                # but including space.
151
152            def substitute(
153                group: int,
154                before: bytes,
155                after: bytes,
156                original_match: RE_Match
157            ) -> bytes:
158                """
159                Mirrors the SUBST function from nmap which is used to
160                format some information found by the regex.
161                by substituting all instances of `before` with `after`.
162                """
163                return original_match.group(group).replace(before, after)
164
165            def unpack_uint(
166                    group: int,
```

```
167                endianness: str,
168                original_match: RE_Match
169            ) -> bytes:
170                """
171                Mirrors the I function from nmap which is used to
172                unpack an unsigned int from some bytes.
173                """
174                return bytes(struct.unpack(
175                    endianness + "I",
176                    original_match.group(group)
177                ))
178
179        text = bytes(string, "utf-8")
180        # fill in the version information from the regex match
181        # find all the dollar groups:
182        dollar_regex = re.compile(r"\$(\d)")
183        # find all the $i's in string
184        numbers = set(int(i) for i in dollar_regex.findall(string))
185        # for each $i found i
186        for group in numbers:
187            text = text.replace(
188                bytes(f"${group}", "utf-8"),
189                original_match.group(group)
190            )
191        # having replaced all of the groups we can now
192        # start doing the SUBST, P and I commands.
193        subst_regex = re.compile(rb"\$SUBST\((\d),(.+),(.+)\)")
194        # iterate over all of the matches found by the SUBST regex
195        for match in subst_regex.finditer(text):
196            num, before, after = match.groups()
197            # replace the full match (group 0)
198            # with the output of substitute
199            # with the specific arguments
200            text.replace(
201                match.group(0),
202                substitute(int(num), before, after, original_match)
203            )
204
205        p_regex = re.compile(rb"\$P\((\d)\)")
206        for match in p_regex.finditer(text):
207            num = match.group(1)
208            # replace the full match (group 0)
209            # with the output of remove_unprintable
210            # with the specific arguments
211            text.replace(
212                match.group(0),
213                remove_unprintable(int(num), original_match)
214            )
215
216        i_regex = re.compile(br"\$I\((\d),\"(\S)\"\)")
```

94

```
217            for match in i_regex.finditer(text):
218                num, endianness = match.groups()
219                # this means replace group 0 -> the whole match
220                # with the output of the unpack_uint
221                # with the specified arguments
222                text.replace(
223                    match.group(0),
224                    unpack_uint(
225                        int(num.decode()),
226                        endianness.decode(),
227                        original_match
228                    )
229                )
230
231            return text.decode()
232
233        search = self.pattern.search(string)
234        if search:
235            # the fields to replace are all the CPE groups,
236            # all of the version info fields.
237            self.version_info = {
238                key: replace_groups(value, search)
239                for key, value in self.version_info.items()
240            }
241            self.cpes = {
242                outer_key: {
243                    inner_key: replace_groups(value, search)
244                    for inner_key, value in outer_dict.items()
245                }
246                for outer_key, outer_dict in self.cpes.items()
247            }
248
249            return True
250        else:
251            return False
252
253
254 @dataclass
255 class Target:
256     """
257     This class holds data about targets to
258     scan. the dataclass decorator is simply
259     a way of python automatically writing some
260     of the basic methods a class for storing data
261     has, such as __repr__ for printing information
262     in the object etc.
263     """
264     address: str
265     open_ports: DefaultDict[str, Set[int]]
266     open_filtered_ports: DefaultDict[str, Set[int]]
```

```python
    services: Dict[int, Match] = field(default_factory=dict)

    def __repr__(self) -> str:
        def collapse(port_dict: DefaultDict) -> str:
            """
            Collapse a list of port numbers so that
            only the unique ones and the start and end
            of a sequence are displayed.
            1,2,3,4,5,7,9,11,13,14,15,16,17 -> 1-5,7,9,11,13-17
            """
            store_results = list()
            for key in port_dict:
                # items is a sorted list of a set of ports.
                items: List[int] = sorted(port_dict[key])
                key_result = f'"{key}":' + "{"
                # if its an empty list return now to avoid errors
                if len(items) != 0:
                    new_sequence = False
                    # enumerate up until the one before
                    # the last to prevent index errors.
                    for index, item in enumerate(items[:-1]):
                        # if its the first one add it on
                        if index == 0:
                            key_result += f"{item}"
                            # if its a sequence start one else put a comma
                            if items[index+1] == item+1:
                                key_result += "-"
                            else:
                                key_result += ","
                        # if the sequence breaks then put a comma
                        elif item+1 != items[index+1]:
                            key_result += f"{item},"
                            new_sequence = True
                        # if its a new sequence the put the '-'s in
                        elif item+1 == items[index+1] and new_sequence:
                            key_result += f"{item}-"
                            new_sequence = False
                    # because we only iterate to the one before
                    # the last element, add the last element on to the end.
                    key_result += f"{items[-1]}" + "}"
                    store_results.append(key_result)
            # format the final result
            result = "{" + ", ".join(store_results) + "}"
            return result

        open_ports = collapse(self.open_ports)
        open_filtered_ports = collapse(self.open_filtered_ports)
        return ", ".join((
            f"Target(address=[{self.address}]",
            f"open_ports=[{open_ports}]",
```

```
317              f"open_filtered_ports=[{open_filtered_ports}]",
318              f"services={self.services})"
319          ))
320
321
322  class Probe:
323      """
324      This class represents the Probe directive of the nmap-service-probes
              file.
325      It holds information such as the protocol to use, the string to send,
326      the ports to scan, the time to wait for a null TCP to return a
              banner,
327      the rarity of the probe (how often it will return a response) and the
328      probes to try if this one fails.
329      """
330
331      # a default dict is one which takes in a
332      # "default factory" which is called when
333      # a new key is introduced to the dict
334      # in this case the default factory is
335      # the set function meaning that when I
336      # do exclude[protocol].update(ports)
337      # but exclude[protocol] has not yet been defined
338      # it will be defined as an empty set
339      # allowing me to update it with ports.
340      exclude: DefaultDict[str, Set[int]] = defaultdict(set)
341      proto_to_socket_type: Dict[str, int] = {
342          "TCP": socket.SOCK_STREAM,
343          "UDP": socket.SOCK_DGRAM
344      }
345
346      def __init__(self, protocol: str, probename: str, probe: str):
347          """
348          This is the initial function that is called by the
349          constructor of the Probe class, it is used to define
350          the variables that are specific to each instance of
351          the class.
352          """
353          if protocol in {"TCP", "UDP"}:
354              self.protocol = protocol
355          else:
356              raise ValueError(
357                  f"Probe object must have protocol TCP or UDP not
                      {protocol}.")
358          self.name: str = probename
359          self.string: str = probe
360          self.payload: bytes = bytes(probe, "utf-8")
361          self.matches: Set[Match] = set()
362          self.softmatches: Set[Match] = set()
363          self.ports: DefaultDict[str, Set[int]] = defaultdict(set)
```

```python
        self.totalwaitms: int = 6000
        self.tcpwrappedms: int = 3000
        self.rarity: int = -1
        self.fallback: Set[str] = set()

    def __repr__(self) -> str:
        """
        This is the function that is called when something
        tries to print an instance of this class.
        It is used to reveal information internal
        to the class.
        """
        return ", ".join([
            f"Probe({self.protocol}",
            f"{self.name}",
            f"\"{self.string}\"",
            f"{len(self.matches)} matches",
            f"{len(self.softmatches)} softmatches",
            f"ports: {self.ports}",
            f"rarity: {self.rarity}",
            f"fallbacks: {self.fallback})"
        ])

    def scan(self, target: Target) -> Target:
        """
        scan takes in an object of class Target to
        probe and attempts to detect the version of
        any services running on the machine.
        """
        # this constructs the set of all ports,
        # that are either open or open_filtered,
        # and are in the set of ports to scan for
        # this particular probe, this means that,
        # we are only connecting to ports that we
        # know are not closed and are not to be excluded.

        ports_to_scan: Set[int] = (
            (
                target.open_filtered_ports[self.protocol]
                | target.open_ports[self.protocol]
            )
        ) - Probe.exclude[self.protocol] - Probe.exclude["ANY"]
        # if the probe defines a set of ports to scan
        # then don't scan any that aren't defined for it
        if self.ports[self.protocol] != set():
            ports_to_scan &= self.ports[self.protocol]
        for port in ports_to_scan:
            # open a self closing IPV4 socket
            # for the correct protocol for this probe.
            with closing(
```

```
414                     socket.socket(
415                         socket.AF_INET,
416                         self.proto_to_socket_type[self.protocol]
417                     )
418             ) as sock:
419                 # setup the connection to the target
420                 try:
421                     sock.connect((target.address, port))
422                     # if the connection fails then continue scanning
423                     # the next ports, this shouldn't really happen.
424                 except ConnectionError:
425                     continue
426                 # send the payload to the target
427                 sock.send(self.payload)
428                 # wait for the target to send a response
429                 time_taken = ip_utils.wait_for_socket(
430                     sock,
431                     self.totalwaitms/1000
432                 )
433                 # if the response didn't time out
434                 if time_taken != -1:
435                     # if the port was in open_filtered move it to open
436                     if port in target.open_filtered_ports[self.protocol]:
437                         target.open_filtered_ports[
438                             self.protocol
439                         ].remove(port)
440                         target.open_ports[self.protocol].add(port)
441
442                     # recieve the data and decode it to a string
443                     data_recieved = sock.recv(4096)
444                     #  print("Recieved", data_recieved)
445                     service = ""
446                     # try and softmatch the service first
447                     for softmatch in self.softmatches:
448                         if softmatch.matches(data_recieved):
449                             service = softmatch.service
450                             target.services[port] = softmatch
451                             break
452                     # try and get a full match for the service
453                     for match in self.matches:
454                         if service in match.service.lower():
455                             if match.matches(data_recieved):
456                                 target.services[port] = match
457                                 break
458         return target
459
460
461 PROBE_CONTAINER = DefaultDict[str, Dict[str, Probe]]
462
463
```

```python
def parse_ports(portstring: str) -> DefaultDict[str, Set[int]]:
    """
    This function takes in a port directive
    and returns a set of the ports specified.
    A set is used because it is O(1) for contains
    operations as opposed for O(N) for lists.
    """
    # matches both the num-num port range format
    # and the plain num port specification
    # num-num form must come first otherwise it breaks.
    proto_regex = re.compile(r"([ TU]?):?([0-9,-]+)")
    # THE SPACE IS IMPORTANT!!!
    # it allows ports specified before TCP/UDP ports
    # to be specified globally as in for all protocols.

    pair_regex = re.compile(r"(\d+)-(\d+)")
    single_regex = re.compile(r"(\d+)")
    ports: DefaultDict[str, Set[int]] = defaultdict(set)
    # searches contains the result of trying the pair_regex
    # search against all of the command seperated
    # port strings

    for protocol, portstring in proto_regex.findall(portstring):
        pairs = pair_regex.findall(portstring)
        # for each pair of numbers in the pairs list
        # seperate each number and cast them to int
        # then generate the range of numbers from x[0]
        # to x[1]+1 then cast this range to a list
        # and "reduce" the list of lists by joining them
        # with operator.ior (inclusive or) and then let
        # ports be the set of all the ports in that list.
        proto_map = {
            "":  "ANY",
            " ": "ANY",
            "U": "UDP",
            "T": "TCP"
        }
        if pairs:
            def pair_to_ports(pair: Tuple[str, str]) -> Set[int]:
                """
                a function to go from a port pair i.e. (80-85)
                to the set of specified ports: {80,81,82,83,84,85}
                """
                start, end = pair
                return set(range(
                    int(start),
                    int(end)+1
                ))
            # ports contains the set of all ANY/TCP/UDP specified ports
            ports[proto_map[protocol]] = set(reduce(
```

```python
            operator.ior,
            map(pair_to_ports, pairs)
        ))

    singles = single_regex.findall(portstring)
    # for each of the ports that are specified on their own
    # cast them to int and update the set of all ports with
    # that list.
    ports[proto_map[protocol]].update(map(int, singles))

return ports


def parse_probes(probe_file: str) -> PROBE_CONTAINER:
    """
    Extracts all of the probe directives from the
    file pointed to by probe_file.
    """
    # lines contains each line of the file which doesn't
    # start with a # and is not empty.
    lines = [
        line
        for line in open(probe_file).read().splitlines()
        if line and not line.startswith("#")
    ]

    # list holding each of the probe directives.
    probes: PROBE_CONTAINER = defaultdict(dict)

    regexes: Dict[str, Pattern] = {
        "probe":       re.compile(r"Probe (TCP|UDP) (\S+) q\|(.*)\|"),
        "match":       re.compile(" ".join([
            r"(?P<type>softmatch|match)",
            r"(?P<service>\S+)",
            r"m([@/%=|])(?P<regex>.+?)\3(?P<flags>[si]*)"
        ])),
        "rarity":      re.compile(r"rarity (\d+)"),
        "totalwaitms": re.compile(r"totalwaitms (\d+)"),
        "tcpwrappedms": re.compile(r"tcpwrappedms (\d+)"),
        "fallback":    re.compile(r"fallback (\S+)"),
        "ports":       re.compile(r"ports (\S+)"),
        "exclude":     re.compile(r"Exclude T:(\S+)")
    }

    # parse the probes out from the file
    for line in lines:
        # add any ports to be excluded to the base probe class
        if line.startswith("Exclude"):
            search = regexes["exclude"].search(line)
            if search:
```

```
564                    # parse the ports from the grouped output of
565                    # a search with the regex defined above.
566                    for protocol, ports in
                            parse_ports(search.group(1)).items():
567                        Probe.exclude[protocol].update(ports)
568                else:
569                    print(line)
570                    input()
571
572            # new probe directive
573            if line.startswith("Probe"):
574                # parse line into probe protocol, name and probestring
575                search = regexes["probe"].search(line)
576                if search:
577                    try:
578                        proto, name, string = search.groups()
579                    except ValueError:
580                        print(line)
581                        raise
582                    probes[name][proto] = Probe(proto, name, string)
583                    # assign current_probe to the most recently added probe
584                    current_probe = probes[name][proto]
585                else:
586                    print(line)
587                    input()
588
589            # new match directive
590            elif line.startswith("match") or line.startswith("softmatch"):
591                search = regexes["match"].search(line)
592                if search:
593                    # the remainder of the string after the match
594                    version_info = line[search.end()+1:]
595                    # escape the curly braces so the regex engine doesn't
596                    # consider them to be special characters
597                    pattern = bytes(search.group("regex"), "utf-8")
598                    # these replace the literal \n, \r and \t
599                    # strings with their actual characters
600                    # i.e. \n -> newline character
601                    pattern = pattern.replace(b"\\n", b"\n")
602                    pattern = pattern.replace(b"\\r", b"\r")
603                    pattern = pattern.replace(b"\\t", b"\t")
604                    matcher = Match(
605                        search.group("service"),
606                        pattern,
607                        search.group("flags"),
608                        version_info
609                    )
610                    if search.group("type") == "match":
611                        current_probe.matches.add(matcher)
612                    else:
```

```
613                        current_probe.softmatches.add(matcher)
614
615            else:
616                print(line)
617                input()
618
619        # new ports directive
620        elif line.startswith("ports"):
621            search = regexes["ports"].search(line)
622            if search:
623                for protocol, ports in
                        parse_ports(search.group(1)).items():
624                    current_probe.ports[protocol].update(ports)
625            else:
626                print(line)
627                input()
628        # new totalwaitms directive
629        elif line.startswith("totalwaitms"):
630            search = regexes["totalwaitms"].search(line)
631            if search:
632                current_probe.totalwaitms = int(search.group(1))
633            else:
634                print(line)
635                input()
636
637        # new rarity directive
638        elif line.startswith("rarity"):
639            search = regexes["rarity"].search(line)
640            if search:
641                current_probe.rarity = int(search.group(1))
642            else:
643                print(line)
644                input()
645
646        # new fallback directive
647        elif line.startswith("fallback"):
648            search = regexes["fallback"].search(line)
649            if search:
650                current_probe.fallback = set(search.group(1).split(","))
651            else:
652                print(line)
653                input()
654    return probes
```

Listing 22: *A Python module I made to dissect and hold protocol headers.*

```
1  import struct
2  import socket
3  from typing import Dict
4
```

```python
class ip:
    """
    A class for parsing, storing and displaying
    data from an IP header.
    """
    def __init__(self, header: bytes):
        # first unpack the IP header
        (
            ip_hp_ip_v,
            ip_dscp_ip_ecn,
            ip_len,
            ip_id,
            ip_flgs_ip_off,
            ip_ttl,
            ip_p,
            ip_sum,
            ip_src,
            ip_dst
        ) = struct.unpack('!BBHHHBBHII', header)
        # now deal with the sub-byte sized components
        hl_v = f"{ip_hp_ip_v:08b}"
        ip_v = int(hl_v[:4], 2)
        ip_hl = int(hl_v[4:], 2)
        # splits hl_v in ip_v and ip_hl which store the IP version
            number and
        # header length respectively
        dscp_ecn = f"{ip_dscp_ip_ecn:08b}"
        ip_dscp = int(dscp_ecn[:6], 2)
        ip_ecn = int(dscp_ecn[6:], 2)
        # splits dscp_ecn into ip_dscp and ip_ecn
        # which are two of the compenents
        # in an IP header
        flgs_off = f"{ip_flgs_ip_off:016b}"
        ip_flgs = int(flgs_off[:3], 2)
        ip_off = int(flgs_off[3:], 2)
        # splits flgs_off into ip_flgs and ip_off which represent the ip
            header
        # flags and the data offset
        src_addr = socket.inet_ntoa(struct.pack('!I', ip_src))
        dst_addr = socket.inet_ntoa(struct.pack('!I', ip_dst))
        self.version: int = ip_v
        self.header_length: int = ip_hl
        self.dscp: int = ip_dscp
        self.ecn: int = ip_ecn
        self.len: int = ip_len
        self.id: int = ip_id
        self.flags: int = ip_flgs
        self.data_offset: int = ip_off
        self.time_to_live: int = ip_ttl
```

```python
53            self.protocol: int = ip_p
54            self.checksum: int = ip_sum
55            self.source: str = src_addr
56            self.destination: str = dst_addr
57
58        def __repr__(self) -> str:
59            return "\n\t".join((
60                "IP header:",
61                f"Version: [{self.version}]",
62                f"Internet Header Length: [{self.header_length}]",
63                f"Differentiated Services Point Code: [{self.dscp}]",
64                f"Explicit Congestion Notification: [{self.ecn}]",
65                f"Total Length: [{self.len}]",
66                f"Identification: [{self.id:04x}]",
67                f"Flags: [{self.flags:03b}]",
68                f"Fragment Offset: [{self.data_offset}]",
69                f"Time To Live: [{self.time_to_live}]",
70                f"Protocol: [{self.protocol}]",
71                f"Header Checksum: [{self.checksum:04x}]",
72                f"Source Address: [{self.source}]",
73                f"Destination Address: [{self.destination}]"
74            ))
75
76
77  class icmp:
78      """
79      A class for parsing, storing and displaying
80      data from an IP header.
81      """
82      # relates the type and code to the message
83      messages: Dict[int, Dict[int, str]] = {
84          0: {
85              0: "Echo reply."
86          },
87          3: {
88              0: "Destination network unreachable.",
89              1: "Destination host unreachable",
90              2: "Destination protocol unreachable",
91              3: "Destination port unreachable",
92              4: "Fragmentation required, and DF flag set.",
93              5: "Source route failed.",
94              6: "Destination network unknown.",
95              7: "Destination host unknown.",
96              8: "Source host isolated.",
97              9: "Network administratively prohibited.",
98              10: "Host administratively prohibited.",
99              11: "Network unreachable for ToS.",
100             12: "Host unreachable for ToS.",
101             13: "Communication administratively prohibited.",
102             14: "Host precedence violation.",
```

```python
                15: "Precedence cutoff in effect."
            },
            4: {
                0: "Source quench."
            },
            5: {
                0: "Redirect datagram for the network",
                1: "Redirect datagram for the host.",
                2: "Redirect datagram for the ToS & network.",
                3: "Redirect datagram for the ToS & host."
            },
            8: {
                0: "Echo request."
            },
            9: {
                0: "Router advertisment"
            },
            10: {
                0: "Router discovery/selection/solicitation."
            },
            11: {
                0: "TTL expired in transit",
                1: "Fragment reassembly time exceeded."
            },
            12: {
                0: "Bad IP header: pointer indicates error.",
                1: "Bad IP header: missing a required option.",
                2: "Bad IP header: Bad length."
            },
            13: {
                0: "Timestamp"
            },
            14: {
                0: "Timestamp reply"
            },
            15: {
                0: "Information request."
            },
            16: {
                0: "Information reply."
            },
            17: {
                0: "Address mask request."
            },
            18: {
                0: "Address mask reply."
            }
        }

    def __init__(self, header: bytes):
```

```python
153             (
154                 ICMP_type,
155                 code,
156                 csum,
157                 remainder
158             ) = struct.unpack('!bbHI', header)
159
160             self.type: int = ICMP_type
161             self.code: int = code
162             self.checksum: int = csum
163
164             self.message: str
165             try:
166                 self.message = icmp.messages[self.type][self.code]
167             except KeyError:
168                 # if we can't assign a message then just set a description
169                 # as to what caused the failure.
170                 self.message = f"Failed to assign message:
                        ({self.type/self.code})"
171
172             self.id: int
173             self.sequence: int
174             if self.type in {0, 8}:
175                 self.id = socket.htons(remainder >> 16)
176                 self.sequence = socket.htons(remainder & 0xFFFF)
177             else:
178                 self.id = -1
179                 self.sequence = -1
180
181         def __repr__(self) -> str:
182             return "\n\t".join((
183                 "ICMP header:",
184                 f"Message: [{self.message}]",
185                 f"Type: [{self.type}]",
186                 f"Code: [{self.code}]",
187                 f"Checksum: [{self.checksum:04x}]",
188                 f"ID: [{self.id}]",
189                 f"Sequence: [{self.sequence}]"
190             ))
191
192
193     class tcp:
194         def __init__(self, header: bytes):
195             (
196                 src_prt,
197                 dst_prt,
198                 seq,
199                 ack,
200                 data_offset,
201                 flags,
```

```python
                window_size,
                checksum,
                urg
            ) = struct.unpack("!HHIIBBHHH", header)

            self.source: int = src_prt
            self.destination: int = dst_prt
            self.seq: int = seq
            self.ack: int = ack
            self.data_offset: int = data_offset >> 4
            self.flags: int = flags + ((data_offset & 0x01) << 8)
            self.window_size: int = window_size
            self.checksum: int = checksum
            self.urg: int = urg

    def __repr__(self) -> str:
        return "\n\t".join((
            "TCP header:",
            f"Source port: [{self.source}]",
            f"Destination port: [{self.destination}]",
            f"Sequence number: [{self.seq}]",
            f"Acknowledgement number: [{self.ack}]",
            f"Data offset: [{self.data_offset}]",
            f"Flags: [{self.flags:08b}]",
            f"Window size: [{self.window_size}]",
            f"Checksum: [{self.checksum:04x}]",
            f"Urgent: [{self.urg}]"
        ))


class udp:
    def __init__(self, header: bytes):
        # parse udp header
        (
            src_port,
            dest_port,
            length,
            checksum
        ) = struct.unpack("!HHHH", header)

        self.src: int = src_port
        self.dest: int = dest_port
        self.length: int = length
        self.checksum: int = checksum

    def __repr__(self) -> str:
        return "\n\t".join((
            "UDP header:",
            f"Source port: {self.src}",
            f"Destination port: {self.dest}",
```

```
252         f"Length: {self.length}",
253         f"Checksum: {self.checksum:04x}"
254     ))
```

Listing 23: *A Python module I wrote to contain lots of useful functions which I found I was declaring in multiple places and makign changes so I decided to keep an up to date central one.*

```
1   import array
2   import socket
3   import struct
4   import select
5   import time
6
7   from contextlib import closing
8   from functools import singledispatch
9   from itertools import islice, cycle
10  from sys import stderr
11  from typing import Set, Union
12
13
14  def eprint(*args: str, **kwargs: str) -> None:
15      """
16      Mirrors print exactly but prints to stderr
17      instead of stdout.
18      """
19      print(*args, file=stderr, **kwargs) # type: ignore
20
21
22  def long_to_dot(long: int) -> str:
23      """
24      Take in an IP address in packed 32 bit int form
25      and return that address in dot notation.
26      i.e. long_to_dot(0x7F000001) = 127.0.0.1
27      """
28      # these are long form values for 0.0.0.0
29      # and 255.255.255.255
30      if not 0 <= long <= 0xFFFFFFFF:
31          raise ValueError(f"Invalid long form IP address: [{long:08x}]")
32      else:
33          # shift the long form IP along 0, 8, 16, 24 bits
34          # take only the first 8 bits of the newly shifted number
35          # cast them to a string and join them with '.'s
36          return ".".join(
37              str(
38                  (long >> (8*(3-i))) & 0xFF
39              )
40              for i in range(4)
41          )
42
```

109

```python
43
44   def dot_to_long(ip: str) -> int:
45       """
46       Take an ip address in dot notation and return the packed 32 bit int
             version
47       i.e. dot_to_long("127.0.0.1") = 0x7F000001
48       """
49
50       # dot form ips: a.b.c.d must have each
51       # part (a,b,c,d) between 0 and 255,
52       # otherwise they are invalid
53
54       parts = [int(i) for i in ip.split(".")]
55
56       if not all(
57               0 <= i <= 255
58               for i in parts
59       ):
60           raise ValueError(f"Invalid dot form IP address: [{ip}]")
61
62       if len(parts) != 4:
63           raise ValueError(f"Invalid dot form IP address: [{ip}]")
64
65       else:
66           # for each part of the dotted IP address
67           # bit shift left each part by eight times
68           # three minus it's position. This puts the bits
69           # from each part in the right place in the final sum
70           # a.b.c.d -> a<<3*8 + b<<2*8 + c<<1*8 + d<<0*8
71           return sum(
72               part << ((3-i)*8)
73               for i, part in enumerate(parts)
74           )
75
76
77   @singledispatch
78   def is_valid_ip(ip: Union[str, int]) -> bool:
79       """
80       checks whether a given IP address is valid.
81       """
82
83
84   @is_valid_ip.register
85   def _(ip: int):
86       # this is the int overload variant of
87       # the is_valid_ip function.
88       try:
89           # try to turn the long form ip address
90           # to a dot form one, if it fails,
91           # then return False, else return True
```

```
 92            long_to_dot(ip)
 93            return True
 94        except ValueError:
 95            return False
 96
 97
 98    # the type ignore comment is required to stop
 99    # mypy exploding over the fact I have defined '_' twice.
100    @is_valid_ip.register  # type: ignore
101    def _(ip: str):
102        # this is the string overload variant
103        # of the is_valid_ip function.
104        try:
105            # try to turn the dot form ip address
106            # to a long form one, if it fails,
107            # then return False, else return True
108            dot_to_long(ip)
109            return True
110        except ValueError:
111            return False
112
113
114    def is_valid_port_number(port_num: int) -> bool:
115        """
116        Checks whether the given port number is valid i.e. between 0 and
                65536.
117        """
118        # port numbers must be between 0 and 65535(2^16 - 1)
119        if 0 <= port_num < 2**16:
120            return True
121        else:
122            return False
123
124
125    def ip_range(ip: str, network_bits: int) -> Set[str]:
126        """
127        Takes a Classless Inter Domain Routing(CIDR) address subnet
128        specification and returns the list of addresses specified
129        by the IP/network bits format.
130        If the number of network bits is not between 0 and 32 it raises an
                error.
131        If the IP address is invalid according to is_valid_ip it raises an
                error.
132        """
133
134        if not 0 <= network_bits <= 32:
135            raise ValueError(f"Invalid number of network bits:
                [{network_bits}]")
136
137        if not is_valid_ip(ip):
```

```
138            raise ValueError(f"Invalid IP address: [{ip}]")
139        # get the ip as long form which is useful
140        # later on for using bitwise operators
141        # to isolate only the constant(network) bits
142        ip_long = dot_to_long(ip)
143
144        # generate the bit mask which specifies
145        # which bits to keep and which to discard
146        mask = int(
147            f"{'1'*network_bits:0<32s}",
148            base=2
149        )
150        lower_bound = ip_long & mask
151        upper_bound = ip_long | (mask ^ 0xFFFFFFFF)
152
153        # turn all the long form IP addresses between
154        # the lower and upper bound into dot form
155        if network_bits <= 30:
156            return set(
157                long_to_dot(long_ip)
158                for long_ip in
159                range(lower_bound+1, upper_bound)
160            )
161        else:
162            return set(
163                long_to_dot(long_ip)
164                for long_ip in
165                range(lower_bound, upper_bound+1)
166            )
167
168
169
170 def get_local_ip() -> str:
171     """
172     Connects to the google.com with UDP and gets
173     the IP address used to connect(the local address).
174     """
175     with closing(
176            socket.socket(
177                socket.AF_INET,
178                socket.SOCK_DGRAM
179            )
180     ) as s:
181        try:
182            s.connect(("google.com", 80))
183            ip, _ = s.getsockname()
184        except:
185            ip = "127.0.0.1"
186     return ip
187
```

```python
188
189  def get_free_port() -> int:
190      """
191      Attempts to bind to port 0 which assigns a free port number to the
              socket,
192      the socket is then closed and the port number assigned is returned.
193      """
194
195      with closing(
196              socket.socket(
197                  socket.AF_INET,
198                  socket.SOCK_STREAM
199              )
200      ) as s:
201          s.bind(('', 0))
202          _, port = s.getsockname()
203      return port
204
205
206  def ip_checksum(packet: bytes) -> int:
207      """
208      ip_checksum function takes in a packet
209      and returns the checksum.
210      """
211      if len(packet) % 2 == 1:
212          # if the length of the packet is odd, add a NULL byte
213          # to the end as padding
214          packet += b"\0"
215
216      total = 0
217      for first, second in (
218              packet[i:i+2]
219              for i in range(0, len(packet), 2)
220      ):
221          total += (first << 8) + second
222
223      # calculate the number of times a
224      # carry bit was added and add it back on
225      carried = (total - (total & 0xFFFF)) >> 16
226      total &= 0xFFFF
227      total += carried
228
229      if total > 0xFFFF:
230          # adding the carries generated a carry
231          total &= 0xFFFF
232          total += 1
233
234      # invert the checksum and take the last 16 bits.
235      return (~total & 0xFFFF)
236
```

```python
237
238  def make_icmp_packet(ID: int) -> bytes:
239      """
240      Takes an argument of the process ID of the calling process.
241      Returns an ICMP ECHO REQUEST packet created with this ID
242      """
243
244      ICMP_ECHO_REQUEST = 8
245      # pack the information for the dummy header needed
246      # for the IP checksum
247      dummy_header = struct.pack(
248          "bbHHh",
249          ICMP_ECHO_REQUEST,
250          0,
251          0,
252          ID,
253          1
254      )
255      # pack the current time into a double
256      time_bytes = struct.pack("d", time.time())
257      # define the bytes to repeat in the data section of the packet
258      # this makes the packets easily identifiable in packet captures.
259      bytes_to_repeat_in_data = map(ord, " y33t ")
260      # calculate the number of bytes left for data
261      data_bytes = (192 - struct.calcsize("d"))
262      # first pack the current time into the start of the data section
263      # the pack the identifiable data into the rest
264      data = (
265          time_bytes +
266          bytes(islice(cycle(bytes_to_repeat_in_data), data_bytes))
267      )
268      # get the IP checksum for the dummy header and data
269      # and switch the bytes into the order expected by the network
270      checksum = socket.htons(ip_checksum(dummy_header + data))
271      # pack the header with the correct checksum and information
272      header = struct.pack(
273          "bbHHh",
274          ICMP_ECHO_REQUEST,
275          0,
276          checksum,
277          ID,
278          1
279      )
280      # concatonate the header bytes and the data bytes
281      return header + data
282
283
284  def make_tcp_packet(
285          src: int,
286          dst: int,
```

```python
            from_address: str,
            to_address: str,
            flags: int) -> bytes:
        """
        Takes in the source and destination port/ip address
        returns a tcp packet.
        flags:
        2 => SYN
        18 => SYN:ACK
        4 => RST
        """
        # validate that the information passed in is valid
        if flags not in {2, 18, 4}:
            raise ValueError(
                f"Flags must be one of 2:SYN, 18:SYN,ACK, 4:RST. not:
                    [{flags}]"
            )
        if not is_valid_ip(from_address):
            raise ValueError(
                f"Invalid source IP address: [{from_address}]"
            )
        if not is_valid_ip(to_address):
            raise ValueError(
                f"Invalid destination IP address: [{to_address}]"
            )
        if not is_valid_port_number(src):
            raise ValueError(
                f"Invalid source port: [{src}]"
            )
        if not is_valid_port_number(dst):
            raise ValueError(
                f"Invalid destination port: [{dst}]"
            )
        # turn the ip addresses into long form
        src_addr = dot_to_long(from_address)
        dst_addr = dot_to_long(to_address)

        seq = ack = urg = 0
        data_offset = 6 << 4
        window_size = 1024
        max_segment_size = (2, 4, 1460)
        # pack the dummy header needed for the checksum calculation
        dummy_header = struct.pack(
            "!HHIIBBHHHBBH",
            src,
            dst,
            seq,
            ack,
            data_offset,
            flags,
```

```
336            window_size,
337            0,
338            urg,
339            *max_segment_size
340        )
341        # pack the psuedo header that is also needed for the checksum
342        # just because TCP and why not
343        psuedo_header = struct.pack(
344            "!IIBBH",
345            src_addr,
346            dst_addr,
347            0,
348            6,
349            len(dummy_header)
350        )
351
352        checksum = ip_checksum(psuedo_header + dummy_header)
353        # pack the final TCP packet with the relevant data and checksum
354        return struct.pack(
355            "!HHIIBBHHHBBH",
356            src,
357            dst,
358            seq,
359            ack,
360            data_offset,
361            flags,
362            window_size,
363            checksum,
364            urg,
365            *max_segment_size
366        )
367
368
369 def make_udp_packet(
370        src: int,
371        dst: int
372 ) -> bytes:
373     """
374     Takes in: source IP address and port, destination IP address and
                port.
375     Returns: a UDP packet with those properties.
376     the IP addresses are needed for calculating the checksum.
377     """
378     # validate data passed in
379     if not is_valid_port_number(src):
380         raise ValueError(
381             f"Invalid source port: [{src}]"
382         )
383     if not is_valid_port_number(dst):
384         raise ValueError(
```

```
385            f"Invalid destination port: [{dst}]"
386        )
387    data = b"Most services don't respond to an empty data field"
388    # pack the data
389    # and return the packed bytes
390    # UDP checksum is optional over IPv4
391    return struct.pack(
392        "!HHHH",
393        src,
394        dst,
395        8+len(data),
396        0
397    ) + data
398
399
400 def wait_for_socket(sock: socket.socket, wait_time: float) -> float:
401     """
402     Wait for wait_time seconds or until the socket is readable.
403     If the socket is readable return a tuple of the socket and the time
            taken
404     otherwise return None.
405     """
406
407     start = time.time()
408     is_socket_readable = select.select([sock], [], [], wait_time)
409     taken = time.time() - start
410     if is_socket_readable[0] == []:
411         return float(-1)
412     else:
413         return taken
```

Listing 24: *A Python module I made to hold all of the listeners I had made for each of the different scanning types.*

```
1  from modules import headers
2  from modules import ip_utils
3  import socket
4  import struct
5  import time
6  from collections import defaultdict
7  from contextlib import closing
8  from typing import Tuple, Set, DefaultDict
9
10
11 PORTS = DefaultDict[str, Set[int]]
12
13
14 def ping(
15         ID: int,
16         timeout: float
```

```python
17  ) -> Set[Tuple[str, float, headers.ip]]:
18      """
19      Takes in a process id and a timeout and returns
20      a list of addresses which sent ICMP ECHO REPLY
21      packets with the packed id matching ID in the time given by timeout.
22      """
23      ping_sock = socket.socket(
24          socket.AF_INET,
25          socket.SOCK_RAW,
26          socket.IPPROTO_ICMP)
27      # opens a raw socket for sending ICMP protocol packets
28      time_remaining = timeout
29      addresses = set()
30      recieved_from = set()
31      while True:
32          time_waiting = ip_utils.wait_for_socket(ping_sock,
33              time_remaining)
33          # time_waiting stores the time the socket took to become readable
34      # or returns minus one if it ran out of time
35
36          if time_waiting == -1:
37              break
38          time_recieved = time.time()
39          # store the time the packet was recieved
40          recPacket, addr = ping_sock.recvfrom(1024)
41          # recieve the packet
42          ip = headers.ip(recPacket[:20])
43          # unpack the IP header into its respective components
44          icmp = headers.icmp(recPacket[20:28])
45          # unpack the time from the packet.
46          time_sent = struct.unpack(
47              "d",
48              recPacket[28:28 + struct.calcsize("d")]
49          )[0]
50          # unpack the value for when the packet was sent
51          time_taken: float = time_recieved - time_sent
52          # calculate the round trip time taken for the packet
53          if icmp.id == ID:
54              # if the ping was sent from this machine then add it to the
                   list of
55              # responses
56              ip_address, port = addr
57              # this is to prevent a bug where IPs were being added twice
58              if ip_address not in recieved_from:
59                  addresses.add((ip_address, time_taken, ip))
60                  recieved_from.add(ip_address)
61          elif time_remaining <= 0:
62              break
63          else:
64              continue
```

```python
65        # return a list of all the addesses that replied to our ICMP echo
              request.
66        return addresses
67
68
69    def udp(dest_ip: str, timeout: float) -> Set[int]:
70        """
71        This listener detects UDP packets from dest_ip in the given timespan,
72        all ports that send direct replies are marked as being open.
73        Returns a list of open ports.
74        """
75
76        time_remaining = timeout
77        ports: Set[int] = set()
78        with socket.socket(
79                socket.AF_INET,
80                socket.SOCK_RAW,
81                socket.IPPROTO_UDP
82        ) as s:
83            while True:
84                time_taken = ip_utils.wait_for_socket(s, time_remaining)
85                if time_taken == -1:
86                    break
87                else:
88                    time_remaining -= time_taken
89                packet = s.recv(1024)
90                ip = headers.ip(packet[:20])
91                udp = headers.udp(packet[20:28])
92                if dest_ip == ip.source and ip.protocol == 17:
93                    ports.add(udp.src)
94
95        return ports
96
97
98    def icmp_unreachable(src_ip: str, timeout: float = 2) -> int:
99        """
100        This listener detects ICMP destination unreachable
101        packets and returns the icmp code.
102        This is later used to mark them as either close, open|filtered,
              filtered.
103        3 -> closed
104        0|1|2|9|10|13 -> filtered
105        -1 -> error with arguments
106        open|filtered means that they are either open or
107        filtered but return nothing.
108        """
109
110        ping_sock = socket.socket(
111            socket.AF_INET,
112            socket.SOCK_RAW,
```

```
113            socket.IPPROTO_ICMP
114        )
115        # open raw socket to listen for ICMP destination unrechable packets
116        time_remaining = timeout
117        code = -1
118        while True:
119            time_waiting = ip_utils.wait_for_socket(ping_sock,
                   time_remaining)
120            # wait for socket to be readable
121            if time_waiting == -1:
122                break
123            else:
124                time_remaining -= time_waiting
125            recPacket, addr = ping_sock.recvfrom(1024)
126            # recieve the packet
127            ip = headers.ip(recPacket[:20])
128            icmp = headers.icmp(recPacket[20:28])
129            valid_codes = [0, 1, 2, 3, 9, 10, 13]
130            if (
131                    ip.source == src_ip
132                    and icmp.type == 3
133                    and icmp.code in valid_codes
134            ):
135                code = icmp.code
136                break
137            elif time_remaining <= 0:
138                break
139            else:
140                continue
141        ping_sock.close()
142        return code


144
145 def tcp(address: Tuple[str, int], timeout: float) -> PORTS:
146        """
147        This function is run asynchronously and listens for
148        TCP ACK responses to the sent TCP SYN msg.
149        """
150        ports: DefaultDict[str, Set[int]] = defaultdict(set)
151        with closing(
152                socket.socket(
153                    socket.AF_INET,
154                    socket.SOCK_RAW,
155                    socket.IPPROTO_TCP
156                )) as s:
157            s.bind(address)
158            # bind the raw socket to the listening address
159            time_remaining = timeout
160            while True:
161                time_taken = ip_utils.wait_for_socket(s, time_remaining)
```

```
162                 # wait for the socket to become readable
163                 if time_taken == -1:
164                     break
165                 else:
166                     time_remaining -= time_taken
167                 packet = s.recv(1024)
168                 # recieve the packet data
169                 tcp = headers.tcp(packet[20:40])
170                 if tcp.flags & 2: # syn flags set
171                     ports["OPEN"].add(tcp.source)
172                 elif tcp.flags & 4:
173                     ports["CLOSED"].add(tcp.source)
174                 else:
175                     continue
176         return ports
```

Listing 25: *A Python module I made to hold all of the scanners I had made for each of the different scanning types.*

```
1   import socket
2   import time
3   from modules import directives
4   from modules import headers
5   from modules import ip_utils
6   from modules import listeners
7   from collections import defaultdict
8   from contextlib import closing
9   from itertools import repeat
10  from multiprocessing import Pool
11  from os import getpid
12  from typing import Set, Tuple
13
14
15  def ping(addresses: Set[str]) -> Set[Tuple[str, float, headers.ip]]:
16      """
17      Send an ICMP ECHO REQUEST to each address
18      in the set addresses. Then return a set which
19      contains all the addresses which replied and
20      which have the correct ID.
21      """
22      with closing(
23              socket.socket(
24                  socket.AF_INET,
25                  socket.SOCK_RAW,
26                  socket.IPPROTO_ICMP
27              )
28      ) as ping_sock:
29          # get the local ip address
30          addresses = {
31              ip
```

```
32          for ip in addresses
33          if (
34              not ip.endswith(".0")
35              and not ip.endswith(".255")
36          )
37      }
38
39      # initialise a process pool
40      p = Pool(1)
41      # get the local process id for use in creating packets.
42      ID = getpid() & 0xFFFF
43      # run the listeners.ping function asynchronously
44      replied = p.apply_async(listeners.ping, (ID, 5))
45      time.sleep(0.01)
46      for address in zip(addresses, repeat(1)):
47          try:
48              packet = ip_utils.make_icmp_packet(ID)
49              ping_sock.sendto(packet, address)
50          except PermissionError:
51              ip_utils.eprint("raw sockets require root priveleges,
                  exiting")
52              exit()
53      p.close()
54      p.join()
55      # close and join the process pool to so that all the values
56      # have been returned and the pool closed
57      return replied.get()
58
59
60  def connect(address: str, ports: Set[int]) -> Set[int]:
61      """
62      This is the most basic kind of scan
63      it simply connects to every specifed port
64      and identifies whether they are open.
65      """
66      import socket
67      from contextlib import closing
68      open_ports: Set[int] = set()
69      for port in ports:
70          # loop through each port in the list of ports to scan
71          try:
72              with closing(
73                  socket.socket(
74                      socket.AF_INET,
75                      socket.SOCK_STREAM
76                  )
77              ) as s:
78                  # open an IPV4 TCP socket
79                  s.connect((address, port))
80                  # attempt to connect the newly created socket to the
```

```python
                        target
                    # address and port
                    open_ports.add(port)
                    # if the connection was successful then add the port to
                        the
                    # list of open ports
            except (ConnectionRefusedError, OSError) as e:
                pass
        return open_ports


def tcp(dest_ip: str, portlist: Set[int]) -> listeners.PORTS:
    src_port = ip_utils.get_free_port()
    # request a local port to connect from
    if "127.0.0.1" == dest_ip:
        local_ip = "127.0.0.1"
    else:
        local_ip = ip_utils.get_local_ip()
    p = Pool(1)
    listener = p.apply_async(listeners.tcp, ((local_ip, src_port), 5))
    time.sleep(0.01)
    # start the TCP ACK listener in the background
    for port in portlist:
        # flag = 2 for syn scan
        packet = ip_utils.make_tcp_packet(
            src_port,
            port,
            local_ip,
            dest_ip,
            2
        )
        with closing(
                socket.socket(
                    socket.AF_INET,
                    socket.SOCK_RAW,
                    socket.IPPROTO_TCP
                )
        ) as s:
            s.sendto(packet, (dest_ip, port))
            # send the packet to its destination
    p.close()
    p.join()
    ports = listener.get()
    ports["FILTERED"] = portlist - ports["OPEN"] - ports["CLOSED"]
    if local_ip == "127.0.0.1":
        ports["OPEN"] -= set([src_port])

    return ports
```

```python
129  def udp(
130          dest_ip: str,
131          ports_to_scan: Set[int]
132  ) -> listeners.PORTS:
133      """
134      Takes in a destination IP address in either dot or long form and
135      a list of ports to scan. Sends UDP packets to each port specified
136      in portlist and uses the listeners to mark them as open,
               open|filtered,
137      filtered, closed they are marked open|filtered if no response is
138      recieved at all.
139      """
140
141      local_port = ip_utils.get_free_port()
142      # get port number
143      ports: listeners.PORTS = defaultdict(set)
144      ports["REMAINING"] = ports_to_scan
145      p = Pool(1)
146      udp_listen = p.apply_async(listeners.udp, (dest_ip, 4))
147      time.sleep(0.01)
148      # start the UDP listener
149      with closing(
150              socket.socket(
151                  socket.AF_INET,
152                  socket.SOCK_RAW,
153                  socket.IPPROTO_UDP
154              )
155      ) as s:
156          for _ in range(2):
157              # repeat 3 times because UDP scanning comes
158              # with a high chance of packet loss
159              for dest_port in ports["REMAINING"]:
160                  try:
161                      packet = ip_utils.make_udp_packet(
162                          local_port,
163                          dest_port
164                      )
165                      # create the UDP packet to send
166                      s.sendto(packet, (dest_ip, dest_port))
167                      # send the packet to the currently scanning address
168                  except socket.error:
169                      packet_bytes = " ".join(map(hex, packet))
170                      print(
171                          "The socket modules sendto method with the
                                  following",
172                          "argument resulting in a socket error.",
173                          f"\npacket: [{packet_bytes}]\n",
174                          "address: [{dest_ip, dest_port}])"
175                      )
176
```

124

```
177        p.close()
178        p.join()
179
180        ports["OPEN"].update(udp_listen.get())
181        # if we are on localhost remove the scanning port
182        if dest_ip == "127.0.0.1":
183            ports["OPEN"] -= set([local_port])
184        ports["REMAINING"] -= ports["OPEN"]
185        # only scan the ports which we know are not open
186        with closing(
187                socket.socket(
188                    socket.AF_INET,
189                    socket.SOCK_RAW,
190                    socket.IPPROTO_UDP
191                )
192        ) as s:
193            for dest_port in ports["REMAINING"]:
194                try:
195                    packet = ip_utils.make_udp_packet(
196                        local_port,
197                        dest_port
198                    )
199                    # make a new UDP packet
200                    p = Pool(1)
201                    icmp_listen = p.apply_async(
202                        listeners.icmp_unreachable,
203                        (dest_ip,),
204                    )
205                    # start the ICMP listener
206                    time.sleep(0.01)
207                    s.sendto(packet, (dest_ip, dest_port))
208                    # send packet
209                    p.close()
210                    p.join()
211                    icmp_code = icmp_listen.get()
212                    # receive ICMP code from the ICMP listener
213                    if icmp_code in {0, 1, 2, 9, 10, 13}:
214                        ports["FILTERED"].add(dest_port)
215                    elif icmp_code == 3:
216                        ports["CLOSED"].add(dest_port)
217                except socket.error:
218                    packet_bytes = " ".join(map("{:02x}".format, packet))
219                    ip_utils.eprint(
220                        "The socket modules sendto method with the following",
221                        "argument resulting in a socket error.",
222                        f"\npacket: [{packet_bytes}]\n",
223                        "address: [{dest_ip, dest_port}])"
224                    )
225        # this creates a new set which contains all the elements that
226        # are in the list of ports to be scanned but have not yet
```

```
227        # been classified
228        ports["OPEN|FILTERED"] = (
229            ports["REMAINING"]
230            - ports["OPEN"]
231            - ports["FILTERED"]
232            - ports["CLOSED"]
233        )
234        del(ports["REMAINING"])
235        # set comprehension to update the list of open filtered ports
236        return ports
237
238
239    def version_detect_scan(
240            target: directives.Target,
241            probes: directives.PROBE_CONTAINER
242    ) -> directives.Target:
243        for probe_dict in probes.values():
244            for proto in probe_dict:
245                target = probe_dict[proto].scan(target)
246        return target
```

A.8   examples

Listing 26: *A program I wrote to run all of the example scripts I made from one main script to solve the issue of the PATH being used for determining import when I could use Pythons built in module structure instead.*

```python
1   #!/usr/bin/env python
2   from icmp_ping import icmp_echo_recv, icmp_echo_send
3   from ping_scanner import ping_scan
4   from tcp_scan.connect_scan import scan_port_list as connect_scan_list
5   from tcp_scan.syn_scan import scan_port_list as syn_scan_list
6   from udp_scan import scan_port_list as udp_scan_list
7   from version_detection import version_detection
8
9   examples = {
10      "icmp_echo_recv": icmp_echo_recv.main,
11      "icmp_echo_send": icmp_echo_send.main,
12      "ping_scanner": ping_scan.main,
13      "connect_scan": connect_scan_list.main,
14      "syn_scan": syn_scan_list.main,
15      "udp_scan": udp_scan_list.main,
16      "version_detection": version_detection.main,
17  }
18
19  print("\n\t".join(("Programs:", *examples)))
20
21  while True:
```

```
22      print()
23      program = input("Enter the name of the example program to run: ")
24      if program.lower() in {"quit", "q", "end", "exit"}:
25          break
26      found = False
27      for name in examples:
28          if name.startswith(program.lower()):
29              program = name
30              print(f"Running: {program}")
31              examples[program]()
32              found = True
33      if not found:
34          print(
35              "The program name must exactly match one of the following
                  examples"
36          )
37          print("\n".join(examples))
```

A.9   netscan

Listing 27: *The program which provides the command line user interface for my projects functionality.*

```
1   #!/usr/bin/env python
2   import re
3   from argparse import ArgumentParser
4   from collections import defaultdict
5   from math import floor, log10
6   from modules import (
7       scanners,
8       ip_utils,
9       directives,
10  )
11  from typing import (
12      DefaultDict,
13      Dict,
14  )
15
16  top_ports = directives.parse_ports(open("top_ports").read())
17  services: DefaultDict[str, Dict[int, str]] = defaultdict(dict)
18  for match in re.finditer(
19          r"(\S+)\s+(\d+)/(\S+)",
20          open("version_detection/nmap-services").read()
21  ):
22      service, portnum, protocol = match.groups()
23      services[protocol.upper()][int(portnum)] = service
24
25  parser = ArgumentParser()
```

127

```python
26  parser.add_argument(
27      "target_spec",
28      help="specify what to scan, i.e. 192.168.1.0/24"
29  )
30  parser.add_argument(
31      "-Pn",
32      help="assume hosts are up",
33      action="store_true"
34  )
35  parser.add_argument(
36      "-sL",
37      help="list targets",
38      action="store_true"
39  )
40  parser.add_argument(
41      "-sn",
42      help="disable port scanning",
43      action="store_true"
44  )
45  parser.add_argument(
46      "-sS",
47      help="TCP SYN scan",
48      action="store_true"
49  )
50  parser.add_argument(
51      "-sT",
52      help="TCP connect scan",
53      action="store_true"
54  )
55  parser.add_argument(
56      "-sU",
57      help="UDP scan",
58      action="store_true"
59  )
60  parser.add_argument(
61      "-sV",
62      help="version scan",
63      action="store_true"
64  )
65  parser.add_argument(
66      "-p",
67      "--ports",
68      help="scan specified ports",
69      required=False,
70      default=top_ports
71  )
72  parser.add_argument(
73      "--exclude_ports",
74      help="ports to exclude from the scan",
75      required=False,
```

```python
76          default=""
77      )
78
79      args = parser.parse_args()
80
81      # check whether the address spec is in CIDR form
82      CIDR_regex =
            re.compile(r"(\d{1,3}\.\d{1,3}\.\d{1,3}\.\d{1,3})/(\d{1,2})")
83      search = CIDR_regex.search(args.target_spec)
84      if search:
85          base_addr, network_bits = search.groups()
86          addresses = ip_utils.ip_range(
87              base_addr,
88              int(network_bits)
89          )
90      else:
91          base_addr = args.target_spec
92          if not ip_utils.is_valid_ip(base_addr):
93              raise ValueError(f"invalid dot form IP address: [{base_addr}]")
94          addresses = {base_addr}
95
96
97      def error_exit(error_type: str, scan_type: str, scanning: str) -> bool:
98          messages = {
99              "permission": "\n".join((
100                 "You have insufficient permissions to run this type of scan",
101                 "EXITING!"
102             ))
103         }
104         print(f"You tried to scan {scanning} using scan type: {scan_type}")
105         try:
106             print(messages[error_type])
107         except KeyError:
108             print(f"ERROR MESSAGE NOT FOUND: {error_type}")
109         exit(-1)
110
111
112     if args.sL:
113         print("Targets:")
114         print("\n".join(sorted(addresses, key=ip_utils.dot_to_long)))
115     else:
116         if args.sn:
117             def sig_figs(x: float, n: int) -> float:
118                 """
119                 rounds x to n significant figures.
120                 sig_figs(1234, 2) = 1200.0
121                 """
122                 return round(x, n - (1 + int(floor(log10(abs(x))))))
123
124             try:
```

```python
            print("\n".join(
                f"host: [{host}]\t" +
                "responded to an ICMP ECHO REQUEST in " +
                f"{str(sig_figs(taken, 2))+'s':<10s} " +
                f"ttl: [{ip_head.time_to_live}]"
                for host, taken, ip_head in scanners.ping(addresses)
            ))
        except PermissionError:
            error_exit("permission", "ping scan", str(addresses))

    else:
        if args.Pn:
            targets = [
                directives.Target(
                    addr,
                    defaultdict(set),
                    defaultdict(set)
                )
                for addr in addresses
            ]
        else:
            try:
                targets = [
                    directives.Target(
                        addr,
                        defaultdict(set),
                        defaultdict(set),
                    )
                    for addr, _, _ in scanners.ping(addresses)
                ]
            except PermissionError:
                error_exit("permission", "ping_scan", str(addresses))
        # define the ports to scan
        if args.ports == "-":
            # case they have specified all ports
            ports = {
                "UDP": set(range(1, 65536)),
                "TCP": set(range(1, 65536)),
            }
        elif isinstance(args.ports, str):
            # case they have specifed ports
            ports = directives.parse_ports(args.ports)
        else:
            # default
            ports = args.ports

        # exclude all the ports speified to be excluded
        to_exclude = directives.parse_ports(args.exclude_ports)
        ports["TCP"] -= to_exclude["TCP"]
        ports["TCP"] -= to_exclude["ANY"]
```

```
175            ports["UDP"] -= to_exclude["UDP"]
176            ports["UDP"] -= to_exclude["ANY"]
177
178            # if version scanning is desired
179            if args.sV:
180                probes = directives.parse_probes(
181                    "./version_detection/nmap-service-probes"
182                )
183
184            for target in targets:
185                if not args.sU and not args.sT or args.sS:
186                    try:
187                        tcp_ports = scanners.tcp(
188                            target.address,
189                            ports["TCP"] | ports["ANY"]
190                        )
191                    except PermissionError:
192                        error_exit("permission", "tcp_scan", target.address)
193                    target.open_ports["TCP"].update(tcp_ports["OPEN"])
194                    target.open_filtered_ports["TCP"].update(
195                        tcp_ports["FILTERED"]
196                    )
197                if args.sT:
198                    target.open_ports["TCP"].update(
199                        scanners.connect(
200                            target.address,
201                            ports["TCP"] | ports["ANY"]
202                        )
203                    )
204                if args.sU:
205                    try:
206                        udp_ports = scanners.udp(
207                            target.address,
208                            ports["UDP"] | ports["ANY"]
209                        )
210                    except PermissionError:
211                        error_exit("permission", "udp_scan", target.address)
212
213                    target.open_ports["UDP"].update(
214                        udp_ports["OPEN"]
215                    )
216                    target.open_filtered_ports["UDP"].update(
217                        udp_ports["FILTERED"]
218                    )
219                    target.open_filtered_ports["UDP"].update(
220                        udp_ports["OPEN|FILTERED"]
221                    )
222                if args.sV:
223                    target = scanners.version_detect_scan(target, probes)
224                # display scan info
```

```
225                    print()
226                    print(f"Scan report for: {target.address}")
227                    # print(target)
228                    print("Open ports:")
229                    for proto, open_ports in target.open_ports.items():
230                        for port in open_ports:
231                            try:
232                                service_name = services[proto][port]
233                            except KeyError:
234                                service_name = "unknown"
235                            if port in target.services:
236                                exact_match = target.services[port]
237                                print(
238                                    f"{port}/{proto}{exact_match.service:>8s}"
239                                )
240                                # print version information
241                                for key, val in exact_match.version_info.items():
242                                    print(f"{key}: {val}")
243                                if exact_match.cpes:
244                                    print()
245                                    print("CPE:")
246                                    for cpe_type, cpe_vals in \
                                             exact_match.cpes.items():
247                                        print(cpe_type)
248                                        try:
249                                            del(cpe_vals["part"])
250                                        except KeyError:
251                                            pass
252                                        for key, val in cpe_vals.items():
253                                            print(f"{key}: {val}")
254                                print()
255                            else:
256                                print(f"{port} service: {service_name}?")
257
258                print("Filtered ports:")
259                for proto, filtered_ports in \
                         target.open_filtered_ports.items():
260                    for port in filtered_ports:
261                        try:
262                            service_name = services[proto][port]
263                        except KeyError:
264                            service_name = "unknown"
265                        print(f"{port} service: {service_name}?")
```

A.10 tests

Listing 28: *Unit tests I wrote for the ip_utils module.*

```python
1   from modules.ip_utils import (
2       dot_to_long,
3       long_to_dot,
4       ip_range,
5       is_valid_ip,
6       is_valid_port_number,
7       ip_checksum,
8       make_tcp_packet,
9       make_udp_packet,
10      make_icmp_packet,
11  )
12  from binascii import unhexlify
13
14
15  def test_dot_to_long_private_ip() -> None:
16      assert(dot_to_long("192.168.1.0") == 0xC0A80100)
17
18
19  def test_long_to_dot_private_ip() -> None:
20      assert(long_to_dot(0xC0A80100) == "192.168.1.0")
21
22
23  def test_dot_to_long_localhost() -> None:
24      assert(dot_to_long("127.0.0.1") == 0x7F000001)
25
26
27  def test_long_to_dot_localhost() -> None:
28      assert(long_to_dot(0x7F000001) == "127.0.0.1")
29
30
31  def test_is_valid_ip_localhost_long() -> None:
32      assert is_valid_ip(0x7F000001)
33
34
35  def test_is_valid_ip_localhost() -> None:
36      assert is_valid_ip("127.0.0.1")
37
38
39  def test_is_not_valid_ip_5_zeros_dotted() -> None:
40      assert not is_valid_ip("0.0.0.0.0")
41
42
43  def test_is_not_valid_ip_5_255s_long() -> None:
44      assert not is_valid_ip(0xFF_FF_FF_FF_FF)
45
46
47  def test_is_valid_port_number_0() -> None:
48      assert is_valid_port_number(0)
49
50
```

```python
51  def test_is_valid_port_number_65535() -> None:
52      assert is_valid_port_number(65535)
53
54
55  def test_is_not_valid_port_number_negative_one() -> None:
56      assert not is_valid_port_number(-1)
57
58
59  def test_is_not_valid_port_number_65536() -> None:
60      assert not is_valid_port_number(65536)
61
62
63  def test_ip_range() -> None:
64      assert(
65          ip_range("192.168.1.0", 28) == {
66              "192.168.1.1",
67              "192.168.1.2",
68              "192.168.1.3",
69              "192.168.1.4",
70              "192.168.1.5",
71              "192.168.1.6",
72              "192.168.1.7",
73              "192.168.1.8",
74              "192.168.1.9",
75              "192.168.1.10",
76              "192.168.1.11",
77              "192.168.1.12",
78              "192.168.1.13",
79              "192.168.1.14",
80          }
81      )
82
83
84  def test_ip_checksum_verify() -> None:
85      packet = unhexlify(
86          "45000073000040004011b861c0a80001c0a800c7"
87      )
88      assert ip_checksum(packet) == 0
89
90
91  def test_ip_checksum_generate() -> None:
92      packet = unhexlify(
93          "45000073000040004011b861c0a80001c0a800c7"
94      )
95      assert ip_checksum(packet) == 0xB861
96
97
98  def test_make_tcp_packet() -> None:
99      correct = unhexlify(
100         "e5470050000000000000000600204002af50000020405b4"
```

```
101        )
102        info = 58695, 80, "192.168.1.45", "192.168.1.28", 2
103        assert correct == make_tcp_packet(*info)
104
105
106    def test_make_udp_packet() -> None:
107        correct = unhexlify(
108            "e5470050003a0000"
109        )
110        info = 58695, 80
111        # clipping the packet at 8 simply removes the data section
112        assert correct == make_udp_packet(*info)[:8]
```

Listing 29: *Unit tests I wrote for the directives module.*

```
1     from modules.directives import (
2         parse_ports
3     )
4     from collections import defaultdict
5     from typing import DefaultDict
6
7
8     def test_parse_probes_single() -> None:
9         portstring = "12345"
10        expected: DefaultDict[str, set] = defaultdict(set)
11        expected["ANY"] = set([12345])
12        assert expected == parse_ports(portstring)
13
14
15    def test_parse_probes_range() -> None:
16        portstring = "10-20"
17        expected: DefaultDict[str, set] = defaultdict(set)
18        expected["ANY"] = set(range(10, 21))
19        assert expected == parse_ports(portstring)
20
21
22    def test_parse_probes_single_and_range() -> None:
23        portstring = "1,2,3,10-20,6,7,8"
24        expected: DefaultDict[str, set] = defaultdict(set)
25        expected["ANY"] = set([1, 2, 3, *range(10, 21), 6, 7, 8])
26        assert expected == parse_ports(portstring)
27
28
29    def test_parse_probes_tcp_single() -> None:
30        portstring = "T:12345"
31        expected: DefaultDict[str, set] = defaultdict(set)
32        expected["TCP"] = set([12345])
33        assert expected == parse_ports(portstring)
34
35
```

```python
36  def test_parse_probes_tcp_range() -> None:
37      portstring = "T:10-20"
38      expected: DefaultDict[str, set] = defaultdict(set)
39      expected["TCP"] = set(range(10, 21))
40      assert expected == parse_ports(portstring)
41
42
43  def test_parse_probes_tcp_single_and_range() -> None:
44      portstring = "T:1,2,3,10-20,6,7,8"
45      expected: DefaultDict[str, set] = defaultdict(set)
46      expected["TCP"] = set([1, 2, 3, *range(10, 21), 6, 7, 8])
47      assert expected == parse_ports(portstring)
48
49
50  def test_parse_probes_udp_single() -> None:
51      portstring = "U:12345"
52      expected: DefaultDict[str, set] = defaultdict(set)
53      expected["UDP"] = set([12345])
54      assert expected == parse_ports(portstring)
55
56
57  def test_parse_probes_udp_range() -> None:
58      portstring = "U:10-20"
59      expected: DefaultDict[str, set] = defaultdict(set)
60      expected["UDP"] = set(range(10, 21))
61      assert expected == parse_ports(portstring)
62
63
64  def test_parse_probes_udp_single_and_range() -> None:
65      portstring = "U:1,2,3,10-20,6,7,8"
66      expected: DefaultDict[str, set] = defaultdict(set)
67      expected["UDP"] = set([1, 2, 3, *range(10, 21), 6, 7, 8])
68      assert expected == parse_ports(portstring)
69
70
71  def test_parse_probes_any_and_tcp_single() -> None:
72      portstring = "12345 T:12345"
73      expected: DefaultDict[str, set] = defaultdict(set)
74      expected["TCP"] = set([12345])
75      expected["ANY"] = set([12345])
76      assert expected == parse_ports(portstring)
77
78
79  def test_parse_probes_any_and_tcp_range() -> None:
80      portstring = "10-20 T:10-20"
81      expected: DefaultDict[str, set] = defaultdict(set)
82      expected["TCP"] = set(range(10, 21))
83      expected["ANY"] = set(range(10, 21))
84      assert expected == parse_ports(portstring)
85
```

```python
86
87   def test_parse_probes_any_and_tcp_single_and_range() -> None:
88       portstring = "1,2,3,10-20,6,7,8 T:1,2,3,10-20,6,7,8"
89       expected: DefaultDict[str, set] = defaultdict(set)
90       expected["TCP"] = set([1, 2, 3, *range(10, 21), 6, 7, 8])
91       expected["ANY"] = set([1, 2, 3, *range(10, 21), 6, 7, 8])
92       assert expected == parse_ports(portstring)
93
94
95   def test_parse_probes_any_and_udp_single() -> None:
96       portstring = "12345 U:12345"
97       expected: DefaultDict[str, set] = defaultdict(set)
98       expected["UDP"] = set([12345])
99       expected["ANY"] = set([12345])
100      assert expected == parse_ports(portstring)
101
102
103  def test_parse_probes_any_and_udp_range() -> None:
104      portstring = "10-20 U:10-20"
105      expected: DefaultDict[str, set] = defaultdict(set)
106      expected["UDP"] = set(range(10, 21))
107      expected["ANY"] = set(range(10, 21))
108      assert expected == parse_ports(portstring)
109
110
111  def test_parse_probes_any_and_udp_single_and_range() -> None:
112      portstring = "1,2,3,10-20,6,7,8 U:1,2,3,10-20,6,7,8"
113      expected: DefaultDict[str, set] = defaultdict(set)
114      expected["UDP"] = set([1, 2, 3, *range(10, 21), 6, 7, 8])
115      expected["ANY"] = set([1, 2, 3, *range(10, 21), 6, 7, 8])
116      assert expected == parse_ports(portstring)
117
118
119  def test_parse_probes_udp_and_tcp_single() -> None:
120      portstring = "U:12345 T:12345"
121      expected: DefaultDict[str, set] = defaultdict(set)
122      expected["TCP"] = set([12345])
123      expected["UDP"] = set([12345])
124      assert expected == parse_ports(portstring)
125
126
127  def test_parse_probes_udp_and_tcp_range() -> None:
128      portstring = "U:10-20 T:10-20"
129      expected: DefaultDict[str, set] = defaultdict(set)
130      expected["TCP"] = set(range(10, 21))
131      expected["UDP"] = set(range(10, 21))
132      assert expected == parse_ports(portstring)
133
134
135  def test_parse_probes_udp_and_tcp_single_and_range() -> None:
```

```python
136         portstring = "U:1,2,3,10-20,6,7,8 T:1,2,3,10-20,6,7,8"
137         expected: DefaultDict[str, set] = defaultdict(set)
138         expected["TCP"] = set([1, 2, 3, *range(10, 21), 6, 7, 8])
139         expected["UDP"] = set([1, 2, 3, *range(10, 21), 6, 7, 8])
140         assert expected == parse_ports(portstring)
141
142
143     def test_parse_probes_all_single() -> None:
144         portstring = "12345 U:12345 T:12345"
145         expected: DefaultDict[str, set] = defaultdict(set)
146         expected["TCP"] = set([12345])
147         expected["UDP"] = set([12345])
148         expected["ANY"] = set([12345])
149         assert expected == parse_ports(portstring)
150
151
152     def test_parse_probes_all_range() -> None:
153         portstring = "10-20 U:10-20 T:10-20"
154         expected: DefaultDict[str, set] = defaultdict(set)
155         expected["TCP"] = set(range(10, 21))
156         expected["UDP"] = set(range(10, 21))
157         expected["ANY"] = set(range(10, 21))
158         assert expected == parse_ports(portstring)
159
160
161     def test_parse_probes_all_single_and_range() -> None:
162         portstring = "1,2,3,10-20,6,7,8 U:1,2,3,10-20,6,7,8
163             T:1,2,3,10-20,6,7,8"
163         expected: DefaultDict[str, set] = defaultdict(set)
164         expected["TCP"] = set([1, 2, 3, *range(10, 21), 6, 7, 8])
165         expected["UDP"] = set([1, 2, 3, *range(10, 21), 6, 7, 8])
166         expected["ANY"] = set([1, 2, 3, *range(10, 21), 6, 7, 8])
167         assert expected == parse_ports(portstring)
```

References

[1] Wireshark Core Developers. Wireshark download page. `https://www.wireshark.org/download.html`.

[2] Information Sciences Institute University of Southern California. Transmission Control Protocol. `https://tools.ietf.org/html/rfc793`, September 1981.

[3] Python Core Developers. Socket module documentation. `https://docs.python.org/3/library/socket.html`, April 2019.

[4] Linux Developers. iptables Man Pages. `https://linux.die.net/man/8/iptables`, March 2019.

[5] Internet Engineering Task Force. Requirements for Internet Hosts – Communication Layers. `https://tools.ietf.org/html/rfc1122`, October 1989.

[6] Linux Developers. TCP Man page. `https://linux.die.net/man/7/tcp`, March 2019.

[7] Gordon "fyodor" lyon. Nmap download page. `https://nmap.org/download.html`.

[8] Linux Developers. grep Man Pages. `https://linux.die.net/man/1/grep`, March 2019.

[9] Anonymous. IPv4 header checksum. `https://en.wikipedia.org/wiki/IPv4_header_checksum`, April 2019.

[10] Anonymous. Hypertext Transfer Protocol. `https://en.wikipedia.org/wiki/Hypertext_Transfer_Protocol`, April 2019.

[11] Anonymous. Daemon (computing). `https://linux.die.net/man/8/dhcpd`, March 2019.

[12] Anonymous. Internet protocol suite. `https://en.wikipedia.org/wiki/Internet_protocol_suite`, March 2019.

[13] Anonymous. OSI model. `https://en.wikipedia.org/wiki/Osi_model`, March 2019.

[14] Anonymous. Wireshark. `https://en.wikipedia.org/wiki/Wireshark`, April 2019.

[15] Joe. send icmp echo request. `https://stackoverflow.com/questions/24575524/send-icmp-echo-request`, July 2014.

[16] brice. Python raw sockets. `https://stackoverflow.com/questions/1117958/how-do-i-use-raw-socket-in-python`, June 2011.

[17] Python Core Developers. defaultdict documentation. `https://docs.python.org/3/library/collections.html?highlight=collection#collections.defaultdict`, April 2019.

[18] Python Core Developers. builtin data structures documentation. `https://docs.python.org/3/tutorial/datastructures.html#data-structures`, April 2019.

[19] Python Core Developers. type hinting documentation. `https://docs.python.org/3/library/typing.html?highlight=typing#module-typing`, April 2019.

[20] Python Core Developers. command line argument parsing documentation. `https://docs.python.org/3/library/argparse.html?highlight=typing`, April 2019.

[21] Python Core Developers. stderr documentation. `https://docs.python.org/3/library/sys.html?highlight=stderr#sys.stderr`, April 2019.

[22] Python Core Developers. multiprocessing documentation. `https://docs.python.org/3/library/multiprocessing.html`, April 2019.

[23] Python Core Developers. struct documentation. `https://docs.python.org/3/library/struct.html`, April 2019.

[24] Python Core Developers. operator documentation. `https://docs.python.org/3/library/operator.html`, April 2019.

[25] Gordon 'Fyodor' Lyon. port scanning techniques. `https://nmap.org/book/man-port-scanning-techniques.html`, January 2001.

[26] Gordon 'Fyodor' Lyon. service and version detection techniques. `https://nmap.org/book/man-version-detection.html`, January 2001.

[27] Gordon 'Fyodor' Lyon. service and version detection techniques described. `https://nmap.org/book/vscan-technique.html`, January 2001.

[28] Gordon 'Fyodor' Lyon. service and version detection file format. `https://nmap.org/book/vscan-fileformat.html`, January 2001.

[29] Information Sciences Institute University of Southern California. Internet Protocol. `https://tools.ietf.org/html/rfc791`, September 1981.

[30] J. Postel ISI. User Datagram Protocol. `https://www.ietf.org/rfc/rfc768.txt`, August 1980.

[31] J. Postel ISI. Internet Control Message Protocol. `https://tools.ietf.org/html/rfc792`, September 1981.

[32] Bucknell University R. Droms. Dynamic Host Configuration Protocol. `https://www.ietf.org/rfc/rfc2131.txt`, March 1997.

[33] et al. Fielding. HyperText Transfer Protocol. `https://tools.ietf.org/html/rfc2616`, 1999.

[34] Berners-Lee & Connolly. HyperText Markup Language - 2.0. `https://tools.ietf.org/html/rfc2616`, November 1995.

[35] Linux Developers. IP Man page. `https://linux.die.net/man/7/ip`, March 2019.

[36] Linux Developers. UDP Man page. `https://linux.die.net/man/7/udp`, March 2019.

[37] Linux Developers. ICMP Man page. `https://linux.die.net/man/7/icmp`, March 2019.

[38] Linux Developers. DHCPD Man Pages. `https://linux.die.net/man/8/dhcpd`, March 2019.

Glossary

API Applications Programming Interface 5, 28

ARP Address Resolution Protocol 57

banner A short piece of text which a service with send to identify itself when it receives a connection request. Often contains information such as version number etc... 24

black box Looking at something from an outsider's perspective knowing nothing about how it works internally. 3, 11, 17, 69

checksum A checksum is a value calculated from a mathematical algorithm which is sent with the packet to its destination to allow the recipient to check whether the packet was corrupted on the way. 18, 39

CIDR Classless Inter-Domain Routing 17, 25, 48, 50

CPE Common Platform Enumeration 65

daemon A process that runs forever in the background to facilitate other programs. 3

dbus-daemon A daemon which enable a common interface for inter-process communication. 3

DHCP Dynamic Host Configuration Protocol 3, 4

DHCPCD Dynamic Host Configuration Protocol Client Daemon 3

DNS Domain Name System 23

driver A tiny software module which is loaded into the kernel when the computer boots up, They mainly interface with hardware and are often very specific for each piece of hardware. 3

FTP File Transfer Protocol 18

header A header is the first few bytes at the start of a packet often consisting of information on where to send the packet next, can also contain information though. 6

HTML HyperText Markup Language 6, 7

HTTP HyperText Transfer Protocol 6, 15

HTTPS HyperText Transfer Protocol Secure 15

ICMP Internet Control Message Protocol 16, 17, 27, 28, 29, 33, 34, 35, 43, 46, 50, 55, 62, 63, 69

IDS Intrusion Detection System 18

IP Internet Protocol 28, 35, 50, 66, 69, 70

IP address Every computer on a network has a unique IP address assigned to them, which is used to identify where exactly message sent by computers are meant to go. 3, 4, 6, 15, 48, 50, 66, 67, 68

kernel The kernel is the foundation of an operating system and it serves as the main interface between the software running on the system and the underlying hardware it performs task such as processor scheduling and managing input/output operations. 3

MAC Media Access Control 57

NIC Network Interface Card 3, 5, 57

OSI model Open Systems Interconnection model 5, 7, 17, 28

packet Packets are simply a list of bytes which contains packed values such as to and from address and they are the basis for almost all inter-computer communications. 4, 5, 6, 7, 8, 10, 11, 15, 16, 18, 39, 41

PCAP Packet CAPture 38

PHP PHP Hypertext Processor 5

port Computers have "ports" for each protocol which can be connected to separately, this makes up part of a "socket" connection. 6, 18, 41, 49

port knocking Port knocking is where packets must be sent to a sequence of ports before access to the desired port is granted. 18

RDP Remote Desktop Protocol 65

SCTP Stream Control Transmission Protocol 18

server A server is any computer which it's purpose is to provide resources to others, either humans or other computers for purposes from hosting website or just as a resource of large computational power. 4, 24

service A service is something running on a machine that offers a service to either other programs on the computer or to people on the internet. 3, 11, 18, 41