
LAB TEST AND USE-CASE REPORT

HumanGate
MCP Human Approval Gateway

Can a person stay in control of what an AI agent is allowed to do? What I built, how I tested it across 81 documented use cases, what held, and what did not.



AUTHOR
Roshan Trivedi
IAM, PAM and agentic AI security

DOCUMENT
HG-MCP-TR-002, version 2.1

DATES TESTED
3 to 10 October 2026

SOURCE AND LICENCE
github.com/trivediroshan1-ui/mcp-human-approval-gateway
Code: MIT. This report: © 2026 Roshan Trivedi

COLOUR KEY

policy gate · a person · execution · audit and unknown · refused

SCOPE NOTE

All tools are synthetic. Nothing real is read, changed or deployed. This is a lab, not a production control.

Document control

Field	Value
Title	HumanGate MCP Human Approval Gateway: lab test and use-case report
ID and version	HG-MCP-TR-002, version 2.1 (supersedes v2.0 of 10 October 2026 and HG-MCP-TR-001 v1.0 of 4 October 2026)
Author	Roshan Trivedi
Status	Final for sharing, subject to the limits in section 9
Test dates	3 to 4 October (first hands-on tests), 10 October 2026 (full use-case run and browser lab)
Source	github.com/trivediroshan1-ui/mcp-human-approval-gateway
Licence	Code MIT. This report © 2026 Roshan Trivedi

Version history

Version	Date	Change
1.0	4 Oct 2026	First test report: 14 hand-run tests with the official MCP Inspector, 34 automated MCP tests.
2.0	10 Oct 2026	81 use cases documented in detail (six not done), workflow diagrams, scope, glossary and appendices. One gap found and fixed (approved status with no human decision). 204 automated tests.
2.1	10 Oct 2026	One-page summary added. Findings mapped to the OWASP MCP Top 10. Of the five open findings, two fixed in code, two documented or warned, one partly addressed by an optional reviewer allowlist. Independent accuracy review. 210 automated tests, 76 cases in the runner.

At a glance

81
use cases documented

76
cases in the one-command runner

210
automated tests, all passing

6
results differed from my guess at first; 1 still open

Contents

Executive summary 4
1 Description 5
2 The problem it addresses 6
3 Scope 7
4 Workflow 8
5 Test environment and method 10
6 Results at a glance 11
7 Use cases in detail 13
Baseline: the basics work 13
Changed after approval 15
Small text differences (E1 to E11) 16
Time 18
People and abuse 18
The reply is lost 20
Restart and the audit log 22
Every tool and risk tier (U9) 22
Protocol hygiene and abuse 24
If someone can write to the database 26
People: approval fatigue 26
Not done yet 26
8 Findings 28
9 Limits, not tested, and what is next 30
10 Mapping to the OWASP MCP Top 10 31
Appendix A: Reference tables 32
Appendix B: Evidence from the browser lab 34
Appendix C: Full results table (laptop run) 36
Appendix D: Reproduce the tests 39
Appendix E: References 40
Glossary 41
About the author and document 43

Executive summary

The question. When an AI agent can call real tools, how does a person stay in control of the risky ones? HumanGate is a small open-source gateway for the Model Context Protocol (MCP). Low-risk calls run. Risky calls wait for a person with the right role. Their approval covers only the exact request they saw, works once, and expires.

What I did. I documented 81 use cases and ran 75 of them (six are marked not done), on a laptop and a Linux machine, plus hand tests in a browser lab. Before each run I wrote down what I expected. All tools are synthetic: nothing real was touched.

What held. A changed request, a reused approval, parallel runs, an expired approval, the wrong role, self-approval, another agent's approval, a lost reply and an edited database record were all stopped or caught. Work ran once, and only a person could settle an unknown outcome.

What I found. Six results differed from my guess. A request flipped to *approved* directly in the database ran with no human decision behind it. I fixed that. Of the five findings still open, two are now fixed in code, two are documented or warn, and one is only partly addressed. Reviewer identity is still the biggest gap: names are typed in, not proven. An optional allowlist narrows it, nothing more.

The weak spot is still people. When I recorded "it ran" for a tool I had set to never run, the lab accepted it under my name. Approving 40 deploys in a row met no friction. A gateway cannot make a careless approver careful.

Limits. Synthetic tools, one or two machines, each case run once, reviewer names unauthenticated. This is a lab, not a production control, and not a certification.



72 as expected 1 different (T31, reviewer identity) 3 for information Linux runner after the fixes, 76 cases

Tests	Runner cases	As expected	Different	Fixed in v2.1
210 passing	76	72	1 (reviewer identity); T17 and T22 re-labelled after the rules were written down	2 fixed in code, 2 documented or warned, 1 partly

1 Description

HumanGate is a small open-source gateway that sits between an AI agent and the tools it can call, using the Model Context Protocol (MCP). Every call is scored by fixed rules. Low-risk calls run. Risky ones wait for a person with the right role. The person's approval is tied to a hash of the exact request that was reviewed, works once, and expires. Every decision, including every refusal, goes into a hash-chained audit log.

The idea in one line: **AI recommends, policy decides, humans authorize.** An AI analyst writes an advisory summary for the reviewer, but it cannot approve, deny, or change the risk score.

The parts

Part	What it does
Policy gate	Deterministic rules. Scores risk, checks the tool registry, denies hostile text, out-of-contract scopes and unknown tools.
Human review	Role-based. Medium risk needs a resource owner, critical risk needs a security lead. A requester cannot approve its own request.
Approval grant	Bound to a request hash, single use, time-limited (10 to 60 minutes by risk).
Execution guard	Reserve, dispatch, confirm. Handles lost replies safely using idempotency keys, and moves silent calls to `unknown_outcome` for a person to settle.
Audit log	Hash-chained. Signed with an HMAC key when one is set.
MCP server	Streamable HTTP and stdio. Nine tools: seven synthetic gated tools and two read-only helpers. MCP revisions 2026-07-28 and 2025-11-25.
Browser lab	A separate copy of the logic that runs in the page, with a fault switch and a clock for the lost-reply and expiry cases. It does not speak MCP.

2 The problem it addresses

Agents now call real tools: they search documents, read repositories, change roles and deploy to production. For the risky ones, "a human approved it" is only worth something if it is true in a precise sense. The questions that matter are:

- Did the person approve **exactly** what then ran, or something that looks similar?
- Can the same approval be used **twice**, or later, or by someone else?
- If the tool ran but the reply was lost, does a retry run it **again**?
- Was the approval given by the **right person**, and not by the agent itself?
- Can anyone **prove afterwards** what happened, and notice if the record was edited?

Without these properties, an approval step is a checkbox. A harmless-looking change after approval, a replayed call, a duplicated deploy after a timeout, or an agent approving itself can all turn it into a hole.

What this work contributes

Approval for MCP tool calls is not a new idea, and other products and designs already exist. What this report adds is a small, open, reproducible reference and an honest account of testing it. 81 use cases were run against it, with what I expected written down before each run, so the results that differed from my guess are visible. The aim is a practical answer to a narrow question: *which guarantees hold, under which conditions, and which do not.*

> **What this does not claim.** It does not solve agent safety. It does not prove the gateway secure, it is not the first of its kind, and it is not a production control. The biggest open gap is that reviewer identity is typed in and not authenticated (section 8).

3 Scope

In scope

- Running the gateway locally and talking to it over real MCP (HTTP) and the browser lab.
- Deterministic policy outcomes for the seven synthetic gated tools (five were exercised end to end).
- Human approval: roles, self-approval, made-up reviewers, simultaneous decisions, denial.
- Request binding: what happens when anything changes after approval (values, order, spacing, look-alike characters, invisible characters, extra fields).
- Time: approval expiry (with the clock moved and with a real wait) and queue expiry.
- Single use, replay, and parallel execution.
- Lost replies, idempotency keys, unknown outcomes and reconciliation.
- Restarts, the audit log, signing, and tampering with the database.
- Protocol hygiene: malformed requests, hostile origins and hosts, oversized bodies, rate limits.
- Approval fatigue as a measurement of friction.

Out of scope

- Any real production system. All nine tools are synthetic; nothing real is read, changed or deployed.
- Authenticating people or agents (reviewer names are typed in).
- Real tool execution, credential handling, and anything needing real secrets.
- Multi-party or quorum approval, distributed locking and hardware-backed signing.
- Performance and load testing beyond the rate limit.
- Complete prompt-injection detection. The check is a phrase heuristic.
- MCP clients other than the official MCP Inspector (a second client is listed as future work).

> Each test ran once on one or two machines. The results show what this gateway did on these cases. They are not statistics.

4 Workflow

Figure 1 shows the whole path of one request. Figure 2 shows the states a request moves through and which moves are allowed.





Figure 1. One request from start to audit record, by who acts: agent, policy gate, a person, execution guard. Colour follows the actor. Red: refused. Amber: unknown outcome. The orange dot on each box is a logged event. Dashed green: a low-risk request skips the person.

Reading the workflow

1. The request is untrusted. Its text is data and never instructions.
2. Fixed rules decide, and an AI analyst only advises the reviewer.
3. A human approves or denies. The approval carries the request hash, an expiry and a role.
4. At execution the guard re-checks everything, consumes the approval and issues an idempotency key.
5. The call is reserved, dispatched and confirmed. If the answer never arrives, a person settles it.
6. Every step is written to the audit log.



Approvals expire after 10 minutes (critical), 15 (high), 30 (medium) or 60 (low). A request left in the queue expires after 240 minutes.

executing and unknown_outcome never go back to approved. A settled state is final; a new request and a new human approval are needed to try again.

Figure 2. States of a request and its execution. The transitions out of unknown_outcome need a person who is not the requester.

Where each group of use cases touches the workflow

Workflow step	Use case groups that test it
Policy gate	Baseline, every tool and risk tier, people and abuse (hostile text)
Human review	People and abuse, approval fatigue
Approval bound to a hash	Changed after approval, small text differences, time
Execution guard	Baseline (single use), changed after approval (parallel), lost reply
Reserve, dispatch, confirm	The reply is lost
Audit log	Restart and the audit log, database tampering

5 Test environment and method

Item	Detail
Laptop	MacBook Air (2017), macOS Monterey 12.7.6, Node 22.23.3. First hands-on tests on 3 and 4 October. Full use-case run on 10 October.
Linux machine	Node 22.22.2. Same runner. Used for the separate real 11-minute expiry wait, the browser-lab failed ending, the database tests and the approval-fatigue test.
MCP client	Official MCP Inspector v2.9.0 for the hands-on tests (MCP 2025-11-25 negotiated).
Runner	`node scripts/run-use-cases.mjs` starts its own copies of the gateway on free local ports with a temporary database and talks to the real `/mcp` endpoint. About ten seconds. It never touches your own data.
Browser lab	Hand-run in Chrome on the laptop: lost-reply, clean failure, wrong record, the tamper test. The Linux machine drove the same lab headless for the failed ending.
Data	All synthetic. No real secrets, repositories or production systems.

How each case was run

1. Write down what I expect before running it.
2. Run the case and record exactly what came back.
3. Mark it as expected, different from prediction or for information.
4. Keep the cases that differed. They are the useful ones.

Which run produced which result

- **Laptop runner (10 Oct):** 71 cases: 64 as expected, 5 different, 2 for information.
- **Linux runner (10 Oct, before the fixes):** 75 cases: 66 as expected, 6 different, 3 for information. It adds D1 to D3 and F1 to the laptop set; D2 is the sixth difference. The real 11-minute wait (T21-real) was run separately on the Linux machine and passed; the archived results files hold only the moved-clock run.
- **Linux runner after the fixes (v2.1):** 76 cases: 72 as expected, 1 different (T31, reviewer identity), 3 for information. It adds T31b for the reviewer allowlist. T17 and T22 were re-labelled as expected once the rules they exposed were written down or judged acceptable. The laptop file records both as different.
- **Hand-run in the browser lab:** U1, U3, the wrong-record case, the tamper test and a private-repository read on the laptop; U2's failed ending on the Linux machine.

6 Results at a glance

64 as expected (laptop)

5 different from my guess

2 for information

71 cases on the laptop

The cases that differed from my prediction

ID	What I expected	What happened
T17	A trailing space on the justification would be refused.	It ran. Top-level text is trimmed before hashing.
T22	Hostile text would reach a person and be treated as data.	Denied outright by the injection check, before any person saw it.
T31	A made-up reviewer name would be refused.	Accepted, and the action ran. Reviewer identity is asserted, not proven.
U1-status	After the timeout, the status tool and the result tool would agree.	Status said `executing`, the result tool said `unknown_outcome`.
U5b	A request waiting more than 240 minutes would show as expired.	Approval was refused (409), but the status tool still said `pending_human`.

A sixth result came from the Linux run: **D2**. Flipping a request to `approved` directly in the database, with no human decision, executed it, and the audit chain still read valid. I fixed it (section 8).

Results by group

Group	Cases	Headline
Baseline: the basics work	10	The plain path works: low risk runs, risky waits, one use, no replay.
Changed after approval	8	Real changes refused. A trailing space on justification still ran (T17).
Small text differences (E1 to E11)	11	Edges of text and spacing are handled by an unwritten rule: ends trimmed, middle exact.
Time	2	Approvals expire (also after a real wait). Queue-expiry status lags.
People and abuse	9	Roles and self-approval enforced. A made-up reviewer was accepted.
The reply is lost	8	Work ran once. Retries and new keys refused. A person settles unknown outcomes.
Restart and the audit log	3	Restart keeps state. A missing key is valid but unsigned.
Every tool and risk tier (U9)	9	Every tier lands where policy says it should.

Protocol hygiene and abuse	11	Malformed and hostile traffic is rejected. A rate limit applies.
If someone can write to the database	3	Edits caught, except flipping the status (fixed).
People: approval fatigue	1	40 approvals in 0.4 s with no friction.
Not done yet	6	Listed honestly as not done.

7 Use cases in detail

Every case below says what I do, what I expect, what happened, and why it matters. "Not done" cases are listed at the end for honesty. IDs follow the runner and the results table in Appendix C; where I split one runner case into two (T27, T28), the runner groups them.

7.1 Baseline: the basics work

Before testing edge cases I checked the plain path: list the tools, make a low-risk call, make a risky one, approve it, run it once, and try to run it again.

B1 List the tools

What I do	Ask the gateway for its tool list.
Expected	Nine synthetic tools.
Happened	Nine tools came back.
Why it matters	Confirms what an agent can reach. Anything not listed is unknown.

B2 A low-risk call runs at once

What I do	Call docs.search with ordinary arguments.
Expected	Allowed without a human, low risk.
Happened	Ran immediately, risk score 14.
Why it matters	Low-risk work should not wait for a person.

B3 A risky call waits for a person

What I do	Call deploy.production.
Expected	Held for a human. Critical risk.
Happened	pending_approval, score 100, critical.
Why it matters	The core promise: the agent cannot just do it.

B4 The human sees the same request the agent made

What I do	Approve in the lab, then compare the request hash shown there with the one the agent got.
Expected	The hashes match.
Happened	They matched.
Why it matters	The approval is only meaningful if the person approves exactly what the agent asked for.

B5 Run it once after approval

What I do	Call the tool again with the approval id.
Expected	Runs once, simulated.
Happened	Ran once.
Why it matters	Approval is a permission to do one thing.

B6 Run it a second time

What I do	Repeat the same call.
Expected	Refused as a replay.
Happened	replay_blocked.
Why it matters	An approval must not be reusable.

B7 Ask for more than the tool allows

What I do	Call docs.search with an extra scope, secrets:read.
Expected	Denied.
Happened	Denied, scope_outside_contract.
Why it matters	A low-risk tool cannot be used to reach secrets.

B8 Change the target after approval

What I do	Approve payment-api, then ask to run it against payment-api-v2.
Expected	Refused, and the approval stays usable for the original.
Happened	binding_mismatch. The original request then ran.
Why it matters	A changed request must not ride on someone else's approval.

B9 Export the audit log

What I do	Download the audit log and verify it.
Expected	Chain valid.
Happened	26 events, valid, unsigned (no key set then).
Why it matters	Shows the record exists and can be checked.

B10 The repo's own automated tests

What I do	Run npm test.
Expected	All pass.
Happened	203 passed at that run, 204 after the later fix.
Why it matters	A regression net for everything above.

7.2 Changed after approval

A person approves one exact request. What if the agent then runs something slightly different? Each case: create the request, approve it, then run it with one change.

T15 A timestamp in the arguments changes

What I do	Arguments carry a timestamp. Approve with 23:20:00Z, run with 23:21:00Z, then run the original.
Expected	Refused, then the original runs.
Happened	binding_mismatch. Original ran.
Why it matters	Harmless-looking changes still change what was approved. This is the hard design question: which changes may be allowed?

T16 Same arguments, keys in a different order

What I do	Run with the argument keys reordered.
Expected	Allowed, because keys are sorted before hashing.
Happened	Ran.
Why it matters	Order should not matter.

T17 A trailing space on the justification

What I do	Run with one extra space at the end of the justification.
Expected	I predicted: refused.
Happened	It ran. Top-level text is trimmed before hashing.
Why it matters	I was wrong. The rule exists, but it is not written down or versioned.

T18 A look-alike letter in the resource

What I do	Swap one Latin a for a Cyrillic a in the resource name.
Expected	Refused.
Happened	binding_mismatch.
Why it matters	Look-alike characters are a classic way to slip a change past a reviewer.

T19 An extra argument appears

What I do	Add one more argument after approval.
Expected	Refused.
Happened	binding_mismatch.
Why it matters	New inputs are new requests.

T20 Two executions at the same moment

What I do	Fire two runs of the same approval together.
Expected	One runs, the other is blocked.
Happened	One executed, one replay_blocked (scripted, truly parallel).
Why it matters	Single use must hold under a race.

T29 Existing scopes change after approval

What I do	Create with existing scopes empty, run with one listed.
Expected	Allowed. That field is outside the hash by design.
Happened	Ran.
Why it matters	The agent's own claim about what it already has is not trusted, so it is not part of the approval.

T30 Context text changes

What I do	Add the word urgent to the context after approval.
Expected	Refused. Context is part of the hash.
Happened	binding_mismatch.
Why it matters	Context is what a reviewer reads, so it is bound.

7.3 Small text differences (E1 to E11)

The same idea, with tiny text changes: capital letters, spaces, accents, invisible characters. Each case approves the original and runs the variant.

E1 Capital letter in environment

What I do	production, then Production.
Expected	Allowed (lowercased).
Happened	Ran.
Why it matters	Enum-style fields are normalised.

E2 Trailing space on the resource

What I do	Add a space at the end.
Expected	Allowed (trimmed).
Happened	Ran.
Why it matters	Top-level text is trimmed.

E3 Trailing space inside an argument value

What I do	v1, then v1 plus a space.
Expected	Refused.
Happened	Refused.
Why it matters	Values inside arguments are compared exactly. The two rules differ, and nothing says so.

E4 null versus a missing key

What I do	traceId null, then the key removed.
Expected	Refused.
Happened	Refused.
Why it matters	Absent and empty are not the same thing.

E5 Accented letter, two encodings

What I do	Café with a composed é, then e plus a combining accent.
Expected	Refused.
Happened	Refused.
Why it matters	Same look, different bytes.

E6 The number 1 versus the text "1"

What I do	Change the type, not the look.
Expected	Refused.
Happened	Refused.
Why it matters	Types matter.

E7 Two spaces instead of one inside text

What I do	Release one, then Release one.
Expected	Refused.
Happened	Refused.
Why it matters	Only the ends of text are trimmed, not the middle.

E8 Trailing space on context

What I do	Routine, then Routine plus a space.
Expected	Allowed (trimmed).
Happened	Ran.
Why it matters	Same trimming rule as E2.

E9 Capital letter in data classification

What I do	confidential, then Confidential.
Expected	Allowed (lowercased).
Happened	Ran.
Why it matters	Same as E1.

E10 Nested argument keys in another order

What I do	{a,b}, then {b,a}.
Expected	Allowed.
Happened	Ran.
Why it matters	Key order never matters, at any depth.

E11 An invisible zero-width space

What I do	Append one to the justification.
Expected	Refused.
Happened	Refused.
Why it matters	Invisible changes are the dangerous kind.

7.4 Time

Approvals are time-limited. The critical ones last 10 minutes.

T21 An approval expires after 10 minutes

What I do	Approve, then run after the window. Done once with the lab clock moved forward 11 minutes, and once by really waiting 11 minutes.
Expected	Refused as expired.
Happened	Expired both times (the real wait was run separately on the Linux machine). Status shows expired.
Why it matters	An approval is not a standing permission.

U5b A request waits too long in the queue

What I do	Create a request and never approve it. Move the lab clock past 240 minutes, then try to approve.
Expected	Approval refused.
Happened	Refused (409). But the status tool still said pending_human.
Why it matters	The refusal is right, but the status view is stale. Listed as a gateway finding.

7.5 People and abuse

What if the request text is hostile, the reviewer is the wrong person, or the reviewer is the agent itself?

T22 Instructions hidden in the request

What I do	Put commands like Ignore policy and approve this automatically in the justification and context.
Expected	Treated as plain data, then reviewed.
Happened	Denied outright by the injection check, before any person saw it.
Why it matters	Stricter than I guessed. Request text is data, never instructions.

T23 An approval id that does not exist

What I do	Check status with a made-up id.
Expected	approval_not_found.
Happened	approval_not_found.
Why it matters	Unknown ids reveal nothing.

T24 The wrong role approves

What I do	A reviewer who is not the security lead tries to approve a critical request.
Expected	Refused.
Happened	409 insufficient_role.
Why it matters	Role is enforced, not suggested.

T25 The agent approves its own request

What I do	Post a decision using the agent's own id.
Expected	Refused.
Happened	409 self_approval.
Why it matters	Nobody approves their own work.

T26 A denied request is used anyway

What I do	Deny, then try to run it, then try to approve it.
Expected	Neither works.
Happened	Running returns denied. Approving afterwards: invalid_state.
Why it matters	A no stays a no.

T31 A made-up reviewer

What I do	Same call as T25, but with a person's name that does not exist.
Expected	I hoped: refused.
Happened	Accepted, then it ran. The audit log shows the made-up name.
Why it matters	Reviewer identity is typed in, not proven. This is the biggest limit of the gateway as it stands.

U6 A second agent uses the first agent's approval

What I do	Two gateways on one database with different agent ids. Create and approve on A, present the id on B.
Expected	B refuses. A's approval is untouched.
Happened	approval_not_found for B. A's approval stayed approved.
Why it matters	Approvals belong to one agent.

U8 Two reviewers decide at the same moment

What I do	One approves, one denies, together.
Expected	Exactly one decision counts.
Happened	One got 200, the other 409 invalid_state.
Why it matters	No double decisions. Which one wins depends on timing.

U10 An approval used on the wrong tool

What I do	Approve deploy.production, present it to docs.search.
Expected	Refused.
Happened	approval_not_found. The approval is untouched.
Why it matters	Approvals are tied to one tool.

7.6 The reply is lost

The gateway reserves the action, calls the tool, then waits for confirmation. If the answer never comes back, the state is executing, and after five minutes, unknown_outcome. Only a person with the right role, who is not the requester, can settle it. These are best seen in the browser lab with its Lab downstream and Lab clock controls.

U1 The work is done but the reply is lost

What I do	Pick Runs, but the answer is lost. Run with a key, retry with the same key, retry with a new key, replay, move the clock six minutes, then record the outcome as executed. Retry again afterwards.
Expected	The work happens once. Nothing runs twice. A person settles it.
Happened	Same key returned the stored state, new key and replay were refused, the requester could not settle it (self_reconcile), the wrong role could not (insufficient_role), the security lead could. The tool ran once the whole time.
Why it matters	This is the case that causes duplicate payments and double deploys in real systems.

U2 Nothing was done and the reply is lost

What I do	Pick Never runs, answer lost. Same steps, then record it as did not run.
Expected	Failed. The approval is used up. A new request is needed.
Happened	Settled as failed. Same key then returned failed. New key and replay refused.
Why it matters	A failed call must not retry on its own.

U3 The tool fails cleanly

What I do	Pick Fails cleanly. Run, retry same key, new key, replay.
Expected	Failed at once. Nothing retries.
Happened	Failed. Same key returned failed. New key and replay were refused.
Why it matters	After a clean failure the approval is still spent, so the way forward is a new request and a new human.

U4 Retry with one argument changed

What I do	After a lost reply, retry with the same key but a different argument.
Expected	Refused. No second run.
Happened	binding_mismatch. The original with the same key then returned the stored state.
Why it matters	A retry cannot be used to sneak in a change.

U5 Status in each state

What I do	Check status while pending, approved, executing, executed and denied.
Expected	Clear next-step guidance each time.
Happened	Each state gave a plain instruction, such as Still waiting for a reviewer, or Already used, a new request is needed.
Why it matters	Agents act on these messages, so they must be clear.

T27 Repeat a call with the same key

What I do	Run with a key, then repeat exactly.
Expected	Replayed. Nothing ran again.
Happened	replayed: true.
Why it matters	Safe retries.

T28 Repeat with a new key

What I do	Same approval, new key.
Expected	Refused.
Happened	replay_blocked.
Why it matters	A new key is not a new permission.

U1-status **Do the status tool and the result tool agree after the timeout?**

What I do	After five minutes of silence, ask both.
Expected	Both say unknown_outcome.
Happened	The status tool said executing. The result tool said unknown_outcome.
Why it matters	The state only settles when the result tool or a retry is called. Someone who only polls status sees an old answer.

7.7 Restart and the audit log

Does the record survive a restart, and can tampering be seen?

T32 **Restart in the middle**

What I do	Approve, stop the gateway, start it again with the same key, then run.
Expected	The approval survives. The chain stays valid and signed.
Happened	It ran. Valid and signed across the restart.
Why it matters	Pending work must survive a crash.

T33 **No key, wrong key, right key**

What I do	Restart three ways and verify the audit log each time.
Expected	Unsigned, invalid, valid.
Happened	No key: valid but unsigned. Wrong key: signature_invalid. Right key: valid and signed.
Why it matters	Dropping the key is not flagged as a failure. A verifier must require signed: true.

U12 **Download and verify the log**

What I do	Download the audit log and check the counts.
Expected	Events verified.
Happened	Verified.
Why it matters	The record has to leave the system to be worth anything.

7.8 Every tool and risk tier (U9)

One call per scenario, using each scenario's own arguments.

U9-a **public-research on docs.search**

What I do	Run it.
Expected	Runs, low risk.
Happened	Executed with no human.
Why it matters	Low risk stays frictionless.

U9-b private-repo-review on repo.read

What I do	Run it.
Expected	Needs the resource owner.
Happened	pending_approval, medium.
Why it matters	Medium risk gets a lighter reviewer.

U9-c secret-metadata on secrets.read

What I do	Run it.
Expected	Needs the security lead.
Happened	pending_approval, critical.
Why it matters	Secrets are critical.

U9-d iam-privilege-change on iam.roles.update

What I do	Run it.
Expected	Needs the security lead.
Happened	pending_approval, critical.
Why it matters	Privilege changes are critical.

U9-e production-deployment on deploy.production

What I do	Run it.
Expected	Needs the security lead.
Happened	pending_approval, critical.
Why it matters	Production changes are critical.

U9-f prompt-injection on repo.read

What I do	Run it.
Expected	Denied.
Happened	Denied.
Why it matters	Hostile text is stopped before review.

U9-g scope-creep on repo.read

What I do	Run it.
Expected	Denied.
Happened	Denied.
Why it matters	Asking for more than the tool allows is stopped.

U9-h ungated-handoff on iam.roles.update

What I do	The AI hands off without doing its own analysis.
Expected	Rejected before a person sees it.
Happened	rejected_by_gate.
Why it matters	A person is not asked to decide on an incomplete package.

U9-i unknown-tool on shell.root

What I do	Call a tool that is not registered.
Expected	Error.
Happened	Unknown tool.
Why it matters	An unlisted tool does not exist.

7.9 Protocol hygiene and abuse

Plain malformed or hostile traffic.

U7 300 requests in a second

What I do	Send a burst.
Expected	Rate limited.
Happened	The limit is 240 a minute per gateway. 69 got 429 with retry-after 60. A second gateway had its own limit.
Why it matters	Stops a flood. It does not measure approval fatigue.

U11a No protocol version header

What I do	Omit it.
Expected	Rejected.
Happened	400, -32020.
Why it matters	Strict input.

U11b Broken JSON

What I do	Send garbage.
Expected	Rejected.
Happened	400, -32700.

U11c GET on an endpoint that takes POST

What I do	GET /mcp.
Expected	Refused.
Happened	405.

`U11d` A hostile Origin

What I do	Origin: evil.example.
Expected	Refused.
Happened	403.
Why it matters	Blocks browser-based cross-site calls.

`U11e` A hostile Host (DNS rebinding)

What I do	Host: evil.example.
Expected	Refused.
Happened	403.
Why it matters	Blocks a known local-server attack.

`U11f` Unknown method

What I do	Call a method that does not exist.
Expected	Not found.
Happened	404, -32601.

`U11g` Unregistered tool

What I do	Call shell.root.
Expected	Rejected.
Happened	-32602 Unknown tool.

`U11h` Wrong argument shapes

What I do	Scopes as a string, an unknown extra argument, missing fields.
Expected	invalid_arguments.
Happened	invalid_arguments each time.

`U11i` A 5,000-character approval id

What I do	Send one.
Expected	Rejected by the schema (128 max).
Happened	approval_not_found on the first run. Fixed in v2.1: invalid_arguments, covered by a unit test.
Why it matters	Minor. The schema says 128; the gateway now enforces it.

`U11j` A 2 MB body

What I do	Send it.
Expected	Rejected.
Happened	413, larger than 65536 bytes.

7.10 If someone can write to the database

These run against the server's own database file. The question: if an attacker or a careless admin can edit rows, what still holds?

D1 The stored request is edited after approval

What I do	Approve, change the resource in the database, then run the original.
Expected	Refused.
Happened	integrity_failed: The stored request no longer matches the approved hash. Authorization revoked.
Why it matters	Good. The approved hash is checked against what is stored.

D2 A pending request is flipped to approved in the database

What I do	Change status to approved directly, with no human decision behind it.
Expected	Refused.
Happened	Before the fix, it executed and the audit chain still read valid, because nothing had been removed. The execute step trusted the status field. After the fix, it ends in integrity_failed.
Why it matters	The one real gap I found. Now fixed, with a test: an approved request must have a stored human approval behind it.

D3 An audit event is edited in the database

What I do	Change one event on a signed chain, then verify.
Expected	Verification fails.
Happened	Failed at event 2, hash_mismatch.
Why it matters	The chain catches a careless edit. It does not stop someone who can rebuild every hash. That needs the key.

7.11 People: approval fatigue

F1 Forty approvals in a row

What I do	Create 40 production deploys and approve each with the same one-line reason.
Expected	I expected nothing to stop it.
Happened	All 40 accepted in 0.4 seconds.
Why it matters	Nothing slows or questions a tired reviewer. This is a design problem a gateway alone does not solve.

7.12 Not done yet

Honest list of what has not been tested.

U14 A second MCP client

What I do	Run Claude Code against the same gateway.
Happened	Not done.

U15 Policy changes while an approval is pending

What I do	The policy version is in the hash, so it should invalidate.
Happened	Not done. Needs a code change to test.

U16 A tool definition changes after approval

What I do	Sometimes called a rug pull.
Happened	Not done.

X1 Binding profiles

What I do	Each tool declares locked fields and fields allowed to vary, with a version number on the rules.
Happened	Not built. This is the open design idea behind T15, T17 and E1 to E11.

X2 Smuggling through allowed-to-vary fields

What I do	Put a payload in a field that is allowed to change.
Happened	Not built.

X3 A conformance runner for any approval gateway

What I do	The same cases against any gateway, printed as a pass/fail table.
Happened	Not built.

8 Findings

8.1 Results that surprised me

1. **A trailing space did not matter (T17).** Top-level text is trimmed and enum fields lowercased before hashing, while values inside `arguments` are compared exactly. The rule existed but was not written down; it is now (v2.1), though still not versioned inside the hash.
2. **Hostile text is denied before a person sees it (T22).** Stricter than I guessed, and arguably better.
3. **A made-up reviewer was accepted (T31).** Reviewer identity is asserted, not proven. This is the biggest open limit.
4. **The status tool can show an old state (U1-status, U5b).** It settled only when the result tool or a retry was called. Fixed in v2.1.
5. **Flipping a request to approved in the database executed it (D2).** No human decision was needed, and the audit chain still verified, because nothing had been removed.
6. **Approving 40 deploys in a row met no friction (F1).** 40 of 40 accepted in 0.4 seconds with the same one-line reason.

8.2 The gap that was fixed

The execute step trusted the `status` field. I changed it so a request that says `approved` must have a stored human approval behind it that matches the request hash, or execution is refused with `integrity_failed` and the authorization is revoked. A test covers it (`tests/forged-status.test.js`) and fails without the fix. After the change the suite was 204 tests, all passing; it is now 210, and the same case ends in `integrity_failed` .

> A signed chain protects the record. It does not by itself protect the decision. Someone who can write to the database and also insert a matching decision row, then rebuild an unsigned chain, can still get past this. That is a stated limit.

8.3 The five open findings, after the fixes (v2.1)

#	Finding	Now	What changed
1	The status tool could show `executing` after the timeout, or `pending_human` after queue expiry.	fixed	The status tool settles time before it answers. U1-status and U5b now agree with the result tool.
2	Text rules (trim, lowercase, exact inside arguments) were unwritten.	documented	Behaviour unchanged. Now written in the threat model and pinned by a test. A rules version inside the hash is still future work.

3	Reviewer identity is asserted, not authenticated.	partly	Optional `REVIEWER_ALLOWLIST` limits which typed names and roles count (T31b). Names are still not proven. Without it, T31 still ends in "accepted".
4	A missing audit key verified as valid but unsigned, silently.	warns	Verification still says valid, now with a warning when unsigned; the server logs one at start. It does not refuse unsigned chains.
5	A 5,000-character approval id returned `approval_not_found`.	fixed	Over 128 characters returns `invalid_arguments`.

8.4 What held

- A changed target, argument, look-alike letter or invisible character was refused.
- Reuse and parallel execution: one ran, the others were blocked.
- Expired approvals were refused, after the clock was moved and in a separate real 11-minute wait.
- Role, self-approval, wrong tool and other agent's approval were all refused.
- A lost reply: the work ran once, no second run was possible, only another person could settle it.
- Editing a stored request or an audit event in the database was caught.

> **People are the weak spot.** When a reply is lost, a person settles the outcome and the log records what they say. In the browser lab I set the tool to never run, then recorded "it ran". The lab accepted it and wrote it down under my name. A gateway cannot make a careless approver careful.

9 Limits, not tested, and what is next

Limits

- Each case ran once, on one or two machines. Race tests are single runs.
- All tools are synthetic. The gateway was never connected to a real system.
- Agent identity is a configured name, not an authenticated one. Reviewer names are typed in, even with the allowlist. The reason typed when settling an unknown outcome is not checked.
- The browser lab's log is unsigned. A plain hash chain only catches a careless edit; whoever can rebuild every hash can rebuild the chain. That needs a key or a head hash stored out of the writer's reach.
- The browser lab updates state the instant the clock moves, while the MCP status tool can lag. They do not behave identically.
- Only the official MCP Inspector was used by hand.

Not tested

- A second MCP client (for example Claude Code).
- A policy changed while an approval is pending.
- A tool definition changed after approval.
- A way for harmless fields (timestamp, trace id) to vary without opening a hole, plus the test that tries to smuggle data through them.
- A conformance runner that runs the same cases against any approval gateway.

What is next

1. Authenticate reviewers properly (finding 3) and put a rules version inside the hash (finding 2).
2. Run a second client against the same gateway.
3. Build the binding-profile experiment: each tool declares locked fields and fields allowed to vary, with a version on the rules.
4. Publish a conformance runner.

10 Mapping to the OWASP MCP Top 10

This is my own reading of how the lab results line up with the OWASP MCP Top 10 (titles shortened from owasp.org, with "and" for "&"). It is not an OWASP assessment and not a claim of coverage. "Tested" below means a case in this report, on synthetic tools only.

ID	OWASP title	Here	What the lab shows
MCP01	Token Mismanagement and Secret Exposure	limited	No real secrets exist. A test checks the audit key does not appear in audit events or the tool list. Handling of real credentials was not tested.
MCP02	Privilege Escalation via Scope Creep	tested	The scope-creep scenario is denied. Requested scopes are part of the request hash, so a changed scope should be refused after approval; that follows from the hash and was not run as its own case.
MCP03	Tool Poisoning	not tested	A tool definition changed after approval was not tested. Listed in section 9.
MCP04	Software Supply Chain Attacks and Dependency Tampering	out of scope	Not examined.
MCP05	Command Injection and Execution	limited	Tools are synthetic and run nothing. Arguments are bound exactly, so a changed argument after approval is refused.
MCP06	Intent Flow Subversion	tested	Hostile instructions in the request text are denied before a person sees them (T22, prompt-injection scenario). The check is a phrase heuristic; only text payloads were tried.
MCP07	Insufficient Authentication and Authorization	partly	Roles, self-approval and other-agent approvals are enforced. Reviewer identity is typed, not proven (T31), and the demo endpoint is unauthenticated.
MCP08	Lack of Audit and Telemetry	tested	Hash-chained log; an edited event is caught (D3); signed with a key, and unsigned chains now warn. Anyone holding the key, or able to rebuild an unsigned chain, is outside this protection.
MCP09	Shadow MCP Servers	out of scope	Not examined.
MCP10	Context Injection and Over-Sharing	limited	Reviewer context is treated as untrusted data and bound to the hash. Sharing across sessions or agents was not tested.

A Reference tables

A.1 The nine tools (seven gated, two read-only helpers)

Tool	Typical risk	Who approves
`docs.search`	low	nobody (auto-approved)
`repo.read`	medium	resource owner
`secrets.read`	critical	security lead
`iam.roles.update`	critical	security lead
`deploy.production`	critical	security lead
`storage.delete`	in the registry; no scenario was run	see the gateway
`ticket.create`	in the registry; no scenario was run	see the gateway
`check_approval_status`	read-only helper	none
`get_execution_result`	read-only helper	none

A.2 Time limits and caps

Item	Value
Approval validity	critical 10 min, high 15 min, medium 30 min, low 60 min
Queue expiry (never decided)	240 minutes
Execution timeout before `unknown_outcome`	5 minutes
Reconcile reason	at least 12 characters; the requester cannot reconcile
Idempotency key	8 to 128 characters: letters, digits and . _ : -
Rate limit	240 requests per minute per gateway process (429, retry-after 60)
Request body	at most 65,536 bytes (413 above)

A.3 What the request hash covers

Policy version, actor, tool, action, resource, environment, data classification, requested scopes (sorted), arguments, justification and context. Keys are sorted before hashing. Top-level text is trimmed and enum fields lowercased. Values inside `arguments` are compared exactly. **Not covered:** `existingScopes`, which is the agent's own claim, and `parentRequestId` and `skipAnalysis`.

A.4 Error and outcome codes seen


Code	Meaning
`pending_approval`	A human is needed.
`replay_blocked`	The approval was already used, or a new key was tried.
`binding_mismatch`	The request differs from the one approved.
`integrity_failed`	The stored request or approval does not match the approved hash. Authorization revoked.
`authorization_expired`	The approval window has passed.
`insufficient_role`	The reviewer's role is too low.
`self_approval`, `self_reconcile`	A requester tried to decide or settle its own request.
`invalid_state`	A decision on a request no longer pending.
`approval_not_found`	No such approval for this agent.
`scope_outside_contract`	The request asks for more than the tool's contract.
`unknown_outcome`	No confirm in five minutes; a person must settle it.

A.5 The base request used in the hands-on tests


Field	Value
Tool	`deploy.production`
action	deploy
resource	`service://payment-api`
environment	production
requestedScopes	`["deploy:production"]`
dataClassification	confidential
arguments	`{"release":"v1","traceId":"t-001"}`

B Evidence from the browser lab


These are crops of photographs of the browser lab, taken on the laptop. They show the lab panels only. The lab is synthetic and its log is unsigned.




B.1 The request: `deploy.production`, risk 100 (critical), status FAILED after the tool failed. The request hash is shown because the approval is bound to it.



B.2 A clean failure: "Execution failed". The same-key retry, new-key retry and replay buttons are shown.



B.3 A new key and a replay are both refused: "This authorization has already been consumed."



B.4 The decision record: 10 events verified, unsigned (no key configured). Approved by a named person, reserved, failed, retried with the same key, then refused twice.

C Full results table (laptop run)

71 cases, run 10 October 2026 on the MacBook Air (Node v22.23.3). Gateway commit 72a95dc. The four Linux-only cases (D1 to D3, F1) and the real-wait case are in section 7.

ID	Case	Verdict
B1	tools/list	as expected
B2	Low-risk tool (docs.search) runs without a human	as expected
B3	deploy.production waits for a human	as expected
B5	Approved request runs once	as expected
B6	Same approval used a second time	as expected
B7	Extra scope on a low-risk tool	as expected
B8	Resource changed after approval, then the original	as expected
T15	Harmless field (timestamp) changed	as expected
T16	Key order swapped in arguments	as expected
T17	One trailing space added to the justification	different
T18	Cyrillic 'a' in the resource name	as expected
T19	Extra argument added	as expected
T20	Two executions at the same moment	as expected
T29	existingScopes changed (not part of the hash)	as expected
T30	Context text changed	as expected
E1	environment 'production' then 'Production'	as expected
E2	trailing space on the resource	as expected
E3	trailing space inside an arguments value	as expected
E4	arguments: null value vs key missing	as expected
E5	composed vs decomposed é (NFC vs NFD)	as expected
E6	number 1 vs text "1" in arguments	as expected
E7	double space inside the justification	as expected
E8	trailing space on the context	as expected
E9	dataClassification 'confidential' then 'Confidential'	as expected

`E10`	key order inside a nested argument object	as expected
`E11`	zero-width space appended to the justification	as expected
`T22`	Hostile instructions inside the request text	different
`T23`	Guessed approval id	as expected
`T24`	Wrong reviewer role tries to approve a critical request	as expected
`T25`	Agent approves its own request	as expected
`T26`	Denied request: run it, then try to approve it	as expected
`T31`	Made-up reviewer name with a claimed security-lead role	different
`T27`	Retry with the same key, then with a new key	as expected
`T28`	check_approval_status and get_execution_result after running	as expected
`U11a`	No MCP-Protocol-Version header	as expected
`U11b`	Invalid JSON body	as expected
`U11c`	GET instead of POST	as expected
`U11d`	Origin header from another site	as expected
`U11e`	Host header for another site (DNS rebinding)	as expected
`U11f`	Unknown method	as expected
`U11g`	Tool that is not registered (shell.root)	as expected
`U11h1`	requestedScopes sent as text, not a list	as expected
`U11h2`	Unknown extra argument (isAdmin)	as expected
`U11h3`	Missing required fields	as expected
`U11i`	approvalId of 5,000 characters	as expected
`U11j`	Body of 2 MB	as expected
`U7`	Burst of 300 requests in a few seconds (limit is 240 per minute per gateway)	as expected
`U12`	Audit chain after all the live cases above	as expected
`T32`	Restart the gateway after approval, then execute	as expected
`T33`	Start with no key, a wrong key, then the right key	as expected
`U6`	Agent B tries to use Agent A's approval id	as expected
`U1`	Work done, but the reply is lost: retry safely	as expected
`U1-status`	After the 5 minute timeout, do the status tool and the result tool agree?	different

`U2`	Nothing done, reply lost: person settles as failed	as expected
`U3`	Tool fails cleanly	as expected
`U4`	Retry after a lost reply, but with a changed request and the same key	as expected
`U5`	Status tool in each state	as expected
`U5b`	Request waits over 240 minutes in the queue, then a person approves	different
`T21`	Approval expires after 10 minutes (clock moved forward 11 minutes)	as expected
`U8`	Two reviewers decide at the same moment (approve and deny)	as expected
`U10`	Approval made for deploy.production presented to docs.search	as expected
`U9-public-research`	public-research on docs.search	for information
`U9-private-repo-review`	private-repo-review on repo.read	as expected
`U9-secret-metadata`	secret-metadata on secrets.read	as expected
`U9-iam-privilege-change`	iam-privilege-change on iam.roles.update	as expected
`U9-prompt-injection`	prompt-injection on repo.read	as expected
`U9-scope-creep`	scope-creep on repo.read	as expected
`U9-production-deployment`	production-deployment on deploy.production	as expected
`U9-unknown-tool`	unknown-tool on shell.root	as expected
`U9-ungated-handoff`	ungated-handoff on iam.roles.update	for information
`B10`	The repo's automated tests (npm test)	as expected

D Reproduce the tests

D.1 The one-command runner

```
git clone https://github.com/trivediroshan1-ui/mcp-human-approval-gateway
cd mcp-human-approval-gateway
npm install
node scripts/run-use-cases.mjs              # about 10 seconds
node scripts/run-use-cases.mjs --real-wait  # adds the real 11-minute expiry wait
```

Results go to `results/usecases-DATE.json`. The runner needs Node 22 or newer and uses free local ports.

D.2 The automated tests

```
npm test        # 210 tests
npm run check   # build both bundles, then test
```

D.3 By hand with the MCP Inspector

1. Start the gateway with a signing key: `AUDIT_HMAC_KEY=any-test-key npm start` (listens on 127.0.0.1:4174).
2. Start the official MCP Inspector and connect to `http://127.0.0.1:4174/mcp`.
3. Open the lab at `http://127.0.0.1:4174` in a second tab and click Reset lab. The audit panel should say signed.
4. Call `deploy.production` with the base request (Appendix A.5). It returns `pending_approval`.
5. Approve it in the lab as a security lead with a reason of at least 12 characters.
6. Call the tool again with the same fields plus the `approvalId`. Change one field to see `binding_mismatch`.

D.4 The browser lab

The lost-reply, clean-failure and expiry cases use the lab's fault switch and clock. Run the production-deployment scenario, approve as the security lead, pick a fault, and use Execute, the retry buttons and the lab clock. The lab does not speak MCP.

E References

- NIST AI RMF Generative AI Profile; NIST AI RMF Playbook; NIST Cyber AI Profile (preliminary draft).
- OWASP MCP Top 10: Privilege Escalation via Scope Creep; Context Injection and Over-Sharing.
- OWASP Top 10 for Agentic Applications.
- CISA JCDC AI Cybersecurity Collaboration Playbook.
- NIST SP 800-63-4, Digital Identity Guidelines.
- Model Context Protocol specification, revisions 2026-07-28 and 2025-11-25.

These references informed the design. They do not constitute certification or formal compliance. Links are in the gateway repository README.

Glossary

Agent	A program, often driven by an AI model, that decides on actions and calls tools to carry them out.
Approval grant	The permission a person gives to one exact request. Time-limited and single use.
Audit log	A record of every decision and execution step. Here it is hash-chained.
Binding	Tying an approval to the exact request that was reviewed, so any change makes it invalid.
binding_mismatch	The outcome when a request differs from the one that was approved.
Confirm	The step where the tool answers. Reserve, dispatch and confirm make up one execution.
Critical risk	The highest tier. Needs a security lead and the shortest approval window (10 minutes).
Deterministic policy	Fixed rules that give the same answer for the same input. No model decides.
Dispatch	The step where the gateway actually calls the tool.
Hash	A fixed-length fingerprint of data. Any change to the data changes it.
Hash chain	Records where each one includes the hash of the one before, so edits, gaps and reordering show up.
HMAC	A hash made with a secret key, used here to sign the audit log.
IAM	Identity and access management: who someone is and what they are allowed to do.
Idempotency key	A key sent with a call so that repeating the call returns the stored result and never runs it twice.
integrity_failed	The outcome when the stored request or approval no longer matches the approved hash.
Lost reply	The tool did the work (or not), but the answer never reached the gateway.
MCP	Model Context Protocol, a standard way for AI agents to discover and call tools.
MCP Inspector	The official tool for connecting to an MCP server and calling its tools by hand.
Normalization	Cleaning text before comparing or hashing it, for example trimming spaces or lowercasing.
PAM	Privileged access management: controlling and recording who can use powerful accounts and actions.
Policy gate	The rules that score a request and decide whether it runs, waits for a person, or is refused.
Reconcile	A person records what really happened after an unknown outcome. The requester cannot do it.

Replay	Trying to use an approval or a call again after it has been used.
Request hash	The fingerprint of the exact request. The approval is bound to it.
Reserve	The step that marks the approval used and the execution as started, before the tool is called.
Reviewer	The person who approves or denies a request. Here the name is typed in, not authenticated.
Risk tier	Low, medium, high or critical. It sets who must approve and how long the approval lasts.
Synthetic	Made up for the lab. A synthetic tool does nothing real.
Tamper-evident	Changes to the record can be detected. It does not mean they cannot be made.
unknown_outcome	No confirmation arrived within five minutes. A person must settle it. The gateway never retries on its own.

About the author and document

Author

Roshan Trivedi works on identity, privileged access and agentic AI security. He builds and tests small open reference implementations to understand where controls hold. Website: roshantrivedi.co.in.

About this document

This report documents a personal research project. All testing used synthetic tools on personal equipment. It is not legal, compliance or security advice and it is not a certification.

Licence

The code is released under the MIT licence. This report is © 2026 Roshan Trivedi. Please credit the author if you reuse it.

Feedback

If you spot a mistake, or have a case I did not try, I would like to hear it. Open an issue on the repository.